



In one line: A **context** is an in-memory scratchpad bound to **one serial queue**; it reaches SQLite through a **coordinator** whose **row cache** holds last-known row values. Contexts see each other's work only after a save reaches the store *and* is **merged** in. Two saves of one row: **optimistic locking** detects it at `save()` and the saver's **merge policy** decides — by default the save **throws**.

The stack — who sees whose changes



another process or a batch request posts **no didSave** here → persistent history (part 2)

Optimistic locking — one row, two writers



B's policy	title	note	done	
.error (default)				save() throws 133020; nothing written
.mergeByPropertyObjectTrump	c	y	true	mine wins per prop
.mergeByPropertyStoreTrump	b	y	true	store wins per prop
.overwrite	c	x	true	whole object: A's note lost
.rollback	b	y	false	B's edits dropped

Queues

- `.mainQueueConcurrencyType` (viewContext) or `.privateQueueConcurrencyType` (.confinement... deprecated iOS 9). An object belongs to its context's queue — reading one property is access.
- `perform {}` enqueues and returns; `performAndWait {}` blocks the caller, **reentrant**. iOS 15 `try await ctx.perform(schedule:)` returns a value: `.immediate` (default) runs inline if already on the queue, else enqueues; `.enqueued` always goes to the back.
- `newBackgroundContext()` / `performBackgroundTask`: a **new** private context per call, parent = the **coordinator**. Two at once = two writers → conflicts, duplicates: keep **one long-lived writer**.

Identity & IDs

- Uniquing**: one object per row *per context*. `object(with:)` always returns (fault may fail later); `existingObject(with:)` throws if gone; `registeredObject(for:)` = only if in memory.
- New objects carry a **temporary** ID (`isTemporaryID`) until the store saves them — it resolves nowhere else: `obtainPermanentIDs(for:)` first. Persist a reference as `objectID.uriRepresentation()`.

Parent/child vs siblings

- A **child's** fetches go through its parent, so they see the parent's *unsaved* state; its `save()` copies changes into the parent's memory. Use: a cancelable edit sheet. Disk needs the parent's save too.
- Siblings** share only the coordinator: nothing crosses until a save reaches the store and a merge runs. `automaticallyMergesChangesFromParent` merges every save of the parent (root context: the coordinator), keeping unsaved local edits. Manual: on `.NSManagedObjectContextDidSave`, `mergeChanges(fromContextDidSave:)` inside the target's `perform`.
- Query generations** (iOS 10, SQLite): `setQueryGenerationFrom(.current)` pins reads to one store snapshot — stable UI during an import; save/merge advances it.
- `refresh(obj, mergeChanges:)`: `true` re-reads, keeps edits; `false` discards them → a fault again.

Example — a cancelable edit, and an upserting writer

```
let draft = NSManagedObjectContext(concurrencyType: .mainQueueConcurrencyType)
draft.parent = container.viewContext // sees parent's unsaved state
let item = draft.object(with: itemID) as! Item
item.title = "New title" // Cancel = just drop 'draft'
try draft.save() // -> viewContext (memory)
try container.viewContext.save() // -> coordinator -> SQLite

// one writer; model: Item has a unique constraint on remoteID
let writer = container.newBackgroundContext()
writer.mergePolicy = NSMergePolicy.mergeByPropertyObjectTrump
try await writer.perform {
    for dto in dtos { // duplicate remoteID -> update
        let i = Item(context: writer); i.remoteID = dto.id; i.title = dto.title }
    try writer.save() } // values/IDs leave, never objects
```

Conflicts — the mechanism

- At fetch a context keeps a **snapshot** (values + row version `Z_OPT`); at save each changed object's snapshot is compared with the row. Mismatch = `NSMergeConflict`, resolved by the context saving **second**. Default `NSErrorMergePolicy`: `userInfo["conflictList"]`, nothing saved.
- Unique constraints** (per entity): with `.error` a duplicate insert throws `NSConstraintConflict` (133021); with a property-trump policy it merges into the existing row = **upsert**.

Traps

- Policy set only on viewContext: the importer saves second and *its* `.error` throws. Set a policy on every saving context.
- `.overwrite` ≠ "mine wins": it writes the *whole* object, undoing others' changes to properties you never touched.
- `performAndWait` onto viewContext from a queue main is waiting on = **deadlock**.
- Returning a managed object from `await perform` compiles; using it outside is still a queue violation. Return IDs or values.
- com.apple.CoreData.ConcurrencyDebug 1 crashes on the first wrong-queue access, in `__Multithreading_Violation_AllThatIsLeftToUsIsHonor__`.

Remember

One queue per context, one writer per store, IDs across queues, a policy on whoever saves second.