


In one line: Every iOS architecture answers three questions: **who owns the state**, **which way does data flow**, and **where do side effects live**. **VIP** (Clean Swift) makes each screen a one-way cycle of three objects; **RIBs** (Uber) drive the app by a *tree of business logic*, not of views; **MVI** and **Redux** keep one immutable state changed only by a reducer; **TCA** is Redux made composable; **MV** says SwiftUI views plus `@observable` models are already enough.



How it works (unverified)

- VIP** (Raymond Law's *Clean Swift*; Clean Architecture per scene): VC (DisplayLogic) sends a *Request* to the Interactor (BusinessLogic, uses **Workers**), which passes a *Response* to the Presenter (PresentationLogic), which formats a *ViewModel* and calls `display...` on the VC. **Router** (RoutingLogic + DataPassing) navigates and hands data via the Interactor's DataStore. Models are nested per use case: `Scene.UseCase.Request/Response/ViewModel`.
- RIBs** = **Router** · **Interactor** · **Builder** (+ optional Presenter, View). Interactor = business logic + Rx subscriptions bound to its active/inactive lifecycle; Router attaches/detaches child RIBs; Builder creates the unit and injects dependencies. A RIB may have **no view**. Up = a Listener protocol the parent implements.
- MVI**: *Intent* = what the user wants (not an Android Intent); a reducer makes the next immutable *State*; the view is a pure `render(state)`. One-shot events (navigate, toast) need a separate channel.
- Redux** (JS, 2015): one store, read-only state, pure reducers. ReSwift: `Store<AppState>(reducer: state:), dispatch, StoreSubscriber with newState(state:); subscribe(self) { $0.select { $0.cart } } narrows updates.`
- MV**: no per-screen *ViewModel*; logic lives in `@observable` models / services passed via `.environment(model)`, read with `@Environment(Model.self)`. Critics: business rules drift into body.

Likely questions

- VIP vs VIPER? — one-way cycle vs presenter-centred two-way.
- Why RIBs? — a logic tree (even viewless) many teams extend safely.
- MVI vs MVVM? — one immutable state vs many observable props.
- Redux cost? — global coupling, boilerplate, effects in middleware.
- MV or MVVM in SwiftUI? — MV small/mid; add models as logic grows.

Example — one VIP use case

```
enum ListOrders { enum Fetch { // per use case
    struct Request {}
    struct Response { let orders: [Order] }
    struct ViewModel { let rows: [String] } }
protocol ListOrdersDisplayLogic: AnyObject {
    func display(_ vm: ListOrders.Fetch.ViewModel) }
final class ListOrdersInteractor { // BusinessLogic
    var presenter: ListOrdersPresenter?; let worker = OrdersWorker()
    func fetch(_ r: ListOrders.Fetch.Request) {
        worker.load { self.presenter?.present(.init(orders: $0)) } } }
final class ListOrdersPresenter { // PresentationLogic
    weak var viewController: ListOrdersDisplayLogic? // no cycle
    func present(_ r: ListOrders.Fetch.Response) {
        viewController?.display(.init(rows: r.orders.map(\.title))) } }
// VC: interactor?.fetch(.init()) in viewDidLoad
```

Interview traps

- ! “VIP is VIPER renamed.” VIPER's Presenter sits *between* View and Interactor, two-way; VIP is a one-way cycle (VC talks to the Interactor directly), no Entity layer, typed Request/Response/ViewModel per use case.
- ! VIP ownership: VC → Interactor → Presenter strong; Presenter → VC **weak**, or the scene never deallocates.
- ! RIBs' Router is not “just navigation” — it owns the *RIB tree*; screens are a side effect of attaching RIBs.
- ! Redux: every subscriber hears every change unless it selects a slice; keep ephemeral UI state (focus, scroll) out of the global store.
- ! MVI: a toast stored in State fires again on re-render — model it as a consumed event.
- ! “MV means no tests” — the logic moves to `@observable` models, which test fine; what you lose is a per-screen seam.

Remember

Place any pattern with 3 questions: who owns state? which way does it flow? where do effects live? VIP = cycle · RIBs = logic tree · MVI/Redux = one state + reducer.