


In one line: Teams stop arguing about JSON when **one machine-readable schema** — OpenAPI, GraphQL SDL, Protobuf or JSON Schema — is the **source of truth** in version control: every client and the server **generate** their types from it, CI **rejects breaking diffs**, and **contract tests** prove the provider still serves what each consumer uses — a mismatch fails a build, not a user's app.



The four contract languages

	shape	evolution rule
OpenAPI	REST/JSON; 3.1 = JSON Schema 2020-12 inside	add optional fields; deprecated: true; breaking → new path/version
GraphQL	one typed graph; clients pick fields per operation	never version: add fields, @deprecated(reason:), remove when unused
Protobuf	binary; field numbers are the wire identity	never reuse a number (reserved 3); unknown fields are kept same as OpenAPI; codegen via quicktype etc.
JSON Schema	payloads, events, config; validates at runtime	

Safe vs breaking — the table that matters

safe	breaking
add endpoint / operation	remove or rename a field / path
add optional response field	change a type (int → string)
add optional request field	make a request field required
loosen validation	tighten validation, shrink limits
add enum case if clients tolerate unknowns	add enum case for strict decoders

Mobile twist: old builds live for **years** — judge “breaking” against every one.

Example — OpenAPI → Swift, generated at build time

```
paths:
  /orders/{id}:
    get:
      operationId: getOrder
      parameters: [{name: id, in: path, required: true, schema: {type: string}}]
      responses:
        '200': {content: {application/json: {schema: {$ref: '#/components/schemas/Order'}}}}
# openapi-generator-config.yaml (beside it, in the target)
generate: [types, client]
accessModifier: internal

let client = Client(serverURL: URL(string: "https://api.example.com")!,
  transport: URLSessionTransport())
switch try await client.getOrder(path: .init(id: "42")) {
case .ok(let ok): let order = try ok.body.json // Components.Schemas.Order
case .undocumented(let status, _): throw APIError.unexpected(status)
}
```

swift-openapi-generator (Apple): SwiftPM **build plugin**, OpenAPI 3.0/3.1 (3.2 preliminary), transports for URLSession, AsyncHTTPClient, Vapor, Hummingbird; nothing generated is committed; every status is an enum case.

Contract tests — what they prove

- Schema checks** prove the *shape* is compatible. **Consumer-driven contracts** (Pact) prove the provider still serves what each consumer *actually uses* — the consumer's test writes the contract, the provider's CI replays it.
- Provider states** (“given order 42 exists”) seed each replay; can-i-deploy asks the broker if this version fits what is deployed — a gate for both sides.
- Pact ≠ E2E: contracts, not business behaviour. Bi-directional: pact vs OpenAPI.

Versioning and deprecation

- Prefer **additive evolution**, no version bump. Breaking: new field/endpoint beside the old, or /v2, or a dated header version (Stripe style).
- Deprecate in the schema, then on the wire: Deprecation: @1688169599 (RFC 9745, 2025) + Sunset: (RFC 8594) — sunset never earlier than deprecation.
- Measure usage **per app version** (User-Agent, an app-version header); remove only when traffic is ~0 or a **minimum-version / force-update** gate covers it.

Sharing models with React Native

- JS layer: TS types from the same schema (openapi-typescript, GraphQL Code Generator), not hand-written DTOs.
- JS ↔ native: the **TurboModule TS spec** is itself a typed contract — Codegen emits the ObjC++/Java interfaces; a mismatch fails the native build. Alternatives: KMP shared models for Android + iOS.

API review process

RFC with the schema diff → CODEOWNERS from each client team → lint + breaking check block the merge → mock + SDKs published → changelog → deprecation window in app adoption, not weeks.

Traps

- ! “Adding an enum value is backward compatible” — a strict Codable enum throws and the *whole* response fails. Decode unknowns to .unknown.
- ! Server sends null where the schema says non-nullable — the decoder fails. Validate responses against the schema in backend tests, or the spec drifts.
- ! Renaming a proto field is wire-safe for binary but breaks ProtoJSON and generated names; reusing a field number silently corrupts data.
- ! Hand-editing generated code — overwritten next build; extend it instead.

Remember

One schema, many generators; CI says no before users do; add, don't change; retire by version telemetry.