



In one line: Every Kotlin type has a **nullable twin**; the hierarchy is a lattice with Any? on top and Nothing (no values) at the bottom, so throw, TODO() and return fit any expected type. Generics are **invariant** unless declared out/in at the class (declaration site) or projected at a use; on the JVM type arguments are **erased**, so runtime checks see only List<*> — unless an inline function makes T **reified**.

The lattice — arrow = “is a subtype of”



Variance — what the arrow does to C<_>



Kotlin	Java	you may	PECS role
C<out T>	C<? extends T>	read T, write nothing	producer
C<in T>	C<? super T>	write T, read Any?	consumer
C<*>	C<?>	read upper bound, write nothing	unknown
C<T>	C<T>	both — invariant	both

Kotlin emits wildcards for parameters only (not returns, not final types);
@JvmSuppressWildcards/@JvmWildcard override it.

Top, bottom, platform

- Nothing makes failure branches type-check: val n: String = x ?: fail("no"). emptyList() is an object EmptyList : List<Nothing> — one instance fits every List<T> because List is out. Same trick: data object Loading : Load<Nothing>.
- Default upper bound of <T> is Any?: fun <T> f(t: T) accepts null. <T : Any> forbids it. T & Any = **definitely non-nullable** (1.7) — e.g. to override Java's @NotNull T.
- Platform type T!** (from un-annotated Java) = “T or T?, you decide”. @Nullable/@NonNull (JSpecify, AndroidX, JetBrains) turn it into a real type. Declare the type explicitly at the boundary.

Smart casts — exactly when

- Stable** values only: val locals; val properties that are not open, have no custom getter and live in the **same module**; var locals not changed between check and use (and not captured by a lambda that changes them). Never: var properties, delegated properties.
- K2** (2.0) adds: a check stored in a local (val isCat = a is Cat), a is B || a is C → closest common supertype, captured vars inside inline lambdas, info carried into catch/finally.
- Contracts** teach the compiler: requireNotNull, check, isEmptyOrNull smart-cast after the call; run/let promise callsInPlace. Your own contract {} still needs @OptIn(ExperimentalContracts::class).

Example

```
fun fail(msg: String): Nothing = throw IllegalStateException(msg)
sealed interface Res<out T> { // out: Res<Nothing> fits
    data class Ok<T>(val v: T) : Res<T>
    data class Err(val e: Throwable) : Res<Nothing>
}
fun copy(from: Array<out Any>, to: Array<in Any>) { /*...*/ } // use-site
fun <T> max(xs: List<T>): T where T : Comparable<T>, T : Any = xs.max()
fun <T> T.orThrow(): T & Any = this ?: fail("null") // DNN type
inline fun <reified T> Any?.asOrNull(): T? = this as? T
val t = typeOf<List<String>>() // reified: keeps the type ARGUMENT
if (x is List<*>) { // is List<String> = compile error
    @JvmInline value class Email(val raw: String) {
        init { require('@' in raw) } // validated, zero-cost when unboxed
    }
}
fun interface Rule { fun ok(s: String): Boolean }
val notBlank = Rule { it.isNotBlank() } // SAM conversion
```

Erasure & reified

- JVM keeps only the class: is List<String> = error, as List<String> = *unchecked* warning — the CCE fires later, at the first element read.
- reified (inline only): the call site pastes the real class, so is T, T::class, typeOf<T>() work. T::class.java still drops arguments (List<User> → List); typeOf keeps them.
- Erased overloads clash (f(List<String>)/f(List<Int>)) → @JvmName.

Variance in practice

- out T: T only in out positions (returns, val); escape hatch List.contains(e: @UnsafeVariance E). Array<T> is invariant (mutable), so copy(from: Array<out Any>) takes an Array<String> but cannot write into it.
- Star: Foo<out T : U> → Foo<*> reads U; Foo<in T> → Foo<*> = Foo<in Nothing>: writes nothing.

Sealed, value, alias, SAM

- sealed:** direct subclasses in the same **module + package**; when on sealed/enum/Boolean must be exhaustive (statements too, since 1.7) — skip else so a new subclass breaks the build.
- value class:** one val, unboxed; **boxed** as nullable, generic T, interface/Any; no ==; functions taking one get a **mangled JVM name** (send-<hash>).
- typealias** = new name, same type, no safety. **fun interface:** one abstract method → lambda converts (Java SAMs always did).

Traps

- ! fun <T> f(t: T): t may be null — the bound is Any?.
- ! val s = javaObj.name infers String!: NPE at first use, far away.
- ! No smart cast on open val/other-module val — copy to a local.
- ! List<Email> of a value class = boxed elements; saving gone.

Remember: Any? top · Nothing bottom · out produces, in consumes · erased unless reified.