

In one line: Accessibility: VoiceOver walks a tree of *elements* and speaks each one's **label, value, traits, hint**; text must scale with **Dynamic Type**; honour user settings (Reduce Motion, contrast). **Localization:** every user-visible string is a *whole sentence* in a **String Catalog**, arguments are **positional**, plurals follow **CLDR** rules, layout is **leading/trailing**, and numbers/dates go through **formatters**.

Accessibility

- **Label** = what it is ("Volume" — never "Volume button", the trait says button). **Value** = current state ("70%"). **Traits** = role/state (.button .header .selected .adjustable .notEnabled). **Hint** = result of acting, spoken last, after a pause; users can turn hints off.
- `isAccessibilityElement = true` makes a view a leaf; on a container it *hides the children*. Order children with `accessibilityElements = [...]`. Decorative: `.accessibilityHidden(true)`.
- **Grouping** (SwiftUI) `.accessibilityElement(children:)`: `.combine` (one swipe, merged) · `.ignore` (you label it) · `.contain` (keep children, group them).
- `.adjustable` needs `accessibilityIncrement()` / `Decrement()` (SwiftUI `.accessibilityAdjustableAction`).
- **Custom actions** (`UIAccessibilityCustomAction`, `.accessibilityAction(named:)`) expose swipe/long-press actions via the **Actions rotor**; custom **rotors** (`.accessibilityRotor`) jump between headings/links. Announce: `UIAccessibility.post(notification: .announcement, ...)`.
- `accessibilityIdentifier` is for **UI tests**: stable, not localized, never spoken.
- **Dynamic Type**: `UIFont.preferredFont(forTextStyle:)` or `UIFontMetrics(forTextStyle:).scaledFont(for:)`, plus `adjustsFontForContentSizeCategory = true` (default false) and `numberOfLines = 0`. SwiftUI text styles scale by themselves; custom sizes: `@ScaledMetric`. At the accessibility sizes, stack vertically.
- **Settings**: Reduce Motion (`\.accessibilityReduceMotion`: swap zooms for fades), Reduce Transparency, Increase Contrast, Bold Text. Never colour alone.
- **Audit**: Accessibility Inspector · `XCUUIApplication().performAccessibilityAudit()` (Xcode 15).


Localization

- **String Catalog** `.xcstrings` (Xcode 15, JSON): keys extracted at build, per-language state, plural + device variants inline. Replaces `.strings + .stringsdict`.
- Code: `String(localized: "key", defaultValue:, comment:)` (iOS 15), `LocalizedStringResource`; SwiftUI `Text("literal")` is a `LocalizedStringKey`. Packages: bundle: `.module`. Always a comment:.
- **Plurals**: "Vary by plural" — the language's CLDR categories (table). Never count == 1 ? :.
- **RTL**: leading/trailing + `.natural` alignment mirror; left/right never do. Opt out per view with `semanticContentAttribute(.playback for media controls)`; SwiftUI `\.layoutDirection`.
- **Formatters**: `date.formatted(...)`, `.currency(code:)`, `Measurement(km↔mi)`. Formats follow `Locale.current` (region settings); the UI language is `Bundle.main.preferredLocalizations`.
- **Test**: pseudolanguages (Accented, Bounded, Double-Length, Right-to-Left); vendors get *Export Localizations* (.xcloc = XLIFF + context).

A volume row, done right


```
HStack { // a volume row
  Image(systemName: "speaker.wave.2").accessibilityHidden(true)
  Text("Volume") // LocalizedStringKey
  Slider(value: $level)
}
.accessibilityElement(children: .ignore)
.accessibilityLabel("Volume") // no "slider" - trait adds it
.accessibilityValue(Text(level, format: .percent))
.accessibilityAdjustableAction { // swipe up / down
  level += $0 == .increment ? 0.1 : -0.1
}
.accessibilityIdentifier("settings.volume") // tests only
// catalog key "%lld files deleted", varied by plural
let msg = String(localized: "%(count) files deleted",
  comment: "Toast after bulk delete")
```

What VoiceOver says



identifier "settings.volume" — never spoken, XCTest only

Positional arguments & mirroring



Numbers

Contrast (WCAG AA)	text ≤ 17 pt ≥ 18 pt, or bold	4.5:1 3:1
Hit target default / min	iOS, iPadOS, watchOS visionOS macOS · tvOS	44 / 28 pt 60 / 28 pt 28 / 20 · 66 / 56 pt
CLDR plurals		
ja	other	
en	one other	
pl · ru	one few many other	
ar	zero one two few many other	

Traps

- ! "Play button" as label → "Play button, button".
- ! `isAccessibilityElement` on a container hides its children.
- ! `preferredFont` without the `adjustsFont...` flag → never re-scales.
- ! UI tests matching localized labels — use `accessibilityIdentifier`.
- ! `"\ (n) " + "items"` — breaks word order *and* plurals.
- ! `Text(aStringVar)` is *not* localized — only literals / keys.

Remember

"L-V-T-H" — Label, Value, Trait, Hint (the order VoiceOver speaks). **Localize sentences, not words; lead, don't left.**