



In one line: Pinning adds an **app-level rule on top of normal validation**: the verified chain must contain a **public key you chose** (its SPKI hash). It stops a *mis-issued, compelled or user/MDM-installed CA* from intercepting you — and turns any unplanned key change into an **outage only an app update fixes**. Android calls it “**not recommended**”, Apple “**not required**”; **CT** and **CAA** now cover most of the mis-issuance risk. Pin only when the threat model demands it, and then with backups.

Why pins brick apps — one year of key rotation



Lesson: pin keys you will move with; generate the backup (K3) now and keep it offline; ship an expiry and a remote off-switch; never pin a key someone else rotates.

Should you pin?



How it works

- What is hashed:** the certificate's **SubjectPublicKeyInfo** (DER: algorithm OID + key) → SHA-256 → base64. A key pin survives renewal if the key is reused (e.g. certbot --reuse-key); a *certificate* pin dies at every renewal.
- When:** after the OS validated chain, name and dates. A pin only narrows trust — Apple: “can only tighten” it.
- Match:** passes if **any one** pinned key is found — Android/OkHttp: anywhere in the chain; Apple: in the leaf (LeafIdentities) or a CA cert (CAIdentities). That is why a backup pin works.
- Which key:** your **leaf** key (you control rotation) or your *private* CA. Not a public intermediate — Let's Encrypt issues from several (R10–R14, E5–E9) and rotates them *on purpose* to discourage pinning. Root: survives most things, protects little.
- Shorter cert lives (200 → 47 days by 2029) mean more rotations — more chances to brick.

Implementations

NSPinnedDomains	iOS 14+, Info.plist, no code; NSPinnedLeafIdentities / NSPinnedCAIdentities; NSIncludesSubdomains = one level only
URLSessionDelegate	trust challenge; SecTrustEvaluateWithError first, then hash the chain's keys; full control (per-request, remote pin lists)
TrustKit	iOS 12+: pins, expiry, failure reports to a URL, optional swizzling
Android NSC	<pin-set expiration> (API 24+); expired → pinning off (fails open)
OkHttp	CertificatePinner “sha256/...” — also what RN libraries wrap

Example — the same policy, both platforms

```
<!-- res/xml/network_security_config.xml -->
<domain-config>
  <domain includeSubdomains="true">api.example.com</domain>
  <pin-set expiration="2027-06-30">
    <pin digest="SHA-256">LIVE_KEY_BASE64=</pin>
    <pin digest="SHA-256">OFFLINE_BACKUP_BASE64=</pin>
  </pin-set>
</domain-config>
Info.plist > NSAppTransportSecurity > NSPinnedDomains
api.example.com > NSPinnedLeafIdentities = [
  { SPKI-SHA256-BASE64 = LIVE_KEY_BASE64= },
  { SPKI-SHA256-BASE64 = OFFLINE_BACKUP_BASE64= } ]

openssl x509 -in leaf.pem -pubkey -noout | openssl pkey -pubin \
-outform der | openssl dgst -sha256 -binary | base64
```

What the platforms say (2026)

- Android:** pinning “is **not recommended** for Android apps” — a CA change strands every installed version. If you must: **multiple backup pins**, one key fully yours, a **short expiration**.
- Apple:** “Pinning certificates is **not required**...only if absolutely necessary”; several keys per domain, plan recovery.
- Browsers gave up first: HPKP (RFC 7469) left Chrome in 2019 (*unverified*).

Certificate Transparency and CAA — the alternatives

CT (RFC 6962): CAs log every public cert in append-only Merkle-tree logs and embed the **SCTs** (signed promises of inclusion). Clients *refuse* unlogged certs: Apple since certs issued after 15 Oct 2018 (all apps, not only Safari); **Android 16** opt-in <certificateTransparency enabled="true"/>, default from **Android 17**. Owners watch the logs (crt.sh, alerts) → a rogue cert for your name is seen. CT is **detective**; pinning is **preventive**. **CAA** (RFC 8659): DNS example.com CAA 0 issue "letsencrypt.org" (+ issuwild, iodef); every public CA must check it before issuing. Stops honest CAs, not a compromised one.

Still justified when...

You control server *and* key custody, **and** the attacker can plausibly install a CA or coerce one: banking, payments, health, gov, enterprise apps on managed devices, or a regulator/pentest requirement (OWASP MASVS-NETWORK-2 (*unverified*)). Not for: CDN/third-party hosts, web content, “stopping reverse engineering”.

Traps

- ! “Pinning stops API reverse engineering” — a jailbroken/rooted phone with Frida or a kill-switch tweak disables it in minutes. It protects the *user* from a MITM, not your API from the user.
- ! Pin check *instead of* default evaluation: expired or wrong-host certs pass.
- ! Android expiration fails **open**; an off-switch fetched over the pinned channel cannot turn itself off — fetch it elsewhere.
- ! Pinning the leaf *certificate* (not key) with 90-day certs: planned outages.
- ! Debug proxies (Charles, Proxyman) need the CA in debug-overrides — debuggable builds only.

Remember

“Pin keys, not certs; pin yours, not theirs; always a backup, an expiry and a way out.”