


In one line: **MASVS** v2.1.0 (Jan 2024) is the standard: **24 controls in 8 groups** saying *what* a secure app does. **MASWE** catalogues *how it fails* (78 weaknesses, v1.0.0 Aug 2026), **MASTG** says *how to test*, and a **MAS profile** (L1 · L2 · R · P) says *how much* to test. The **Mobile Top 10** (2024) is an awareness list of risks, not a checklist.



The MAS family

- MASVS** = *what* (controls) → **MASWE** = *how it fails* (weakness IDs MASWE-0001...0078) → **MASTG** = *how to test* (tests, techniques, tools, demos, per iOS/Android).
- v2.0.0** (Apr 2023) rewrote v1: short, platform-agnostic controls and **no verification levels** in the standard. **v2.1.0** (Jan 2024) added only **MASVS-PRIVACY** (+ CycloneDX format).
- Levels became **MAS testing profiles** (2026: own “MAS Profiles” section): **MAS-L1** baseline for every app · **MAS-L2** defence in depth for sensitive data (banking, health) · **MAS-R** resilience against reverse engineering + tampering, *on top of* L1/L2 · **MAS-P** privacy. OWASP prefers a profile cut from *your* threat model over the defaults.
- Same control, different depth per profile: pinning (NETWORK-2) or anti-debugging (RESILIENCE-4) are L2 / R territory.

The 24 controls (“The app ...”, condensed)

STORAGE	1 stores sensitive data securely · 2 prevents its leakage
CRYPTO	1 current strong crypto, used per best practice · 2 key management
AUTH	1 secure authN/authZ protocols · 2 local auth per platform practice · 3 extra auth for sensitive operations
NETWORK	1 secures all traffic · 2 identity pinning for endpoints <i>under the developer’s control</i>
PLATFORM	1 IPC used securely · 2 WebViews used securely · 3 UI used securely
CODE	1 requires an up-to-date platform · 2 can enforce updates · 3 no components with known vulns · 4 validates + sanitises untrusted input
RESILIENCE	1 validates platform integrity · 2 anti-tampering · 3 anti-static analysis · 4 anti-dynamic analysis
PRIVACY	1 minimises access · 2 prevents identification of the user · 3 transparent · 4 user control

Example — map one feature (“pay a friend”, profile L2 + R)

inventory item	control → what you verify
refresh token	STORAGE-1: Keychain, ThisDeviceOnly; AUTH-1: server revokes
payee list cache	STORAGE-2: not in backups, logs, Cache.db
pay://send?to= link	PLATFORM-1 + CODE-4: parse, allowlist, confirm screen
T&C WebView	PLATFORM-2: no bridge, HTTPS only, own domain
payment API	NETWORK-1/2: ATS on, pinned; AUTH-3: biometric-bound key signs
cloned / hooked app	RESILIENCE-1/2 as <i>signals</i> ; server checks attestation

Findings are written as **MASWE id** → **MASVS control**, rolled up to Top 10 buckets for managers.

OWASP Mobile Top 10 — 2024 (final)

M1	Improper Credential Usage	hard-coded keys, creds stored/sent badly
M2	Inadequate Supply Chain Security	bad SDKs, build + signing compromise
M3	Insecure Authentication / Authorization	client-side checks, spoofable IDs
M4	Insufficient Input/Output Validation	injection via links, WebViews, IPC
M5	Insecure Communication	cleartext, broken cert validation
M6	Inadequate Privacy Controls	PII over-collected, leaked, undeletable
M7	Insufficient Binary Protections	reverse engineering, tampering, repacks
M8	Security Misconfiguration	exported components, debug flags, backups
M9	Insecure Data Storage	plaintext files, prefs, DB, logs, caches
M10	Insufficient Cryptography	weak algorithms, ECB, static IV, DIY

vs 2016: **credentials**, **supply chain**, **input/output validation** and **privacy** are new headline risks; 2016’s separate authentication and authorization merged into M3. Top 10 = *what to talk about*; MASVS = *what to verify*.

How to run the review

- Inventory: data, entry points (links, IPC, WebViews, push), SDKs, endpoints.
- Threat model → profile: L1 always; L2 sensitive data; +R if the client itself holds value; +P personal data.
- Map items to controls; run that profile’s MASTG tests on both platforms.
- Report MASWE-tagged findings; fix server-side first; re-test.

Traps

- ! “We’re MASVS-L2 compliant” — v2 has no levels; say “MASVS v2.1, tested against the MAS-L2 profile”.
- ! The Top 10 is not a standard you “comply” with; audits use MASVS/MASTG.
- ! RESILIENCE never replaces L1/L2: an obfuscated app that logs tokens is still M9.
- ! NETWORK-2 covers endpoints *you* control — not an analytics SDK’s host.
- ! M1 is not “weak passwords”: it is *secrets in the client* — anything shipped is public.

Remember

MASVS says *what*, **MASWE** *how it fails*, **MASTG** *how to test*, the profile *how much*, the **Top 10** *what to talk about*.