


Threat modelling a mobile feature — DFD, trust boundaries, STRIDE

security · folio

In one line: Threat modelling is answering four questions *while designing*: **What are we working on?** (draw the data flow) · **What can go wrong?** (STRIDE at every **trust boundary**) · **What are we going to do about it?** (mitigate, eliminate, transfer, accept) · **Did we do a good enough job?** (tests, review). On mobile the first boundary is the device itself: the client is in the attacker's hands, so **the server enforces**.

Worked DFD — “pay with a saved card”



The process

- Scope + DFD:** one feature, level-0/1 data-flow diagram: external entities, processes, data stores, flows. Include the unglamorous paths: push, deep links, WebViews, analytics SDKs, logs, backups, support tools.
- Assets + classification:** secrets (tokens, keys), regulated (card data, health), personal (PII, location), internal, public. The class sets the controls.
- Trust boundaries:** wherever data changes privilege — device ↔ network, app ↔ other apps (URL schemes, pasteboard, extensions), WebView ↔ native, backend ↔ third party.
- Enumerate threats:** STRIDE per element, hardest at boundary crossings; attack trees for the crown jewels; abuse cases (“a user who ...”).
- Rate + respond:** likelihood × impact → **mitigate, eliminate** (drop the data or feature), **transfer** (PSP, insurer), **accept** (written down, owner signs).
- Validate:** each mitigation gets a test or review item; the model lives in the repo and is revisited when the design changes.

STRIDE — six threats, six properties

threat	violates	mobile example	mitigation
Spoofing	authentication	stolen token, fake server, other user	OAuth + PKCE, short tokens, TLS, App Attest
Tampering	integrity	edited price, patched app	server-side rules, signed data, AEAD
Repudiation	non-repudiation	“I never paid”	server audit log, signed receipts
Info disclosure	confidentiality	PAN in logs, snapshot, IDOR	tokenize, redact, object-level authZ
Denial of service	availability	retry storms, card testing, SMS pumping	rate limits, backoff, quotas
Elevation of privilege	authorization	isAdmin in the client, hidden debug menu	authZ on every request

STRIDE per element (Shostack)

	S	T	R	I	D	E
external entity	✓		✓			
process	✓	✓		✓	✓	✓
data store			(logs)	✓	✓	
data flow		✓		✓	✓	

Cuts the checklist: ask only the questions that apply to each shape.

Rating risk — and the DREAD debate

DREAD (Damage, Reproducibility, Exploitability, Affected users, Discoverability) scores each 1–10; Microsoft dropped it — “different people selected very different numbers” (Shostack, 2008). Prefer **likelihood** × **impact** on a 3-level scale (OWASP Risk Rating), CVSS for concrete vulnerabilities, and a ranked top-N. Related methods: **PASTA** (risk-centric), **LINDUN** (privacy threats), **attack trees**.

Enforce on the server

The device owner controls the binary, memory, storage and network (own CA → pinning bypassed). So anything the client *decides* is a suggestion: price, discount, role, entitlement, “OTP already verified”, rate limit, feature flag for paid features. Client checks are UX; attestation (App Attest / Play Integrity) raises the cost, it does not create trust. Check object ownership on every ID (GET /orders/123 of another user = BOLA, OWASP API11).

Example — one row of the threat register

```
- id: T3
element: flow 2 (app -> API, crosses TB1)
stride: Tampering
threat: user edits price/total in POST /orders (proxy, Frida)
risk: likelihood high x impact high => HIGH
mitigation: server prices the cart from its catalogue;
             client total is display-only; Idempotency-Key
             stops double charges on retry
verify: API test posts a tampered total, expects server price
status: mitigated
```

More rows for this DFD: token theft from a backup (S) → Keychain ThisDeviceOnly + rotation; forged webhook (S/T) → verify HMAC + timestamp; replayed payment (T) → idempotency; PAN in logs/analytics (I) → PSP SDK + redaction.

Traps

- ! “It’s our app, so the client is trusted” — TB1 sits at *the device*.
- ! A one-off document at the end — it is a design activity, redone when the flow changes.
- ! Only the happy path: forgetting deep links, push payloads, backups, logs, SDKs, support tools.
- ! Everything rated “High” — no priority; DREAD decimals are false precision.
- ! Pinning or obfuscation as *the* mitigation — they slow an attacker, the server decides.

Remember

Draw it, box the boundaries, STRIDE every crossing, rank, fix, test — and never let the client decide what the server must enforce.

Related: encoding-encryption-hashing-signing (HMAC webhooks) · oauth-oidc-jwt · keychain-secure-enclave · app-hardening-privacy (App Attest) · api-design (idempotency) · tls-pki