



In one line: Git is a **content-addressed object store** plus **movable pointers**. A **commit** is a full *snapshot* (a tree) with pointers to its **parent(s)**; history is the resulting **DAG**; a **branch** is just a ref naming one commit. **Merge** adds a commit with two parents (history kept); **rebase** *re-creates* your commits on a new base (new IDs, linear history) — which is why rebasing commits others already have breaks their clones.


Objects + refs




Before



git merge feature (on main)



git rebase main (on feature)



How it works

- **4 object types:** blob (content), tree (names + modes → blobs/trees), commit (tree + parents + author/committer + message), annotated tag. Stored zlib'd, later delta-packed; a commit is a snapshot, diffs are computed on demand. Default hash SHA-1 (SHA-256 repos exist).
- **Refs:** a branch is a file with a commit ID; HEAD names the current branch (detached = a raw ID). origin/main is a remote-tracking ref, moved only by fetch. The **index** is the next commit's tree.
- **Fast-forward:** target is an ancestor → move the ref, no commit (--ff-only insists, --no-ff forces a merge commit to keep the feature visible).
- **Squash merge:** one new commit on main; the branch's commits are *not* ancestors, so a branch continued after it conflicts with itself — delete it.

Conflicts

- A **3-way merge** compares base (git merge-base) with both sides; only lines both changed conflict. merge.conflictStyle = zdiff3 also prints the *base* — resolve by intent.
- In a **rebase**, --ours = the branch you are rebasing *onto*, --theirs = your replayed commit — the reverse of a merge.
- **rerere** (rerere.enabled true) records each resolved hunk and re-applies it when the same conflict returns: repeated rebases, back-merging a release branch.
- Escape hatches: git merge --abort, git rebase --abort.

Example — git bisect with a run script

```
git bisect start
git bisect bad HEAD           # broken now
git bisect good v5.11.0       # last known good tag
git bisect run ./repro.sh     # ~log2(N) builds
git bisect reset              # back to where you were
# repro.sh -- exit 0 good, 1..127 bad, 125 = skip
xcodebuild build-for-testing -scheme App -quiet || exit 125
xcodebuild test-without-building -scheme App \
  -only-testing:AppTests/CartTests/testTotal || exit 1
```

1,000 commits → ~10 steps. A build that fails for an unrelated reason must **skip** (125), not say "bad". git bisect skip by hand; --first-parent walks only merges into main.

Recovery — the reflog

Every move of HEAD and each branch tip is logged *locally*: git reflog → git branch rescue HEAD@{3}. Survives a bad rebase, reset or deleted branch; entries expire (gc.reflogExpire 90 days, unreachable 30). Never pushed — another clone cannot help.

Remember

"Snapshots in a DAG, branches are pointers, rebase makes new commits — never under someone else."

Branching strategies

Model	Shape	Fits
trunk-based	branches live hours–2 days, merge to main daily; unfinished work behind flags	CI/CD, large teams
GitHub flow	main + PR branches, main always releasable	web, continuous deploy
GitFlow (2010)	develop, feature/*, release/*, hotfix/*, main = shipped	versioned products; its author (2020) points CD teams to simpler flows
mobile: trunk + release branches	cut release/5.12 at code freeze; only fixes land there; tag each build	store review + phased rollout

Hotfix a shipped version

Fix on main first (with a test), then git switch release/5.12, git cherry-pick -x <sha> (-x records "cherry picked from commit ..."), bump the build number, tag v5.12.1. One direction by policy — fixes made only on the release branch get lost in 5.13.

Team scale

- **Merge queue** (GitHub merge queue, GitLab merge trains): each PR is re-tested on top of main *plus the PRs queued ahead*, then merged in order. Fixes "two green PRs, red main" (semantic conflicts no text merge sees).
- **Monorepo:** git sparse-checkout set --cone apps/ios packages/ui, partial clone --filter=blob:none, LFS for big binaries, git maintenance start. **CODEOWNERS** (.github/, root or docs/): *last* matching pattern wins; branch protection makes owner review required.
- **Signed commits:** commit.gpgsign true with GPG, SSH (gpg.format ssh) or X.509; "Verified" proves *who* committed, not that the code is safe.

Traps

- ! Build number from git rev-list --count HEAD on a CI **shallow clone** (--depth 1) = 1 → upload rejected. Shallow clones also break bisect and describe.
- ! push --force over a teammate's commits — use --force-with-lease.
- ! git pull merge-commit noise — set pull.rebase true or pull.ff only.