


In one line: An RN app on Android fails in **five** ways — fatal **JS** error, **JVM** exception, **native signal** in a **.so**, **ANR** (main thread blocked **5 s** on input), **silent kill**. Each leaves a *different* record read by a *different* tool.



ANR — what triggers it (exact)

- **Input dispatch:** no response to a key/touch within **5 s**.
- **BroadcastReceiver** not finished in time — **5 s** with a foreground activity.
- **startForegroundService()** without **startForeground()** within **5 s**.
- **Service** onCreate/onStartCommand/onBind and **JobService** onStartJob/onStopJob: "a few seconds" (job ANRs are reported to the app only when targeting Android 14+).
- Causes: **I/O** or heavy work **on main**, **deadlocks**, slow onReceive(), **binder** calls.

The RN angle

- ANRs are about the **main (UI) thread**. A busy **JS** thread freezes your React UI but the main thread still consumes input — usually *no* ANR, so it hides from vitals: measure JS stalls yourself (Longtask observer).
- Typical RN ANRs: SDK init in MainApplication.onCreate, a native module doing I/O on the UI thread, main blocked on a lock another thread holds.
- Native crashes in RN often sit in libhermes.so / libreactnative.so (merged lib since 0.76) — the *cause* is often a native module misuse higher up. A fatal JS error in release surfaces as a JVM crash (JavaScriptException (unverified) carrying the JS stack).

Diagnose

- **StrictMode** (debug): flags disk/network on main before users see an ANR.
- **Traces:** /data/anr/anr_* (was traces.txt); no root? adb bugreport.
- **ApplicationExitInfo** (API 30): REASON_ANR, REASON_CRASH, REASON_CRASH_NATIVE, REASON_LOW_MEMORY...; getTraceInputStream() = the ANR trace, or the tombstone as protobuf.
- **Tombstones:** logcat DEBUG = signal, fault address, registers, backtrace; the file adds every thread, maps, fds. Written by crash_dump since 8.0 (debuggerd before). SIGSEGV = bad memory access; SIGABRT = abort() (assert, uncaught C++ exception).
- **R8:** retrace + that build's mapping.txt (AAB + AGP 4.1+: Play takes it itself). Native: ndk { debugSymbolLevel 'SYMBOL_TABLE' } or 'FULL'.

Example — commands + in-app capture

```
# one app only, crash buffer, JS + crash tags
adb logcat --pid=$(adb shell pidof -s com.example.app)
adb logcat -b crash -d
adb logcat ReactNativeJS:V AndroidRuntime:E DEBUG:V *:S
adb bugreport ./bug.zip # ANR traces, tombstones
adb logcat -d | $NDK/ndk-stack -sym \
  app/build/intermediates/cxx/RelWithDebInfo/<hash>/obj/arm64-v8a
retrace mapping.txt stack.txt # R8, per build

// next launch: why did the last process die?
val am = getSystemService(ActivityManager::class.java)
am.getHistoricalProcessExitReasons(packageName, 0, 5)
  .filter { it.reason == ApplicationExitInfo.REASON_ANR }
  .forEach { i -> i.traceInputStream?.use { upload(it) } }

// debug builds: catch main-thread I/O early
if (BuildConfig.DEBUG) StrictMode.setThreadPolicy(
  StrictMode.ThreadPolicy.Builder().detectDiskReads()
    .detectDiskWrites().detectNetwork().penaltyLog().build())
```

Logcat essentials

- Filter spec TAG:LEVEL (V D I W E F S), *:S silences the rest; --pid scopes to one process; -b crash = crash buffer; -d dump and exit; -c clear. A new PID after a crash = the process restarted — re-run pidof.
- Paste a tombstone to ndk-stack with its first *** *** *** line, or it finds nothing.

Traps

- ! "Move it to a coroutine" when main is *waiting* on that coroutine (runBlocking) — still an ANR, and a deadlock risk.
- ! Symbolicating with the wrong build's .so/mapping — the build ID must match; output looks plausible and is wrong.
- ! Not every ANR has a stack in your code: the main thread may be idle in nativePollOnce when the trace is taken (the block already ended).

Remember

Five failures, five records: ReactNativeJS · AndroidRuntime · DEBUG/tombstone · /data/anr · ApplicationExitInfo.