


In one line: A cold start runs **native init** → **JS runtime** → **bundle load** → **module factories** (the top-level code of every imported module) → **first render/mount** = **TTID** → real content = **TTFD/TTI**. Every optimisation is “do less before the first frame”: precompiled bytecode, lazy modules, a thin root, deferred SDKs. Measure it on a **release build** on a **low-end Android**.



How it works

- **Cold** = new process (everything above); **warm** = process alive, activity recreated; **hot** = brought to front. Optimise and report *cold*.
- **Hermes** compiles JS to bytecode *at build time* (release builds only); bytecode is loaded on demand, no parse. **Hermes V1** (opt-in 0.82, default **0.84**): Expensify measured Android low-end —3.2% bundle load / —7.6% TTI, iOS —9% / —2.5%.
- **Module factories:** Metro wraps each module in a function; `import` runs it at first require. A root that imports every screen runs them all at start. **Inline requires** move each require to its first use, so unused paths never execute. RN CLI inlines requires by default; Expo: enable `inlineRequires` in `metro.config.js`.
- **RAM bundles** (indexed/file bundles, parse on demand) — legacy, **not supported with Hermes**; Hermes’ on-demand bytecode replaces them.
- **TurboModules** initialise on first access (legacy modules all at start); a module touched in the root still costs at startup.
- **Splash:** iOS launch storyboard; Android 12+ always draws the system splash (`installSplashScreen()`, `setKeepOnScreenCondition()`; Expo: `SplashScreen.preventAutoHideAsync()` → `hideAsync()` when the first screen has laid out.

Example — lazy paths + marks

```
// index.js - first line executed
performance.mark('js-start');
// screens off the first path load on navigation
const Settings = lazy(() => import('./Settings'));
let Charts = null; // lazy require
const openCharts = () => {
  Charts ??= require('./Charts').default; nav('charts'); };
function Home() {
  const feed = useFeed(); // cache first, then network
  useEffect(() => { if (feed.ready)
    performance.measure('ttfd', 'js-start'); }, [feed.ready]);
} // PerformanceObserver ships 'measure' entries to analytics
```

Where the time really goes

- **Native:** analytics/crash/ads SDKs in `onCreate` / `didFinishLaunching`, synchronous storage reads, big DI

graphs — defer until after first frame or init on a background thread.

- **JS:** moment/lodash-size deps, i18n loading every locale, a store rehydrating megabytes before render, polyfills, JSON config parsing.
- **First render:** a navigator that builds every tab, providers that compute on mount, images decoded at full size.

Bundle analysis

- `npx react-native-bundle-visualizer@latest (--expo for Expo)` — source-map-explorer over Metro’s output, treemap per package.
- Expo Atlas: `EXPO_ATLAS=true npx expo export`, then `npx expo-atlas .expo/atlas.jsonl`.
- source-map-explorer on a Hermes export needs `--no-bytecode`.

Traps

- ! Timing a **debug** build: bundle streamed from Metro, no bytecode, dev checks — startup numbers mean nothing.
- ! Inline requires change **evaluation order**: modules with side effects (polyfills, global setup) break — `blockList` / `nonInlinedRequires`.
- ! A long splash makes TTID look great; users feel **TTFD**. Report both.
- ! “Use RAM bundles” on a Hermes app — not supported, and not needed.
- ! A lazy screen with module side effects (subscribing, globals) defeats laziness.

Remember

Less native init · bytecode · lazy modules · thin root · cached first paint — and measure TTID *and* TTFD on a release build.