

In one line: You never animate frame by frame: you **change state** (SwiftUI) or set the **final value** (UIKit) *inside an animation context*, and the framework interpolates every **animatable** property old → new. The questions are always: *which* change is in the context, and *can* it be interpolated?

SwiftUI

- **Explicit** `withAnimation(.spring) { open.toggle() }`: animates *every* view depending on state changed in the block (mutation site decides). **Implicit** `.animation(.easeIn, value: s)`: only changes of `s`, only in that subtree (view decides). `.animation(_:)` without value: is deprecated — it animated *any* change.
- **Transaction** carries the animation through one update: `withTransaction` is the general form; `.transaction { $0.animation = nil }` strips an inherited one; `disablesAnimations = true` forces a snap.
- **Animatable**: built-in modifiers interpolate (opacity, offset, scale, frame, colour). A custom Shape/modifier must expose `animatableData: VectorArithmetic` (two values → `AnimatablePair`) — otherwise it *jumps*.
- **Transition** (`.opacity`, `.move(edge:)`, `.asymmetric(insertion:removal:)`) = entering or leaving the tree: needs an **identity change** (if, new .id) *and* an animation context, and sits on the conditional view.
- **matchedGeometryEffect(id:in:)**: same id, same @Namespace, views mounted *exclusively*, inside `withAnimation` → hero morph.
- **Springs** (default since iOS 17): `.spring(duration: 0.5, bounce: 0.2)`, `.smooth/.snappy/.bouncy`. Interruptible, re-target *keeping velocity*; curves have fixed duration.
- **iOS 17**: `PhaseAnimator` steps through discrete phases (loop or trigger:); `KeyframeAnimator` = timed per-property `KeyframeTracks` (Linear/Spring/CubicKeyframe).

Example


```
struct Ring: Shape {
    var p: CGFloat // 0...1
    var animatableData: CGFloat { get { p } set { p = newValue } }
    func path(in r: CGRect) -> Path { Path() } // arc to p
}

struct Card: View {
    @State private var open = false
    @Namespace private var ns
    var body: some View {
        if open { Big().matchedGeometryEffect(id: "c", in: ns) }
        else { Small().matchedGeometryEffect(id: "c", in: ns) }
        Button("Go") { withAnimation(.snappy) { open.toggle() } }
    }
}
```

UIKit


- `UIView.animate(withDuration:...)`: set *final* values in the block. Animatable: frame, bounds, center, transform, alpha, backgroundColor; text/isHidden snap. Springs: `usingSpringWithDamping: (<1 bounces)`; iOS 17 `animate(springDuration:bounce:)`.
- **UIViewPropertyAnimator** is an *object*: `startAnimation()`, `pauseAnimation()`, `scrub fractionComplete`, `isReversed`, finish with `continueAnimation(withTimingParameters:...)` — interruptible gesture-driven UI.
- **Auto Layout**: change constant, then `layoutIfNeeded()` *inside* the block (flush once before).
- `UIView.transition(with:...)` + `.transitionCrossDissolve`; custom VC transitions must call `completeTransition(_:)`.

Model vs presentation



UIView animations set the model for you. A raw `CABasicAnimation` drives only the presentation ⇒ it **snaps back** unless you also set the model value.

When does a transition run?



Traps

- ! `withAnimation` animates *all* dependent views — scope with `.animation(_:value:)` or strip with `.transaction`.
- ! `.transition` without an animation = instant; on a stable ancestor = never runs.
- ! Custom Shape jumps → no `animatableData`. `matchedGeometry` glitch → both views mounted / two namespaces.
- ! Layer animation snaps back → model never set (`fillMode = .forwards + isRemovedOnCompletion = false` only hides it).
- ! Constraint change jumps → no `layoutIfNeeded()` inside the block.
- ! Scrubbing a spring: `pauseAnimation()` first; `fractionComplete` maps through the curve.

Remember

“State in the block, value in the modifier, identity for transitions.” UIKit: *final value in — the model is already there.* Cheapest to animate: transform, opacity.