


In one line: DI = a type **receives** its collaborators instead of creating or finding them. The substance: *where* the graph is built (one **composition root**), *how long* each object lives (**scopes**; never long-lived holding short-lived), *who* may ask a container (only the root — anywhere else it is a **service locator**). Environment and @Dependency are *ambient* DI: handy, but the dependency leaves the init.



How it works

- Constructor** — default: required, let, never half-built.
Property — optional/late (storyboard VCs); risk: used before set. **Method** — varies per call. **Ambient** — looked up from an implicit scope (@Environment, @Dependency, @TaskLocal).
- Composition root** (Seemann): one place near the entry point where the graph is composed. Coordinators/factories are *sub-roots* handed what they need.
- Pure DI** = hand-wired, no library, compile-checked; a **container** automates wiring + lifetimes. Container vs locator depends on *where it is called*, not on the library.
- Scopes**: app · session (rebuild on logout) · screen/flow (owned by its coordinator) · transient. **Captive dependency**: a longer-lived object holding a shorter-lived one keeps it alive past its scope.
- Cycles**: usually a smell — extract the shared part into C, or let one side emit events. Else break one edge: weak property or a lazy provider closure. Swinject: initCompleted + a property; init↔init cycles unsupported.

Example — Pure DI at the root

```
@MainActor final class AppContainer { // built ONCE, App.init
    let http = HTTPClient(session: .shared) // app scope
    let db = Database(file: "app.sqlite")
    var session: UserSession? // session scope
    func logout() { session = nil } // drop that scope
    func makeFeed() -> FeedViewModel { // screen: new each
        FeedViewModel(repo: FeedRepository(http: http, db: db),
            now: { Date() }) } // closure dependency
}
```

Remember

One root builds, everyone else receives. Arrows point to longer lives. A container asked from inside a type is a locator.

SwiftUI Environment = DI by tree position

```
extension EnvironmentValues {
    @Entry var api: APIClient = .live // Xcode 16 macro
    struct FeedView: View {
        @Environment(\.api) private var api // absent: default
        @Environment(Session.self) private var session // absent: CRASH
        var body: some View { Text(session.name) } }
    FeedView().environment(\.api, .mock).environment(Session())
}
```

@Entry (Xcode 16) back-deploys: it only generates the key. A keyed value always has a **default**; an @Observable object via .environment(obj) (iOS 17) or .environmentObject has none — missing ⇒ runtime crash. Flows **down** the tree only; read it in body, not init.

pointfree swift-dependencies

```
extension APIClient: DependencyKey {
    static let liveValue = APIClient.live
}
extension DependencyValues {
    var api: APIClient {
        get { self[APIClient.self] }
        set { self[APIClient.self] = newValue } }
    @Observable @MainActor final class FeedModel {
        @ObservationIgnored @Dependency(\.api) var api
        @ObservationIgnored @Dependency(\.date.now) var now
    }
    let model = withDependencies { // in a test
        $0.api.fetchFeed = { [] } // ONE endpoint
    } operation: { FeedModel() }
```

Three values per key: liveValue · previewValue (defaults to live) · testValue (defaults to preview); a **live** value reached in a test **fails the test**. @DependencyClient (import DependenciesMacros) makes every endpoint *unimplemented* by default. Captured when the object is created inside withDependencies.

Containers — only what they document

Swinject	c.register(API.self) { _ in LiveAPI() }, c.resolve(API.self)!; scopes .transient · graph (default) · .container (singleton) · .weak
Factory	extension Container { var api: Factory<API> { self { LiveAPI() } }.singleton } }; @Injected(\.api); test: Container.shared.api.register { Mock() }; scopes unique (default) · cached · shared (weak) · singleton · graph
Resolver	same author; officially deprecated , replaced by Factory

Traps

- ! @Injected/@Dependency are *lookups* (locator-shaped): a default removes the missing-registration crash, not the hiding.
- ! Hand-rolled @Injected over static var currentValue = a global mutable registry: overrides leak between tests; Swift 6 rejects the nonisolated static var (SE-0412).
- ! Logout without rebuilding the session scope = the next user sees old data.
- ! Singleton holding a per-screen object = captive dependency.
- ! @Environment read in init: not installed yet → the default.