


In one line: Every signing error is a **mismatch between four things** that must agree — the **identity** (certificate + *private key* in a reachable keychain), the **profile** (App ID, certificates, entitlements, devices, expiry), the **signed entitlements** and the **bundle** (every nested binary signed, nothing changed after). First ask *when* it fails — build, CI only, install, upload, launch — then **decode both sides and diff them** instead of toggling Xcode settings.



Message (abridged)	Real cause	Fix
No signing certificate “Apple Distribution” found	identity not in a searched keychain, or the cert is there <i>without</i> its private key	import the .p12 from the Mac that made the CSR (or match); revoking + recreating breaks other machines
Provisioning profile “X” doesn’t include the aps-environment entitlement ... doesn’t include signing certificate “Apple Development: Alice (...)” profile / cert from another team	capability in .entitlements but not enabled on the App ID, or the profile predates it	enable on the App ID → regenerate profile → download (automatic signing does all three)
certificate expired or revoked	profile lists other certs (new Mac, cert renewed)	regenerate the profile with your cert selected
A valid provisioning profile for this executable was not found	DEVELOPMENT_TEAM ≠ profile’s TeamIdentifier (often an extension target)	one team per target set; check every target
resource fork, Finder information, or similar detritus not allowed	1-year Development/Distribution cert ran out, or a teammate revoked it	new cert → new profiles; App Store builds already live are unaffected
code object is not signed at all — In subcomponent: .../Frameworks/X.framework	at install: expired profile, device missing, or profile/cert mismatch	decode embedded.mobileprovision inside the .ipa and compare
ITMS-90035 Invalid Signature	extended attributes on files in the bundle (iCloud Drive / Dropbox folder, downloaded assets)	xattr -cr App.app, build outside synced folders
ITMS-90164 / ITMS-90046	nested binary unsigned: “Embed Without Signing”, a Mach-O in Resources/, a patched vendor binary	Embed & Sign; put code where code goes; re-sign inside-out
unsupported architectures [x86_64, i386] (ITMS-90087 <i>unverified</i>)	dev/ad hoc identity, sealed resource missing/invalid, odd filenames, script files in the bundle	distribution identity, Release config, clean build, rename files
	signed entitlements not all in the profile / not valid on iOS (wildcard associated domain, malformed application-identifier)	diff codesign -d --entitlements vs the profile; explicit values only
	simulator slices in a fat vendor framework	ship an .xcframework, or strip before signing

Example — decode both sides and diff

```

unzip -q App.ipa && APP=Payload/App.app
security cms -D -i $APP/embedded.mobileprovision > prof.plist
/usr/libexec/PlistBuddy -c 'Print :Entitlements' prof.plist # allowed
/usr/libexec/PlistBuddy -c 'Print :ProvisionedDevices' prof.plist
codesign -d --entitlements :- $APP # actually signed
codesign -dvvv $APP 2>&1 | grep -E 'Authority|TeamIdentifier'
security find-identity -v -p codesigning # SHA-1 of your certs
xcodebuild -showBuildSettings | grep -E 'CODE_SIGN|PROVISIONING|TEAM'
codesign --verify --deep --strict -vvv $APP # nested damage
    
```

Where things live

- Profiles: **Xcode 16+**
~/Library/Developer/Xcode/UserData/Provisioning Profiles; Xcode ≤ 15
~/Library/MobileDevice/Provisioning Profiles — tools and CI scripts hard-coding the old path need updating.
- In the product: embedded.mobileprovision (iOS), embedded.provisionprofile (macOS). Keys: TeamIdentifier, Entitlements, DeveloperCertificates, ProvisionedDevices, ExpirationDate.

Automatic vs manual signing

- Automatic** (CODE_SIGN_STYLE = Automatic): Xcode creates certs, App IDs, “Xcode Managed” profiles, registers the connected device. On CI: xcodebuild -allowProvisioningUpdates + an App Store Connect API key (-authenticationKey{Path, ID, IssuerID}).
- Manual:** CODE_SIGN_IDENTITY + PROVISIONING_PROFILE_SPECIFIER per target; deterministic — usual on CI with match.

- Every target signs separately:** each app extension / watch app has its own App ID and profile; the host’s profile does not cover them.

On the device

- iOS 16+: development-signed apps need **Developer Mode** (Settings > Privacy & Security); TestFlight / App Store builds don’t.
- Enterprise builds: the user must trust the developer (Settings > General > VPN & Device Management) and the first launch verifies online (*unverified*).
- No debugger on a distribution build: no get-task-allow.

Traps

- ! “Revoke and recreate the certificate” — kills every other machine’s key and CI; export the .p12 instead.
- ! Capability works in Debug, fails in Release: only the *development* profile was regenerated.
- ! Toggling “Automatically manage signing” hides the real mismatch — diff first.
- ! Anything that edits the bundle after signing (a script phase, strip, install_name_tool) invalidates it — sign last.

Remember

“When does it fail? Decode the profile, dump the entitlements, list the identities — diff, regenerate, sign inside-out.”