


**In one line:** A big upload over a mobile network *will* be interrupted. **Resumable:** the server keeps the bytes it has under an **upload URL** and reports its **offset**; after a drop the client asks “where were we?” and continues from there. **Chunked / multipart:** the file is split into parts that are sent, retried and **checksummed** independently, then **assembled** by an explicit *complete*. On iOS a **background URLSession** hands the transfer to a system daemon — **from a file**, never from Data.

### Upload state machine



### Sent ≠ stored

0-6 MB: server has it  
6-7 MB: sent, lost in flight  
client counter says 7 MB → ask:  
HEAD → Upload-Offset: 6291456  
resume at 6 MB, not 7

send from the local counter  
= a hole or a 409 Conflict

### How it works

- Why:** cells drop, NAT rows expire, the app is killed — restarting 500 MB at 90 % burns time, battery and data.
- Resumable** = one sequential stream with a **server-authoritative offset** (IETF draft, tus, GCS). **Multipart** = N parts, any order, **in parallel**, assembled at the end (S3). Both need an **upload id/URL persisted** on the device.
- Integrity:** a checksum per chunk (tus Upload-Checksum → 460 on mismatch; S3 x-amz-checksum-\*, CRC64NVME default) + a whole-file hash checked at *complete*. Hash first → server can **dedupe** (already have it: skip).
- Retries:** exponential backoff + jitter; on every resume re-read the offset. Chunk size trades request overhead against bytes re-sent after a failure.
- Progress:** didSendBodyData / task.progress count bytes sent; show the server-acknowledged offset. Multipart: a parent Progress with one child per part, weighted by bytes.

### The protocols

|                   |                                                                                                                                                                                                                                                                                                                                                   |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>IETF draft</b> | draft-ietf-httpbis-resumable-upload (-12, Jul 2026, not yet an RFC). Server may answer the POST with <b>104 Upload Resumption Supported</b> + Location; offset: HEAD → Upload-Offset; append: PATCH, application/partial-upload, Upload-Complete: ?1 on the last; cancel: DELETE. Also Upload-Length, Upload-Limit, Upload-Draft-Interop-Version. |
| <b>tus 1.0</b>    | Tus-Resumable: 1.0.0. POST → 201 + Location; HEAD → Upload-Offset; PATCH application/offset+octet-stream → 204 + new offset (409 if offsets differ); DELETE; Upload-Expires.                                                                                                                                                                      |
| <b>S3</b>         | Create → UploadPart 1-10,000 (5 MiB-5 GiB, last smaller; each returns an ETag) → <b>Complete</b> with every PartNumber + ETag. Max object 48.8 TiB. Abort; lifecycle AbortIncompleteMultipartUpload. Client: one <b>presigned URL per part</b> .                                                                                                  |
| <b>GCS</b>        | POST ?uploadType=resumable → session URI (valid 1 week); PUT chunks, multiples of 256 KiB, Content-Range: bytes 0-262143/*; <b>308</b> + Range = incomplete; status = empty PUT bytes */SIZE.                                                                                                                                                     |

### Server contract (what to ask the backend for)

Idempotent create (client upload id / Idempotency-Key) · offset is the server's truth · size limits up front · auth on *every* chunk (re-signable URLs) · expiry + garbage collection of abandoned uploads · *complete* verifies the hash, then processing (scan, transcode) runs async → 202 + status URL.

### Example — the IETF draft on the wire, then iOS 17

```
POST /uploads # Upload-Complete: ?1, whole file
← 104 Upload Resumption Supported
Location: /uploads/7f3 # save it!
# ... connection lost ...
HEAD /uploads/7f3
← Upload-Offset: 6291456, Upload-Complete: ?0
PATCH /uploads/7f3 # Upload-Offset: 6291456
Content-Type: application/partial-upload
Upload-Complete: ?1 # bytes 6291456..end
← 200 OK # the original request's answer

// iOS 17+: URLSession resumes by itself if the server
// speaks the draft; you can also pause and resume later
let task = session.uploadTask(with: req, fromFile: file)
task.resume()
task.cancel(byProducingResumeData: { data in
    store.save(data) }) // nil: not resumable
if let data = store.load() { // file must be unchanged
    session.uploadTask(withResumeData: data).resume() }
```

### On iOS

- iOS 17: upload tasks are **automatically resumable** when the server supports the draft (WWDC23 *Build robust and resumable file transfers*; interop version 3).
- Background session:** Apple: “Only upload tasks from a file are supported (uploads from data instances or a stream fail after the app exits).” Multipart: write each part to its own file — uploadTask(fromFile:) sends the whole file.
- Keep files in Application Support (not tmp/Caches, which the system may purge).
- RN: fetch has no resume. tus-js-client resumes in the foreground; background needs a native module on URLSession / WorkManager.

### Traps

- ! Resuming from the *client's* byte counter — bytes in flight were lost. Ask the server.
- ! uploadTask(with:from: Data) in a background session — fails once the app exits.
- ! S3 parts under 5 MiB (except the last) are rejected; unfinished uploads are **billed** until aborted — add the lifecycle rule.
- ! Presigned URL expired mid-upload → re-sign that part, don't restart.
- ! “Chunked” ≠ HTTP/1.1 Transfer-Encoding: chunked — that streams one request of unknown length and resumes nothing.

### Remember

**“Ask where you are, send from there, check every piece, finish explicitly, sweep the abandoned.”**