


In one line: Before the first response byte, the phone may have to **wake its radio**, **resolve** the name, open **TCP**, negotiate **TLS** and **send** the request — each step costs a network **round trip (RTT)**. Cold over TCP + TLS 1.3: **4 RTT** + server time; HTTP/3: 3; a **reused** connection: **1**. Every latency trick removes one of these rows.

Timeline of the first request (bars = 1 RTT; server time and radio not to scale)



Worked: RTT 100 ms ⇒ cold h2 = 400 ms before server time; pooled = 100 ms. TLS 1.2 adds one more RTT (5). Body > first congestion window (≈10 segments ≈ 14 KB, RFC 6928) costs extra RTTs.

The nine steps

- Parse:** scheme, host, port, path (non-ASCII host → Punycode). A browser applies **HSTS** (incl. preload): http → https before any packet; an app's **ATS** refuses cleartext.
- Caches first:** a fresh URLCache hit returns with *no* network (resourceFetchType == .localCache); an open connection to the same origin in the session's pool skips steps 3–6 (isReusedConnection).
- Radio:** an idle modem (LTE RRC_IDLE; 5G adds RRC_INACTIVE) must be promoted to CONNECTED before the first packet — latency first, the energy *tail* afterwards.
- DNS:** stub resolver (mDNSResponder on Apple) cache → recursive resolver (carrier, 1.1.1.1, Private Relay) → root → TLD → authoritative. A, AAAA and, since iOS 14, **HTTPS** (type 65) records are asked in parallel; answers live for their TTL.
- Connect: Happy Eyeballs** (RFC 8305) prefers IPv6, starts IPv4 250 ms later if it is slow; TCP 3-way handshake = 1 RTT.
- TLS 1.3:** ClientHello (SNI, ALPN, key_share) → Finished = 1 RTT; chain + hostname checked; ALPN picks h2.
- Request:** HTTP/2 HEADERS (HPACK) on a new stream → CDN edge / load balancer → app server → cache / DB. **TTFB** = 1 RTT + server think time.
- Response:** status + headers (Cache-Control, ETag, Content-Encoding) → decompress → stored in URLCache → your code: status, decode, main actor.
- Render:** browser — DOM + CSSOM, JS, layout, paint, composite; each sub-resource is another (pooled) request. App — decode off-main, diff, UI on main, pre-decode images.

Example — where did the time go?

```
func urlSession(_ s: URLSession, task: URLSessionTask,
  didFinishCollecting m: URLSessionTaskMetrics) {
  func ms(_ a: Date?, _ b: Date?) -> String {
    guard let a, let b else { return "-" } // skipped step
    return "\(Int(b.timeIntervalSince(a) * 1000))" }
  for t in m.transactionMetrics { // redirects = several
    print(t.networkProtocolName ?? "?", t.isReusedConnection,
      "dns", ms(t.domainLookupStartDate, t.domainLookupEndDate),
      "tcp", ms(t.connectStartDate, t.secureConnectionStartDate),
      "tls", ms(t.secureConnectionStartDate, t.secureConnectionEndDate),
      "ttfb", ms(t.requestStartDate, t.responseStartDate),
      "body", ms(t.responseStartDate, t.responseEndDate),
      t.isCellular, t.remoteAddress ?? "" ) // v6 or v4?
  }
}
```

Related: dns-for-apps · tcp-udp-quic · tls-pki (handshake) · http-deep (h2/h3, caching) · urlsession-networking · app-size-and-energy (radio tail) · rendering-pipeline

Where the milliseconds go — and the fix

step	cost	how to remove it
radio	promotion	batch; prefetch while the radio is up
DNS	1 RTT (miss: more)	fewer hostnames; honour TTLS; HTTPS record
TCP	1 RTT	reuse: one shared session, h2/h3 multiplexing
TLS	1 RTT (1.2: 2)	TLS 1.3 resumption; 0-RTT for idempotent GETs
request	1 RTT + server	CDN edge near the user; cache; fewer serial calls
body	slow start	small first screen (<≈14 KB), compression
render	CPU	decode off-main, downsample images, paginate

The mobile angle

- Sequential calls multiply RTTs:** login → profile → feed = 3 round trips minimum. Parallelise (async let) or aggregate server-side (BFF, GraphQL).
- Network switch** (Wi-Fi → cellular) kills every TCP connection: back to cold. HTTP/3 migrates by connection ID; multipathServiceType = .handover (MPTCP) keeps TCP alive.
- Lab ≠ field:** the simulator uses the Mac's network. Measure on a device, on cellular, and collect URLSessionTaskMetrics in production (sampled).
- The first request after launch pays everything: warm the connection with the first needed call, not a dummy ping.

Traps

- ! “HTTPS is one handshake” — TCP *then* TLS: two RTTs before the request (QUIC merges them).
- ! Timing with Date() around data(for:) mixes queueing, DNS and server time — use the metrics.
- ! A pooled connection may already be closed by the server: ~1005 (connection lost). URLSession retries it only for **idempotent** methods — a POST surfaces the error (QA1941).
- ! “DNS is instant” — a cold miss walks root → TLD → authoritative; bad Wi-Fi DNS stalls everything.

Remember

“Wake, resolve, connect, secure, ask, render” — each is a round trip until you reuse it.