


In one line: The frontend parses, **type-checks** (a constraint solver), lowers to **SIL** — Swift’s own IR that still sees generics, ownership and ARC — runs *mandatory* then *performance* passes, then emits LLVM IR. At run time every type has **metadata**; generic and protocol code goes through **value/protocol witness tables** unless the optimiser could **specialise** it, which needs the body visible.



Compiler

- **Per-file vs WMO.** Debug: one frontend job per file (“primary file”), incremental via a dependency graph — fast edits, no cross-file optimisation. Release: **whole-module optimisation** — one job sees every file: cross-file inlining, devirtualisation, specialisation, dead-code removal.
- -Onone keeps every check and no inlining; -O speed; -Osize; -Ounchecked drops overflow/precondition checks. Never benchmark Debug.
- **Module boundary** hides bodies. @inlinable ships the body (SIL / in the .swiftinterface) so clients can inline and specialise; every internal symbol it touches needs @usableFromInline. The body is then part of your ABI — old clients keep the old copy until they rebuild.
- **ABI stability** (Swift 5.0, Apple platforms): calling convention, mangling (\$s...), metadata and witness-table layout frozen — the runtime ships *in the OS* (iOS 12.2+), apps stopped bundling libswiftCore.
- **Module stability** (Swift 5.1): the textual .swiftinterface imports into *later* compilers. Build setting BUILD_LIBRARY_FOR_DISTRIBUTION turns on both it and **library evolution**.
- **Library evolution / resilience:** clients may not bake in a type’s layout — they ask metadata for size and use accessors, so the library can add stored properties or cases. Public non-@frozen enums force @unknown default. @frozen = layout promise forever. Apps and source packages pay nothing.
- Lexical lifetimes (5.7): -O no longer ends a variable’s life early, so “deinit fires sooner in Release” is mostly gone.


Example — a library that ships to clients

```

public struct Stack<Element> {
    @usableFromInline internal var items: [Element] = []
    public init() {}
    @inlinable public mutating func push(_ e: Element) {
        items.append(e) // body ships: client specialises
    }
    public mutating func pop() -> Element? {
        items.popLast() // opaque: witness-table path
    }
}
@frozen public enum Axis { case x, y } // exhaustive switch OK
// type-checker: annotate + split one giant expression
let part: Double = a * 2 + b / 3
let total: Double = part - Double(c) + e * 1.5

```

An unspecialised generic call



Runtime

- **Type metadata:** one record per type — kind, VWT pointer, generic arguments; classes add superclass + vtable and are ObjC-isa compatible (the instance’s first word). Generic instantiations (Array<User>) are built *lazily* by the runtime and cached.
- **VWT:** how to copy/move/destroy a value of unknown type. For a trivial specialised type these become memcpy or vanish.
- **PWT:** one per (type, protocol) conformance, an entry per requirement. Conformance records live in the binary; as? P searches them (cached; iOS 16’s dyld precomputes them).
- **Dispatch:** final/private/structs/extension methods = direct · class = vtable · protocol/generic = PWT · dynamic = objc_msgSend.
- any P = 3-word inline buffer + metadata + 1 PWT per protocol (boxed if larger) — see ownership-and-memory-layout.
- Swift generics are **not** C++ templates: zero-cost only when specialised (same module, WMO, or @inlinable).

Traps

- ! “Compiles forever”: long mixed-literal / overloaded-operator expressions (huge SwiftUI bodies too) explode the solver. Find: -Xfrontend -warn-long-expression-type-checking=100, Build With Timing Summary. Fix: annotate, split.
- ! ARC reasoning belongs to **SIL**, not LLVM IR. A bug fix in an @inlinable body never reaches clients that inlined the old one.
- ! Stride ≠ size: (Int64, Int8) is size 9, stride 16.

Remember

“Parse, check, **SIL** twice, **IR**, link.” Metadata says *what*, VWT says *how to copy*, PWT says *which method*.