



In one line: DNS maps a **name** to **records** through a hierarchy: your device's **stub resolver** asks a **recursive resolver**, which walks **root** → **TLD** → **authoritative** and **caches** every answer for its **TTL**. Classic DNS is **plaintext UDP/53**; encrypted DNS (DoT/DoH) hides it, DNSSEC authenticates it. On iOS the app must work on **IPv6-only** networks (NAT64/DNS64) — App Review tests it.

Resolving `api.example.com` — a cold cache



1-2 **recursive** query ("give me the answer?"); 3-5 **iterative** ("who knows?" → referral). Warm caches skip 3-5 (root and TLD answers live for days). A, AAAA and HTTPS (type 65) are asked in parallel. Transport: UDP/53 (TCP when truncated), DoT :853, DoH :443.

IPv6-only network: DNS64 + NAT64



Breaks: hard-coded IPv4 literals, AF_INET-only sockets, `inet_addr/gethostbyname`, IPv4 in payloads. Test: Mac Internet Sharing → **Create NAT64 Network** (Option-click).

Records you should know

A/AAAA	IPv4 / IPv6 address
CNAME	alias to another name; nothing else may sit beside it ⇒ not at the zone apex
NS/SOA	who is authoritative / zone serial + negative-cache TTL
MX	mail servers with priority
TXT	free text: SPF, DKIM, domain-ownership proofs
SRV	<code>_svc._proto.name: priority, weight, port, target</code> (RFC 2782) — XMPP, SIP
HTTPS/SCVB	RFC 9460, types 65/64: <code>alpn</code> (h3!), port, IP hints, ECH config; AliasMode works at the apex. iOS 14+ asks for it
CAA	which CAs may issue certificates
PTR	reverse: IP → name

Example — a zone, and encrypted DNS for one app

```
api.example.com. 300 IN A 192.0.2.10
api.example.com. 300 IN AAAA 2001:db8::10
www.example.com. 3600 IN CNAME cdn.example.net.
example.com. 3600 IN HTTPS 1 . alpn="h3,h2" ipv4hint=192.0.2.10
_sip._tcp.example.com. 86400 IN SRV 10 60 5060 sip.example.com.
example.com. 3600 IN MX 10 mail.example.com.
example.com. 3600 IN CAA 0 issue "ca.example.net"
```

```
import Network
NWParameters.PrivacyContext.default.requireEncryptedNameResolution(
    true, fallbackResolver: .https(
        URL(string: "https://dns.example.net/dns-query")!,
        serverAddresses: [.hostPort(host: "192.0.2.53", port: 443)])
    // every later URLSession / NWConnection lookup: DoH (or system DoH)
```

DNS failures on mobile

symptom	usual cause
-1003 cannot find host	NXDOMAIN, typo, split-horizon name outside the VPN
-1006 DNS lookup failed	resolver unreachable, captive portal, blocked DoH
slow first request only	cold cache, slow carrier / Wi-Fi resolver
works on Wi-Fi, fails on LTE	IPv6-only carrier + IPv4 literal (NAT64)
old server after migration	high TTL, or the app cached the IP
.local device not found	Local Network permission denied

Traps

- ! "My app is IPv6-ready because the server has AAAA" — App Review runs on **NAT64**: the server can stay IPv4; your *client* must avoid IPv4 literals and v4-only APIs.
- ! Resolving yourself and connecting to an IP: breaks Happy Eyeballs, TLS SNI/hostname checks, CDN routing and NAT64. Connect by **name**.
- ! Caching IPs in the app or pinning one address — the TTL was the contract.
- ! DNSSEC ≠ encryption; DoH ≠ authenticity of the zone.
- ! Pre-creating a name after querying it: negative caching keeps it NXDOMAIN.

Remember

"Stub asks, recursive walks, everyone caches for the TTL — and your app speaks names, never IPv4 literals."

Caching and TTLs

- **Layers:** authoritative → recursive resolver cache → home router / forwarder → OS cache (mDNSResponder) → (never) your app. Each keeps a record for its **TTL**, counting down from when it fetched it.
- **Negative caching** (RFC 2308): NXDOMAIN/no-data is cached for `min(SOA TTL, SOA MINIMUM)`. Querying a name *before* creating it keeps it "missing" for that long.
- **Migration:** lower the TTL a full old-TTL *before* moving; resolvers that ignore TTLs, and apps that cache IPs, still hit the old address — keep it up for a while.
- **Encrypted DNS: DoT** (RFC 7858, TCP :853), **DoH** (RFC 8484, HTTPS :443), DoQ (RFC 9250). **DNSSEC** signs records: authenticity, *not* privacy.
- **Split-horizon:** the same name answers differently inside a VPN / office / home LAN. VPN profiles scope DNS with match domains (NEDNSSettings.matchDomains).
- **Happy Eyeballs v2** (RFC 8305): AAAA first, A right after; waits 50 ms for AAAA if A wins, then races IPv6 vs IPv4 connects 250 ms apart. Built into URLSession + Network.framework.

Apple APIs

- **System-wide:** NEDNSSettingsManager (iOS 14) installs a DoH/DoT config (NEDNSOverHTTPSSettings, onDemandRules); the **user** must enable it in Settings.
- **Per app:** NWParameters.PrivacyContext (iOS 14) — `requireEncryptedNameResolution`; on `.default` it covers the process (URLSession, getaddrinfo). iOS 16: DDR auto-upgrades to the network's encrypted resolver.
- **DNSSEC:** `URLRequest.requiresDNSSECValidation` (iOS 16.1) — lookup fails if validation fails. Custom records (SRV, TXT): `DNSServiceQueryRecord` (dns_sd.h).
- **Local names** (.local, Bonjour): Local Network permission (iOS 14): `NSLocalNetworkUsageDescription` + `NSBonjourServices`.
- **Debug** from a Mac: `dig api.example.com AAAA +short`, `dig +trace` (walks the chain above), `dig @1.1.1.1 ...` (compare resolvers); on device: `URLSessionTaskMetrics domainLookup*` dates and `domainResolutionProtocol` (udp / tcp / tls / https).