



In one line: An Operation is a **single-shot**, KVO-observable unit of work; an OperationQueue starts it when isReady (every dependency isFinished), caps parallelism with maxConcurrentOperationCount, and drops it when it posts isFinished. **Cancellation is a flag**, dependencies are **ordering only** (no data), and an async subclass must drive its own state **with KVO** — or it never finishes.

State machine (KVO keys the queue watches)



Dependencies — a graph across queues



How it works

- Sync op:** override main(); finished when it returns (async work started inside is *not* awaited). **Async op:** override start() (never super.start()), isAsynchronous = true, own isExecuting/isFinished behind a lock, KVO for both, finish exactly once — also when cancelled before starting.
- A queue **always** calls start() on a separate thread and ignores isAsynchronous; it matters only when you call start() yourself.
- b.addDependency(a): works across queues; "finished" includes cancelled; a cycle never becomes ready (silent hang). Results: b reads a.output (or an adapter op copies it).
- maxConcurrentOperationCount defaults to -1 (system decides); 1 = serial, but order = readiness → queuePriority → insertion.
- qualityOfService(.userInteractivebackground) sets the thread's priority and energy class; queuePriority(.veryLowveryHigh) only reorders *ready* ops in *one* queue.
- BlockOperation: its blocks run concurrently, finished when all return. addBarrierBlock (iOS 13) waits for everything queued before it. isSuspended stops *starting* ops. OperationQueue.main = serial, main thread; underlyingQueue targets a DispatchQueue.
- completionBlock runs after finish on an **arbitrary thread**, and is set to nil once it starts (iOS 8+).

Example — KVO-correct async Operation

```
class AsyncOperation: Operation {
    private let lock = NSLock()
    private var _exec = false, _done = false
    private func locked<T>(<_ f: () -> T) -> T {
        lock.lock(); defer { lock.unlock() }; return f() }
    override var isAsynchronous: Bool { true }
    override var isExecuting: Bool { locked { _exec } }
    override var isFinished: Bool { locked { _done } }
    override func start() {
        // never super.start()
        if isCancelled { finish(); return } // still must finish
        willChangeValue(forKey: "isExecuting")
        locked { _exec = true }
        didChangeValue(forKey: "isExecuting")
        run { self.finish() } // subclass: async work
    }
    func run(_ done: @escaping () -> Void) { done() }
    final func finish() {
        // exactly once
        let keys = ["isExecuting", "isFinished"]
        keys.forEach(willChangeValue(forKey:))
        locked { _exec = false; _done = true }
        keys.forEach(didChangeValue(forKey:))
    }
}
```

Operation vs GCD vs async/await

Need	Operation	GCD	Swift concurrency
dependency graph	addDependency, cross-queue	group notify, by hand	async let, ordered await
cancel a graph	cancelAll() sets flags	work item cancel(): only if not started	task.cancel() reaches child tasks
cap parallelism	maxConcurrent...	semaphore / serial queue	task group: seed n, add one per finish
observe state	KVO, progress (iOS 13)	—	—
delay	—	asyncAfter	Task.sleep(for:)

Operation still wins for: a **cancellable graph** across queues, a hard concurrency cap, KVO/Progress UI, subclassable reusable types, legacy code. New code on async/await: task groups + Task.checkCancellation().

Traps

- ! Async op without the manual KVO → stuck "executing" forever.
- ! cancel() does not stop a running op or its URLSessionTask — check isCancelled and cancel the task yourself.
- ! Cancelled dependency = finished → the dependent still runs.
- ! op.completionBlock = { use(op.result) } captures op strongly — a cycle until it runs; use [unowned op]. Hop to main for UI.
- ! Adding the same instance twice / after it finished → NSInvalidArgumentException. Single-shot.
- ! waitUntilAllOperationsAreFinished() / waitUntilFinished: true on main → hang, watchdog 0x8badf00d.

The two priorities, side by side

qualityOfService	raw	queuePriority	raw
.userInteractive	0x21	.veryHigh	8
.userInitiated	0x19	.high	4
.default	-1	.normal	0
.utility	0x11	.low	-4
.background	0x09	.veryLow	-8

QoS = which CPU/energy class the thread gets (across the whole system); queue priority = which ready op this queue starts first. Neither beats a dependency.

Remember

Ready → Executing → Finished; cancel is only a flag; no KVO, no finish.