


In one line: Patterns trade **indirection** for **changeability**; these principles say what changeable code looks like: **high cohesion, low coupling** (named by kind — connascent), **talk to friends, tell don't ask, compose**, one home per *piece of knowledge*, build only what's needed, the right class for each responsibility (**GRASP**), dependencies **toward stability**.



Coupling & cohesion (Constantine, structured design) Coupling, worst→best: **content** (reach into internals) · **common** (shared globals — .shared state) · **external** (shared format/device) · **control** (pass a flag that picks the callee's branch) · **stamp** (pass a whole struct, use one field) · **data** (pass only what's used). **Cohesion**, worst→best: **coincidental** (Utils) · **logical** (same category: handle(type:)) · **temporal** (runs at the same time: setUpEverything) · **procedural** · **communicational** (same data) · **sequential** (output feeds next) · **functional** (one well-defined task).

Connascent — a vocabulary for coupling Connascent = changing one forces changing the other. **Name** (rename → callers), **Type**, **Meaning** (status == 2 means shipped → use an enum), **Position** (argument order → labels, a struct), **Algorithm** (client + server hash the same way → share one implementation), **Execution** (configure() before start() → make it an init), **Timing** (races), **Value** (values that must change together — invariants), **Identity** (must be the same instance, e.g. one NSManagedObjectContext).

Law of Demeter · tell, don't ask LoD (Holland/Lieberherr, 1987): "only talk to your immediate friends" — the 4 allowed targets in the picture. A train wreck couples the caller to every intermediate type. Fix: **hide delegate** (order.pay) or pass in what is needed. **Tell, don't ask**: don't pull state out, decide and push it back — tell the data's owner to do it (= Information Expert).

Composition over inheritance (GoF, 1994) Inheritance is **white-box reuse**: the subclass depends on the base's *implementation*. **Fragile base class**: a harmless base change breaks subclasses (Bloch's InstrumentedHashSet: addAll calls add, so the override counts twice). Composition = black-box, swappable at runtime, no LSP traps. Swift nudges you: final, open to subclass across modules, protocols + extensions, value types. Inherit only for a true is-a with a stable contract.

```
// ASK: train wreck, logic outside the data
if order.customer.wallet.balance >= total {
  order.customer.wallet.balance -= total }
// TELL: the data's owner does it (Information Expert)
struct Wallet { private(set) var balance: Decimal
  mutating func pay(_ x: Decimal) throws {
    guard balance >= x else { throw PayError.insufficient }
    balance -= x } }
try order.pay(total) // Order -> customer -> wallet, hidden
```

Remember Cohesion in, coupling out · weak and local connascent · talk to friends, tell them · compose · one home per fact · build what's needed · point at stability.

GRASP — Larman's 9: who gets the job?

Information Expert	the class that <i>has the data</i> : Cart.total, not the VC
Creator	B makes A if B contains, uses or has A's init data
Controller	first non-UI object handling a system event (use case, VM)
Low Coupling	pick the assignment that adds the fewest dependencies
High Cohesion	keep each class focused; reject what dilutes it
Polymorphism	varies by type → polymorphic call, not a type switch
Pure Fabrication	invented non-domain class: Repository, ImageCache
Indirection	an intermediary to decouple: protocol, Adapter, Coordinator
Protected Var.	hide each <i>predicted</i> change behind a stable interface

DRY · KISS · YAGNI DRY (Hunt & Thomas, 1999): "every *piece of knowledge* must have a single, unambiguous, authoritative representation" — knowledge, not text: identical lines encoding *different* rules stay separate. **The wrong abstraction** (Sandi Metz): "duplication is far cheaper than the wrong abstraction" — a shared helper growing per-caller flags: inline it back. Abstract at the **rule of three**. **KISS**: the simplest design that works. **YAGNI** (XP): don't build for a guessed future (Fowler: cost of build, delay, carry, repair) — but keep code easy to change.

Least astonishment · separation of concerns POLA: code does what its name promises — no network I/O in a getter; sort() mutates, sorted() returns (Swift API Design Guidelines, which also require documenting a computed property that is not O(1)). **SoC** (Dijkstra, 1974): one concern per part — view / state / domain / persistence; the root of SRP and layering.

Dependency direction (Martin's package principles) ADP: no cycles in the module graph. **SDP**: depend in the direction of *stability* (towards low I). **SAP**: as *abstract* as it is stable, so it can still be extended. *Stable* = many dependents, hard to change — not "rarely edited". iOS: Feature → DomainInterfaces ← Networking.

Traps

- ! LoD ≠ "count the dots"; DRY ≠ "no repeated lines".
- ! GRASP Controller ≠ UINavigationController.
- ! Name the *kind*: control coupling, temporal cohesion, connascent of position.