



In one line: A **lock** makes a critical section mutually exclusive and has an **owner** (the thread that took it, which must release it); a **semaphore** is a **counter** with no owner; a **serial queue** or **actor** serialises by *ownership* instead. Pick by: is there an **await** inside? how short is it? do you need a count? Then: never block the cooperative pool, never hold a lock across a call-out.



Priority inversion — and why the lock's owner matters



Owner-aware lock (os_unfair_lock, Mutex, pthread_mutex): the lock records its owner, so the kernel can **boost low** to high's priority → it finishes, frees L, high runs. A DispatchSemaphore has **no owner** — nothing to boost (*unverified*); Xcode's Thread Performance Checker flags that (*unverified*). Same trap on iOS: a .userInteractive main thread waiting on a semaphore signalled from a .background queue — the UI waits at background priority.

Deadlock is different: a cycle of waits (T1 holds A wants B, T2 holds B wants A) — fix with a global lock order (design/concurrency-patterns). **Inversion** ends; deadlock never does.

The primitives

Primitive	since	recursive	Know this
Mutex<State>	iOS 18	no	Synchronization; ~Copyable, Sendable; withLock closure is sync ⇒ no await inside
OSAllocatedUnfairLock	iOS 16	no	import os; heap-allocated = stable address; withLock, lockIfAvailable
os_unfair_lock	iOS 10	no	fastest; unlock on another thread aborts ; Swift & lock may copy/move it
NSLock	iOS 2	no	2nd Lock() on the same thread hangs forever; unlock on the locking thread
NSRecursiveLock	iOS 2	yes	same thread may re-take it; unlock as often
pthread_mutex_t	POSIX	attribute	init/destroy; heap-allocate it in Swift
DispatchSemaphore	GCD	—	counter, no owner , any thread signals; freed while value < initial ⇒ crash
serial queue, actor	—	—	ownership, not a lock; q.sync onto itself deadlocks

How it works

- Uncontended locks are cheap; **contention** costs — copy out, work outside.
- Barrier** (async(flags: .barrier)) waits for earlier blocks, runs alone, then lets reads resume — only on a **private concurrent** queue: on a global or serial queue it is a plain async/sync.
- DispatchQueue.concurrentPerform(iterations:) = parallel for, returns when all iterations are done; give each iteration its own slot, never append.
- Thread {...}.start(); selectors are #selector(job(_:)), not ObjC's job::; raw pthread_create takes its context via Unmanaged. Rarely worth it over GCD / tasks.

Sizing: CPU- vs I/O-bound

CPU-bound: threads ≈ cores; more only adds context switches.

I/O-bound: threads = cores/(1 - b), b = fraction of time blocked (8 cores, b = 0.9 → 80). On Apple you size *concurrency*, not threads: GCD and the cooperative pool (≈ one thread per core, never grows) own the threads — set maxConcurrentOperationCount, a task-group width, or httpMaximumConnectionsPerHost; do I/O with async APIs.

RunLoop — sleeps when idle, wakes for work

Every thread has one; the **main** run loop is started by UIApplicationMain, a **secondary** thread must run its own — and with no source or timer it exits at once. A GCD worker never runs it, so a Timer.scheduledTimer made there never fires (*unverified*). **Modes** filter sources: a scroll switches main to *tracking* mode, so a timer in .default stalls — add it for .common. Touch a RunLoop only from its own thread.

Example — the three you will write

```

import Synchronization // iOS 18
final class Counter: Sendable { // no @unchecked
    private let n = Mutex(0)
    func next() -> Int { n.withLock { $0 += 1; return $0 } } }
final class Store { // reader-writer
    private let q = DispatchQueue(label: "store",
        attributes: .concurrent)
    private var d: [String: Int] = [:]
    func get(_ k: String) -> Int? { q.sync { d[k] } }
    func set(_ k: String, _ v: Int) {
        q.async(flags: .barrier) { self.d[k] = v } } }
let sem = DispatchSemaphore(value: 3) // max 3 at once
for job in jobs { // bg thread, not main
    sem.wait() // wait BEFORE dispatch
    work.async { defer { sem.signal() }; run(job) } }
    
```

Traps

- ! "Semaphore(1) = mutex" — no owner: any thread signals, no priority boost.
- ! sem.wait() inside 15 queued blocks parks up to 12 workers → GCD spawns more (thread explosion). On main: hang → watchdog.
- ! &m on a var m = pthread_mutex_t(): valid for that call only — the lock can move. Use OSAllocatedUnfairLock / Mutex.
- ! Appending to one array from concurrent blocks = data race (crash, lost items).
- ! A lock or semaphore held across await: the task may resume on another thread.
- ! sleep(2) blocks the thread; Task.sleep(for:) suspends the task.

Remember

Short and sync → **Mutex**. **Has await** → **actor**. **Counting** → **semaphore**. **Many readers** → **barrier**. **Owners beat inversion**.