



In one line: Layout is **one pass**: a parent hands each child **Constraints** (min/max width, height), the child is **measured once** and reports a **size**, the parent **places** it. A Modifier chain wraps outer → inner; each link may change the constraints going down and the size coming up — **order is behaviour**.

Icon(Modifier.padding(8.dp).size(64.dp).background(c)) in a 360 dp Row



Order = wrapping order (outer → inner)



Input too: `clickable{} .padding(12) = padding tappable; reversed = not · clip before background`

Measure → size → place

- `MeasurePolicy` gets (measurables, constraints); `measure()` twice on one child **throws** — single pass is enforced, so deep nesting is cheap (unlike nested `RelativeLayout`).
- **Tight** = min = max (Constraints.fixed); **loose** = min 0; **unbounded** = max Infinity (in a scrollable).
- `layout(w, h) { p.placeRelative(x, y) }` — `placeRelative` mirrors in RTL, `place` does not. A size outside the constraints is coerced + centred.

Size modifiers & intrinsics

- `size` = a *preference* coerced into incoming constraints; the first tight one wins: `size(100).size(50) = 100`. `requiredSize` ignores them.
- `fillMaxWidth(f)`: min = max = f-max. `wrapContentSize()`: min → 0 + align — a child smaller than a tight parent.
- `weight(w)`: unweighted children measured first, the rest split by weight (`fill = false = a cap`). `Box: matchParentSize()` takes the size *after* siblings set it; `fillMaxSize()` helps set it.
- `Row(Modifier.height(IntrinsicSize.Min))` asks children `minIntrinsicHeight` *before* measuring, so a `fillMaxHeight()` divider matches the tallest text. A query, not a measure — but a second walk. A custom `Layout`'s default intrinsics are **approximated**: override them.

Example — a custom Layout

```
@Composable fun Stack(modifier: Modifier = Modifier,
    content: @Composable () -> Unit) =
    Layout(content, modifier) { measurables, constraints ->
        val loose = constraints.copy(minWidth = 0, minHeight = 0)
        val ps = measurables.map { it.measure(loose) } // once each
        val w = (ps.maxOrNull { it.width } ?: 0)
        val h = (ps.maxOrNull { it.height } ?: 0)
        .coerceIn(constraints.minWidth, constraints.maxWidth)
        .coerceIn(constraints.minHeight, constraints.maxHeight)
        layout(w, h) {
            var y = 0
            ps.forEach { it.placeRelative(0, y); y += it.height }
        }
    }
```

One wrapped node only? `Modifier.layout { m, c -> ... }` (measure it, add an offset/baseline gap). **vs SwiftUI Layout**: a proposal is a *suggestion* and a subview may be asked `sizeThatFits` several times; Compose constraints are hard *bounds* and each child is measured **once**.

SubcomposeLayout & BoxWithConstraints

- `SubcomposeLayout` **composes during layout** — children exist only once constraints are known (`LazyColumn`, `Scaffold`, `BoxWithConstraints`). Composition moves into the layout pass; a new constraint re-subcomposes.
- Use it only when the *tree* depends on size (1 vs 2 panes); to *position* by size use `Layout`. `onSizeChanged` + state write = a frame late.

Modifier.Node, not composed{ }

`composed{ }` runs composition per use site, allocates, never skips. A `Modifier.Node` lives long; its `ModifierNodeElement` (`create`, `update`, **equals/hashCode** — a data class) is diffed and `update()` mutates the node. Roles: `LayoutModifierNode`, `DrawModifierNode`, `PointerInputModifierNode`, `SemanticsModifierNode`.

```
fun Modifier.circle(c: Color) = this then CircleEl(c)
private data class CircleEl(val c: Color) :
    ModifierNodeElement<CircleNode>() {
    override fun create() = CircleNode(c)
    override fun update(node: CircleNode) { node.c = c }
}
private class CircleNode(val c: Color) :
    Modifier.Node(), DrawModifierNode {
    override fun ContentDrawScope.draw() { drawCircle(c); drawContent() }
```

Moving things & lazy lists

- Animating `padding/size/offset(x.dp) → relayout`, neighbours move. `graphicsLayer { translationX; scaleX; alpha }` transforms the drawn layer only — **no remeasure**; a scaled item keeps its old slot.
- `key = { it.id }` (Bundle-able) keeps item state across inserts; `contentType` reuses same-type compositions; `Modifier.animateItem()` (fade + placement, needs keys) replaced `animateItemPlacement`.

Traps

- ! `LazyColumn` in a `verticalScroll` → crash: **infinite max height**. Use one lazy list with several `item{ }`s.
- ! “`size(50)` is 50” — not after `fillMaxSize()`: the min wins.
- ! No margin API: padding *before* background is the margin.

Remember: *constraints down, sizes up, place last · measure once · order = wrapping · move with `graphicsLayer`.*