


In one line: Core Graphics (Quartz 2D) is a C, **CPU**, immediate-mode 2D renderer. You talk to a CGContext — a **state machine** (CTM, clip, colours, line style, shadow, alpha, blend mode) with a stack you push/pop with `saveGState()` / `restoreGState()` — build a **path**, then **paint** it (fill / stroke), and the context rasterises into its destination: a **bitmap**, a view's **backing store**, or a **PDF** (vectors kept). UIKit's `UIBezierPath`, `UIGraphicsImageRenderer` and `draw(_:)` are thin wrappers over it.



How it works

- Order:** set state → build path (`move(to:)`, `addLine`, `addCurve`, `addArc`, `addRect`, `addEllipse(in:)`, `closePath`) → paint (`fillPath`, `strokePath`, `drawPath(using: .fillStroke)`). Painting clears the path.
- CTM** maps user space → device space; `translateBy` / `rotate(by:)` / `scaleBy` *concatenate*, so order matters (`rotate-then-translate` ≠ `translate-then-rotate`). Wrap every local transform in `save/restore`.
- Fill rules:** non-zero winding (default) vs **even-odd** (`fillPath(using: .evenOdd)`, uses `EvenOddFillRule`) — a ring = two circles, even-odd punches the hole regardless of direction.
- Strokes** straddle the path: half the width lands outside. A 1-pixel hairline = width 1/scale centred on a pixel (offset 0.5/scale), or it smears over two.
- Clipping:** `clip()` / `addClip()` intersects the clip with the current path. **Gradients** (`CGGradient` + `drawLinearGradient` / `drawRadialGradient`) fill the *whole clip* — clip to your shape first.
- Shadows** (`setShadow(offset:blur:color:)`) apply to every later draw; to shadow a group once: `beginTransparencyLayer ... endTransparencyLayer`.
- CGImage** = immutable bitmap: width, height, `bitsPerComponent`, `bitsPerPixel`, `bytesPerRow` (may be *padded* past w·4 — never assume), colour space, `bitmapInfo`. iOS-native: 8-bit **BGRA premultiplied** (`.premultipliedFirst` + `.byteOrder32Little`); pass `bytesPerRow: 0` to let CG align it.
- Colour spaces:** sRGB · **Display P3** (wide colour) · extended sRGB (values outside 0–1, 16-bit float, 8 B/px). `UIGraphicsImageRendererFormat.preferredRange` (iOS 12): `.automatic` picks by content, `.standard` forces 8-bit sRGB.
- Renderer vs old API:** `UIGraphicsImageRenderer` (iOS 10) is block-scoped (no unbalanced `begin/end`), reusable, picks scale + range; `UIGraphicsBeginImageContextWithOptions` is **deprecated in the iOS 27 SDK**.

Example — badge: clip, gradient, restore, flip

```
let fmt = UIGraphicsImageRendererFormat(); fmt.scale = 1 // exact pixels
let r = UIGraphicsImageRenderer(size: CGSize(width: 300, height: 300),
                                format: fmt)

let badge = r.image { rc in
    let ctx = rc.cgContext // UIKit-flipped: top-left
    ctx.saveGState() // push
    UIBezierPath(roundedRect: rc.format.bounds, cornerRadius: 48).addClip()
    let g = CGGradient(colorsSpace: nil, colors: [UIColor.systemBlue.cgColor,
        UIColor.systemTeal.cgColor] as CFArray, locations: [0, 1])!
    ctx.drawLinearGradient(g, start: .zero, end: CGPoint(x: 0, y: 300),
        options: []) // fills the CLIP, not a shape
    ctx.restoreGState() // pop: clip gone again
    ctx.translateBy(x: 0, y: 300); ctx.scaleBy(x: 1, y: -1) // to Quartz y-up
    ctx.draw(logoCG, in: CGRect(x: 100, y: 100, width: 100, height: 100))
}
```

draw(_:) rules

`rect` is the *dirty* area — draw only what intersects it; `setNeedsDisplay(_ rect:)` narrows it. Never call `draw` yourself. Default `contentMode = .scaleToFill` *stretches the old bitmap* on resize — set `.redraw`. Opaque view + solid `backgroundColor` = no blending.

Which drawing tool?

tool	cost	use for
<code>draw(_:)</code> override	CPU redraw into a backing store on every <code>setNeedsDisplay</code>	custom content that changes rarely
<code>CAShapeLayer</code>	path rendered by the render server; no app bitmap	shapes, rings, animated path / <code>strokeEnd</code>
renderer → <code>UIImage</code>	one CPU draw, then just an image	badges, thumbnails, export, snapshots
<code>CGContext(data:...)</code> <code>UIGraphicsPDFRenderer</code>	you own the bytes vectors, resolution-free	pixel access, custom formats invoices, reports, print

PDF — out and in

```
let a4 = CGRect(x: 0, y: 0, width: 595, height: 842) // points = 1/72 inch
let data = UIGraphicsPDFRenderer(bounds: a4).pdfData { ctx in
    ctx.beginPage() // one per page
    "Invoice".draw(at: CGPoint(x: 48, y: 48), withAttributes: attrs) }
let page = CGPDFDocument(url as CFURL)?.page(at: 1) // 1-BASED index
// render: scale the CTM to fit getBoxRect(.mediaBox), flip, drawPDFPage(page)
```

Traps

- ! `clip()` without `saveGState` — nothing outside that shape can be drawn again.
- ! Gradient floods the view: forgot to clip to the path first.
- ! Animating by `setNeedsDisplay` every frame — a full CPU redraw per frame; animate a layer property or use `CAShapeLayer`.
- ! “300×300” export is 900×900 px: the renderer’s default scale is the screen’s.
- ! Reading pixels with `bytesPerRow = width·4` — rows are padded; alpha is *premultiplied*, so un-premultiply before comparing colours.

Remember

“State, path, paint — save before you clip; UIKit looks down, Quartz looks up.”

Related: rendering-pipeline (ImageIO downsampling, lazy decode) · core-animation-rendering (`CAShapeLayer`, `commit`) · image-loading-pipeline (bytes per pixel) · swiftui-gestures-canvas (Canvas) · core-image-filters · metal-essentials