



In one line: Compose re-runs a composable only if it **read** snapshot State that was **written**; the **phase** of the read decides how much work follows (composition → layout → draw), and a re-run parent **skips** a child whose parameters are **stable and equal** (strong skipping: unstable ones compared by ==). Performance work = **read later, read lower, keep inputs stable**.

Where a state read happens → what a write re-runs



One write — which scopes re-run?



Composition & the snapshot system

- The compiler adds \$composer + \$changed bitmask params; results live in the **slot table**. Identity = **call site** + call order; key(id){} gives it explicitly (loops, reordering).
- mutableStateOf is a **snapshot** object (MVCC). Each phase runs under a **read observer** recording which scope read which state; an **applied** write invalidates exactly those scopes; many writes per frame = one recomposition.
- Recompose scope** = a restartable (non-inline, Unit-returning) composable. Column/Row/Box are inline: their content re-runs with the caller. A content lambda is its own scope ("donut-hole skipping").
- Backwards write** (write after reading in the same composition) → endless recomposition.

Stability & skipping

- Stable** = equals forever consistent, public changes notify composition, all public props stable: primitives, String, function types, val-only classes of those. **Unstable**: any var, List/Set/Map, classes from a module **without** the Compose compiler.
- @Immutable = never changes after construction; @Stable = may change but only through State. **Promises, not checks** — lie and the UI goes stale.
- Strong skipping** (default since **Kotlin 2.0.20**): every restartable composable is skippable; **unstable** params compared by === (instance), stable by equals; **every lambda is auto-remembered**, keyed on its captures. Opt out: @NonSkippableComposable, @DontMemoize.
- Today's bug: a **new instance each pass** (list.filter{} in the body) → !== → re-run. Fix: remember, ImmutableList (kotlinx), @Immutable, or a stabilityConfigurationFile.

Example

```
@Immutable data class Item(val id: Long, val kind: Kind,
                           val tags: ImmutableList<String>)
@Composable fun Feed(items: ImmutableList<Item>) {
    val list = rememberLazyListState()
    val showTop by remember { // recompose only on the flip
        derivedStateOf { list.firstVisibleItemIndex > 0 } }
    Header(Modifier.offset { // read in LAYOUT, not composition
        IntOffset(0, -list.firstVisibleItemScrollOffset / 2) })
    LazyColumn(state = list) {
        items(items, key = { it.id }, contentType = { it.kind }) {
            ItemRow(it) // key: state follows the item
        }
    }
    if (showTop) ScrollTopButton()
}
```

vs SwiftUI: both track **reads** (@Observable in body ≈ snapshot reads); SwiftUI diffs view **values** by structural identity + .id(), Compose re-runs **functions** and skips by parameter equality.

remember family — when which

- remember(k1, k2) {}: recompute when a key changes (like React's useMemo with deps). rememberSaveable: + rotation and process death (Bundle or Saver).
- derivedStateOf (inside remember): only when the **input changes more often than the output** (scroll index → Boolean); else remember(x).
- Lazy lists:** key (default = index) keeps item state across inserts and moves; contentType reuses compositions between same-type items.

Side effects — beyond the basics

- LaunchedEffect(k): new key ⇒ **cancel + relaunch**; to call the *latest* lambda without restarting, rememberUpdatedState.
- DisposableEffect(k) must end in onDispose{};
- SideEffect{} runs after every **successful** composition.
- produceState: source → State; snapshotFlow{}: State → cold Flow of distinct values (analytics, debounce).

```
@Composable fun Splash(onTimeout: () -> Unit) {
    val latest by rememberUpdatedState(onTimeout)
    LaunchedEffect(Unit) { delay(3_000); latest() } // no restart
}
```

Measure, don't guess

- Compiler reports** (composeCompiler { reportsDestination }, release build): -composables.txt = restartable skippable + per-param stable/unstable; -classes.txt = inferred stability.
- Layout Inspector:** recomposition + skip counts per node. Judge jank on release only.

Traps

- ! Scroll offset read in composition → recompose every frame.
- ! Strong skipping + a fresh List per pass → still re-runs.
- ! LaunchedEffect(Unit) + captured callback → stale.

Remember: *read later (draw > layout > composition), read lower (small scopes), same instance or stable type.*