


In one line: Tasks run on the **cooperative thread pool** (as many threads as CPU cores, **never grows**) or on the **main actor's** main thread. The runtime's contract is **forward progress**: `await` suspends and frees the thread; a *blocked* thread is simply lost. Four failures follow — **main-actor blocking** (hang), **actor contention** and **pool exhaustion** (parallel code turned serial, or deadlock), **continuation misuse** (leak or crash). Concurrency instruments show task / actor / executor *state*; System Trace shows *why* a thread is not running.



How the runtime behaves

- Pool width = CPU cores**, fixed. A GCD concurrent queue adds a thread when one blocks; the pool does not.
- Safe:** `await`; a lock around a tight, known critical section (Mutex, `os_unfair_lock`, `NSLock`). **Unsafe:** semaphores, condition variables, `DispatchGroup.wait()`, blocking file / network I/O — they hide the dependency from the runtime. All pool threads waiting on pool work = **deadlock**.
- `LIBDISPATCH_COOPERATIVE_POOL_STRICT=1` (scheme → Run → Arguments): pool width **1 per QoS**, so a hidden blocking wait deadlocks *now*, in dev.
- Main actor** = the main thread. Each hop main ↔ actor is a context switch: hand over arrays, not one item per hop.
- Where code runs (Swift 6.2):** new app projects in Xcode 26 default to MainActor isolation; *Approachable Concurrency* turns on SE-0461, so a nonisolated `async func` runs on the *caller's* actor; @concurrent always switches off it.
- Priority:** awaiting a task escalates it and its children, never lowered (SE-0462); an actor may run a higher-priority job first. A semaphore or continuation hides who will resume you — no escalation (6.2: withTaskPriorityEscalationHandler). **Thread Performance Checker** (TPC; on for Run, iOS + macOS) flags such waits: `dispatch_semaphore_wait` / `dispatch_group_wait` cannot pass priority on. Mute known ones: `PERFC_SUPPRESSION_FILE`.

Instruments + LLDB, release by release

Xcode (Swift)	adds
14 (5.7)	Swift Concurrency template = <i>Swift Tasks</i> (Running / Alive / Total Tasks, state per task, Task Forest, creation backtrace, narrative: which Task it waits on) + <i>Swift Actors</i> (queueing per actor). Needs an iOS 16 / macOS 13 runtime. Thread Performance Checker; Hang Tracing; Leaks / heap label Swift AsyncTask allocations.
26 (6.2)	Task(name:) names shown (SE-0469; read with Task.name, groups: addTask(name:)). Stepping follows a Task migrated to another thread. LLDB language swift task backtrace select <task>, info (new in 6.2).
27 (6.4)	Swift Executors: tracks for the Cooperative Thread Pool, the Main Actor, each TaskExecutor / SerialExecutor (OS 27; older: "Unknown executor"). Swift Task Collection: tasks grouped by name or creation site, lifetimes or states. <i>Profile</i> detail = call tree of samples taken while a Task / Collection / Actor / Executor was <i>Running</i> (+ Time or CPU Profiler). Tasks begun before the trace now shown (state "Unknown"); all-process recordings group Tasks and Executors per process. System Trace: syscalls, VM faults, thread states in one plot; ←/→ walks the scheduling chain; priority over time graph. Thread Activity: effective QoS per thread. LLDB language swift task tree. Instruments needs iOS 17+ devices.

Example — suspend, don't block

```
// BAD: parks a pool thread until the callback fires
func thumb(_ u: URL) async -> UIImage? {
    let sem = DispatchSemaphore(value: 0); var img: UIImage?
    legacyLoad(u) { img = $0; sem.signal() }
    sem.wait(); return img } // Blocked, thread lost
// GOOD: the task suspends; resume exactly once
func thumb(_ u: URL) async -> UIImage? {
    await withCheckedContinuation { c in
        legacyLoad(u) { c.resume(returning: $0) } } }
// CPU work off the caller's actor (6.2); a named task
@concurrent func decode(_ d: Data) async -> UIImage? {
    UIImage(data: d) }
Task(name: "thumb") { await show(thumb(url)) }
```

The runtime's own messages

```
SWIFT TASK CONTINUATION MISUSE: load() leaked its
continuation without resuming it. // task waits forever
SWIFT TASK CONTINUATION MISUSE: load() tried to resume
its continuation more than once, returning ... // fatalError
BUG IN CLIENT OF LIBDISPATCH: Assertion failed: Block was
expected to execute on queue [com.apple.main-thread (0x ... )]
```

Lines 1-2: CheckedContinuation only — UnsafeContinuation (same API) checks nothing. Line 3 = Swift 6's **dynamic isolation check** (SE-0423, 6.0): synchronous isolated code reachable from unchecked callers (@objc thunks, @preconcurrency witnesses, closures given to unchecked APIs, calls into Swift 6 modules) gets a compiler-inserted executor check (main actor: `dispatch_assert_queue`) and **crashes instead of racing**. Old-SDK apps only log "data race detected"; opt-out: `-disable-dynamic-actor-isolation`. `0x40000000000bad0` in a crash (ObjC, Xcode 26) = a racing nonatomic property: synthesized setters store that value briefly.

Traps

- ! "Spawn more tasks" — the pool never grows.
- ! Task.yield() is no starvation fix: the highest-priority task resumes at once.
- ! Blocked ≠ hang: an idle main thread is blocked too — ask Hangs, not thread states.
- ! Queue inspector (27) skips tasks enqueued before the trace.
- ! Profiling a Run-launched app: TPC's checks can show in stacks — use *Profile*.

Remember

Suspend, never block — the pool never grows.