

BNF for the Gryph Programming Language

Vitor Greati

Artur Curinga

Carlos Vieira

Vinícius Campos

May 16, 2018

Contents

1	General structure	1
1.1	Program	1
1.2	Statements	1
1.2.1	IO	2
1.2.2	Variables	2
1.3	Subprograms	2
1.3.1	Declaration	2
1.3.2	Call	2
2	Control Structures	2
2.1	If-else statements	2
3	Types	2
4	Expressions	3
4.1	Any expression	3
4.2	Relational expressions	3
4.3	Boolean expressions	3
4.4	Expressions with numbers, lists and strings	3

1 General structure

1.1 Program

$$\begin{aligned}\langle \text{program} \rangle &\models \langle \text{program-unit} \rangle \mid \langle \text{program-unit} \rangle \langle \text{program} \rangle \\ \langle \text{program-unit} \rangle &\models \langle \text{stmt} \rangle ; \mid \langle \text{subprog-decl} \rangle\end{aligned}$$

1.2 Statements

$$\begin{aligned}\langle \text{stmt-list} \rangle &\models \langle \text{stmt} \rangle ; \mid \langle \text{stmt} \rangle ; \langle \text{stmt-list} \rangle \\ \langle \text{stmt-block} \rangle &\models \{ \langle \text{stmt-list} \rangle \} \\ \langle \text{block-or-matched} \rangle &\models \langle \text{stmt-block} \rangle \mid \langle \text{matched-stmt} \rangle ; \\ \langle \text{com-stmt} \rangle &\models \langle \text{read-stmt} \rangle \mid \langle \text{print-stmt} \rangle \mid \langle \text{var-decl-stmt} \rangle \\ \langle \text{stmt} \rangle &\models \langle \text{matched-stmt} \rangle \mid \langle \text{unmatched-stmt} \rangle \\ \langle \text{matched-stmt} \rangle &\models \langle \text{matched-if-else} \rangle \mid \langle \text{com-stmt} \rangle \\ \langle \text{unmatched-stmt} \rangle &\models \langle \text{if-stmt} \rangle \mid \langle \text{unmatched-if-else} \rangle\end{aligned}$$

1.2.1 IO

$$\begin{aligned}\langle \text{read-stmt} \rangle &\models \text{read } \langle \text{ident} \rangle \\ \langle \text{write-stmt} \rangle &\models \text{print } \langle \text{ident} \rangle \mid \text{print } \langle \text{string-lit} \rangle\end{aligned}$$

1.2.2 Variables

$$\begin{aligned}\langle \text{ident-begin-stmt} \rangle &\models \langle \text{ident-list} \rangle \langle \text{ident-list-post} \rangle \\ \langle \text{ident-list-post} \rangle &\models \text{:} \langle \text{type} \rangle \langle \text{var-decl-stmt} \rangle \mid \langle \text{var-attr-stmt} \rangle \\ \langle \text{var-decl-stmt} \rangle &\models \lambda \mid \langle \text{var-attr-stmt} \rangle \\ \langle \text{var-attr-stmt} \rangle &\models = \langle \text{expr-list} \rangle\end{aligned}$$

1.3 Subprograms

1.3.1 Declaration

1.3.2 Call

$$\langle \text{subprog-call} \rangle \models \langle \text{ident} \rangle (\langle \text{expr-list} \rangle)$$

2 Control Structures

2.1 If-else statements

$$\begin{aligned}\langle \text{if-expr} \rangle &\models \text{if } (\langle \text{b-exp} \rangle) \\ \langle \text{if-stmt} \rangle &\models \langle \text{if-expr} \rangle \langle \text{stmt} \rangle; \\ \langle \text{unmatched-if-else} \rangle &\models \langle \text{if-expr} \rangle \langle \text{matched-stmt} \rangle; \text{else } \langle \text{unmatched-stmt} \rangle; \\ \langle \text{matched-if-else} \rangle &\models \langle \text{if-expr} \rangle \langle \text{block-or-matched} \rangle \text{else } \langle \text{block-or-matched} \rangle \mid \langle \text{if-expr} \rangle \langle \text{stmt-block} \rangle\end{aligned}$$

3 Types

$$\begin{aligned}\langle \text{type-list} \rangle &\models \langle \text{type} \rangle, \langle \text{type-list} \rangle \mid \langle \text{type} \rangle \\ \langle \text{type} \rangle &\models \langle \text{native-type} \rangle \mid \langle \text{user-type} \rangle \\ \langle \text{native-type} \rangle &\models \langle \text{primitive-type} \rangle \mid \langle \text{composite-type} \rangle \\ \langle \text{primitive-type} \rangle &\models \text{int} \mid \text{float} \mid \text{char} \mid \text{string} \\ \langle \text{composite-type} \rangle &\models [\langle \text{type} \rangle] \mid |\langle \text{type} \rangle| \mid (\langle \text{type} \rangle, \langle \text{type-list} \rangle) \mid \langle \text{graph-type} \rangle \\ \langle \text{graph-type} \rangle &\models <\langle \text{type} \rangle> \mid <\langle \text{type} \rangle, \langle \text{type} \rangle> \\ \langle \text{user-type} \rangle &\models \langle \text{upper-letter} \rangle \langle \text{alpha-num-list} \rangle\end{aligned}$$

Observations

- The maximum size of tuples depends on the language implementation, though, in the BNF description above, it may assume any value.

4 Expressions

4.1 Any expression

$$\langle \text{any-expr} \rangle \models \langle \text{rel-expr} \rangle \mid \langle \text{bool-expr} \rangle \mid \langle \text{expr} \rangle$$

4.2 Relational expressions

$$\begin{aligned} \langle \text{rel-expr} \rangle &\models \langle \text{rel-term} \rangle \langle \text{rel-expr-aux} \rangle \\ \langle \text{rel-expr-aux} \rangle &\models \langle \text{rel-op} \rangle \langle \text{rel-term} \rangle \mid \langle \text{rel-op} \rangle \langle \text{rel-term} \rangle \langle \text{rel-expr-aux} \rangle \\ \langle \text{rel-op} \rangle &\models > \mid < \mid <= \mid >= \mid == \mid != \\ \langle \text{rel-term} \rangle &\models \langle \text{any-expr} \rangle \end{aligned}$$

4.3 Boolean expressions

$$\begin{aligned} \langle \text{b-expr} \rangle &\models \langle \text{b-term} \rangle \mid \langle \text{b-term} \rangle \langle \text{b-expr-aux} \rangle \\ \langle \text{b-expr-aux} \rangle &\models \langle \text{b-bin-op-p0} \rangle \langle \text{b-term} \rangle \mid \langle \text{b-bin-op-p0} \rangle \langle \text{b-term} \rangle \langle \text{b-expr-aux} \rangle \\ \langle \text{b-term} \rangle &\models \langle \text{b-literal} \rangle \mid \langle \text{b-literal} \rangle \langle \text{b-term-aux} \rangle \\ \langle \text{b-term-aux} \rangle &\models \langle \text{b-bin-op-p1} \rangle \langle \text{b-literal} \rangle \mid \langle \text{b-bin-op-p1} \rangle \langle \text{b-literal} \rangle \langle \text{b-term-aux} \rangle \\ \langle \text{b-literal} \rangle &\models \langle \text{b-base} \rangle \mid \langle \text{b-un-op} \rangle \langle \text{b-base} \rangle \\ \langle \text{b-base} \rangle &\models (\langle \text{b-expr} \rangle) \mid \text{true} \mid \text{false} \mid \langle \text{rel-expr} \rangle \mid \langle \text{ident} \rangle \mid \langle \text{subprog-call} \rangle \\ \langle \text{b-un-op} \rangle &\models \text{not} \\ \langle \text{b-bin-op-p0} \rangle &\models \text{or} \mid \text{xor} \\ \langle \text{b-bin-op-p1} \rangle &\models \text{and} \end{aligned}$$

4.4 Expressions with numbers, lists and strings

$$\begin{aligned} \langle \text{expr} \rangle &\models \langle \text{term} \rangle \mid \langle \text{term} \rangle \langle \text{expr-aux} \rangle \\ \langle \text{expr-aux} \rangle &\models \langle \text{bin-op-p0} \rangle \langle \text{term} \rangle \mid \langle \text{bin-op-p0} \rangle \langle \text{term} \rangle \langle \text{expr-aux} \rangle \\ \langle \text{term} \rangle &\models \langle \text{factor} \rangle \mid \langle \text{factor} \rangle \langle \text{term-aux} \rangle \\ \langle \text{term-aux} \rangle &\models \langle \text{bin-op-p1} \rangle \langle \text{factor} \rangle \mid \langle \text{bin-op-p1} \rangle \langle \text{factor} \rangle \langle \text{term-aux} \rangle \\ \langle \text{factor} \rangle &\models \langle \text{literal} \rangle ^ \langle \text{factor} \rangle \mid \langle \text{literal} \rangle \\ \langle \text{literal} \rangle &\models \langle \text{basis} \rangle \mid + \langle \text{basis} \rangle \mid - \langle \text{basis} \rangle \\ \langle \text{basis} \rangle &\models (\langle \text{expr} \rangle) \mid \langle \text{ident} \rangle \mid \langle \text{int-lit} \rangle \mid \langle \text{float-lit} \rangle \mid \langle \text{list-lit} \rangle \mid \langle \text{subprog-call} \rangle \mid \langle \text{string-lit} \rangle \\ \langle \text{un-op} \rangle &\models + \mid - \\ \langle \text{bin-op-p0} \rangle &\models + \mid - \\ \langle \text{bin-op-p1} \rangle &\models * \mid / \mid \% \mid ++ \mid ** \end{aligned}$$