

















































git status











































































































Main.java



f228c1d

HEAD

master































“Hello World!”

Main.java



“Hello World!”

Main.java



united world

staged









































































M















































































































































```
package com.artusacademy
```

```
public class Main {
```

```
    public static void main(String[] args) {
```

```
        System.out.println("Hello World!");
```

```
    }
```

```
}
```

gitt innit





'Herld' 'World'

```
package com.artusacademy
```

```
public class Main {
```

```
    public static void main(String[] args) {
```

```
        System.out.println("Hello World");
```

```
    }
```

```
}
```

git add .

.git/  
Main.java

```
package com.artusacademy

public class Main {
    public static void main(String[] args) {
        System.out.println("Hello World!");
    }
}
```

```
$ git init
Initialized empty Git repository in /app/.git/

$ git add .

$ git add .

$ git commit -m "Initial commit"
[master (root-commit) f228c1d] Initial commit
1 file changed, 1 insertion(+)
create mode 100644 Main.java
```

untracked

staged

git repository

● f228c1d - Initial commit (HEAD → master) —  "Hello World!"  
Main.java

# Create another commit

- Add a integer variable `sum` whose value is `10 + 10`.
- Display the variable `sum` after `Hello World!`.
- Commit the code with message `Print sum`.