


Remote Exploit

Compass Security Schweiz AG
Werkstrasse 20
Postfach 2038
CH-8645 Jona

Tel +41 55 214 41 60
Fax +41 55 214 41 61
team@csnc.ch
www.csnc.ch



Remote Exploit Payload Types

Compass Security Schweiz AG
Werkstrasse 20
Postfach 2038
CH-8645 Jona

Tel +41 55 214 41 60
Fax +41 55 214 41 61
team@csnc.ch
www.csnc.ch

What is a remote exploit?

- ✦ Attacking an application **on another computer**
- ✦ Via the network

Local: Payload can be in :


- ✦ Program arguments
- ✦ File
- ✦ Environment variable
- ✦ Etc.

Remote:

- ✦ "Packets"
- ✦ Data sent to server

What is different between local and remote exploits?

- ✦ Theoretically, nothing
- ✦ Practically, there are some interesting differences
- ✦ These slides are mostly useful as reference for the hacking challenges



Payload differences:

- ✦ What exactly should we execute?


Payload possibilities:


Local server:


- ✦ Server:
 - ✦ Listen shell with netcat
 - ✦ `$ nc -l -e /bin/sh 192.168.1.1 4444`
- ✦ Client:
 - ✦ Connect with netcat
 - ✦ `$ nc 192.168.1.1 4444`

Connect-Back:

- ✦ Client: listen for shell with netcat
 - ✦ `$ nc -l`
- ✦ Server: connects back
 - ✦ Special shellcode







Remote Exploit

How do Daemons work?

Compass Security Schweiz AG
Werkstrasse 20
Postfach 2038
CH-8645 Jona

Tel +41 55 214 41 60
Fax +41 55 214 41 61
team@csnc.ch
www.csnc.ch

How do daemons work?




Server listens on a port

When a client connects (finished TCP handshake):


- ✦ Fork (Create new process, copy of current)
- ✦ Child handles the client

The parent is always ready for new connections


All connections are handled by children




How do daemons work?



How do daemons work?



How do daemons work?




How do daemons work?




Parent

- Server socket (listen)
- "Client 1" socket




Kernel

How do daemons work?



How do daemons work?



```
while (1) {  
    // Accept blocks until a client connects  
    newsockfd = accept(sockfd, ...);  
  
    // Make a copy of myself  
    pid = fork();  
  
    if (pid == 0) {  
        /* This is the client process */  
        doprocessing(newsockfd);  
    } else {  
        /* Server process - do nothing */  
    }  
}
```

WTF is this fork()?

- ✦ Create an EXACT copy of the current process
 - ✦ Duplicate memory pages as COW (copy on write), pretty cool stuff
- ✦ If return value == 0: You are in child
- ✦ If return value > 0: You are the parent

WTF are sockets?

- ✦ "Bidirectional pipes"
- ✦ Pipe: read(), write()
- ✦ Or: An integer which represents a pipe
- ✦ Child processes inherits sockets of parent
- ✦ Processes write/read to socket
 - ✦ OS makes sure it transports it to the other side (TCP/IP and stuff)


How do daemons work?



```
# ps axw | grep -i challenge
```

```
9008 pts/1 S+ 0:00 ./challenge6
```

```
9012 pts/1 Z+ 0:00 [challenge6] <defunct>
```



How do daemons work?



What is this <defunct> ?

A zombie process

"A zombie is a child, whose parent did not check their status after it died or was killed"

- ✦ Cant make this stuff up ☺

What if the parent of a child dies?

- ✦ When the parent dies too, the child gets adopted by init (pid 1) (true story ☺)

Why all this?

- ✦ No fork: all clients are served by the same process (serially)
- ✦ Worst case: process crashes, no more serving children

What are the alternatives?

- ✦ Threads
- ✦ A thread is not a new process (all threads run in the same process)
- ✦ Threads are created much faster than forks
- ✦ Fork() is kinda expensive

Apache

- ✦ mpm-pre-fork: Several (already started) children, no threads
- ✦ mpm-multi-threaded: Create one process, but several threads
- ✦ mpm-worker: Multiple processes, with multiple threads

Remote Exploit: Forking Daemon

Compass Security Schweiz AG
Werkstrasse 20
Postfach 2038
CH-8645 Jona

Tel +41 55 214 41 60
Fax +41 55 214 41 61
team@csnc.ch
www.csnc.ch


Exploiting differences:

- ✦ Everything is transmitted as packets
- ✦ Exploit may use several packets
- ✦ Or even use information in responses

How do daemons work?



Server



```
write (int fd, void *buf, size_t count);  
read  (int fd, void *buf, size_t count);
```


How do daemons

Internet in
between


COMPASS
SECURITY

Server

Client



```
write (int fd, void *buf, size_t count);  
read  (int fd, void *buf, size_t count);
```



Remote Exploit: Exploiting Differences



e.g.: Apache

Receive Data

- Defragmentation

Respond Data: HTTP Response

- Low level stuff

Parse Data: HTTP Request

- GET, POST?
- URL / PATH?

GET /1.0/addUser.php?id=1

Load File

Response

Start PHP

Response

Redirect

Response

Remote Exploit: Example

Compass Security Schweiz AG
Werkstrasse 20
Postfach 2038
CH-8645 Jona

Tel +41 55 214 41 60
Fax +41 55 214 41 61
team@csnc.ch
www.csnc.ch

How to interact with a remote server?

Netcat

- ✦ Netcat (nc) is like "telnet", but much simpler
- ✦ Allows sending and receiving bytes

```
[user@host]# nc smtp.domain.com 25
220 myrelay.domain.com ESMTP
HELO smtp.domain.com
250 myrelay.domain.com
MAIL FROM:<alice@hacker.com>
250 sender <alice@hacker.com> ok
RCPT TO:<bob@secure.net>
250 recipient <bob@secure.net> ok
DATA
```

How to interact with a remote server?

Netcat

- ✦ Connect to socket, write(socket) what we read(stdin)
- ✦ Just print() the exploit, and use nc to transfer it

```
./exploit.py | nc localhost 1337
```

Exploit.py:

```
print "A" * 200 + "BBB"
```

How to interact with a remote server?

Use perl/python/ruby/whatever

- ✦ Connect() to server
- ✦ Write() exploit

```
payload = "A" * 200 + "BBB"  
sock = socket.socket(socket.AF_INET,  
                        socket.SOCK_STREAM)  
server_address = ('localhost', 10000)  
sock.connect(server_address)  
sock.send(payload)  
data = sock.recv()
```

How to interact with a remote server?

Python and pwntools

```
tube = connect("localhost", 5001)
payload = "A" * 200 + "BBB"
```

```
def doBof():
    tube.recvuntil(">")
    tube.sendline("1");
    tube.sendline(payload)
    tube.recv()
```

```
doBof()
```

Remote Exploit debugging basics

Compass Security Schweiz AG
Werkstrasse 20
Postfach 2038
CH-8645 Jona

Tel +41 55 214 41 60
Fax +41 55 214 41 61
team@csnc.ch
www.csnc.ch

Remote Exploit debugging basics



Start vulnerable server in the background:

```
$ ./challenge16 &
```

Port already used? Kill old process/zombie:

```
$ pkill challenge16
```

Start GDB with the program:

```
$ gdb -q challenge16
```

Find <pid>:

```
$ ps axw | grep challenge16
```

Attach the parent:

```
(gdb) attach <pid>
```

Set follow-fork-mode child:

```
(gdb) set follow-fork-mode child
```

Continue:

```
(gdb) c
```

When executing the exploit:

- ✦ GDB will see fork()
- ✦ GDB will detach from parent
- ✦ GDB will attach to child
- ✦ Memory corruption in child -> debug along

Want to try improved exploit? Attach again:

```
(gdb) attach <pid>
```

```
(gdb) c
```


A vertical strip on the left side of the slide shows a close-up of a computer keyboard with a yellow padlock resting on one of the keys.

Recap

Compass Security Schweiz AG
Werkstrasse 20
Postfach 2038
CH-8645 Jona

Tel +41 55 214 41 60
Fax +41 55 214 41 61
team@csnc.ch
www.csnc.ch

Remote Exploit Recap:

- ✦ Shellcode needs to make shell available via network
- ✦ Services usually fork (identical copy of the parent) to handle connections