

HTML FORM

Form

- Un insieme di elementi in una pagina web con cui l'utente interagisce per inviare informazioni ad uno script

First name:

Last name:

https://www.w3schools.com/html/html_forms.asp

Mailing List Signup

MAILING LIST SIGNUP

Get news about the band such as tour dates and special MP3 releases sent to your own in-box.


Name:

Email:

Done ✓

Data

Name = Sally Strongarm
Email = strongarm@example.com



Mailing List Signup

THANKS

You are now on the band mailing list. Can't wait to see you out at the shows.

[Go back to the main page](#)

Done ✓

Elemento form

- `<form>...</form>`
- Serve a contenere gli elementi appartenenti al form
 - Attivi: campi di testo, bottoni, menu
 - Altri elementi descrittivi: tutti tranne form

Elemento input

- Un `<input>` elemento può essere visualizzato in molti modi, a seconda dell'attributo **type**.

<code><input type="text"></code>	Visualizza un campo di input di testo a riga singola
<code><input type="radio"></code>	Visualizza un pulsante di opzione
<code><input type="checkbox"></code>	Visualizza una casella di controllo
<code><input type="submit"></code>	Visualizza un pulsante di invio
<code><input type="button"></code>	Displays a clickable button
...	

Esempio

```
<form>
  <label for="fname">First name:</label><br>
  <input type="text" id="fname" name="fname"><br>
  <label for="lname">Last name:</label><br>
  <input type="text" id="lname" name="lname">
</form>
```

First name:

Last name:

Variabili e contenuto

- Ogni elemento nel form definisce una **variabile** che ha un **nome**
- L'utente interagendo con il form varia il **contenuto** delle variabili che vengono inviate al server
- Attributo **name**: id della variabile
- Attributo **value**: valore di default (opzionale)

```
<input type="text" id="fname" name="fname" value="John">
```

Elemento label

- Il `<label>` tag definisce un'etichetta per gli elementi form.
- Se cliccato attiva il corrispondente input
- Due modalità per associarli:
 - Circondare l'elemento da descrivere (implicita)
 - Usare l'attributo `for` di `<label>` che deve essere uguale all'attributo `id` di `<input>` (esplicita)

Esempio associazione Label

– associazione implicita

```
<ul>
  <li><label><input type="checkbox" name="genre" value="punk">Punk rock</label></li>
  <li><label><input type="checkbox" name="genre" value="indie">Indie rock</label></li>
  <li><label><input type="checkbox" name="genre" value="hiphop">Hip Hop</label></li>
  <li><label><input type="checkbox" name="genre" value="rockabilly">Rockabilly</label></li>
</ul>
```

– associazione esplicita

```
<label for="form-login-username">Login account</label>
<input type="text" name="login" id="form-login-username">

<label for="form-login-password">Password</label>
<input type="password" name="password" id="form-login-password">
```

Attributo action

- Contiene la **URL** dello script che elaborerà i dati

```
<form action="/action_page.php">
```

- Se non presente si assume che il suo valore sia quello della pagina corrente!!!

Attributo method

- Specifica la modalità di invio dei dati
 - valori: **get** o **post**

Dati:

username = Sally Strongarm

email = strongarm@example.com

- **GET (default)**
 - HTTP GET con i dati concatenati nella URL
 - si usa ? all'inizio e & fra i dati
 - <http://www.example.com/maillinglist.php?name=Sally%20Strongarm&email=strongarm%40example.com>
- **POST**
 - Dati inviati nel body della richiesta

ES. GET <http://pw.netgroup.uniroma2.it/esf/exf.html>

ES. POST <http://pw.netgroup.uniroma2.it/esf/exf2.html>

altri attributi form

- **accept-charset**
 - Specifies the charset used in the submitted form (default: the page charset).
- **action**
 - Specifies an address (url) where to submit the form (default: the submitting page).
- **autocomplete**
 - Specifies if the browser should autocomplete the form (default: on).
- **enctype**
 - Specifies the encoding of the submitted data (default: is **url-encoded**).
 - http://www.w3schools.com/tags/ref_urlencode.asp
- **method**
 - Specifies the HTTP method used when submitting the form (default: GET).
- **name**
 - Specifies a name used to identify the form (for DOM usage: `document.forms.name`).
- **novalidate**
 - Specifies that the browser should not validate the form.
- **target**
 - Specifies the target of the address in the action attribute (default: `_self`).

<http://pw.netgroup.uniroma2.it/esf/maillinglist.php?username=Pierpaolo&email=pierpaolo.loreti%40uniroma2.it>

Esempi

- http://www.w3schools.com/htmL/html_form_input_types.asp
- http://www.w3schools.com/htmL/html_form_attributes.asp
- http://www.w3schools.com/tags/tag_input.asp

Input Testuali singola riga

```
<input type="text">  
<input type="radio">  
<input type="button">  
<input type="checkbox">  
<input type="submit">
```

```
<input type="password">  
<input type="reset">  
<input type="hidden">  
<input type="file">
```

- HTML5 type
 - color, date, datetime, datetime-local, email, month, number, range, search, tel, time, url, week

Principali Attributi

disabled	Specifies that an input field should be disabled
max	Specifies the maximum value for an input field
maxlength	Specifies the maximum number of character
min	Specifies the minimum value for an input field
pattern against	Specifies a regular expression to check the input value
readonly changed)	Specifies that an input field is read only (cannot be
required out)	Specifies that an input field is required (must be filled
size	Specifies the width (in characters) of an input field
step	Specifies the legal number intervals for an input field
value	Specifies the default value for an input field

Text Area

- Area di input testuale multi riga

```
<label for="w3review">Review of W3Schools:</label>
```

```
<textarea id="w3review" name="w3review" rows="4" cols="50">
```

At w3schools.com you will learn how to make a website. They offer free tutorials in all web development technologies.

```
</textarea>
```

At w3schools.com you will learn how to make a website. They offer free tutorials in all web development technologies.

Submit

La dimensione di un'area di testo è specificata dagli attributi **cols** e **rows** (o con CSS).

Radio e checkbox

<p>How old are you?</p>

```
<li><input type="radio" name="age" value="under24" checked> under 24</li>
<li><input type="radio" name="age" value="25-34"> 25 to 34</li>
<li><input type="radio" name="age" value="35-44"> 35 to 44</li>
<li><input type="radio" name="age" value="over45"> 45+</li>
```


<p>What type of music do you listen to?</p>

```
<li><input type="checkbox" name="genre" value="punk" checked> Punk rock</li>
<li><input type="checkbox" name="genre" value="indie" checked> Indie rock</li>
<li><input type="checkbox" name="genre" value="hiphop"> Hip Hop</li>
<li><input type="checkbox" name="genre" value="rockabilly"> Rockabilly</li>
</ul>
```

Radio buttons

How old are you?

- ☒ under 24
- ☐ 25 to 34
- ☐ 35 to 44
- ☐ 45+

Checkbox buttons

What type of music do you listen to?

- ☒ Punk rock
- ☒ Indie rock
- ☐ Hip Hop
- ☐ Rockabilly

Menu drop down

- `<select>`
 - definisce il menu
- `<option>`
 - opzione del menu

```
<p>What is your favorite 80s band?
<select name="EightiesFave">
  <option>The Cure</option>
  <option>Cocteau Twins</option>
  <option>Tears for Fears</option>
  <option>Thompson Twins</option>
  <option value="EBTG">Everything But the Girl</option>
  <option>Depeche Mode</option>
  <option>The Smiths</option>
  <option>New Order</option>
</select>
</p>
```

What is your favorite 80s band?

Menu scelta multipla

```
<p>What 80s bands did you listen to?
<select name="EightiesBands" size="6" multiple>
  <option>The Cure</option>
  <option>Cocteau Twins</option>
  <option selected>Tears for Fears</option>
  <option selected>Thompson Twins</option>
  <option value="EBTG">Everything But the Girl</option>
  <option>Depeche Mode</option>
  <option>The Smiths</option>
  <option>New Order</option>
</select>
</p>
```

What 80s bands did you listen to?

The Cure
Cocteau Twins
Tears for Fears
Thompson Twins
Everything But the Girl
Depeche Mode

```
<select name="icecream" size="7" multiple>
  <optgroup label="traditional">
    <option>vanilla</option>
    <option>chocolate</option>
  </optgroup>
  <optgroup label="fancy">
    <option>Super praline</option>
    <option>Nut surprise</option>
    <option>Candy corn</option>
  </optgroup>
</select>
```

traditional
vanilla
chocolate
fancy
Super praline
Nut surprise
Candy corn

File

- Seleziona un file dall'computer locale
- Servono
 - method="post"
 - enctype="multipart/form-data"

```
<form action="/client.php" method="POST" enctype="multipart/form-data">
  <label>Send a photo to be used as your online icon <em>(optional)</em><br>
  <input type="file" name="photo" size="28"><label>
</form>
```

File input (Firefox)

Send a photo to be used as your online icon (*optional*):

File input (Chrome)

Send a photo to be used as your online icon (*optional*):

 No file chosen

Type hidden

- **Inviare informazioni che non provengono dall'utente**
 - dati query precedenti
 - referral
 - nonce

```
<input type="hidden" name="success-link"  
value="http://www.example.com/ littlechair_thankyou.html">
```

Design

- **Usabilità**

- Evitare gli input opzionali o non necessari
- Posizionare le label in modo opportuno
- Scegliere il tipo di input
- Raggruppare gli input correlati
- Evidenziare le azioni

- **Usate il CSS per posizionare e gestire lo stile del form**

fieldset e legend

- servono a creare dei gruppi logici ed a fornire una descrizione

```
<fieldset>
  <legend>Mailing List Sign-up</legend>
  <ul>
    <li><label>Add me to your mailing list
      <input type="radio" name="list" value="yes" checked="checked"></label></li>
    <li><label>No thanks <input type="radio" name="list" value="no"></label></li>
  </ul>
</fieldset>

<fieldset>
  <legend>Customer Information</legend>
  <ol>
    <li><label>Full name: <input type="text" name="username"></label></li>
    <li><label>Email: <input type="text" name="email"></label></li>
    <li><label>State: <input type="text" name="state"></label></li>
  </ol>
</fieldset>
```

Contest Entry Information

Name

Email

Telephone

Your story
No more than 300 characters long

Size Sizes reflect standard men's sizes

Color

- ☐ Red
- ☐ Blue
- ☐ Black
- ☐ Silver

Features

- ☐ Sparkley laces
- ☒ Metallic logo
- ☐ Light-up heels
- ☐ MP3-enabled

Contest Entry Information

Name

Email

Telephone

Your story
No more than 300 characters long

Size Sizes reflect standard men's sizes

Color ☐ Red ☐ Blue ☐ Black ☐ Silver

Features ☐ Sparkley laces
☒ Metallic logo
☐ Light-up heels
☐ MP3-enabled

Pimp My Shoes!

Reset

TABELLE HTML

<https://www.w3.org/TR/html4/struct/tables.html>

Tag per tabella

Tag	Description of the tag
<code><table></code>	Used to create tables.
<code><th></code>	Used to create table headers.
<code><tr></code>	Used to create rows of tables.
<code><td></code>	Used to create table cells or data.
<code><caption></code>	Used to set table captions.
<code><colgroup></code>	Used to group more than one column.
<code><col></code>	Used to set column properties in the <code><colgroup></code> element.
<code><thead></code>	Used to set table headers.
<code><tbody></code>	Used to set the body of the table.
<code><tfoot></code>	Used to set the footer of the table.

Esempio

```
<table style="width:100%">
  <tr>
    <th>Firstname</th>
    <th>Lastname</th>
    <th>Age</th>
  </tr>
  <tr>
    <td>Jill</td>
    <td>Smith</td>
    <td>50</td>
  </tr>
  <tr>
    <td>Eve</td>
    <td>Jackson</td>
    <td>94</td>
  </tr>
</table>
```

Firstname	Lastname	Age
Jill	Smith	50
Eve	Jackson	94
John	Doe	80