




## OPTIMIZATION OF AERO-BRACKET FOR LASER POWDER BED FUSION



### What?



- Optimized an aerospace bracket for **LP-PBF** manufacturing
- Aimed to minimize mass while ensuring safety under a **1600 N** tensile load

### How?

- Used Fusion 360 **Generative Design** to create an optimized **AlSi10Mg** structure
- Validated **FEA** results using hand calculations and physical tensile testing

### Results

- Achieved **86%** mass reduction (223g to 31g) with a **Safety Factor of 6.5**
- Withstood **9018 N** (machine limit) without failure, exceeding requirements by **560%**
- Calculations confirmed peak stress (**~209 MPa**) remained safely below the **460 MPa** limit



1

PRESERVE AND  
OBSTACLE  
GEOMETRIES

2

SETUP LOADS AND  
CONSTRAINTS

3

OBJECTIVES AND  
MANUFACTURING

4

MATERIAL  
SELECTION

5

EXPLORE  
GENERATIVE DESIGN

# ALFONSO RUIZ


MECHANICAL ENGINEERING AT THE UNIVERSITY OF TEXAS AT EL PASO

✉ aruiz40@miners.utep.edu

in linkedin.com/in/alfonso-ruiz01/

☎ (915)-834-9824

## TRANSPORTATION VIA ULTRASONIC LEVITATION SYSTEM



### What?


- Created a transport system using **ultrasonic levitation**
- Aimed to **move small particles of styrofoam** without any physical contact
- Focused on demonstrating non-contact object handling

### How?


- Utilized Arduino Nanos to control the systems
- Integrated transducers, buck converters, H-bridges, IR sensor and motors for levitation and transportation
- Used **Fusion 360** to design and **3D-print** a custom base for stability and transportation of the systems

### Results

- Achieved stable levitation of small particles of styrofoam using ultrasonic waves
- Enabled precise remote control for object movement
- Demonstrated effective non-contact transport capabilities







### Ultrasonic Levitation





## LASER SECURITY ALARM SYSTEM



### What?

- Designed a **Laser Security Alarm System** for enhanced vault security.
- Aimed to detect unauthorized access



### How?

- Integrated a laser with strategically placed mirrors to form a detection grid.
- Utilized mirrors, alarms, laser, servo, photoresistor, LCD display, and **RFID and I2C technology**
- Connected **audiovisual components** to trigger an alarm when the laser beam was interrupted
- Implemented an **RFID sensor** for key card access for authorized entry

### Results

- Achieved accurate detection of obstacles breaking the laser grid
- Successfully integrated RFID access control for user convenience
- Delivered a reliable, effective security solution for sensitive areas

## HEAT SINK DESIGN



### What?

- Design a heat sink that lowers a simulating CPU surface by  $22 \pm 1^\circ\text{C}$
- Performed a natural convection-cooled thermal simulation

### How?

- Used **Fusion 360** to design the heat sink and perform the thermal simulations
- Used **heat transfer formulas** to determine characteristics

### Results

- The design fulfilled its purpose by reducing the temperature of the surface from  $85^\circ\text{C}$  to  $64.3^\circ\text{C}$