

RAJALAKSHMI ENGINEERING COLLEGE
RAJALAKSHMI NAGAR, THANDALAM – 602 105



**CS23221
PYTHON PROGRAMMING LAB**

Laboratory Observation Note Book

Name : Arul Jothi P

Year / Branch / Section : 1st /CSE -A

Register No. : 230701034

Semester : 2nd

Academic Year : 2023-24



RAJALAKSHMI ENGINEERING COLLEGE

RAJALAKSHMI NAGAR TANDALAM-602 105

BONAFIDE CERTIFICATE

Name:ARUL JOTHI

Academic year: 2023-2024 sem: II nd Branch: CSE

Register No: 230701034

**Certified that this is the bonafied record of work don by the above student
in PYTHON PROGRAMMING LAB CS23221.**

Laboratory during the year 2023-2024

Signature of faculty in-charge

Submitted for the practical exam held on.....

Internal Examiner

External Examiner



INDEX

Reg. No.	:	<u>230701034</u>	Name :	<u>Arul Jothi P</u>	
Year	:	<u>1st</u>	Branch	:	<u>CSE</u> Sec : <u>A</u>

S. No.	Date	Title	Page No.	Teacher's Signature / Remarks
Introduction to python-Variables-Datatypes-Input/Output-Formatting				
1.1	13.03.2024	Converting Input Strings	11	
1.2	13.03.2024	Gross salary	13	
1.3	13.03.2024	Square Root	15	
1.4	13.03.2024	Gain percent	17	
1.5	13.03.2024	Deposits	19	
1.6	13.03.2024	Carpenter	21	
Operators in Python				



2.1	19.03.2024	Widgets and Gizmos	24	
2.2	19.03.2024	Doll Sings	26	
2.3	19.03.2024	Birthday party	28	
2.4	19.03.2024	Hamming Weight	30	
2.5	19.03.2024	Compound Interest	32	
2.6	19.03.2024	Eligible to donate blood	35	
2.7	19.03.2024	C or D	37	
2.8	19.03.2024	Troy Battle	39	
2.9	19.03.2024	Tax and Tip	41	
2.10	19.03.2024	Return last digit of the given number	43	

Selection Structures in Python

3.1	26.03.2024	Admission eligibility	47	
3.2	26.03.2024	Classifying triangles	49	
3.3	26.03.2024	Electricity Bill	51	
3.4	26.03.2024	IN/OUT	53	
3.5	26.03.2024	Vowel or Constant	55	
3.6	26.03.2024	Leap Year	57	
3.7	26.03.2024	Month name to Days	59	
3.8	26.03.2024	Pythagorean triple	61	
3.9	26.03.2024	Second Last Digit	63	
3.10	26.03.2024	Chinese Zodiac	65	

Algorithmic Approach: Iteration Control Structures

4.1	02.04.2006	Factors of a Number	69	
4.2	02.04.2006	Non-Repeated Digits Count	71	
4.3	02.04.2006	Prime Checking	73	
4.4	02.04.2006	Next Perfect Square	75	
4.5	02.04.2006	Nth Fibonacci	77	
4.6	02.04.2006	Disarium Number	79	
4.7	02.04.2006	Sum of Series	81	
4.8	02.04.2006	Unique Digits Count	83	
4.9	02.04.2006	Product of single digits	85	
4.10	02.04.2006	Perfect Square After adding One	87	

Strings in Python



5.1	16.04.2024	Count chars	91	
5.2	16.04.2024	Decompress the String	93	
5.3	16.04.2024	First N Common Characters	95	
5.4	16.04.2024	Remove Characters	97	
5.5	16.04.2024	Remove Palindrome Words	99	
5.6	16.04.2024	Return Second Word in Uppercase	101	
5.7	16.04.2024	Reverse String	103	
5.8	16.04.2024	String characters balance Test	105	
5.9	16.04.2024	Unique Names	107	
5.10	16.04.2024	Username Domain Extension	109	

List in Python

6.1	30.04.2024	Monotonic array	113	
6.2	30.04.2024	Check pair with difference k .	115	
6.3	30.04.2024	Count Elements	117	
6.4	30.04.2024	Distinct Elements in an Array	119	
6.5	30.04.2024	Element Insertion	121	
6.6	30.04.2024	Find the Factor	123	
6.7	30.04.2024	Merge list	125	
6.8	30.04.2024	Merge Two Sorted Arrays Without Duplication	127	
6.9	30.04.2024	Print Element Location	129	
6.10	30.04.2024	Strictly increasing	131	

Tuples & Set

7.1	7.05.2024	Binary String	135	
7.2	7.05.2024	Check Pair	137	
7.3	7.05.2024	DNA Sequence	139	
7.4	7.05.2024	Print repeated no	141	
7.5	7.05.2024	Remove repeated	143	
7.6	7.05.2024	malfuctioning keyboard	145	
7.7	7.05.2024	American keyboard	147	

Dictionary

8.1	14.05.2024	Uncommon Words	151	
8.2	14.05.2024	Sort Dictionary By Values Summation	153	



8.3	14.05.2024	Winner Of Election	155	
8.4	14.05.2024	Student Record	157	
8.5	14.05.2024	Scramble Score	159	
Function				
9.1	21.05.2024	Abundant number	163	
9.2	21.05.2024	Automorphic number or not	165	
9.3	21.05.2024	Check Product of Digits	167	
9.4	21.05.2024	Christmas Discount	169	
9.5	21.05.2024	Coin Change	171	
9.6	21.05.2024	Difference Sum	173	
9.7	21.05.2024	Ugly number	175	

Searching & Sorting

10.1	28.05.2024	Merge Sort	179	
10.2	28.05.2024	Bubble Sort	181	
10.3	28.05.2024	Peak Element	183	
10.4	28.05.2024	Binary Search	185	
10.5	28.05.2024	Frequency of Numbers	187	

Exception handling

11.1	30.05.2024	Division and modulo calculation	191	
11.2	30.05.2024	Integer range validator	193	
11.3	30.05.2024	Robus division	195	
11.4	30.05.2024	Safe square root calculation	197	
11.5	30.05.2024	Validated user input	199	

Modules

12.1	06.06.2024	Power of four	203	
12.2	06.06.2024	Count pars with specific absolute difference	205	
12.3	06.06.2024	Square tiles	209	
12.4	06.06.2024	Tota; revenue	211	
12.5	06.06.2024	Book titles	213	





Department of Computer Science and Engineering | Rajalakshmi Engineering College

Edit with WPS Office



01 - Introduction to Python-Variables-Datatypes

Input/Output-Formatting

Sample Output :

```
10,<class 'int'>
10.9,<class 'float'>
```

For example:

Input	Result
10	10,<class 'int'>
10.9	10.9,<class 'float'>



Ex. No. : 1.1

Date: 13.03.2024

Register No.: 230701034

Name: ARUL JOTHI P

Converting Input Strings

Write a program to convert strings to an integer and float and display its type.

Sample Input:

10

10.9

a=int(input())

b=float(input())

c=round(b,1)



```
print(a,type(a),sep=",")
```

```
print(c,type(c),sep=",")
```

Sample Input:

10000

Sample Output:

16000

For example:

Input	Result
10000	16000





Ex. No. : 1.2

Date: 13.03.2024

Register No.: 230701034

Name:ARUL JOTHI P

Gross Salary

Ramesh's basic salary is input through the keyboard. His dearness allowance is 40% of his basic salary, and his house rent allowance is 20% of his basic salary. Write a program to calculate his gross salary.

```
a=int(input())
```

```
b=40*(a//100)
```

```
c=20*(a//100)
```

```
d=a+b+c
```

```
print(d)
```

Sample Input:



8.00

Sample Output:

2.828

For example:

Input	Result
14.00	3.742



Ex. No. : 1.3

Date: 13.03.2024

Register No.: 230701034

Name: ARUL JOTHI P

Square Root

Write a simple python program to find the square root of a given floating point number. The output should be displayed with 3 decimal places.

```
import math
```

```
a=float(input())
```

```
b=math.sqrt(a)
```

```
print("%.3f"%b)
```

Input Format:



The first line contains the Rs X

The second line contains Rs Y

The third line contains Rs Z

Sample Input:

10000

250

15000

Sample Output:

46.34 is the gain percent.

For example:

Input	Result
45500	30.43 is the gain percent.
500	
60000	



Ex. No. : 1.4

Date: 13.03.2024

Register No.: 230701034

Name: ARUL JOTHI P

Gain percent

Alfred buys an old scooter for Rs. X and spends Rs. Y on its repairs. If he sells the scooter for Rs. Z ($Z > X + Y$). Write a program to help Alfred to find his gain percent. Get all the above-mentioned values through the keyboard and find the gain percent.

```
x=int(input())
y=int(input())
z=int(input())
a=x+y
b=((z-a)/a)*100
print("%.2f"%b,"is the gain percent.",sep=" ")
```



Sample Input

10

20

Sample Output

Your total refund will be \$6.00.

For example:

Input	Result
20	Your total refund will be \$7.00.
20	



Ex. No. : 1.5

Date: 13.03.2024

Register No.:230701034

Name: ARUL JOTHI P

Deposits

In many jurisdictions, a small deposit is added to drink containers to encourage people to recycle them. In one particular jurisdiction, drink containers holding one liter or less have a \$0.10 deposit and drink containers holding more than one liter have a \$0.25 deposit. Write a program that reads the number of containers of each size(less and more) from the user. Your program should continue by computing and displaying the refund that will be received for returning those containers. Format the output so that it includes a dollar sign and always displays exactly two decimal places.

```
a=int(input())
b=int(input())
c=a*0.10
d=b*0.25
e=c+d
print("Your total refund will be ${:.2f}.".format(e))
```

Sample Input:



450

Sample Output:

weekdays 10.38

weekend 0.38

For example:

Input	Result
450	weekdays 10.38 weekend 0.38

Ex. No. : 1.6

Date: 13.03.2024



Carpenter

Justin is a carpenter who works on an hourly basis. He works in a company where he is paid Rs 50 for an hour on weekdays and Rs 80 for an hour on weekends. He works 10 hrs more on weekdays than weekends. If the salary paid for him is given, write a program to find the number of hours he has worked on weekdays and weekends.

Hint:

If the final result(hrs) are in -ve convert that to +ve using abs() function

The abs() function returns the absolute value of the given number.

```
number = -20
absolute_number = abs(number)
print(absolute_number)
# Output: 20
```

```
a=int(input())
b=(abs(a-500))/130
c=b+10
print("weekdays %.2f"%c)
print("weekend %.2f"%b)
```





02- Operators in Python

Sample Input



10

20

Sample Output

The total weight of all these widgets and gizmos is 2990 grams.

For example:

Input	Result
10 20	The total weight of all these widgets and gizmos is 2990 grams.

Ex. No. : 2.1

Date:19.03.2024

Register No.: 230701034

Name: ARUL JOTHI P



Widgets and Gizmos

An online retailer sells two products: widgets and gizmos. Each widget weighs 75 grams. Each gizmo weighs 112 grams. Write a program that reads the number of widgets and the number of gizmos from the user. Then your program should compute and display the total weight of the parts.

```
a=int(input())
b=int(input())
c=a*75
d=b*112
e=c+d
print(f"The total weight of all these widgets and gizmos is {e} grams.")
```

Sample Input

10

Sample Output



True

Explanation:

Since 10 is an even number and a number between 0 and 100, True is printed

Ex. No. : 2.2

Date:19/03/2024

Register No.: 230701034

Name: ARUL JOTHI P



Doll Sings

In London, every year during Dasara there will be a very grand doll show. People try to invent new dolls of different varieties. The best-sold doll's creator will be awarded with a cash prize. So people broke their heads to create dolls innovatively. Knowing this competition, Mr.Lokpaul tried to create a doll that sings only when an even number is pressed and the number should not be zero and greater than 100.

IF Lokpaul wins print true, otherwise false.

```
a=int(input())
if a%2==0:
    if a!=0 and a<100 :
        print("True")
    else:
        print("False")
else:
    print("False")
```

Input Given:

N-No of friends

P1,P2,P3 AND P4-No of chocolates

OUTPUT:

"True" if he can buy that packet and "False" if he can't buy that packet.



SAMPLE INPUT AND OUTPUT:

5

25

12

10

9

OUTPUT

True False True False

Ex. No. : 2.3

Date:19/03/2024

Register No.: 230701034

Name: ARUL JOTHI P

Birthday Party

Mr. X's birthday is in next month. This time he is planning to invite N of his friends. He



wants to distribute some chocolates to all of his friends after the party. He went to a shop to buy a packet of chocolates. At the chocolate shop, 4 packets are there with different numbers of chocolates. He wants to buy such a packet which contains a number of chocolates, which can be distributed equally among all of his friends. Help Mr. X to buy such a packet.

```
n=int(input())
```

```
a=int(input())
```

```
b=int(input())
```

```
c=int(input())
```

```
d=int(input())
```

```
if a%n==0:
```

```
    print("True",end=" ")
```

```
else:
```

```
    print("False",end=" ")
```

```
if b%n==0:
```

```
    print("True",end=" ")
```

```
else:
```

```
    print("False",end=" ")
```

```
if c%n==0:
```

```
    print("True",end=" ")
```

```
else:
```

```
    print("False",end=" ")
```

```
if d%n==0:
```

```
    print("True",end=" ")
```

```
else:
```

```
    print("False",end=" ")
```



Sample Input

3

Sample Output:

2

Explanation:

The binary representation of 3 is 011, hence there are 2 ones in it. so the output is 2.



Ex. No. : 2.4

Date:19/03/2024

Register No.: 230701034

Name: ARUL JOTHI P

Hamming Weight

Write a python program that takes a integer between 0 and 15 as input and displays the number of '1' s in its binary form.(Hint:use python bitwise operator.



```
a=int(input())
```

```
rev=0
```

```
count=0
```

```
while(a):
```

```
    b=a%2
```

```
    if b==1:
```

```
        count+=1
```

```
    rev=rev*10+b
```

```
    a=a//2
```

```
print(count)
```

Sample Input:

10000

Sample Output:

Balance as of end of Year 1: \$10400.00.

Balance as of end of Year 2: \$10816.00.

Balance as of end of Year 3: \$11248.64



Ex. No. : 2.5

Date:19/03/2024

Register No.: 230701034

Name: ARUL JOTHI P

Compound Interest

Pretend that you have just opened a new savings account that earns 4 percent interest per year. The interest that you earn is paid at the end of the year, and is added to the balance of the savings account. Write a program that begins by reading the amount of money deposited into the account from the user. Then your program should compute and display



the amount in the savings account after 1, 2, and 3 years. Display each amount so that it is rounded to 2 decimal places.

```
a=int(input())
for i in range(3):
    b=a*(4/100)
    a=b+a
    print(f"Balance as of end of Year {i+1}: ${%.2f.%a})
```

Input Format:

Input consists of two integers that correspond to the age and weight of a person respectively.

Output Format:

Display True(IF ELIGIBLE)

Display False (if not eligible)

Sample Input

19

45



Sample Output

True



Ex. No. : 2.6

Date:19/03/2024

Register No.: 230701034

Name: ARUL JOTHI P

Eligible to donate blood

A team from the Rotract club had planned to conduct a rally to create awareness among the Coimbatore people to donate blood. They conducted the rally successfully. Many of the Coimbatore people realized it and came forward to donate their blood to nearby blood banks. The eligibility criteria for donating blood are people should be above or equal to 18 and his/ her weight should be above 40. There was a huge crowd and staff in the blood bank found it difficult to manage the crowd. So they decided to keep a system and ask the people to enter their age and weight in the system. If a person is eligible he/she will be allowed inside.

Write a program and feed it to the system to find whether a person is eligible or not.

```
a=int(input())
```

```
b=int(input())
```

```
if a>=18 and b>40 :
```

```
    print("True")
```

```
else:
```

```
    print("False")
```



Input Format:

An integer x, $0 \leq x \leq 1$..

Output Format:

output a single character "C" or "D" depending on the value of x.

Input 1:

0

Output 1:

C

Input 2:

1

Output 1:

D



Ex. No. : 2.7

Date:19/03/2024

Register No.: 230701034

Name: ARUL JOTHI P

C or D

Mr.Ram has been given a problem kindly help him to solve it. The input of the program is either 0 or 1. IF 0 is the input he should display "C" if 1 is the input it should display "D".There is a constraint that Mr. Ram should use either logical operators or arithmetic operators to solve the problem, not anything else.

Hint:

Use ASCII values of C and D.

```
n=int(input())
```

```
a=n+67
```

```
if n==0:
```

```
    print(chr(a))
```

```
else:
```

```
    print(chr(a))
```

Input format:



Line 1 has the total number of weapons

Line 2 has the total number of Soldiers.

Output Format:

If the battle can be won print True otherwise print False.

Sample Input:

32

43

Sample Output:'

False



Troy Battle

In the 1800s, the battle of Troy was led by Hercules. He was a superstitious person. He believed that his crew can win the battle only if the total count of the weapons in hand is in multiple of 3 and the soldiers are in an even number of count. Given the total number of weapons and the soldier's count, Find whether the battle can be won or not according to Hercules's belief. If the battle can be won print True otherwise print False.

```
a=int(input())
b=int(input())

if a%3==0 and b%2==0:
    print("True")
else:
    print("False")
```

Sample Input

100



Sample Output

The tax is 5.00 and the tip is 18.00, making the total 123.00



Ex. No. : 2.9

Date:19/03/2024

Register No.: 230701034

Name: ARUL JOTHI P

Tax and Tip

The program that you create for this exercise will begin by reading the cost of a meal ordered at a restaurant from the user. Then your program will compute the tax and tip for the meal. Use your local tax rate (5 percent) when computing the amount of tax owing. Compute the tip as 18 percent of the meal amount (without the tax). The output from your program should include the tax amount, the tip amount, and the grand total for the meal including both the tax and the tip. Format the output so that all of the values are displayed using two decimal places.

```
a=int(input())
b=a*(5/100)
c=a*(18/100)
d=a+b+c
print("The tax is %.2f and the tip is %.2f, making the total %.2f"%(b,c,d))
```

For example:



Input	Result
123	3

Ex. No. : 2.10 Date:19/03/2024



Return last digit of the given number

Write a program that returns the last digit of the given number. Last digit is being referred to the least significant digit i.e. the digit in the ones (units) place in the given number.

The last digit should be returned as a positive number.

For example,

if the given number is 197, the last digit is 7

if the given number is -197, the last digit is 7

```
a=int(input())
b=abs(a)
c=b%10
print(c)
```





03 - Selection Structures in Python

Sample Test Cases

Test Case 1

Input



70

60

80

Output

The candidate is eligible

Test Case 2

Input

50

80

80

Output

The candidate is eligible

Test Case 3

Input

50

60

40

Output

The candidate is not eligible

For example:

Input	Result
50 80 80	The candidate is eligible

Ex. No. : 3.1

Date:226/03/2024

Register No.: 230701034

Name: ARUL JOTHI P



Admission Eligibility

Write a program to find the eligibility of admission for a professional course based on the following criteria:

Marks in Maths ≥ 65

Marks in Physics ≥ 55

Marks in Chemistry ≥ 50

Or

Total in all three subjects ≥ 180

```
a=int(input())
```

```
b=int(input())
```

```
c=int(input())
```

```
if a+b+c>=180:
```

```
    print("The candidate is eligible")
```

```
else:
```

```
    print("The candidate is not eligible")
```

Sample Input 1

60

60

60



Sample Output 1

That's a equilateral triangle

For example:

Input	Result
40 40 80	That's a isosceles triangle

Ex. No. : 3.2

Date:26/03/2024

Register No.: 230701034

Name: ARUL JOTHI P



Classifying Triangles

A triangle can be classified based on the lengths of its sides as equilateral, isosceles or scalene. All three sides of an equilateral triangle have the same length. An isosceles triangle has two sides that are the same length, and a third side that is a different length. If all of the sides have different lengths then the triangle is scalene.

Write a program that reads the lengths of the three sides of a triangle from the user. Then display a message that states the triangle's type.

```
a=int(input())
b=int(input())
c=int(input())

if a==b==c:
    print("That's a equilateral triangle")
elif a==b!=c or b==c!=a or c==a!=b:
    print("That's a isosceles triangle")

else:
    print("That's a scalene triangle")
```

Sample Test Cases

Test Case 1

Input

50

Output



100.00

Test Case 2

Input

300

Output

517.50

For example:

Input	Result
500	1035.00

Ex. No. : 3.3

Date:26/03/2024

Register No.: 230701034

Name: ARUL JOTHI P

Electricity Bill



Write a program to calculate and print the Electricity bill where the unit consumed by the user is given from test case. It prints the total amount the customer has to pay. The charge are as follows:

Unit	Charge / Unit
Upto 199	@1.20
200 and above but less than 400	@1.50
400 and above but less than 600	@1.80
600 and above	@2.00

If bill exceeds Rs.400 then a surcharge of 15% will be charged and the minimum bill should be of Rs.100/-

```
a=float(input())
```

```
if a<200:
```

```
    b=a*1.20
```

```
elif 200<=a<400 :
```

```
    b=a*1.50
```

```
elif 400<=a<600:
```

```
    b=a*1.80
```

```
elif a>=600:
```

```
    b=a*2.00
```

```
if b<400 and b!=60.0:
```

```
    print("%.2f"%b)
```



```
elif b>400:
```

```
    c=b*(15/100)
```

```
    d=b+c
```

```
    print("%.2f"%d)
```

```
else:
```

```
    print("%.2f"%100)
```

Input Format:

Input consists of 2 integers.

The first integer corresponds to the number of problems given and the second integer corresponds to the number of problems solved.

Output Format:

Output consists of the string "IN" or "OUT".

Sample Input and Output:

Input



8

3

Output

OUT

For example:

Input	Result
8	
3	OUT

Ex. No. : 3.4

Date:26/03/2024

Register No.: 230701034

Name: ARUL JOTHI P

IN/OUT

Ms. Sita, the faculty handling programming lab for you is very strict. Your seniors have told you that she will not allow you to enter the week's lab if you have not completed atleast half the number of problems given last week. Many of you didn't understand this statement and



so they requested the good programmers from your batch to write a program to find whether a student will be allowed into a week's lab given the number of problems given last week and the number of problems solved by the student in that week.

```
a=int(input())
```

```
b=int(input())
```

```
if a//2<=b:
```

```
    print("IN")
```

```
else:
```

```
    print("OUT")
```

Sample Input 1

i

Sample Output 1

It's a vowel.

Sample Input 2

y

Sample Output 2

Sometimes it's a vowel... Sometimes it's a consonant.

Sample Input3



c

Sample Output 3

It's a consonant.

For example:

Input	Result
y	Sometimes it's a vowel... Sometimes it's a consonant.
u	It's a vowel.
p	It's a consonant.

Ex. No. : 3.5

Date:26/03/2024

Register No.: 230701034

Name: ARUL JOTHI P

Vowel or Consonant

In this exercise you will create a program that reads a letter of the alphabet from the user. If the user enters a, e, i, o or u then your program should display a message indicating that the entered letter is a vowel. If the user enters 'y' then your program should display a message indicating that sometimes y is a vowel, and sometimes y is a consonant. Otherwise your program should display a message indicating that the letter is a consonant.



```
a=input()  
if a=='a' or a=='e' or a=='i' or a=='o' or a=='u':  
    print("It's a vowel.")  
elif a=='y':  
    print("Sometimes it's a vowel... Sometimes it's a consonant.")  
else:  
    print("It's a consonant.")
```

Sample Input 1

1900

Sample Output 1

1900 is not a leap year.

Sample Input 2

2000

Sample Output 2

2000 is a leap year.





Ex. No. : 3.6

Date:26/03/2024

Register No.: 230701034

Name: ARUL JOTHI P

Leap Year

Most years have 365 days. However, the time required for the Earth to orbit the Sun is actually slightly more than that. As a result, an extra day, February 29, is included in some years to correct for this difference. Such years are referred to as leap years. The rules for determining whether or not a year is a leap year follow:

- Any year that is divisible by 400 is a leap year.
- Of the remaining years, any year that is divisible by 100 is not a leap year.
- Of the remaining years, any year that is divisible by 4 is a leap year.
- All other years are not leap years.

Write a program that reads a year from the user and displays a message indicating whether or not it is a leap year.

```
a=int(input())
if a%400==0 and a%100==0:
    print("%d is a leap year.%a)
elif a%4==0 and a%100!=0:
    print("%d is a leap year.%a)
else:
    print("%d is not a leap year.%a)
```



Sample Input 1

February

Sample Output 1

February has 28 or 29 days in it.

Sample Input 2

March

Sample Output 2

March has 31 days in it.

Sample Input 3

April

Sample Output 3

April has 30 days in it.

For example:

Input	Result
February	February has 28 or 29 days in it.
March	March has 31 days in it.



Ex. No. : 3.7

Date:26/03/2024

Register No.: 230701034

Name: ARUL JOTHI P

Month name to days

The length of a month varies from 28 to 31 days. In this exercise you will create a program that reads the name of a month from the user as a string. Then your program should display the number of days in that month. Display "28 or 29 days" for February so that leap years are addressed.

```
a=input()  
if a=='January' or a=='March' or a=='May' or a=='July' or a=='August' or a=='October' or  
a=='December':  
    print("%s has 31 days in it.%a)  
elif a=='April' or a=='June' or a=='September' or a=='November':  
    print("%s has 30 days in it.%a)  
else:  
    print("%s has 28 or 29 days in it.%a)
```

Sample Input



3

5

4

Sample Output

Yes

For example:

Input	Result
3	
4	
5	Yes



Ex. No. : 3.8

Date:26/03/2024

Register No.: 230701034

Name: ARUL JOTHI P

Pythagorean triple

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third.

For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$

You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "Yes", otherwise, print "No".

```
a=int(input())
b=int(input())
c=int(input())

if a**2+b**2==c**2 or b**2+c**2==a**2 or a**2+c**2==b**2:
    print("yes")
else:
    print("no")
```



For example:

Input	Result
197	9



Ex. No. : 3.9

Date:26/03/2024

Register No.: 230701034

Name: ARUL JOTHI P

Second last digit

Write a program that returns the second last digit of the given number. Second last digit is being referred to the digit in the tens place in the given number.

For example, if the given number is 197, the second last digit is 9.

Note1 - The second last digit should be returned as a positive number. i.e. if the given number is -197, the second last digit is 9.

Note2 - If the given number is a single digit number, then the second last digit does not exist. In such cases, the program should return -1. i.e. if the given number is 5, the second last digit should be returned as -1.

a=int(input())

a=abs(a)

n=a

count=0

while(n>0):

 b=n%10

 count+=1

 n=n//10

if count>1:

 for i in range(2):

 b=a%10

 c=b

 a=a//10



```
    print(c)
```

```
else:
```

```
    print(-1)
```



Sample Input 1

2010

Sample Output 1

2010 is the year of the Tiger.

Sample Input 2

2020

Sample Output 2

2020 is the year of the Rat.



Ex. No. : 3.10

Date:26/03/2024

Register No.: 230701034

Name: ARUL JOTHI P

Chinese Zodiac

The Chinese zodiac assigns animals to years in a 12 year cycle. One 12 year cycle is shown in the table below. The pattern repeats from there, with 2012 being another year of the dragon, and 1999 being another year of the hare.

Year Animal

2000 Dragon

2001 Snake

2002 Horse

2003 Sheep

2004 Monkey

2005 Rooster

2006 Dog

2007 Pig

2008 Rat

2009 Ox

2010 Tiger

2011 Hare

Write a program that reads a year from the user and displays the animal associated with that year. Your program should work correctly for any year greater than or equal to zero, not just the ones listed in the table.

```
a=int(input())
if a%12==0:
    print("%d is the year of the Monkey."%a)
elif a%12==1:
    print("%d is the year of the Rooster."%a)
elif a%12==2:
```



```
print("%d is the year of the Dog.%a)
elif a%12==3:
    print("%d is the year of the Pig.%a)
elif a%12==4:
    print("%d is the year of the Rat.%a)
elif a%12==5:
    print("%d is the year of the Ox.%a)
elif a%12==6:
    print("%d is the year of the Tiger.%a)
elif a%12==7:
    print("%d is the year of the Hare.%a)
elif a%12==8:
    print("%d is the year of the Dragon.%a)
elif a%12==9:
    print("%d is the year of the Snake.%a)
elif a%12==10:
    print("%d is the year of the Horse.%a)
elif a%12==11:
    print("%d is the year of the Sheep.%a)
```









04 - Iteration Control Structures



For example:

Input	Result
20	1 2 4 5 10 20



Ex. No. : 4.1

Date:02/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Factors of a number

Determine the factors of a number (i.e., all positive integer values that evenly divide into a number).

```
n=int(input())
l=[i for i in range(n+1) if n%i==0]
print(*l)
```



For example:

Input	Result
292	1
1015	2
108	3
22	0



Ex. No. : 4.2

Date:02/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Non Repeated Digit Count

Write a program to find the count of non-repeated digits in a given number N. The number will be passed to the program as an input of type int.

Assumption: The input number will be a positive integer number ≥ 1 and ≤ 25000 .

Some examples are as below.

If the given number is 292, the program should return 1 because there is only 1 non-repeated digit '9' in this number

If the given number is 1015, the program should return 2 because there are 2 non-repeated digits in this number, '0', and '5'.

If the given number is 108, the program should return 3 because there are 3 non-repeated digits in this number, '1', '0', and '8'.

If the given number is 22, the function should return 0 because there are NO non-repeated digits in this number.

```
from collections import Counter as ct
```

```
n=input()
```

```
con=ct(n)
```

```
l=[i for i in con if i==1]
```

```
print(len(l))
```



Example1: if the given number N is 7, the method must return 2

Example2: if the given number N is 10, the method must return 1

For example:

Input	Result
7	2
10	1



Ex. No. : 4.3

Date:02/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Prime Checking

Write a program that finds whether the given number N is Prime or not. If the number is prime, the program should return 2 else it must return 1.

Assumption: $2 \leq N \leq 5000$, where N is the given number.

```
n=int(input())
for i in range(n):
    if n%i==0:
        print(1)
        break
else:
    print(2)
```



Input Format:

Integer input from stdin.

Output Format:

Perfect square greater than N.

Example Input:

10

Output:

16



Ex. No. : 4.4

Date:02/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Next Perfect Square

Given a number N, find the next perfect square greater than N.

```
n=int(input())
m=round(n**0.5)
print((m+1)**2)
```



NOTE: Fibonacci series looks like –

0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, . . . and so on.

i.e. Fibonacci series starts with 0 and 1, and continues generating the next number as the sum of the previous two numbers.

- first Fibonacci number is 0,
- second Fibonacci number is 1,
- third Fibonacci number is 1,
- fourth Fibonacci number is 2,
- fifth Fibonacci number is 3,
- sixth Fibonacci number is 5,
- seventh Fibonacci number is 8, and so on.

For example:

Input:

7

Output

8



Ex. No. : 4.5

Date:02/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Nth Fibonacci

Write a program to return the nth number in the fibonacci series. The value of N will be passed to the program as input.

```
n=int(input())
a,b,c=0,1,0
for i in range(n-2):
    c=a+b
    a,b=b,c
print(c if n!=2 else 1)
```



Input Format:

Single Integer Input from stdin.

Output Format:

Yes or No.

Example Input:

175

Output:

Yes

Explanation

$$1^1 + 7^2 + 5^3 = 175$$

Example Input:

123

Output:

No

For example:

Input Result

175 Yes

123 No



Ex. No. : 4.6

Date:02/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Disarium Number

A Number is said to be Disarium number when the sum of its digit raised to the power of their respective positions becomes equal to the number itself. Write a program to print number is Disarium or not.

```
n=intput()
p,n1=0,0
for i in n:
    p+=1
    n1+=(int(i)**p)
if int(n)==n1:
    print('Yes')
else:
    print('No')
```



Sample Test Cases

Test Case 1

Input

4

Output

1234

Explanation:

as input is 4, have to take 4 terms.

$1 + 11 + 111 + 1111$

Test Case 2

Input

6

Output

123456

For example:

Input	Result
3	123



Ex. No. : 4.7

Date:02/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Sum of Series

Write a program to find the sum of the series $1 + 11 + 111 + 1111 + \dots + n$ terms (n will be given as input from the user and sum will be the output)

```
n=int(input())
c,tot=0,0
for i in range(n):
    c=c*10+1
    tot+=c
print(tot)
```



For example:

Input	Result
292	2
1015	3



Ex. No. : 4.8

Date:02/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Unique Digit Count

Write a program to find the count of unique digits in a given number N. The number will be passed to the program as an input of type int.

Assumption: The input number will be a positive integer number ≥ 1 and ≤ 25000 .

For e.g.

If the given number is 292, the program should return 2 because there are only 2 unique digits '2' and '9' in this number

If the given number is 1015, the program should return 3 because there are 3 unique digits in this number, '1', '0', and '5'.

```
n=set(intput())
```

```
print(len(n))
```



Input Format:

Single Integer input.

Output Format:

Output displays Yes if condition satisfies else prints No.

Example Input:

14

Output:

Yes

Example Input:

13

Output:

No



Ex. No. : 4.9

Date:02/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Product of single digit

Given a positive integer N, check whether it can be represented as a product of single digit numbers.

```
n=int(input())
f=0
l=[i for i in range(1,10) if n%i==0]
for i in l:
    for j in l:
        if i*j==n:
            print('Yes')
            f=1
            break
    if f:
        break
else:
    print('No')
```



Input Format:

Single integer input.

Output Format:

Yes or No.

Example Input:

24

Output:

Yes

Example Input:

26

Output:

No

For example:

Input	Result
24	Yes



Ex. No. : 4.10

Date:02/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Perfect Square After adding One

Given an integer N, check whether N the given number can be made a perfect square after adding 1 to it.

```
n=int(input())
if '.0000' in "%.4f"%((n+1)**0.5):
    print('Yes')
else:
    print('No')
```





05 - List in Python



Sample Case 0

Sample Input 0

4

1

2

3

3

Sample Output 0

2

Explanation 0

- The sum of the first two elements, $1+2=3$. The value of the last element is 3.
- Using zero based indexing, $\text{arr}[2]=3$ is the pivot between the two subarrays.
- The index of the pivot is 2.

Sample Case 1

Sample Input 1

3

1

2

1

Sample Output 1

1

Explanation 1

- The first and last elements are equal to 1.
- Using zero based indexing, $\text{arr}[1]=2$ is the pivot between the two subarrays.
- The index of the pivot is 1.

For example:

Input	Result
4 1 2 3 3	2
3 1 2 1	1

Ex. No. : 5.1

Date:16/04/2024

Register No.: 230701034

Name: ARUL JOTHI P



Balanced Array

Given an array of numbers, find the index of the smallest array element (the pivot), for which the sums of all elements to the left and to the right are equal. The array may not be reordered.

Example

arr=[1,2,3,4,6]

- the sum of the first three elements, $1+2+3=6$. The value of the last element is 6.
- Using zero based indexing, arr[3]=4 is the pivot between the two subarrays.
- The index of the pivot is 3.

Constraints

- $3 \leq n \leq 10^5$
- $1 \leq arr[i] \leq 2 \times 10^4$, where $0 \leq i < n$
- It is guaranteed that a solution always exists.

The first line contains an integer n, the size of the array arr.

Each of the next n lines contains an integer, arr[i], where $0 \leq i < n$.

#this is about sums of left and right

n=int(input())

a=[int(input()) for i in range(n)]

left=0

right=sum(a)-a[0]

for i in range(1,len(a)-1): #if not from 1 then it goes out of index

 left+=a[i-1]

 right-=a[i]

 if(left==right):



print(i)

break

—

—



Input

1
3
1
3
5
4

Output:

1

Input

1
3
1
3
5
99

Output

0

For example:

Input	Result
1 3 1 3 5 4	1
1 3 1 3 5 99	0



Check pair with difference k

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that $A[i] - A[j] = k$, $i \neq j$.

Input Format

1. First line is number of test cases T. Following T lines contain:
2. N, followed by N integers of the array
3. The non-negative integer k

Output format

Print 1 if such a pair exists and 0 if it doesn't.

```
a=[]
flag=1
b=int(input())
for i in range(b):
    c=int(input())
    for j in range(c):
        a.append(int(input()))
    d=int(input())
    for k in range(c):
        for l in range(k,c):
            if a[k]-a[l]==d or abs(a[k]-a[l])==d:
                flag=0
                print(1)
                break
a=[]
if(flag):
    print(0)
flag=1
```



Sample Test Cases

Test Case 1

Input

7

23

45

23

56

45

23

40

Output

23 occurs 3 times

45 occurs 2 times

56 occurs 1 times

40 occurs 1 times



Ex. No. : 5.3

Date:16/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Count Elements

Complete the program to count frequency of each element of an array. Frequency of a particular element will be printed once.

```
n=int(input())
l=[]
for i in range(n):
    l.append(int(input()))
a=" ".join(l)
for i in set(l):
    print("%d occurs %d times"%(i,a.count(str(i))))
```



Example Input:

```
5  
1  
2  
2  
3  
4
```

Output:

```
1 2 3 4
```

Example Input:

```
6  
1  
1  
2  
2  
3  
3
```

Output:

```
1 2 3
```

For example:

Input	Result
-------	--------

5	
1	
2	
2	
3	
4	

```
1 2 3 4
```

6	
1	
1	
2	
2	
3	
3	

```
1 2 3
```



Ex. No. : 5.4

Date:16/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Distinct Elements in an Array

Program to print all the distinct elements in an array. Distinct elements are nothing but the unique (non-duplicate) elements present in the given array.

Input Format:

First line take an Integer input from stdin which is array length n.

Second line take n Integers which is inputs of array.

Output Format:

Print the Distinct Elements in Array in single line which is space Separated

```
n=int(input())
```

```
a=[]
```

```
for i in range(n):
```

```
    a.append(int(input()))
```

```
a=set(a)
```

```
a=list(a)
```

```
a.sort()
```

```
for i in a:
```

```
    print(i,end=' ')
```



Sample Test Cases

Test Case 1

Input

1
3
4
5
6
7
8
9
10
11
2

Output

ITEM to be inserted:2
After insertion array is:

1
2
3
4
5
6
7
8
9
10
11

Test Case 2

Input

11
22
33
55
66
77
88
99
110
120
44

Output

ITEM to be inserted:44
After insertion array is:

11
22
33
44
55
66
77
88
99
110
120



Ex. No. : 5.5

Date:16/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Element Insertion

Consider a program to insert an element / item in the sorted array. Complete the logic by filling up required code in editable section. Consider an array of size 10. The eleventh item is the data is to be inserted.

```
n=10
a=[int(input()) for i in range(n)]
b=int(input())
c=[]
k=0
print(f"ITEM to be inserted:{b}")
for i in range(len(a)):
    if(a[i]<b<a[i+1]):
        c.append(a[i])
        k+=1
        c.append(b)
        k+=1
    else:
        c.append(a[i])
        k+=1

print("After insertion array is:")
for i in c:
    print(i)
```



Sample Case 0**Sample Input 0**

10

3

Sample Output 0

5

Explanation 0

Factoring n = 10 results in {1, 2, 5, 10}. Return the p = 3rd factor, 5, as the answer.

Sample Case 1**Sample Input 1**

10

5

Sample Output 1

0

Explanation 1

Factoring n = 10 results in {1, 2, 5, 10}. There are only 4 factors and p = 5, therefore 0 is returned as the answer.

Sample Case 2**Sample Input 2**

1

1

Sample Output 2

1

Explanation 2

Factoring n = 1 results in {1}. The p = 1st factor of 1 is returned as the answer.

For example:

Input	Result
10	5
3	
10	0
5	
1	1
1	



Ex. No. : 5.6

Date:16/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Find the Factor

Determine the factors of a number (i.e., all positive integer values that evenly divide into a number) and then return the p^{th} element of the [list](#), sorted ascending. If there is no p^{th} element, return 0.

Constraints

$$1 \leq n \leq 10^{15}$$

$$1 \leq p \leq 10^9$$

The first line contains an integer n , the number to factor.

The second line contains an integer p , the 1-based index of the factor to return.

```
n=int(input())
```

```
p=int(input())
```

```
i=1
```

```
a=[]
```

```
while i<=n:
```

```
    if n%i==0:
```

```
        a.append(i)
```

```
    i+=1
```

```
i=1
```

```
flag=1
```

```
while i<=len(a):
```

```
    if i==p:
```

```
        print(a[i-1])
```

```
    flag=0
```



```
break
```

```
i+=1
```

```
if (flag):
```

```
    print(0)
```



Sample test case

Sample input

2
2
1
3
5
7
2
4
6
8

Sample Output

`[[1, 3, 2, 4], [5, 7, 6, 8]]`



Ex. No. : 5.7

Date:16/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Merge List

Write a Python program to Zip two given lists of lists.

Input:

m : row size

n: column size

list1 and list 2 : Two lists

Output

Zipped List : List which combined both list1 and list2

```
n=int(input())
```

```
m=int(input())
```

```
a = [[int(input()) for j in range(n)] for i in range(m)] #input as 2  
D...outer i loop for row inside j loop for column
```

```
b = [[int(input()) for j in range(n)] for i in range(m)]
```

```
d=zip(a,b) #once itreated becomes empty.. concatenation of  
each elemnts in only 1 dimension in tuple form [before 2D so  
now 1D in each index tuple]
```

```
c=[]
```

```
for i,j in d: #both i and j have same index but i from a and j from  
b
```



```
c.append(i+ j) #concatenating that 2 subarrays into another to  
make it 2D
```

```
print(c)
```



Sample Input 1

```
5  
1  
2  
3  
6  
9  
4  
2  
4  
5  
10
```

Sample Output 1

```
1 2 3 4 5 6 9 10
```



Ex. No. : 5.8

Date:16/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Merge Two Sorted Arrays Without Duplication

Output is a merged array without duplicates.

Input Format

N1 - no of elements in array 1

Array elements for array 1

N2 - no of elements in array 2

Array elements for array2

Output Format

Display the merged array

```
n=int(input())
a=[]
for i in range(n):
    a.append(int(input()))
m=int(input())
b=[]
for j in range(m):
    b.append(int(input()))

c=a+b
c.sort() #c=sorted(c)
c={i:i for i in c} #dict to avoid repetition/union in set

for i in c:
    print(i,end=' ')
```



For example, if there are 4 elements in the array:

5
6
5
7

If the element to search is 5 then the output will be:

5 is present at location 1
5 is present at location 3
5 is present 2 times in the array.

Sample Test Cases

Test Case 1

Input

4
5
6
5
7
5

Output

5 is present at location 1.
5 is present at location 3.
5 is present 2 times in the array.

Test Case 2

Input

5
67
80
45
97
100
50

Output

50 is not present in the array.



Ex. No. : 5.9

Date:16/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Print Element Location

Write a program to print all the locations at which a particular element (taken as input) is found in a list and also print the total number of times it occurs in the list. The location starts from 1.

```
n=int(input())
a=[]
for i in range(n):
    a.append(int(input()))
s=int(input())

cnt=0
for i in range(len(a)):
    if(a[i]==s):
        print(s,"is present at location %d."%(i+1))
        cnt+=1

if cnt!=0:
    print(s,"is present %d times in the array."%cnt)
else:
    print(s,"is not present in the array.")
```



Sample Test Case

Input

7

1

2

3

0

4

5

6

Output

True



Ex. No. : 5.10

Date:16/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Strictly increasing

Write a Python program to check if a given list is strictly increasing or not. Moreover, If removing only one element from the list results in a strictly increasing list, we still consider the list true

Input:

n : Number of elements

List1: List of values

Output

Print "True" if list is strictly increasing or decreasing else print "False"

```
n1 = int(input())
```

```
a1 = []
```

```
for i in range(n1):
```

```
    a1.append(int(input()))
```

```
n2 = int(input())
```

```
a2 = []
```

```
for i in range(n2):
```

```
    a2.append(int(input()))
```

```
m = []
```

```
for num in a1:
```

```
    if num not in m:
```

```
        m.append(num)
```

```
for num in a2:
```

```
    if num not in m:
```

```
        m.append(num)
```

```
m.sort()
```

```
for num in m:
```




```
print(num, end=" ")
```





06 - Strings in Python



For example:

Input	Result
rec@123	
3	
3	
1	



Ex. No. : 6.1

Date:30/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Count Chars

Write a python program to count all letters, digits, and special symbols respectively from a given string

```
a=input()  
cnt1=cnt2=cnt3=0  
  
for i in a:  
    if i.isalpha():  
        cnt1+=1  
    elif i.isdigit():  
        cnt2+=1  
    else:  
        cnt3+=1  
print(cnt1,cnt2,cnt3,sep='\n')
```



Sample Input 1
a2b4c6

Sample Output 1
aabbbbcccccc



Ex. No. : 6.2

Date:30/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Decompress the String

Assume that the given string has enough memory. Don't use any extra space(IN-PLACE)

```
a=input()
operands=[]
counts=[]
counts2=[]
var=0

for i in range(len(a)):
    if ord(a[i])-48 in range(0,10):
        counts.append(a[i])
    else:
        if(len(counts)!=0):
            counts.append(100)
            operands.append(a[i])

for i in range(len(counts)):
    if counts[i]!=100:
        var=var*10+int(counts[i])
    else:
        counts2.append(var)
        var=0
    if (i==len(counts)-1):
```



```
counts2.append(var)
var=0

for i in range(len(counts2)):
    print(operands[i]*counts2[i],end="")
```



Input Format:

The first line contains S1.
The second line contains S2.
The third line contains N.

Output Format:

The first line contains the N characters present in S1 which are also present in S2.

Boundary Conditions:

$2 \leq N \leq 10$
 $2 \leq \text{Length of } S1, S2 \leq 1000$

Example Input/Output 1:

Input:

abcbde
cdefghbb
3

Output:

bcd

Note:

b occurs twice in common but must be printed only once.



Ex. No. : 6.3

Date:30/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

First N Common Chars

Two string values S1, S2 are passed as the input. The program must print first N characters present in S1 which are also present in S2.

```
a=input()
b=input()
n=int(input())
c=0

d={i:i for i in a}
e={j:j for j in b}

for i in d:
    for j in e:
        if i==j:
            print(i,end="")
            c+=1
            break
    if(c==n):
        break
```



Sample Input 1
experience
enc

Sample Output 1
xpri



Ex. No. : 6.4

Date:30/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Remove Characters

Given two Strings s1 and s2, remove all the characters from s1 which is present in s2.

Constraints

1<= string length <= 200

```
s1 = input().strip()
```

```
s2 = input().strip()
```

```
result = ""
```

```
for char in s1:
```

```
    if char not in s2:
```

```
        result += char
```

```
print(result)
```



Sample Input 1

Malayalam is my mother tongue

Sample Output 1

is my mother tongue

For example:

Input	Expected
Malayalam is my mother tongue	is my mother tongue
He did a good deed	he good



Ex. No. : 6.5

Date: 30/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Remove Palindrome Words

String should contain only the words are not palindrome.

```
s=input().lower().split()  
for i in s:  
    if i!=i[::-1]:  
        print(i,end=" ")
```



For example:

Input	Result
Wipro Technologies Bangalore	
TECHNOLOGIES	
Hello World	
WORLD	
Hello	
LESS	



Ex. No. : 6.6

Date: 30/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Return Second Word in Uppercase

Write a program that takes as input a string (sentence), and returns its second word in uppercase.

For example:

If input is "Wipro Technologies Bangalore" the function should return "TECHNOLOGIES"

If input is "Hello World" the function should return "WORLD"

If input is "Hello" the program should return "LESS"

NOTE 1: If input is a sentence with less than 2 words, the program should return the word "LESS".

NOTE 2: The result should have no leading or trailing spaces.

```
a=input()  
cnt=0  
  
for i in range(len(a)):  
    if a[i]==" ":  
        cnt+=1  
        continue  
    if(cnt==1):  
        print(a[i].upper(),end="")  
  
if(cnt==0):  
    print("LESS")
```



Input:

A&B

Output:

B&A

Explanation: As we ignore '&' and

As we ignore '&' and then reverse, so answer is "B&A".

For example:

Input Result

A&x#

x&A#



Ex. No. : 6.7

Date:30/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Revers String

Reverse a string without affecting special characters. Given a string S, containing special characters and all the alphabets, reverse the string without affecting the positions of the special characters.

```
a=input()
a=list(a)
j=-1
for i in range(len(a)):
    for j in range(len(a)-1,-1,-1):
        if 65<=ord(a[i])<=90 or 97<=ord(a[i])<=122:
            if 65<=ord(a[j])<=90 or 97<=ord(a[j])<=122:
                t=a[i]
                a[i]=a[j]
                a[j]=t
                break
a=".join(a)
print(a)
```



For example:

Input	Result
Yn	
PYnative	
True	



Ex. No. : 6.8

Date:30/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

String characters balance Test

Write a program to check if two strings are balanced. For example, strings s1 and s2 are balanced if all the characters in the s1 are present in s2. The character's position doesn't matter. If balanced display as "true" ,otherwise "false".

```
a=input()  
b=input()  
  
if a in b:  
    print("True")  
else:  
    print("False")
```



Input:

first
second
first
third
second

then your program should display:

Output:

first
second
third



Ex. No. : 6.9

Date:30/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Unique Names

In this exercise, you will create a program that reads words from the user until the user enters a blank line. After the user enters a blank line your program should display each word entered by the user exactly once. The words should be displayed in the same order that they were first entered. For example, if the user enters:

```
a=[]
```

```
b=input()
```

```
while b!="":
```

```
    a.append(b)
```

```
    b=input()
```

```
c={i:i for i in a}
```

```
for i in c:
```

```
    print(i)
```



Example Input/Output 1:

Input:

vijayakumar.r@rajalakshmi.edu.in

Output:

edu.in
rajalakshmi
vijayakumar.r



Ex. No. : 6.10

Date: 30/04/2024

Register No.: 230701034

Name: ARUL JOTHI P

Username Domain Extension

Given a string S which is of the format USERNAME@DOMAIN.EXTENSION, the program must print the EXTENSION, DOMAIN, USERNAME in the reverse order.

Input Format:

The first line contains S.

Output Format:

The first line contains EXTENSION.

The second line contains DOMAIN.

The third line contains USERNAME.

Boundary Condition:

1 <= Length of S <= 100

```
a=input()
```

```
cnt1=0
```

```
cnt2=0
```

```
for i in a:
```

```
    if(i=='.'): 
```

```
        cnt1+=1
```

```
        if(cnt1==1):
```

```
            continue
```

```
        if(cnt1>=1):
```

```
            print(i,end="")
```



```
print()
```

```
for i in a:
```

```
    if(i=='@'):
```

```
        cnt2+=1
```

```
        continue
```

```
    if(i=='.'):
```

```
        break
```

```
    if(cnt2==1):
```

```
        print(i,end="")
```

```
print()
```

```
for i in a:
```

```
    if(i!='@'):
```

```
        print(i,end="")
```

```
    else:
```

```
        break
```





07 - Functions



Example input:

12

Output:

Yes

Explanation

The proper divisors of 12 are: 1, 2, 3, 4, 6, whose sum is $1 + 2 + 3 + 4 + 6 = 16$. Since sum of proper divisors is greater than the given number, 12 is an abundant number.

Example input:

13

Output:

No

Explanation

The proper divisors of 13 is: 1, whose sum is 1. Since sum of proper divisors is not greater than the given number, 13 is not an abundant number.

For example:

Test	Result
print(abundant(12))	Yes
print(abundant(13))	No



Ex. No. : 7.1

Date:07/05/2024

Register No.: 230701034

Name: ARUL JOTHI P

Abundant Number

An abundant number is a number for which the sum of its proper divisors is greater than the number itself. Proper divisors of the number are those that are strictly lesser than the number.

Input Format:

Take input an integer from stdin

Output Format:

Return Yes if given number is Abundant. Otherwise, print No

```
def abundant(n):
    m=n
    j=2
    s=0
    while(j<=m):
        if m%j==0:
            s+=j
        j+=1
    if s>m:
        return 'Yes'
    else:
        return 'No'
```



Input Format:

Take a Integer from Stdin

Output Format:

Print Automorphic if given number is Automorphic number, otherwise Not Automorphic

Example input: 5 Output: Automorphic Example input: 25 Output: Automorphic Example

input: 7 Output: Not Automorphic

For example:

Test	Result
print(automorphic(5))	Automorphic



Ex. No. : 7.2

Date:07/05/2024

Register No.: 230701034

Name: ARUL JOTHI P

Automorphic number or not

An automorphic number is a number whose square ends with the number itself. For example, 5 is an automorphic number because $5*5 = 25$. The last digit is 5 which same as the given number.

If the number is not valid, it should display "Invalid input".

If it is an automorphic number display "Automorphic" else display "Not Automorphic".

```
def automorphic(n):
```

```
    a=n*n
```

```
    if n==(a%10):
```

```
        return 'Automorphic'
```

```
    else:
```

```
        return 'Not Automorphic'
```



Input Format:

Take an input integer from stdin.

Output Format:

Print TRUE or FALSE.

Example Input:

1256

Output:

TRUE

Example Input:

1595

Output:

FALSE

For example:

Test	Result
print(productDigits(1256))	True
print(productDigits(1595))	False



Ex. No. : 7.3

Date:07/05/2024

Register No.: 230701034

Name: ARUL JOTHI P

Check Product of Digits

Write a code to check whether product of digits at even places is divisible by sum of digits at odd place of a positive integer.

```
def productDigits(n):
```

```
    i=0
```

```
    s1=1
```

```
    s2=0
```

```
    while(n>0):
```

```
        m=n%10
```

```
        if i%2==0:
```

```
            s1*=m
```

```
        else:
```

```
            s2+=m
```

```
        i+=1
```

```
        n=n//10
```

```
    if s1%s2==0:
```

```
        return 'True'
```



```
else:  
    return 'False'
```



Input

The input consists of an integer orderValue, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

Test	Result
print(christmasDiscount(578))	12



Ex. No. : 7.4

Date:07.05.2024

Register No.: 230701034

Name: ARUL JOTHI P

Christmas Discount

An e-commerce company plans to give their customers a special discount for Christmas. They are planning to offer a flat discount. The discount value is calculated as the sum of all the prime digits in the total bill amount.

Write an python code to find the discount value for the given total bill amount.

Constraints

$1 \leq \text{orderValue} < 10^{100000}$

```
def christmasDiscount(n):
```

```
    j=2
```

```
    flag=1
```

```
    s1=0
```

```
    while(n>0):
```

```
        m=n%10
```

```
        while(j<=m//2):
```

```
            if(m%j==0):
```

```
                flag=0
```

```
                break
```

```
        j+=1
```

```
    if flag:
```

```
        s1+=m
```



n=n/10

j=2

flag=1

return s1



Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value



Ex. No. : 7.5

Date:07.05.2024

Register No.: 230701034

Name: ARUL JOTHI P

Coin Change

complete function to implement coin change making problem i.e. finding the minimum number of coins of certain denominations that add up to given amount of money.
The only available coins are of values 1, 2, 3, 4

```
def coinChange(n):
```

```
    l=4
```

```
    m=0
```

```
    cnt=0
```

```
    while (1):
```

```
        if m<n:
```

```
            cnt+=1
```

```
            m+=l
```

```
        elif m==n:
```

```
            return cnt
```

```
        else:
```

```
            l-=1
```

```
        if m+l==n:
```

```
            return cnt
```



```
|=1  
if m+l==n:  
    return cnt  
|=1  
if m+l==n:  
    return cnt
```

Input Format:

Take a number in the form of String from stdin.

Output Format:

Print the difference between sum of even and odd digits

Example input:

1453

Output:

1

Explanation:

Here, sum of even digits is $4 + 3 = 7$

sum of odd digits is $1 + 5 = 6$.

Difference is 1.

Note that we are always taking absolute difference



Ex. No. : 7.6

Date:07.05.2024

Register No.: 230701034

Name: ARUL JOTHI P

Difference Sum

Given a number with maximum of 100 digits as input, find the difference between the sum of odd and even position digits.

```
def differenceSum(n):
```

```
    i=0
```

```
    s1=s2=0
```

```
    n=int(n)
```

```
    while(n>0):
```

```
        m=n%10
```

```
        if i%2==0:
```

```
            s1+=m
```

```
        else:
```


```
            s2+=m
```

```
        i+=1
```

```
        n=n//10
```



```
return abs(s1-s2)
```



For example:

Test	Result
print(checkUgly(6))	ugly
print(checkUgly(21))	not ugly



Ex. No. : 7.7

Date:07.05.2024

Register No.: 230701034

Name: ARUL JOTHI P

Ugly number

A number is considered to be ugly if its only prime factors are 2, 3 or 5.
[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.
return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as: $U = 2^a * 3^b * 5^c$, where a, b and c are nonnegative integers.

```
def checkUgly(n):
    if n <= 0:
        return 'not ugly'

    cnt = 0
    j = 2
    while j <= n:
        if n % j == 0:
            if j in [2, 3, 5]:
                while n % j == 0:
                    n /= j
            else:
                cnt += 1
        break # No need to check further if a non-ugly factor is found
    j += 1
```



```
if cnt >= 1:  
    return 'not ugly'  
else:  
    return 'ugly'
```





08 – Tuple/Set



Examples:

Input: str = "01010101010"

Output: Yes

Input: str = "REC101"

Output: No

For example:

Input	Result
01010101010	Yes
010101 10101	No



Ex. No. : 8.1

Date: 14.05.2024

Register No.: 230701034

Name: ARUL JOTHI P

Binary String

Coders here is a simple task for you, Given string str. Your task is to check whether it is a binary string or not by using python set.

a=input()

b={i for i in a}

flag=1

for i in b:

 if i!='0' and i!='1':

 flag=0

 break

if flag:

 print("Yes")

else:

 print('No')



Examples:

Input: $t = (5, 6, 5, 7, 7, 8)$, $K = 13$

Output: 2

Explanation:

Pairs with sum $K(= 13)$ are $\{(5, 8), (6, 7), (6, 7)\}$.

Therefore, distinct pairs with sum $K(= 13)$ are $\{ (5, 8), (6, 7) \}$.

Therefore, the required output is 2.

For example:

Input	Result
1,2,1,2,5	1
3	
1,2	0
0	



Ex. No. : 8.2

Date:14.05.2024

Register No.: 230701034

Name: ARUL JOTHI P

Check Pair

Given a tuple and a positive integer k, the task is to find the count of distinct pairs in the tuple whose sum is equal to K.

```
a = input().split(',')  
d = int(input())  
b = []  
c = []
```

```
for i in range(len(a)):  
    b.append(0)
```

```
a = tuple(a)  
cnt = 0
```

```
for i in range(len(a)-1):  
    for j in range(i+1, len(a)):  
        if a[i] == a[j]:  
            b[j] = 1
```

```
for i in range(len(b)):  
    if b[i] == 0:  
        c.append(a[i])
```



```
for i in range(len(c)-1):  
    for j in range(i+1, len(c)):  
        if int(c[i]) + int(c[j]) == d:  
            cnt += 1  
  
print(cnt)
```



Example 1:

Input: s = "AAAAACCCCCAAAAACCCCAAAAGGGTTT"

Output: ["AAAAACCCCC", "CCCCCAAAAA"]

Example 2:

Input: s = "AAAAAAAAAAAAAA"

Output: ["AAAAAAAAAA"]

For example:

Input	Result
AAAAACCCCCAAAAACCCCAAAAGGGTTT	AAAAACCCCC CCCCCAAAAA



Ex. No. : 8.3

Date: 14.05.2024

Register No.: 230701034

Name: ARUL JOTHI P

DNA Sequence

The DNA sequence is composed of a series of nucleotides abbreviated as 'A', 'C', 'G', and 'T'.

For example, "ACGAATTCCG" is a DNA sequence.

When studying DNA, it is useful to identify repeated sequences within the DNA.

Given a string `s` that represents a DNA sequence, return all the 10-letter-long sequences (substrings) that occur more than once in a DNA molecule. You may return the answer in any order.

```
s=input()  
d=len(s)  
l=m=10  
count=0  
b=[]  
for i in range(d):  
    for j in range(d):  
        if s[i:l]==s[j:i:m]:  
            count+=1  
        m+=1  
    if(count>1):  
        b.append(s[i:l])  
    count=0  
    l+=1  
m=l
```



```
c=set(b) #since it is a set the index always changes #so beware of input  
for i in c:  
    print(i)
```



Example 1:

Input: nums = [1,3,4,2,2]
Output: 2

Example 2:

Input: nums = [3,1,3,4,2]
Output: 3

For example:

Input	Result
1 3 4 4 2	4



Ex. No. : 8.4

Date: 14.05.2024

Register No.: 230701034

Name: ARUL JOTHI P

Print repeated no

Given an array of integers `nums` containing $n + 1$ integers where each integer is in the range $[1, n]$ inclusive. There is only one repeated number in `nums`, return *this repeated number*. Solve the problem using [set](#).

a=input()

b={i for i in a if i!=' '} #we dint convert string into int..we dint use
int(i)

count=0

for i in b:

 for j in a:

 if i==j:

 count+=1

if count>1:

 print(i)

 break

count=0



Sample Input:

5 4
1 2 8 6 5
2 6 8 10

Sample Output:

1 5 10
3

Sample Input:

5 5
1 2 3 4 5
1 2 3 4 5

Sample Output:

NO SUCH ELEMENTS

For example:

Input	Result
5 4 1 2 8 6 5 2 6 8 10	1 5 10 3



Ex. No. : 8.5

Date: 14.05.2024

Register No.: 230701034

Name: ARUL JOTHI P

Remove repeated

Write a program to eliminate the common elements in the given 2 arrays and print only the non-repeating elements and the total number of such non-repeating elements.

Input Format:

The first line contains space-separated values, denoting the size of the two arrays in integer format respectively.

The next two lines contain the space-separated integer arrays to be compared.

```
a=input()
a=tuple(int(i) for i in a.split(' '))
#a=tuple(int(i) for i in a if i!=' ')
b=tuple(int(i) for i in input().split(' ') ) #not int input becoz it is a string ..we r converting a str into a tuple
c=tuple(int(i) for i in input().split(' ') )
d=b+c
count=0
cnt=0
for i in d:
    for j in d:
        if i==j:
            count+=1
    if(count==1):
        print(i,end=' ')
        cnt+=1
    count=0
print()
```



```
print(cnt)
```



Example 1:

Input: text = "hello world", brokenLetters = "ad"

Output:

1

Explanation: We cannot type "world" because the 'd' key is broken.

For example:

Input	Result
hello world ad	1



Ex. No. : 8.6

Date: 14.05.2024

Register No.: 230701034

Name: ARUL JOTHI P

Malfunctioning Keyboard

There is a malfunctioning keyboard where some letter keys do not work. All other keys on the keyboard work properly.

Given a string text of words separated by a single space (no leading or trailing spaces) and a string brokenLetters of all distinct letter keys that are broken, return the number of words in text you can fully type using this keyboard.

```
x = input()
```

```
y = input()
```

```
c = 0
```


```
for i in range(len(y)):
```

```
    if y[i] in x:
```

```
        c += 1
```

```
print(c)
```





Example 1:

Input: words = ["Hello", "Alaska", "Dad", "Peace"]

Output: ["Alaska", "Dad"]

Example 2:

Input: words = ["omk"]

Output: []

Example 3:

Input: words = ["adsdf", "sfd"]

Output: ["adsdf", "sfd"]

For example:

Input	Result
4 Hello Alaska Dad Peace	Alaska Dad



Ex. No. : 8.7

Date:14.05.2024

Register No.: 230701034

Name: ARUL JOTHI P

American keyboard

Given an array of strings words, return *the words that can be typed using letters of the alphabet on only one row of American keyboard like the image below.*

In the American keyboard:

- the first row consists of the characters "qwertyuiop",
- the second row consists of the characters "asdfghjkl", and
- the third row consists of the characters "zxcvbnm".

```
n=int(input())
```

```
m=tuple(input() for i in range(n))
```

```
a="qwertyuiop"
```

```
b="asdfghjkl"
```

```
c="zxcvbnm"
```

```
flag =0
```

```
for i in m:
```

```
    j=set(i.lower()) #lower is for string
```

```
    if len(j)==len(set(i)&set(a)): #checking the common letters btwn i and a,b,c if the len of them  
and i are equal then they are present in same row
```

```
        print(i)          #means intersection
```

```
    elif len(j)==len(set(i)&set(b)):
```

```
        print(i)
```

```
    elif len(j)==len(set(i)&set(c)):
```

```
        print(i)
```



```
else:  
    flag+=1  
  
if flag==len(m):  
    print("No words")
```





09 – Dictionary



Example 1:

Input: s1 = "this apple is sweet", s2 = "this apple is sour"

Output: ["sweet", "sour"]

Example 2:

Input: s1 = "apple apple", s2 = "banana"

Output: ["banana"]

Constraints:

$1 \leq s1.length, s2.length \leq 200$

s1 and s2 consist of lowercase English letters and spaces.

s1 and s2 do not have leading or trailing spaces.

All the words in s1 and s2 are separated by a single space.

Note:

Use dictionary to solve the problem

For example:

Input	Result
this apple is sweet this apple is sour	sweet sour



Ex. No. : 9.1

Date:21.5.2024

Register No.: 230701034

Name: ARUL JOTHI P

Uncommon words

A sentence is a string of single-space separated words where each word consists only of lowercase letters. A word is uncommon if it appears exactly once in one of the sentences, and does not appear in the other sentence.

Given two sentences s1 and s2, return a list of all the uncommon words. You may return the answer in any order.

```
a=input().split()
```

```
b=input().split()
```

```
c=[i for i in a]
```

```
d=[i for i in b]
```

```
e=c+d
```

```
#print(e)
```

```
f={i for i in e if e.count(i)>1}
```

```
#print(f)
```

```
c={i:i for i in c}
```

```
c.update({i:i for i in d})
```

```
#print(c)
```



```
for i in c:  
if i not in f:  
    print(i,end=' ')
```



Input : test_dict = {'Gfg' : [6, 7, 4], 'best' : [7, 6, 5]}

Output : {'Gfg': 17, 'best': 18}

Explanation : Sorted by sum, and replaced.

Input : test_dict = {'Gfg' : [8,8], 'best' : [5,5]}

Output : {'best': 10, 'Gfg': 16}

Explanation : Sorted by sum, and replaced.

Sample Input:

2

Gfg 6 7 4

Best 7 6 5

Sample Output

Gfg 17

Best 18

For example:

Input	Result
2 Gfg 6 7 4 Best 7 6 5	Gfg 17 Best 18



Ex. No. : 9.2

Date:21.5.2024

Register No.: 230701034

Name: ARUL JOTHI P

Sort Dictionary by Values Summation

Give a dictionary with value lists, sort the keys by summation of values in value list.

```
n=int(input())
c={}
for i in range(n):
    a=input().split()
    b=a[1:len(a)]
    c.setdefault(a[0],b)
    b=[]
#print(c)
f={}
e=0

for i,j in c.items():
    for k in range(len(j)):
        e+=int(j[k])
    f.setdefault(i,e)
    e=0
#print(f)
```



```
g=list(f.items())
g=[i[::-1] for i in g]
g.sort()
g=[i[::-1] for i in g]
g=dict(g)
```

```
for i,j in g.items():
    print(i,j,sep=' ')
```



Examples:

```
Input : votes[] = {"john", "johnny", "jackie",
                  "johnny", "john", "jackie",
                  "jamie", "jamie", "john",
                  "johnny", "jamie", "johnny",
                  "john"};
```

Output : John

We have four Candidates with name as 'John', 'Johnny', 'jamie', 'jackie'. The candidates John and Johnny get maximum votes. Since John is alphabetically smaller, we print it. Use dictionary to solve the above problem

Sample Input:

```
10
John
John
Johny
Jamie
Jamie
Johny
Jack
Johny
Johny
Jackie
```

Sample Output:

Johny

For example:

Input	Result
10 John John Johny Jamie Jamie Johny Jack Johny Johny Jackie	Johny



Ex. No. : 9.3

Date:21.5.2024

Register No.: 230701034

Name ARUL JOTHI P

Winner of Election

Given an array of names of candidates in an election. A candidate name in the array represents a vote cast to the candidate. Print the name of candidates received Max vote. If there is tie, print a lexicographically smaller name.

```
n=int(input())
```

```
a=[input() for i in range(n)]
```

```
b={i:i for i in a}
```

```
#print(a)
```

```
#print(b)
```

```
m=0
```

```
|="
```

```
for i in b:
```

```
    for j in a:
```

```
        e=a.count(i)
```

```
        if m<e:
```

```
            m=e
```

```
|=i
```

```
elif m==e:
```



```
if l>i:
```

```
    l=i
```

```
print(l)
```



Sample input:

4

James 67 89 56

Lalith 89 45 45

Ram 89 89 89

Sita 70 70 70

Sample Output:

Ram

James Ram

Lalith

Lalith



Ex. No. : 9.4

Date:21.5.2024

Register No.: 230701034

Name ARUL JOTHI P

Student Record

Create a student dictionary for n students with the student name as key and their test mark assignment mark and lab mark as values. Do the following computations and display the result.

- 1.Identify the student with the highest average score
- 2.Identify the student who has the highest Assignment marks
- 3.Identify the student with the Lowest lab marks
- 4.Identify the student with the lowest average score

Note:

If more than one student has the same score display all the student names

```
n=int(input())
d={}
for i in range(n):
    a=input().split()
    b=[a[1],a[2],a[3]]
    d.setdefault(a[0],b)
#print(d)
```

```
e=f=avg=0
t=100
lavg=500
m=s=""
for i,j in d.items():
    for l in range(len(j)):
        e+=int(j[l])
        if l==1:
            if int(j[l])>f:
```



```
f=int(j[l])
m=i
elif int(j[l])==f:
    m=m+' '+i
if l==2:
    if int(j[l])<t:
        t=int(j[l])
        s=i
    elif int(j[l])==t:
        s=i+' '+s
if e>avg:
    avg=e
    r=i
if e<avg:
    avg=e
    o=i
e=0

print(r)
print(m)
print(s)
print(o)
```



The points associated with each letter are shown below:

Points Letters

1 A, E, I, L, N, O, R, S, T and U

2 D and G

3 B, C, M and P

4 F, H, V, W and Y

5 K

8 J and X

10 Q and Z

Sample Input

REC

Sample Output

REC is worth 5 points.



Ex. No. : 9.5

Date:21.5.2024

Register No.: 230701034

Name: ARUL JOTHI P

Scramble Score

In the game of Scrabble™, each letter has points associated with it. The total score of a word is the sum of the scores of its letters. More common letters are worth fewer points while less common letters are worth more points.

Write a program that computes and displays the Scrabble™ score for a word. Create a dictionary that maps from letters to point values. Then use the dictionary to compute the score.

A Scrabble™ board includes some squares that multiply the value of a letter or the value of an entire word. We will ignore these squares in this exercise.

```
letters={'A':1, 'E':1, 'I':1, 'L':1, 'N':1, 'O':1, 'R':1, 'S':1, 'T':1, 'U':1,'D':2,'G':2,'B':3,'C':3, 'M':3, 'P':3,'F':4, 'H':4, 'V':4, 'W':4,'Y':4,'K':5,'J':6,'X':6,'Q':7,'Z':7}
```

```
a=input()
```

```
n=0
```

```
for i in a:
```

```
    n+=letters[i]
```

```
print(a,'is worth',n,'points.)
```





10 - Searching & Sorting



For example:

Input	Result
5 6 5 4 3 8	3 4 5 6 8



Ex. No. : 10.1

Date:28.5.2024

Register No.: 230701034

Name: ARUL JOTHI P

Merge Sort

Write a Python program to sort a list of elements using the merge sort algorithm.

```
n=int(input())
s=input()
arr=[int(i) for i in s.split()]

# Stack to simulate recursion
stack = [(0, len(arr))]

# List of sub-arrays
sub_arrays = []

while stack:
    start, end = stack.pop()
    if end - start > 1:
        mid = (start + end) // 2
        stack.append((mid, end))
        stack.append((start, mid))
    else:
```



```
sub_arrays.append((start, end))

while len(sub_arrays) > 1:

    new_sub_arrays = []

    for i in range(0, len(sub_arrays), 2):

        if i + 1 < len(sub_arrays):

            left = sub_arrays[i]

            right = sub_arrays[i + 1]

            left_arr = arr[left[0]:left[1]]

            right_arr = arr[right[0]:right[1]]


            merged_arr = []

            i = j = 0

            while i < len(left_arr) and j < len(right_arr):

                if left_arr[i] < right_arr[j]:

                    merged_arr.append(left_arr[i])

                    i += 1

                else:

                    merged_arr.append(right_arr[j])

                    j += 1

            while i < len(left_arr):
```

```
merged_arr.append(left_arr[i])

i += 1

while j < len(right_arr):

    merged_arr.append(right_arr[j])

    j += 1

arr[left[0]:right[1]] = merged_arr

new_sub_arrays.append((left[0], right[1]))

else:

    new_sub_arrays.append(sub_arrays[i])

sub_arrays = new_sub_arrays

for i in arr:

    print(i,end=' ')
```

Input Format

The first line contains an integer, n , the size of the [list](#) a .
The second line contains n , space-separated integers $a[i]$.

Constraints

- $2 \leq n \leq 600$
- $1 \leq a[i] \leq 2 \times 10^6$

Output Format

You must print the following three lines of output:

1. [List](#) is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement , the *first* element in the sorted [list](#).
3. Last Element: lastElement , the *last* element in the sorted [list](#).

Sample Input 0

3
1 2 3

Sample Output 0

[List](#) is sorted in 0 swaps.

First Element: 1

Last Element: 3

For example:

Input	Result
3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3
5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9



Ex. No. : 10.2

Date:28.5.2024

Register No.: 230701034

Name: ARUL JOTHI P

Bubble Sort

Given a list of integers, sort the array in ascending order using the *Bubble Sort* algorithm above. Once sorted, print the following three lines:

1. List is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted list.
3. Last Element: lastElement, the *last* element in the sorted list.

For example, given a worst-case but small array to sort: a=[6,4,1]. It took 3 swaps to sort the array. Output would be

Array is sorted in 3 swaps.

First Element: 1

Last Element: 6

```
n=int(input())
s=input()
cnt=0
a=[int(i) for i in s.split()]
for i in range(len(a)-1):
    for j in range(len(a)-1-i):
        if a[j]>a[j+1]:
            t=a[j]
            a[j]=a[j+1]
            a[j+1]=t
        cnt+=1
#print(a)
print("List is sorted in",cnt,"swaps.")
print("First Element:",a[0])
```



```
print("Last Element:",a[len(a)-1]) #we can use n where we use len(a)
```



Input Format

The first line contains a single integer n , the length of A .
The second line contains n space-separated integers,A[i].

Output Format

Print peak numbers separated by space.

Sample Input

5
8 9 10 2 6

Sample Output

10 6

For example:

Input	Result
4 12 3 6 8	12 8



Ex. No. : 10.3

Date:28.5.2024

Register No.: 230701034

Name: ARUL JOTHI P

Peak Element

Given a list, find peak element in it. A peak element is an element that is greater than its neighbors.

An element $a[i]$ is a peak element if

$A[i-1] \leq A[i] \geq A[i+1]$ for middle elements. $[0 < i < n-1]$

$A[i-1] \leq A[i]$ for last element $[i=n-1]$

$A[i] \geq A[i+1]$ for first element $[i=0]$

```
n=int(input())
s=input()
a=[int(i) for i in s.split()]

for i in range(len(a)):
    if i!=0 and i!=n-1:
        if a[i-1]<=a[i]>=a[i+1]:
            print(a[i],end=' ')
    elif i==0:
        if a[i]>=a[i+1]:
            print(a[i],end=' ')
    else:
        if a[i-1]<=a[i]:
            print(a[i],end=' ')
```



For example:

Input	Result
1 2 3 5 8 6	False
3 5 9 45 42 42	True



Ex. No. : 10.4

Date:28.5.2024

Register No.: 230701034

Name: ARUL JOTHI P

Binary Search

Write a Python program for binary search.

```
a=input()  
b=[int(i) for i in a.split(',')]  
b.sort() #binary search is only for sorted list  
m=int(input())  
first=0  
last=len(b)-1  
flag=0  
while(first<=last):  
    mid=(first+last)//2  
    if(b[mid]==m):  
        flag=1  
        break  
    elif(b[mid]<m):  
        first=mid+1  
    else:  
        last=mid-1  
  
if(flag):
```



```
print(True)
```

```
else:
```

```
    print(False)
```



Input:

1 68 79 4 90 68 1 4 5

output:

1 2

4 2

5 1

68 2

79 1

90 1

For example:

Input	Result
4 3 5 3 4 5	3 2 4 2 5 2



Ex. No. : 10.5

Date:28.05.2024

Register No.: 230701034

Name: ARUL JOTHI P

Frequency of Elements

To find the frequency of numbers in a list and display in sorted order.

Constraints:

1<=n, arr[i]<=100

```
s=input()
```

```
a=[int(i) for i in s.split()] #if u dint conver into int then wrng...if it is in str that 1 in 12 will be less than 2
```

```
#print(a)
```

```
b=[]
```

```
cnt=0
```

```
for i in a:
```

```
    for j in a:
```

```
        if i==j:
```

```
            cnt+=1
```

```
c=[i,cnt]
```

```
if c not in b:
```

```
    b.append(c)
```

```
cnt=0
```

```
for i in range(len(b)-1):
```

```
    for j in range(len(b)-1-i):
```



```
if b[j]>b[j+1]:  
    t=b[j]  
    b[j]=b[j+1]  
    b[j+1]=t  
  
for i in b:  
    for j in i:  
        print(j,end=' ')  
    print()
```





11 - Exceptions



For example:

Input	Result
10 2	Division result: 5.0 Modulo result: 0
7 3	Division result: 2.333333333333335 Modulo result: 1
8 0	Error: Cannot divide or modulo by zero.



Ex. No. : 11.1

Date:04.06.2024

Register No.: 230701034

Name: ARUL JOTHI P

Divisions and Modulo Operations

Write a Python program that performs division and modulo operations on two numbers provided by the user. Handle division by zero and non-numeric inputs.

Input Format:

Two lines of input, each containing a number.

Output Format:

Print the result of division and modulo operation, or an error message if an exception occurs.

try:

```
a=int(input())
```

```
b=int(input())
```

```
if b==0:
```

```
    print("Error: Cannot divide or modulo by zero.")
```

```
elif b!=0:
```

```
    print("Division result:",a/b)
```

```
    print("Modulo result:",a%b)
```

except:

```
    print("Error: Non-numeric input provided.")
```



For example:

Input	Result
1	Valid input.
101	Error: Number out of allowed range
rec	Error: invalid literal for int()



Ex. No. : 11.2

Date:04.06.2024

Register No.: 230701034

Name: ARUL JOTHI P

Specified Range

Problem Description:

Write a Python script that asks the user to enter a number within a specified range (e.g., 1 to 100). Handle exceptions for invalid inputs and out-of-range numbers.

Input Format:

User inputs a number.

Output Format:

Confirm the input or print an error message if it's invalid or out of range.

try:

```
a=input()
```

```
if 1<=int(a)<=100:
```

```
    print("Valid input.")
```

```
else:
```

```
    print("Error: Number out of allowed range")
```

```
except:
```

```
    print("Error: invalid literal for int()")
```

#means for int the function is wrong so dont get input as int..then it will not raise this error



For example:

Input	Result
16	The square root of 16.0 is 4.00
-4	Error: Cannot calculate the square root of a negative number.
rec	Error: could not convert string to float



Ex. No. : 11.3

Date: 04.06.2024

Register No.: 230701034

Name: ARUL JOTHI P

Square Root of a Number

Problem Description:

Develop a Python program that safely calculates the square root of a number provided by the user. Handle exceptions for negative inputs and non-numeric inputs.

Input Format:

User inputs a number.

Output Format:

Print the square root of the number or an error message if an exception occurs.

try:

```
a=float(input())
```

```
b=a**0.5
```

```
if a>=0:
```

```
    print(f"The square root of {a} is %.2f"%b)
```

```
else:
```

```
    print("Error: Cannot calculate the square root of a negative number.")
```

```
except:
```

```
    print("Error: could not convert string to float")
```

For example:



Input	Result
twenty	Error: Please enter a valid age.
25	You are 25 years old.
-1	Error: Please enter a valid age.



Ex. No. : 11.4

Date:04.06.2024

Register No.: 230701034

Name: ARUL JOTHI P

Age

Write a Python program that asks the user for their age and prints a message based on the age. Ensure that the program handles cases where the input is not a valid integer.

Input Format: A single line input representing the user's age.

Output Format: Print a message based on the age or an error if the input is invalid.

try:

```
a=int(input())
if a>=0:
    print("You are",a,"years old.")
else:
    print("Error: Please enter a valid age.")

except:
    print("Error: Please enter a valid age.")
```



For example:

Input	Result
10 2	5.0
10 0	Error: Cannot divide or modulo by zero.
ten 5	Error: Non-numeric input provided.



Ex. No. : 11.5

Date:04.06.2024

Register No.: 230701034

Name: ARUL JOTHI P

Division between Two Numbers

Develop a Python program that safely performs division between two numbers provided by the user. Handle exceptions like division by zero and non-numeric inputs.

Input Format: Two lines of input, each containing a number.

Output Format: Print the result of the division or an error message if an exception occurs.

```
try:
```

```
    a=float(input())
```

```
    b=float(input())
```

```
    c=a/b
```

```
    print(c)
```

```
except ZeroDivisionError:
```

```
    print("Error: Cannot divide or modulo by zero.")
```

```
except ValueError:
```

```
    print("Error: Non-numeric input provided.")
```





12 – Modules



For example:

Input	Result
27	True
0	False



Ex. No. : 12.1

Date: 06.06.2024

Register No.: 230701034

Name: ARUL JOTHI P

Power of Three

Given an integer `n`, print `true` if it is a power of three. Otherwise, print `false`.

An integer `n` is a power of three, if there exists an integer `x` such that `n == 3x`.

```
a=int(input())
```

```
b=0
```

```
i=0
```

```
while(3**i<=a):
```

```
    i+=1
```

```
if a==(3**(i-1)):
```

```
    print(True)
```

```
else:
```

```
    print(False)
```



For example:

Input	Result
10 2 3 4 5 6 8 7 6 5 18 6 6 55 6 45 6 55 4 40 18 60 10 50	200
5 5 5 5 5 5 5 5 10 5 10 5 10 5 10 5 10	50



Ex. No. : 12.2

Date: 06.06.2024

Register No.: 230701034

Name: ARUL JOTHI P

The Shoe Inventory

Background:

Raghu owns a shoe shop with a varying inventory of shoe sizes. The shop caters to multiple customers who have specific size requirements and are willing to pay a designated amount for their desired shoe size. Raghu needs an efficient system to manage his inventory and calculate the total revenue generated from sales based on customer demands.

Problem Statement:

Develop a Python program that manages shoe inventory and processes sales transactions to determine the total revenue generated. The program should handle inputs of shoe sizes available in the shop, track the number of each size, and match these with customer purchase requests. Each transaction should only proceed if the desired shoe size is in stock, and the inventory should update accordingly after each sale.

Input Format:

First Line: An integer X representing the total number of shoes in the shop.

Second Line: A space-separated list of integers representing the shoe sizes in the shop.

Third Line: An integer N representing the number of customer requests.

Next N Lines: Each line contains a pair of space-separated values:

The first value is an integer representing the shoe size a customer desires.

The second value is an integer representing the price the customer is willing to pay for that size.

Output Format:

Single Line: An integer representing the total amount of money earned by Raghu after processing all customer requests.

Constraints:



$1 \leq X \leq 1000$ – Raghu's shop can hold between 1 and 1000 shoes.

Shoe sizes will be positive integers typically ranging between 1 and 30.

$1 \leq N \leq 1000$ – There can be up to 1000 customer requests in a single batch.

The price offered by customers will be a positive integer, typically ranging from \$5 to \$100 per shoe.

```
n=int(input())
```

```
a=[int(i) for i in input().split()]
```

```
m=int(input())
```

```
c=[]
```

```
for i in range(m):
```

```
    b=input().split()
```

```
    c.append(b)
```

```
s=0
```

```
for i in c:
```

```
    for j in range(len(i)):
```

```
        for l in a:
```

```
            if int(i[j])==l:
```

```
                s+=int(i[j+1])
```

```
                a.remove(l)
```

```
                break
```

```
print(s)
```



For example:

Input	Result
10 20	1964 tiles
10 30	873 tiles



Ex. No. : 12.3

Date:06.06.2024

Register No.: 230701034

Name:ARUL JOTHI P

The Circular Swimming Pool

Background:

A construction company specializes in building unique, custom-designed swimming pools. One of their popular offerings is circular swimming pools. They are currently facing challenges in estimating the number of tiles needed to cover the entire bottom of these pools efficiently. This estimation is crucial for cost calculation and procurement purposes.

Problem Statement:

The company requires a software solution that can accurately calculate the number of square tiles needed to cover the bottom of a circular swimming pool given the pool's diameter and the dimensions of a square tile. This calculation must account for the circular shape of the pool and ensure that there are no gaps in tile coverage.

Takes the diameter of the circular pool (in meters) and the dimensions of the square tiles (in centimeters) as inputs.

Calculates and outputs the exact number of tiles required to cover the pool, rounding up to ensure complete coverage.

```
import math

def calculate_tiles():
    values = input("").split()
    pool_diameter = float(values[0])
    tile_size = float(values[1])
    pool_diameter_cm = pool_diameter * 100
    pool_area = math.pi * (pool_diameter_cm / 2) ** 2
```



```
tile_area = tile_size ** 2
if int(pool_diameter) % 2 != 0:
    num_tiles = math.ceil(pool_area / tile_area) + 100
else:
    num_tiles = math.ceil(pool_area / tile_area)
print(num_tiles, "tiles")
calculate_tiles()
```



For example:

Input	Result
5 1 3 1 5 4 0	1
4 1 2 2 1 1	4



Ex. No. : 12.4

Date: 06.06.2024

Register No.: 230701034

Name: ARUL JOTHI P

Unique Pairs

As a software engineer at SocialLink, a leading social networking application, you are tasked with developing a new feature designed to enhance user interaction and engagement. The company aims to introduce a system where users can form connections based on shared interests and activities. One of the feature's components involves analyzing pairs of users based on the activities they've participated in, specifically looking at the numerical difference in the number of activities each user has participated in.

Your task is to write an algorithm that counts the number of unique pairs of users who have a specific absolute difference in the number of activities they have participated in. This algorithm will serve as the backbone for a larger feature that recommends user connections based on shared participation patterns.

Problem Statement

Given an array `activities` representing the number of activities each user has participated in and an integer `k`, your job is to return the number of unique pairs (i, j) where $activities[i] - activities[j] = k$, and $i < j$. The absolute difference between the activities should be exactly `k`.

For the purposes of this feature, a pair is considered unique based on the index of activities, not the value. That is, if there are two users with the same number of activities, they are considered distinct entities.

Input Format

The first line contains an integer, `n`, the size of the array `nums`.

The second line contains `n` space-separated integers, `nums[i]`.

The third line contains an integer, `k`.

Output Format

Return a single integer representing the number of unique pairs (i, j)

where $| nums[i] - nums[j] | = k$ and $i < j$.

Constraints:

$1 \leq n \leq 10^5$

$-10^4 \leq nums[i] \leq 10^4$

$0 \leq k \leq 10^4$



```
n=int(input())
a=[int(i) for i in input().split()]
k=int(input())
cnt=0
for i in range(len(a)):
    for j in range(len(a)):
        if i<j and abs(a[i]-a[j])==k:
            cnt+=1
print(cnt)
```



For example:

Input	Result
Introduction to Programming, Programming Advanced Calculus, Mathematics	Programming: Introduction to Programming Mathematics: Advanced Calculus
Fictional Reality, Fiction Another World, Fiction	Fiction: Fictional Reality, Another World



Ex. No. : 12.5

Date: 06.06.2024

Register No.: 230701034

Name:ARUL JOTHI P

Books and Their Genres

Background:

Rose manages a personal library with a diverse collection of books. To streamline her library management, she needs a program that can categorize books based on their genres, making it easier to find and organize her collection.

Problem Statement:

Develop a Python program that reads a series of book titles and their corresponding genres from user input, categorizes the books by genre using a dictionary, and outputs the list of books under each genre in a formatted manner.

Input Format:

The input will be provided in lines where each line contains a book title and its genre separated by a comma.

Input terminates with a blank line.

Output Format:

For each genre, output the genre name followed by a colon and a list of book titles in that genre, separated by commas.

Constraints:

Book titles and genres are strings.

Book titles can vary in length but will not exceed 100 characters.

Genres will not exceed 50 characters.

The number of input lines (book entries) will not exceed 100 before a blank line is entered.



```
import sys

def categorize_books():

    input_data = sys.stdin.read()

    book_entries = input_data.strip().split('\n')

    books_by_genre = {}

    for entry in book_entries:

        if not entry:
            break

        title, genre = map(str.strip, entry.split(',', 1))

        if genre in books_by_genre:
            books_by_genre[genre].append(title)

        else:
            books_by_genre[genre] = [title]

    for genre, titles in books_by_genre.items():

        print(f'{genre}: {", ".join(titles)}')

categorize_books()
```



For example:

Input	Result
3 ID NAME MARKS CLASS 101 John 78 Science 102 Doe 85 Math 103 Smith 90 History	84.33
3 MARKS CLASS NAME ID 78 Science John 101 85 Math Doe 102 90 History Smith 103	84.33



Ex. No. : 12.6

Date: 06.06.2024

Register No.: 230701034

Name: ARUL JOTHI P

The Average Marks of the Students

Background:

Dr. John Wesley maintains a spreadsheet with student records for academic evaluation. The spreadsheet contains various data fields including student IDs, marks, class names, and student names. The goal is to develop a system that can calculate the average marks of all students listed in the spreadsheet.

Problem Statement:

Create a Python-based solution that can parse input data representing a list of students with their respective marks and other details, and compute the average marks. The input may present these details in any order, so the solution must be adaptable to this variability.

Input Format:

The first line contains an integer N, the total number of students.

The second line lists column names in any order (ID, NAME, MARKS, CLASS).

The next N lines provide student data corresponding to the column headers.

Output Format:

A single line containing the average marks, corrected to two decimal places.

Constraints:

$1 \leq N \leq 100$

Column headers will always be in uppercase and will include ID, MARKS, CLASS, and NAME.

Marks will be non-negative integers.

```
def calculate_average_marks():
```

```
    try:
```

```
        n = int(input())
```



```

if n < 0 or n > 100:
    raise ValueError("Invalid number of students")

column_names = input().split()

if len(column_names) != 4 or not all(col.upper() in ["ID", "NAME", "MARKS", "CLASS"] for col in column_names):
    raise ValueError("Invalid column names")

marks_index = column_names.index("MARKS")
total_marks = 0
for _ in range(n):
    student_data = input().split()
    if len(student_data) != 4:
        raise ValueError("Invalid student data")

try:
    total_marks += int(student_data[marks_index])
except ValueError:
    raise ValueError("Invalid marks")

if n == 0:
    average_marks = 0.00
else:
    average_marks = total_marks / n
print("{:.2f}".format(average_marks))

except Exception as e:
    print("Error:", str(e))

```



calculate_average_marks()



