**Ex. No.: 3**

# PASSIVE AND ACTIVE RECONNAISSANCE

## Aim:

To perform passive and active reconnaissance in TryHackMe platform.

## Algorithm:


### Passive Reconnaissance


1. Open the Passive Reconnaissance lab on the TryHackMe platform using the provided link: https://tryhackme.com/r/room/passiverecon
2. Launch the AttackBox to start the Kali Linux environment.
3. Use the whois command on tryhackme.com to collect relevant domain registration and ownership information.
4. Determine the IP address of tryhackme.com using the nslookup and dig commands.
5. Identify the subdomains associated with tryhackme.com using DNSDumpster.
6. Use Shodan to gather additional information about the target, including its IP address, hosting provider, geographical location, and server type and version.


### Active Reconnaissance


1. Open the Active Reconnaissance lab on TryHackMe using the provided link: https://tryhackme.com/r/room/activerecon
2. Start the AttackBox to launch the Kali Linux environment.
3. Conduct active reconnaissance against the target using tools and commands such as traceroute, ping, and netcat to gather information about network connectivity, routing, and available services.


## Output:



Try Hack Me
Dashboard
Learn
Practice
Compete
Go Premium
0
0
H
Back to all walkthroughs
Active Reconnaissance
Learn how to use simple tools such as traceroute, ping, telnet, and a web browser to gather information.
60 min
209,040
Share your achievement
Start AttackBox
Save Room
3744 Recommend
Connectivity
Options
Room completed: 100%
Task 1
Introduction
Task 2
Web Browser
Ping


Room completed: 100%
The following diagram illustrates a packet leaving a system with a TTL of 64. After passing through four routers, each decrementing the TTL by one, the packet arrives at the target with a TTL of 60.
192.168.0.202
10.1.2.254
IP (tos 0x48, ttl 64,...)
192.168.0.202.37600 > 10.1.2.254.ssh:
Flags [S], cksum 0x4b55
10.1.2.254
IP (tos 0x48, ttl 63,...)
10.1.2.254
IP (tos 0x48, ttl 62,...)


Room completed: 100%
10.1.2.254
192.168.0.202
192.168.0.1
IP (tos 0x0, ttl 1, id 61007, ...)
192.168.0.202.33615 > 10.1.2.254.33435: ...
192.168.0.202
IP (tos 0x0, ttl 64, id 4839, ...)
192.168.0.1 > 1192.168.0.202:
ICMP time exceeded in-transit, ...
IP (tos 0x0, ttl 1, id 61007, ...)


Try Hack Me
Dashboard
Learn
Practice
Compete
Go Premium
0
0
H
Back to all walkthroughs
Passive Reconnaissance
Learn about the essential tools for passive reconnaissance, such as whois, nslookup, and dig.
60 min
267,031
Share your achievement
Start AttackBox
Save Room
5276 Recommend
Connectivity
Options
Room completed: 100%
Task 1 Introduction
Task 2 Passive Versus Active Recon
Whois




**Result:**

Thus, the passive and active reconnaissance has been performed successfully in the TryHackMe platform.