

# EDGELOYALTYMWSERVICE SPECIFICATION

Release: 1.0

Date: 13 May, 2015

Author: Sumeet Madan

# Specification for EdgeLoyaltyMWService

Table of Contents	Page
Objective	3
View Catalogue	3
View Loyalty Points	5
Redeem Loyalty Points	7

# **Objective**

The objective of this document is to list the specifications for EdgeLoyaltyMWService which interacts with Loyalty Points System to provide the following functionalities:

- 1. View Catalogue
- 2. View Loyalty Points
- 3. Redeem Loyalty Points

# View Catalogue

This service fetches the list of products linked with the provided Catalogue:

**Operation Name**: ViewCatalogue

# **REQUEST**

# **HEADER**

HE IDEN				
Field	Length	M/O	Description	
UniqueId	9	M	Unique Alphanumeric ID (without special characters) from the source system	
ServiceRequestId	30	M	Hardcoded Value – MW.HKN	
ServiceRequestVersion	3	M	Hardcoded Value – 1.0	
ChannelId	3	M	Hardcoded Value – HKN	

# **BODY**

Field	Length	M/O	Description
CatalogueName	5		Catalogue Name for which linked products are required.

# Specification for EdgeLoyaltyMWService

# **RESPONSE**

# **HEADER**

Field	Length	M/O	Description
UniqueId	9	M	Unique Alphanumeric ID (without special characters) from the source system
ServiceRequestId	30	M	Hardcoded Value – MW.HKN
ServiceRequestVersion	3	M	Hardcoded Value – 1.0
ChannelId	3	M	Hardcoded Value – HKN

# **BODY**

Field	Length	M/O	Description	
ResponseCode	3	M	Status code of the request.	
ResponseDescription	999	M	Status description of the request.	
Catalogue List				
CatalogueProduct	10	M	Product Name linked to the provided Catalogue.	
Points	19	M	Loyalty points to be redeemed for the product	

```
<NS3:ViewCatalogueRsp>
            <NS3:CatalogueProduct>C01P1</NS3:CatalogueProduct>
            <NS3:Points>5</NS3:Points>
         </NS3:ViewCatalogueRsp>
         <NS3:ViewCatalogueRsp>
            <NS3:CatalogueProduct>C01P2</NS3:CatalogueProduct>
            <NS3:Points>5</NS3:Points>
         </NS3:ViewCatalogueRsp>
         <NS3:ViewCatalogueRsp>
            <NS3:CatalogueProduct>C01P3</NS3:CatalogueProduct>
            <NS3:Points>10</NS3:Points>
         </NS3:ViewCatalogueRsp>
         <NS3:ViewCatalogueRsp>
            <NS3:CatalogueProduct>C01P4</NS3:CatalogueProduct>
            <NS3:Points>5</NS3:Points>
         </NS3:ViewCatalogueRsp>
         <NS3:ViewCatalogueRsp>
            <NS3:CatalogueProduct>C01P5</NS3:CatalogueProduct>
            <NS3:Points>7</NS3:Points>
         </NS3:ViewCatalogueRsp>
      </NS3:CatalogueViewResponse>
   </NS1:Body>
</NS1:Envelope>
```

# **View Loyalty Points**

This service provides the available loyalty points for the provided customer id:

**Operation Name**: ViewPoints

# **REQUEST**

# **HEADER**

Field	Length	M/O	Description
UniqueId	9	M	Unique Alphanumeric ID (without special characters) from the source system
ServiceRequestId	30	M	Hardcoded Value – MW.HKN
ServiceRequestVersion	3	M	Hardcoded Value – 1.0
ChannelId	3	M	Hardcoded Value – HKN

# **BODY**

Field	Length	M/O	Description
CustomerId	9	M	Customer Id for which available loyalty points are required to be fetched.

# Sample

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"</pre>
xmlns:tem="http://tempuri.org">
 <soapenv:Header>
   <tem:subHeader>
     <tem:UniqueId>VP0000001</tem:UniqueId>
     <tem:ServiceRequestId>MW.HKN</tem:ServiceRequestId>
     <tem:ServiceRequestVersion>1.0</tem:ServiceRequestVersion>
     <tem:ChannelId>HKN</tem:ChannelId>
   </tem:subHeader>
 </soapenv:Header>
 <soapenv:Body>
   <tem:ViewPointsRequest>
     <tem:ViewPointsReq>
      <tem:CustomerId>CUST00798</tem:CustomerId>
     </tem:ViewPointsReq>
   </tem:ViewPointsRequest>
 </soapenv:Body>
</soapenv:Envelope>
```

# **RESPONSE**

### **HEADER**

Field	Length	M/O	Description
UniqueId	9	M	Unique Alphanumeric ID (without special characters) from the source system
ServiceRequestId	30	M	Hardcoded Value – MW.HKN
ServiceRequestVersion	3	M	Hardcoded Value – 1.0
ChannelId	3	M	Hardcoded Value – HKN

# **BODY**

Field	Length	M/O	Description
ResponseCode	3	M	Status code of the request.
ResponseDescription	999	M	Status description of the request.
CustomerId	9	M	Customer Id.
RegisteredFlag	1	M	Flag to determine if customer is registered for Loyalty Points. 'Y' – Registered. 'N' – Not Registered.
AvailablePoints	19	M	Loyalty points available for customer to redeem.

```
<NS1:Envelope xmlns:NS1="http://schemas.xmlsoap.org/soap/envelope/">
<NS1:Header>
<NS2:subHeader xmlns:NS2="http://tempuri.org">
```

# Specification for EdgeLoyaltyMWService

```
<NS2:UniqueId>VP0000001</NS2:UniqueId>
    <NS2:ServiceRequestId>MW.HKN</NS2:ServiceRequestId>
    <NS2:ServiceRequestVersion>1.0</NS2:ServiceRequestVersion>
    <NS2:ChannelId>HKN</NS2:ChannelId>
   </NS2:subHeader>
 </NS1:Header>
 <NS1:Body>
   <NS3:ViewPointsResponse xmlns:NS3="http://tempuri.org">
    <NS3:ResponseCode>000</NS3:ResponseCode>
    <NS3:ResponseDescription>Success</NS3:ResponseDescription>
    <NS3:ViewPointsRsp>
      <NS3:CustomerId>CUST00798</NS3:CustomerId>
      <NS3:RegisteredFlag>Y</NS3:RegisteredFlag>
      <NS3:AvailablePoints>147852963</NS3:AvailablePoints>
    </NS3:ViewPointsRsp>
   </NS3:ViewPointsResponse>
 </NS1:Body>
</NS1:Envelope>
```

# **Redeem Loyalty Points**

This service redeems the provided number of loyalty points against the customer id.

**Operation Name**: RedeemPoints

# **REQUEST**

# **HEADER**

Field	Length	M/O	Description
UniqueId	9	M	Unique Alphanumeric ID (without special characters) from the source system
ServiceRequestId	30	M	Hardcoded Value – MW.HKN
ServiceRequestVersion	3	M	Hardcoded Value – 1.0
ChannelId	3	M	Hardcoded Value – HKN

### **BODY**

Field	Length	M/O	Description
CustomerId	9	M	Customer Id.
RedeemPoints	19	M	No. of loyalty points to be redeemed.

# Sample

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"</pre>
xmlns:tem="http://tempuri.org">
 <soapenv:Header>
   <tem:subHeader>
     <tem:UniqueId>RP0000001</tem:UniqueId>
     <tem:ServiceRequestId>MW.HKN</tem:ServiceRequestId>
     <tem:ServiceRequestVersion>1.0</tem:ServiceRequestVersion>
     <tem:ChannelId>HKN</tem:ChannelId>
   </tem:subHeader>
 </soapenv:Header>
 <soapenv:Body>
   <tem:RedeemPointsRequest>
     <tem:RedeemPointsReq>
      <tem:CustomerId>CUST00798</tem:CustomerId>
      <tem:RedeemPoints>113</tem:RedeemPoints>
     </tem:RedeemPointsReq>
   </tem:RedeemPointsRequest>
 </soapenv:Body>
</soapenv:Envelope>
```

# **RESPONSE**

# **HEADER**

Field	Length	M/O	Description
UniqueId	9	M	Unique Alphanumeric ID (without special characters) from the source system
ServiceRequestId	30	M	Hardcoded Value – MW.HKN
ServiceRequestVersion	3	M	Hardcoded Value – 1.0
ChannelId	3	M	Hardcoded Value – HKN

# **BODY**

Field	Length	M/O	Description
ResponseCode	3	M	Status code of the request.
ResponseDescription	999	M	Status description of the request.
CustomerId	9	M	Customer Id.
RegisteredFlag	1	M	Flag to determine if customer is registered for Loyalty Points. 'Y' – Registered. 'N' – Not Registered.
AvailablePoints	19	M	Loyalty points available for customer to redeem.

```
<NS1:Envelope
xmlns:NS1="http://schemas.xmlsoap.org/soap/envelope/">
   <NS1:Header>
      <NS2:subHeader xmlns:NS2="http://tempuri.org">
         <NS2:UniqueId>RP0000001</NS2:UniqueId>
         <NS2:ServiceRequestId>MW.HKN</NS2:ServiceRequestId>
         <NS2:ServiceRequestVersion>1.0</NS2:ServiceRequestVersion>
         <NS2:ChannelId>HKN</NS2:ChannelId>
      </NS2:subHeader>
   </NS1:Header>
   <NS1:Body>
      <NS3:RedeemPointsResponse xmlns:NS3="http://tempuri.org">
         <NS3:ResponseCode>000</NS3:ResponseCode>
         <NS3:ResponseDescription>Success/NS3:ResponseDescription>
         <NS3:RedeemPointsRsp>
            <NS3:CustomerId>CUST00798</NS3:CustomerId>
            <NS3:RegisteredFlag>Y</NS3:RegisteredFlag>
            <NS3:AvailablePoints>147852850/NS3:AvailablePoints>
         </NS3:RedeemPointsRsp>
      </NS3:RedeemPointsResponse>
   </NS1:Body>
</NS1:Envelope>
```