

OSPF ROUTE CONFIGURE

Host file:

[routers]

catalyst8000v ansible_host=devnetsandboxiosxec8k.cisco.com

[routers:vars]

ansible_user=arunstemps

ansible_password=Z_k-gA5WS81mN7

ansible_network_os=cisco.ios.ios

ansible_connection=network_cli

ansible_become=yes

ansible_become_method=enable

ansible_command_timeout=120

ansible_connect_timeout=60

ansible_ssh_common_args='-o KexAlgorithms=+diffie-hellman-group14-sha1 -o

HostKeyAlgorithms=+ssh-rsa -o PubkeyAcceptedAlgorithms=+ssh-rsa'

Playbook:

- name: Configure OSPF

hosts: routers

gather_facts: no

vars:

ospf_networks:

- { network: "10.10.10.1", wildcard: "0.0.0.0", area: 0 }

- { network: "10.10.20.1", wildcard: "0.0.0.0", area: 0 }

tasks:

- name: Set OSPF Router ID

cisco.ios.ios_config:

parents: router ospf 1

lines:

- router-id 1.1.1.1

match: line

```
- name: Advertise Networks in OSPF
  cisco.ios.ios_config:
    parents: router ospf 1
    lines:
      - "network {{ item.network }} {{ item.wildcard }} area {{ item.area }}"
    match: line
```

Execute:

```
ansible-playbook -i hosts.ini playbooks/4-ospf_route_config.yml
```

Output:

Verification command: `ansible routers -i hosts.ini -m cisco.ios.ios_command -a "commands='show ip ospf neighbor'"`

```
catalyst8000v | SUCCESS => {
  "changed": false,
  "stdout": [
    ""
  ],
  "stdout_lines": [
    [
      ""
    ]
  ]
}
```

(venv) arunshnkr@ArunShankar:~/ansible-projects\$ |

Empty because we are using cisco sandbox and not neighbors can be formed.