



# Web Services Agent Partner API Specification

Money Transfer Management Solution

Version 3.1  
February 2026

# Table of Contents

## Contents

|                                                                  |    |
|------------------------------------------------------------------|----|
| Table of Contents .....                                          | 2  |
| Introduction .....                                               | 4  |
| Connection Parameters .....                                      | 4  |
| Response Format .....                                            | 5  |
| Sample Request/Response .....                                    | 6  |
| Testing Web Services Functionality .....                         | 7  |
| Using Web Services in a Live Environment: Some suggestions ..... | 7  |
| Data Integrity Hashing .....                                     | 8  |
| Web Service Method Details .....                                 | 9  |
| getAgentDetails .....                                            | 9  |
| getDestinationCountries .....                                    | 10 |
| getRates .....                                                   | 10 |
| getCurrentCredit .....                                           | 11 |
| createRemitter .....                                             | 12 |
| searchRemitter .....                                             | 13 |
| updateRemitter .....                                             | 16 |
| verifyRemitter .....                                             | 19 |
| getBeneficiaryAccountTypes .....                                 | 20 |
| createBeneficiary .....                                          | 21 |
| searchBeneficiary .....                                          | 23 |
| updateBeneficiary .....                                          | 25 |
| createTransaction .....                                          | 28 |
| confirmTransaction .....                                         | 31 |
| getTransactionStatus .....                                       | 32 |
| getTransactionStatusByAgentTransRef .....                        | 32 |
| getCharges .....                                                 | 34 |
| getDeliveryBanks .....                                           | 35 |
| getDeliveryBankBranches .....                                    | 37 |
| getCollectionPoints .....                                        | 38 |
| getMobileNetworkOperators .....                                  | 39 |
| getMobileNetworkCreditTypes .....                                | 39 |
| Appendix A : Destination Country ISO Codes .....                 | 42 |
| Appendix B : Remitter ID Type Codes .....                        | 49 |
| Appendix C : Beneficiary ID Type Codes .....                     | 49 |
| Appendix D : Payment Method Codes .....                          | 49 |
| Appendix E : Service Level (Delivery Speed) Codes .....          | 50 |
| Appendix F : Source of Income Codes .....                        | 50 |
| Appendix G : Remittance Purpose Codes .....                      | 50 |



## Introduction

The RemitONE WebServices Infrastructure uses the REST protocol. Our services use the POST method for invoking the service, and hence all data must be provided as POST variables. The response is provided as structured XML.

This document outlines the input and output parameters of the USI Money WebServices.

This document contains APIs:

1. Sending Agent API: This allows you to create transactions on the USI Money system

It is collectively known as the Partner API.

PLEASE NOTE: By accessing or using Remit One's API, you confirm that you have read and accepted the API Terms available at <https://www.remitone.com/legal/#developer-terms>.

## Connection Parameters

The BASE\_URL is the URL at which the WebServices are hosted. This BASE\_URL is then followed by the required GROUP name, and then the required METHOD name.

<BASE\_URL>/<GROUP>/<METHOD>

For example,

BASE\_URL

<https://test4.remit.by/universalsecuritiestest/ws/>

GROUP = transaction

METHOD = createTransaction

This would give a complete URL of :

<https://test4.remit.by/universalsecuritiestest/ws/transaction/createTransaction>

The client application would need to make a POST to this URL to invoke this particular WebService. *In the specification below, a \* indicates a required input parameter.*

Every invocation must contain the following parameters (as POST variables) :

| Name       | Type | Notes |
|------------|------|-------|
| username * | Text |       |
| password * | Text |       |
| pin *      | Text |       |

These will be provided to you when your WebService Account is activated.

All other parameters will depend on the particular WebService being invoked.

## Response Format

A Successful Response will always contain the following XML structure :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <status>SUCCESS</status>
  <result>
    [Specific response for the particular Web Service]
  </result>
</response>
```

An Error Response is as follows :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <status>FAIL</status>
  <result>
    <message>[Error message]</message>
  </result>
</response>
```

An Error Response with Validation errors is as follows :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <status>FAIL</status>
  <result>
    <message>VALIDATION FAILED</message>
    <errors>
      <error>[Validation error message]</error>
      <error>[Validation error message]</error>
      <error>[Validation error message]</error>
    </errors>
  </result>
```

</response>

## Sample Request/Response

### Sample Request (using curl):

```
curl -i -X POST \  
  -H "Content-Type:application/x-www-form-urlencoded" \  
  -d \  
'username=another_ws_agent&password=Apassword1&pin=12345' \  
https://test4.remit.by/universalsecuritiestest/ws/country/getDestinationCountries
```

### Sample Response:

```
<?xml version="1.0" encoding="utf-8"?>  
<response>  
  <responseId>1030111</responseId>  
  <status>SUCCESS</status>  
  <result>  
    <countries>  
      <country>  
        <id>999</id>  
        <name>Bangladesh</name>  
        <iso_code>BD</iso_code>  
        <currency>BDT</currency>  
        <allowed_currencies>  
          <currency>BDT</currency>  
        </allowed_currencies>  
      </country>  
      <country>  
        <id>986</id>  
        <name>Brazil</name>  
        <iso_code>BR</iso_code>  
        <currency>BRL</currency>  
        <allowed_currencies>  
          <currency>BRL</currency>  
          <currency>USD</currency>  
          <currency>DZD</currency>  
        </allowed_currencies>  
    </result>  
</response>
```

```
        </country>
    </countries>
</result>
</response>
```

## Testing Web Services Functionality

It is possible to test the output of the WebServices.  
The URL for accessing forms for each of the WebServices is :

<https://test4.remit.by/universalsecuritiestest/wstest/>

You can enter values for each of the WebService Forms and the result will be presented back as neatly formatted HTML.

If the system is in live mode, then the result will be returned as pure XML, and hence you can still use the 'View Source' option in the Web Browser to see the XML that is returned.

## Using Web Services in a Live Environment: Some suggestions

### Sending Agent API

Although it is possible to use the WebServices in any way that seems fit, we would suggest the following procedure.

1. Obtain a list of valid Destination Countries using `getDestinationCountries`. This can be done on a weekly or monthly basis.
2. Obtain the current Agent Credit level using `getCurrentCredit`. The credit response will also indicate the *source currency* that the system is expecting transactions to be created in.
3. Obtain delivery entity information by calling `getDeliveryBanks`, `getDeliveryBankBranches` and `getCollectionPoints`. This information will be needed when creating beneficiaries and transactions.
4. Create a new remitter using `createRemitter`, or search for an existing one using `searchRemitter`.
5. Create a new beneficiary using `createBeneficiary`, or search for an existing one using `searchBeneficiary`. Provide the `remitter_id` from the previous step to ensure the correct beneficiary is found. Also, the `updateBeneficiary`

method can be used at this point to set transfer details required in the next step.

6. Create a transaction between this remitter and beneficiary by calling `createTransaction`. *NOTE:* When creating a Cash Collection transaction the collection point details are specified in the `createTransaction` call. For all other transfer types (Account Transfer, Utility Bill, Mobile Transfer, Home Delivery) the details are retrieved from the beneficiary profile, so it is necessary to add those details using `createBeneficiary` or `updateBeneficiary` beforehand.
7. Receive a transaction creation response containing the actual charges as calculated by the system, compliance check results, and a temporary transaction session id. It is the responsibility of the user to examine these results.
8. Once the user is satisfied with the results, call `confirmTransaction` and provide the temporary transaction session id from step 6 above to actually create the transaction in the system.
9. At some later time, `getTransactionStatus` or `getTransactionStatusByAgentTranRef` can be used to determine whether the transaction has been processed.

## Data Integrity Hashing

If you enabled Data Integrity Hashing for a WS user and set a key, for all requests done on the API by this user, the field `data_integrity_hash` will need to be added. The data integrity hash can be created by doing the following:

1. Take all the POST parameters except for `username`, `password`, `pin`, `id1_scan` and `id2_scan` and concatenate them into a single string.
2. Append the "Data integrity key" value set on the WS users profile, to the end of the concatenated string.
3. Then generate a SHA256 Hash of the this string, and send that in the new POST variable `data_integrity_hash`.

The hash will be checked and validated on the server side.

The response XML from the server will also include a `<data_integrity_hash>` generated by taking all the string data from `<result>` open and close tags, add the "Data integrity key" to the end on the XML string and generate a SHA256 hash of that data. This can be used by the partner to verify data integrity on their end by regenerating the same has and comparing.

The hash can be generated by doing the following:



Given a response XML take the string with the opening and closing <result> tags. E.g.

```
"<result>
    <trans_ref>12345</trans_ref>
    <fname>Adam</fname>
    <lname>West</lname>
</result>"
```

Append the key to the end of the result string and hash the result. This will produce the hash returned in the response <data\_integrity\_hash> field.

## Web Service Method Details

### *Sending Agent API*

#### getAgentDetails

Group: agent

Method : getAgentDetails

This method provides the agent credentials including the agent name, country, currency and the destination countries.

Input fields :

none (apart from username, password and pin which are required in every invocation).

Example output XML:

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>289</responseId>
  <status>SUCCESS</status>
  <result>
    <agent>
      <id>8</id>
      <username>Test Agent</username>
      <name>Test Agent Company</name>
      <country>United Kingdom</country>
      <currency>GBP</currency>
      <destination_countries>
        <country>
          <name>India</name>
          <code>IN</code>
          <currency>INR</currency>
        </country>
      </destination_countries>
    </agent>
  </result>
</response>
```

## getDestinationCountries

Group : country

Method : getDestinationCountries

This method provides a list of available destination countries on the system.

Input fields :

none (apart from username, password and pin which are required in every invocation).

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>291</responseId>
  <status>SUCCESS</status>
  <result>
    <countries>
      <country>
        <id>999</id>
        <name>India</name>
        <iso_code>IN</iso_code>
        <currency>INR</currency>
        <allowed_currencies>
          <currency>INR</currency>
        </allowed_currencies>
      </country>
    </countries>
  </result>
</response>
```

---

## getRates

Group : rates

Method : getRates

This method provides current rates from the system.

Input fields:

| Name            | Type | Notes                                                                              |
|-----------------|------|------------------------------------------------------------------------------------|
| source_currency | Text | Optional                                                                           |
| dest_country *  | Text | The name of the Destination Country, as per the output of getDestinationCountries. |

|                    |      |          |
|--------------------|------|----------|
| dest_currency      | Text | Optional |
| Delivery Bank Name | Text | Optional |

### Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>293</responseId>
  <status>SUCCESS</status>
  <result>
    <rate>
      <account>102.35049589</account>
      <cash_collection>102.35049589</cash_collection>
      <card>102.35049589</card>
      <home_delivery>102.35049589</home_delivery>
      <utility_bill>102.35049589</utility_bill>
      <mobile_transfer>102.35049589</mobile_transfer>
    </rate>
    <source_country>United Kingdom</source_country>
    <source_currency></source_currency>
    <dest_country>India</dest_country>
    <dest_currency></dest_currency>
  </result>
</response>
```

---

### getCurrentCredit

Group : agent

Method : getCurrentCredit

Input fields :

none

### Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>295</responseId>
  <status>SUCCESS</status>
  <result>
    <credit>
      <currency>GBP</currency>
      <available_credit>9999999948.51</available_credit>
      <date_last_updated>2021-07-17T12:17:46+01:00</date_last_updated>
    </credit>
  </result>
</response>
```

## createRemitter

Group : remitter

Method : createRemitter

Input fields :

| Name             | Type | Notes                                                                                                                                       |
|------------------|------|---------------------------------------------------------------------------------------------------------------------------------------------|
| firstname *      | Text | Please send first name and any middle names.<br><br>If it's a corporate remitter, please send company first name - (e.g JPMorgan).          |
| lastname *       | Text | If it's a corporate remitter, please send company last name - (e.g Limited).                                                                |
| type *           | Text | registered                                                                                                                                  |
| Nationality *    | Text | 2 letter country ISO code. Please refer to Appendix A.<br><br>If it's a corporate remitter, please send company's country of incorporation. |
| gender *         | Text | Male / Female / Unspecified<br><br>If it's a corporate remitter, please send "Unspecified".                                                 |
| status *         | Text | valid / expired / blocked                                                                                                                   |
| address1 *       | Text | Please send house number and street name                                                                                                    |
| address2         | Text |                                                                                                                                             |
| city *           | Text |                                                                                                                                             |
| state            | Text |                                                                                                                                             |
| postcode *       | Text |                                                                                                                                             |
| mobile *         | Text | Format ( +4474xxxxxxx)                                                                                                                      |
| dob *            | Date | YYYY-MM-DD.                                                                                                                                 |
| country_of_birth | Text | 2 letter country ISO code. Please refer to Appendix A.                                                                                      |
| id_type *        | Code | See Appendix B for codes.                                                                                                                   |
| id_details *     | Text | Id number                                                                                                                                   |
| id_start         | Date | YYYY-MM-DD.                                                                                                                                 |

|                |      |                                     |
|----------------|------|-------------------------------------|
| id_expiry *    | Date | YYYY-MM-DD.                         |
| orgtype *      | Text | 'Individual' or 'Corporate'         |
| company_name   | Text | Required, if orgtype is 'Corporate' |
| company_reg_no | Text | Required, if orgtype is 'Corporate' |

### Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>145</responseId>
  <status>SUCCESS</status>
  <new_remitter_id>10005</new_remitter_id>
</response>
```

---

### searchRemitter

Group : remitter

Method : searchRemitter

Input fields :

| Name            | Type | Notes                                      |
|-----------------|------|--------------------------------------------|
| remitter_id     | Text | Required if the full name is not provided. |
| firstname *     | Text | Required if remitter_id is not provided.   |
| lastname *      | Text | Required if remitter_id is not provided.   |
| dob *           | Date | YYYY-MM-DD                                 |
| address_line1 * | Text |                                            |
| city *          | Text |                                            |
| postcode *      | Text |                                            |
| mobile *        | Text |                                            |
| id1_type *      | Text | See Appendix C for codes                   |

|               |      |  |
|---------------|------|--|
| id1_details * | Text |  |
|---------------|------|--|

|               |         |                               |
|---------------|---------|-------------------------------|
| remitter_type | Text    | registered                    |
| show_scans    | Boolean | Show the Base64 encoded scans |

## Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>147</responseId>
  <status>SUCCESS</status>
  <result>
    <remitters>
      <remitter>
        <remitter_id>10005</remitter_id>
        <status>valid</status>
        <firstname>Test</firstname>
        <middlename></middlename>
        <lastname>Remitter</lastname>
        <address1>56 Wilmers Close</address1>
        <address2></address2>
        <address3></address3>
        <city>London</city>
        <state>London</state>
        <postcode>E20 6LD</postcode>
        <country>United Kingdom</country>
        <telephone>+445456567</telephone>
        <mobile>+443823484</mobile>
        <email>test@remitter.com</email>
        <dob>2003-08-06</dob>
        <place_of_birth>London</place_of_birth>
        <country_of_birth>England</country_of_birth>
        <nationality>British</nationality>
        <fathers_name>Jack</fathers_name>
        <mothers_name>Jill</mothers_name>
        <national_id_number>123213123</national_id_number>
        <id_type>test type</id_type>
        <id_details>
<![CDATA['test details']]>
        </id_details>
        <id_issued_by>test issued</id_issued_by>
        <id_issue_place>test place of issue</id_issue_place>
        <id_start>1995-04-16</id_start>
        <id_expiry>2030-05-06</id_expiry>
        <id_scan1>10005_3657528_202107161051.jpg</id_scan1>
        <id_scan2>10005_2243319_202107161051.jpg</id_scan2>
        <id_scan3>10005_8114685_202107161051.jpg</id_scan3>
        <id2_type></id2_type>
        <id2_details></id2_details>
        <id2_issued_by></id2_issued_by>
        <id2_issue_place></id2_issue_place>
        <id2_start></id2_start>
        <id2_expiry></id2_expiry>
      </remitter>
    </remitters>
  </result>
</response>
```

```

<id2_scan1></id2_scan1>
<id2_scan2></id2_scan2>
<id2_scan3></id2_scan3>
<id3_type></id3_type>
<id3_details></id3_details>
<id3_issued_by></id3_issued_by>
<id3_issue_place></id3_issue_place>
<id3_start></id3_start>
<id3_expiry></id3_expiry>
<id3_scan1></id3_scan1>
<id3_scan2></id3_scan2>
<id3_scan3></id3_scan3>
<id4_type></id4_type>
<id4_details></id4_details>
<id4_issued_by></id4_issued_by>
<id4_issue_place></id4_issue_place>
<id4_start></id4_start>
<id4_expiry></id4_expiry>
<id4_scan1></id4_scan1>
<id4_scan2></id4_scan2>
<id4_scan3></id4_scan3>
<kyc_video></kyc_video>
<comments>Test Comment</comments>
<groups>Default</groups>
<credit_balance>0.00</credit_balance>
<credit_currency>GBP</credit_currency>
(NOT PRESENT: <bank_name></bank_name>
<bank_branch_name></bank_branch_name>
<bank_account_number></bank_account_number>
<bank_iban></bank_iban>
<bank_swift_code></bank_swift_code>
  <bank_bic_code></bank_bic_code>)
  <orgtype>Individual</orgtype>
  <sector>Finance</sector>
  <employer>Remit One</employer>
  <business_address>34 Lamda Way London England C65
FB4</business_address>
  <contract_date>2006-03-17</contract_date>
  <annual_income>60000.00</annual_income>
  <annual_remittance>10000.00</annual_remittance>
  <purpose>Remit</purpose>
  <source_of_income>SALARY</source_of_income>
  <hear_about_us>Family or Friend</hear_about_us>
  <hear_about_us_other>Here specify how you heard about
us...</hear_about_us_other>
  <residency_status>resident</residency_status>
  <nearest_airport>Heathrow</nearest_airport>
  <visa_status>T</visa_status>
</remitter>
</remitters>
</result>
</response>

```

---

## updateRemitter

Group : remitter

Method : updateRemitter

Input fields :

| Name               | Type | Notes                                                  |
|--------------------|------|--------------------------------------------------------|
| remitter_id *      | Text |                                                        |
| firstname *        | Text |                                                        |
| lastname *         | Text |                                                        |
| type *             | Text | registered                                             |
| nationality *      | Text | 2 letter country ISO code. Please refer to Appendix A. |
| status *           | Text | valid / expired / blocked                              |
| address1 *         | Text |                                                        |
| address2           | Text |                                                        |
| city *             | Text |                                                        |
| state *            | Text |                                                        |
| postcode *         | Text |                                                        |
| mobile *           | Text |                                                        |
| dob *              | Date | YYYY-MM-DD                                             |
| country_of_birth * | Text | 2 letter country ISO code. Please refer to Appendix A. |



|               |      |                            |
|---------------|------|----------------------------|
| id_type *     | Code | See Appendix B for codes   |
| id_details *  | Text |                            |
| id_start      | Date | YYYY-MM-DD                 |
| id_expiry *   | Date | YYYY-MM-DD                 |
| id_verified * | Text | VERIFIED, UNVERIFIED, FAIL |

|                |      |                                     |
|----------------|------|-------------------------------------|
| orgtype *      | Text | 'Individual' or 'Corporate'         |
| company_name   | Text | Required, if orgtype is 'Corporate' |
| company_reg_no | Text | Required, if orgtype is 'Corporate' |

**NOTE:** All valid fields must be provided on update, otherwise existing fields may be blanked out.

### Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>152</responseId>
  <status>SUCCESS</status>
  <result>
    <remitter>
      <remitter_id>10005</remitter_id>
      <firstname>Test</firstname>
      <middlename></middlename>
      <lastname>Remitter</lastname>
      <address1>56 Wilmers Close</address1>
      <address2></address2>
      <address3></address3>
      <city>London</city>
      <state>London</state>
      <postcode>E20 6LD</postcode>
      <country>United Kingdom</country>
      <telephone>+445456567</telephone>
      <mobile>+443823484</mobile>
      <email>test@remitter.com</email>
      <dob>2003-08-06</dob>
      <fathers_name>Jack</fathers_name>
      <mothers_name>Jill</mothers_name>
      <national_id_number></national_id_number>
      <gender>MALE</gender>
      <place_of_birth>London</place_of_birth>
      <country_of_birth>England</country_of_birth>
      <nationality>united kingdom</nationality>
      <visa_status></visa_status>
      <id_type>test type</id_type>
      <id_details>test details</id_details>
      <id_issued_by>test issued</id_issued_by>
      <id_issue_place>test place of issue</id_issue_place>
```

<id\_issue\_country></id\_issue\_country>  
<id\_start>1995-04-16</id\_start>  
<id\_expiry>2030-05-06</id\_expiry>  
<id\_scan>10005\_3260042\_202107161206.jpg</id\_scan>  
<id\_scan1\_content>  
</id\_scan1\_content>  
<id\_scan2>10005\_4720254\_202107161206.jpg</id\_scan2>  
<id\_scan2\_content>  
</id\_scan2\_content>  
<id\_scan3>10005\_1475864\_202107161206.jpg</id\_scan3>

```

        <id_scan3_content>
        </id_scan3_content>
        <orgtype>Individual</orgtype>
        <purpose>Tourism</purpose>
        <source_of_income>SALARY</source_of_income>
        <sector>Finance</sector>
        <employer>Remit One</employer>
        <business_address></business_address>
        <contract_date>2006-03-17</contract_date>
        <annual_income>60000.00</annual_income>
        <annual_remittance>10000.00</annual_remittance>
        <hear_about_us>Family or Friend</hear_about_us>
        <hear_about_us_other>Here specify how you heard about
us...</hear_about_us_other>
        <residency_status>resident</residency_status>
        <nearest_airport>Heathrow</nearest_airport>
        <remitter_username>testremitter@username.com</remitter_username>
        <visa_status></visa_status>
    </remitter>
</result>
</response>

```

---

## verifyRemitter

Group : remitter

Method : verifyRemitter

Input fields :

| Name          | Type | Notes                              |
|---------------|------|------------------------------------|
| remitter_id * | Text |                                    |
| agent_name *  | Text | Agent code of the remitter's Agent |

Example Output XML :

```

<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>154</responseId>
    <status>SUCCESS</status>
    <result>
        <remitter>
            <remitter_id>10005</remitter_id>
            <firstname>Test</firstname>
            <lastname>Remitter</lastname>
            <verified>t</verified>
            <status>valid</status>
            <orgtype>Individual</orgtype>

```

```
        </remitter>
    </result>
</response>
```

---

## **getBeneficiaryAccountTypes**

Group : beneficiary

Method : getBeneficiaryAccountTypes

### **Example Output XML :**

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>792</responseId>
    <status>SUCCESS</status>
    <result>
        <benef_ac_types>
            <benef_ac_type>INDIVIDUAL</benef_ac_type>
            <benef_ac_type>CORPORATE</benef_ac_type>
        </benef_ac_types>
    </result>
</response>
```

---

## createBeneficiary

Group : beneficiary

Method : createBeneficiary

Input fields :

| Name                | Type | Notes                                                                             |
|---------------------|------|-----------------------------------------------------------------------------------|
| name *              | Text |                                                                                   |
| fname *             | Text | If it's a corporate beneficiary, please send company first name - (e.g JPMorgan). |
| lname *             | Text | If it's a corporate beneficiary, please send company last name - (e.g Limited).   |
| organisation_type * | Text | INDIVIDUAL or CORPORATE                                                           |
| company_name        | Text | Required, if organisation_type is 'CORPORATE'                                     |
| company_reg_no      | Text | Required, if organisation_type is 'CORPORATE'                                     |
| address1 *          | Text |                                                                                   |
| address2            | Text |                                                                                   |
| city *              | Text |                                                                                   |
| state               | Text |                                                                                   |
| postcode            | Text |                                                                                   |
| country *           | Text | Country Name, as per output of getDestinationCountries                            |

|                  |      |                                                                             |
|------------------|------|-----------------------------------------------------------------------------|
| mobile *         | Text |                                                                             |
| email            | Text | Required for SOUTH AFRICA account transactions                              |
| account_number   | Text | If IBAN based corridor, please pass iban otherwise it always account number |
| bank             | Text | Required if beneficiary is for account transactions                         |
| bank_branch      | Text |                                                                             |
| bank_branch_city | Text | Any branch                                                                  |

|                       |        |                                             |
|-----------------------|--------|---------------------------------------------|
| bank_branch_state     | Text   | Any branch                                  |
| benef_bank_swift_code | Text   |                                             |
| benef_bank_ifsc_code  | Text   | Required for INDIA account transactions     |
| benef_bank_iban       | Text   | If IBAN based corridor, please pass iban    |
| linked_member_id *    | Number | The member ID this beneficiary is linked to |

**NOTE:** If the Bank needs to create a new Card for the beneficiary, then specify the Card Number as 'REQUESTED'. This data will then be fed to the Bank dealing with that country for creation of the ATM Card.

### Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>267</responseId>
  <status>SUCCESS</status>
  <new_beneficiary_id>11</new_beneficiary_id>
</response>
```

---

## searchBeneficiary

Group : beneficiary

Method : searchBeneficiary

Input fields :

| Name                 | Type   | Notes                                                             |
|----------------------|--------|-------------------------------------------------------------------|
| beneficiary_id       | Number |                                                                   |
| linked_remitter_id * | Number | member_id of the linked remitter. This will filter the result set |
| name *               | Text   |                                                                   |
| fname *              | Text   | Beneficiary's first name                                          |
| lname *              | Text   | Beneficiary's last name                                           |
| address_line1 *      | Text   |                                                                   |
| city *               | Text   |                                                                   |
| country *            | Text   | Required, as per output of getDestinationCountries                |
| mobile *             | Text   |                                                                   |
| account_number       | Text   | Required if beneficiary is for account transaction                |

## Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>287</responseId>
  <status>SUCCESS</status>
  <result>
```

```
<beneficiaries>
  <beneficiary>
    <beneficiary_id>11</beneficiary_id>
    <name>TEST BENEFICIARY</name>
    <fname>TEST</fname>
    <mname></mname>
    <lname>BENEFICIARY</lname>
    <address1>34 Test road</address1>
    <address2>London</address2>
    <address3>England</address3>
    <city>London</city>
    <state>London</state>
    <postcode>T8 37</postcode>
    <country>India</country>
    <dob>1982-06-18</dob>
    <fathers_name>John</fathers_name>
    <mothers_name>Jill</mothers_name>
    <national_id_number>123213123</national_id_number>
    <telephone>+44234567</telephone>
```



```
<mobile>+44234567</mobile>
<email>test@beneficiary.com</email>
<status>t</status>
<id_type>Test Type</id_type>
<id_details>Test Details</id_details>
<id2_type>Test Type 2</id2_type>
<id2_details>Test Details 2</id2_details>
<account_number>12134</account_number>
<bank>Test Proc Bank</bank>
<bank_branch>Avro Vulcan</bank_branch>
<bank_branch_city>Test</bank_branch_city>
<bank_branch_state>Test</bank_branch_state>
<bank_branch_telephone>+44656879098</bank_branch_telephone>
<bank_branch_manager>Test</bank_branch_manager>
<benef_bank_swift_code>765</benef_bank_swift_code>
<benef_bank_ifsc_code>PUNB0999900</benef_bank_ifsc_code>
<benef_bank_account_name>Test</benef_bank_account_name>
<card_type>VISA</card_type>
<card_number>123456789</card_number>
<homedelivery_notes>Test</homedelivery_notes>
<suspicious>f</suspicious>
<suspicion_reason></suspicion_reason>
<linked_remitter_ids>
  <remitter_id>10005</remitter_id>
</linked_remitter_ids>
</beneficiary>
</beneficiaries>
</result>
</response>
```

---

## **updateBeneficiary**

Group : beneficiary

Method : updateBeneficiary

Input fields :

| Name              | Type   | Notes                                                               |
|-------------------|--------|---------------------------------------------------------------------|
| beneficiary_id *  | Number |                                                                     |
| name              | Text   |                                                                     |
| fname             | Text   |                                                                     |
| lname             | Text   |                                                                     |
| organisation_type | Text   | INDIVIDUAL or CORPORATE                                             |
| company_name      | Text   |                                                                     |
| company_reg_no    | Text   |                                                                     |
| address1          | Text   |                                                                     |
| address2          | Text   |                                                                     |
| city              | Text   |                                                                     |
| state             | Text   |                                                                     |
| postcode          | Text   |                                                                     |
| country           | Text   | As per output of<br>getDestinationCountries                         |
| mobile            | Text   |                                                                     |
| email             | Text   | Required if beneficiary is for SOUTH<br>AFRICA account transactions |

|                       |      |  |
|-----------------------|------|--|
| account_number        | Text |  |
| bank                  | Text |  |
| bank_branch           | Text |  |
| bank_branch_city      | Text |  |
| bank_branch_state     | Text |  |
| benef_bank_swift_code | Text |  |
| benef_bank_ifsc_code  | Text |  |

**NOTE:** All valid fields must be provided on update, otherwise existing fields may be blanked out.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>273</responseId>
  <status>SUCCESS</status>
  <result>
    <beneficiary>
      <beneficiary_id>11</beneficiary_id>
      <name>TEST BENEFICIARY</name>
      <fname>TEST</fname>
      <mname></mname>
      <lname>BENEFICIARY</lname>
      <alias></alias>
      <type>DEFAULT</type>
      <tel>+44234567</tel>
      <mobile>+44234567</mobile>
      <email>test@beneficiary.com</email>
      <gender>MALE</gender>
      <address1>34 Test road</address1>
      <address2>London</address2>
      <address3>England</address3>
      <city>London</city>
      <state>London</state>
      <postcode>T8 37</postcode>
      <country_id>999</country_id>
      <nationality></nationality>
      <dob>1982-06-18</dob>
      <fathers_name>John</fathers_name>
      <mothers_name>Jill</mothers_name>
      <national_id_number>123213123</national_id_number>
      <id_type>Test Type</id_type>
      <id_details>Test Details</id_details>
      <id_issued_by>Test By</id_issued_by>
      <id_issue_place>Test Place</id_issue_place>
      <id_issue_country>Iceland</id_issue_country>
      <id_start>1998-12-08</id_start>
      <id_expiry>2030-12-08</id_expiry>
      <id2_type>Test Type 2</id2_type>
      <id2_details>Test Details 2</id2_details>
      <id2_issue_place>Test Place 2</id2_issue_place>
    </beneficiary>
  </result>
</response>
```

```

        <id2_expiry>2040-12-08</id2_expiry>
        <linked_member_id></linked_member_id>
        <enabled>t</enabled>
        <suspicious>f</suspicious>
        <suspicion_reason></suspicion_reason>
    </beneficiary>
</result>
</response>

```

---

## createTransaction

Group: transaction

Method: createTransaction

Input fields:

| Name                  | Type   | Notes                                                                                                                                                                                                                                  |
|-----------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| remitter_id *         | Number |                                                                                                                                                                                                                                        |
| beneficiary_id *      | Number |                                                                                                                                                                                                                                        |
| relation_to_remitter  | Text   |                                                                                                                                                                                                                                        |
| destination_country * | Text   | Name of country retrieved from calling<br>getDestinationCountries                                                                                                                                                                      |
| agent_trans_ref *     | Text   | Agent's reference number for<br>transaction                                                                                                                                                                                            |
| benef_trans_ref       | Text   | Beneficiary reference number for<br>transaction                                                                                                                                                                                        |
| trans_type *          | Text   | Account / Cash Collection / Mobile<br>Transfer                                                                                                                                                                                         |
| purpose *             | Code   | See Appendix G for codes                                                                                                                                                                                                               |
| source_of_income *    | Code   | See Appendix F for codes                                                                                                                                                                                                               |
| collection_point_id   | Number | The collection point id                                                                                                                                                                                                                |
| collection_point      | Text   | Name of collection point where money<br>will be collected by beneficiary. Required<br>if transaction is of type Cash Collection.<br>All the fields starting with 'collection_'<br>below only apply to Cash Collection<br>transactions. |
| collection_point_code | Text   | Collection point code.                                                                                                                                                                                                                 |

|                                 |        |                                                                                                                      |
|---------------------------------|--------|----------------------------------------------------------------------------------------------------------------------|
| collection_point_bank           | Text   | Name of bank or organisation that the collection point is under. Required if transaction is of type Cash Collection. |
| collection_point_address        | Text   | Collection point address.                                                                                            |
| collection_point_city           | Text   | Collection transaction point city.                                                                                   |
| collection_point_state          | Text   | Collection point state.                                                                                              |
| benef_mobiletransfer_number     | Text   | The mobile number of the beneficiary for mobile transfer. Required for Mobile Wallet transactions                    |
| benef_mobiletransfer_network_id | Number | The beneficiary mobile network id                                                                                    |
| benef_mobiletransfer_network    | Text   | The mobile phone network of the beneficiary for mobile transfer. Required for Mobile Wallet transactions             |

|                                             |         |                                                                          |
|---------------------------------------------|---------|--------------------------------------------------------------------------|
| benef_mobiletransfer_network_credit_type_id | Text    |                                                                          |
| payment_method *                            | Code    | Fixed value = "74".<br>For the rest of values, see Appendix D for codes. |
| service_level *                             | Code    | Fixed value = "1"<br>For the rest of values, see Appendix E for codes.   |
| sms_confirmation *                          | Boolean | f                                                                        |
| sms_notification *                          | Boolean | f                                                                        |
| source_currency                             | Text    | Source currency, if blank will use default                               |
| dest_currency                               | Text    | Dest currency, if blank will use default                                 |
| amount_type *                               |         | Fixed value = "DESTINATION".                                             |
| amount_to_send *                            | Numeric |                                                                          |

**NOTE:** After invoking this method, confirmTransaction must be called with the trans\_session\_id to successfully create the transaction.

### Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>325</responseId>
  <status>SUCCESS</status>
  <result>
```

```
<trans_session_id>830016270356710161</trans_session_id>
<remitter_id>10005</remitter_id>
<remitter_name>TEST REMITTER</remitter_name>
<beneficiary_id>11</beneficiary_id>
<beneficiary_name>TEST BENEFICIARY</beneficiary_name>
<trans_type>Cash Collection</trans_type>
<destination_country>India</destination_country>
<source_currency>GBP</source_currency>
<source_transfer_amount>10.00</source_transfer_amount>
<rate>102.18465795</rate>
<destination_currency>INR</destination_currency>
<destination_amount>1021.85</destination_amount>
<commission>2.3</commission>
<agent_fee>0</agent_fee>
<hq_fee>0</hq_fee>
<tax>0.00</tax>
<remitter_pay_amount>12.30</remitter_pay_amount>
<agent_deduction>1.15</agent_deduction>
<agent_to_pay_hq>11.15</agent_to_pay_hq>
<delivery_date>2021-07-23T11:21:00+01:00</delivery_date>
<payment_token/>
</result>
</response>
```

---

## confirmTransaction

Group: transaction

Method: confirmTransaction

Input fields:

| Name               | Type    | Notes                                                                            |
|--------------------|---------|----------------------------------------------------------------------------------|
| trans_session_id * | Numeric | Temporary ID generated by the system and returned as result of createTransaction |

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>326</responseId>
  <status>SUCCESS</status>
  <result>
    <reference_number>RC000821000117</reference_number>
    <remitter_id>10005</remitter_id>
    <remitter_name>TEST REMITTER</remitter_name>
    <beneficiary_id>11</beneficiary_id>
    <beneficiary_name>TEST BENEFICIARY</beneficiary_name>
    <status>AGENT_OK</status>
    <trans_type>Cash Collection</trans_type>
    <destination_country>India</destination_country>
    <source_currency>GBP</source_currency>
    <source_transfer_amount>10.00</source_transfer_amount>
    <rate>102.18465795</rate>
    <destination_currency>INR</destination_currency>
    <destination_amount>1021.85</destination_amount>
    <commission>2.30</commission>
    <agent_fee>0.00</agent_fee>
    <hq_fee>0.00</hq_fee>
    <tax>0.00</tax>
    <remitter_pay_amount>12.30</remitter_pay_amount>
    <agent_deduction>1.15</agent_deduction>
    <agent_to_pay_hq>11.15</agent_to_pay_hq>
    <delivery_date>2021-07-23T11:21:00+01:00</delivery_date>
    <payment_token/>
    <compliance_check_required>t</compliance_check_required>
    <ext_compliance_check_required>f</ext_compliance_check_required>
    <collection_pin>309558</collection_pin>
    <agent_trans_ref>TEST-111</agent_trans_ref>
    <benef_trans_ref>RC000821000117</benef_trans_ref>
  </result>
</response>
```

## getTransactionStatus

Group: transaction

Method: getTransactionStatus

Input fields:

| Name       | Type | Notes                                                                                                                                                     |
|------------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| trans_ref* | Text | Transaction reference from the USI system. See <code>getTransactionStatusByAgentTransRef</code> below to request using the agent's transaction reference. |

### Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>29</responseId>
  <status>SUCCESS</status>
  <result>
    <trans_ref>RA000263000102</trans_ref>
    <agent_trans_ref></agent_trans_ref>
    <benef_trans_ref>RA000263000102</benef_trans_ref>
    <status>PROCESSED</status>
    <compliance_check_required>t</compliance_check_required>
    <compliance_checked>t</compliance_checked>
    <ext_compliance_check_required>f</ext_compliance_check_required>
    <ext_compliance_checked>f</ext_compliance_checked>
    <error_reason></error_reason>
    <error_details></error_details>
    <deleted_reason></deleted_reason>
    <admin_comments>
<![CDATA[]]>
      </admin_comments>
    <agent_comments>
<![CDATA[]]>
      </agent_comments>
    </result>
  </response>
```

---

## getTransactionStatusByAgentTransRef

Group: transaction

Method: getTransactionStatusByAgentTransRef



Input fields:

| Name        | Type | Notes                                                                                                                                                                                            |
|-------------|------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| trans_ref * | Text | Agent's unique transaction reference (if provided at the time of creation). See <code>getTransactionStatus</code> above to request the transaction status using the USI's transaction reference. |

## Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>42</responseId>
  <status>SUCCESS</status>
  <result>
    <trans_ref>RA000241000104</trans_ref>
    <agent_trans_ref>6244</agent_trans_ref>
    <benef_trans_ref>RA000241000104</benef_trans_ref>
    <status>AGENT_OK</status>
    <compliance_check_required>t</compliance_check_required>
    <compliance_checked>f</compliance_checked>
    <ext_compliance_check_required>f</ext_compliance_check_required>
    <ext_compliance_checked>f</ext_compliance_checked>
    <error_reason></error_reason>
    <error_details></error_details>
    <deleted_reason></deleted_reason>
    <admin_comments>
<![CDATA[]]>
      </admin_comments>
    <agent_comments>
<![CDATA[]]>
      </agent_comments>
    </result>
  </response>
```

---

## getCharges

Group: transaction

Method: getCharges

Input fields:

| Name                  | Type    | Notes                                                                          |
|-----------------------|---------|--------------------------------------------------------------------------------|
| destination_country * | Text    | Name of country retrieved from calling<br>getDestinationCountries              |
| trans_type *          | Text    | Account / Cash Collection / Card Transfer<br>/ Home Delivery / Mobile Transfer |
| payment_method *      | Code    | See Appendix D for codes.                                                      |
| service_level *       | Code    | See Appendix E for codes.                                                      |
| sms_confirmation *    | Boolean | t / f                                                                          |
| sms_notification *    | Boolean | t / f                                                                          |

|                      |         |                                                           |
|----------------------|---------|-----------------------------------------------------------|
| amount_type *        |         | Fixed values = "DESTINATION".                             |
| amount_to_send *     | Numeric |                                                           |
| Source Currency      | Text    | Same code as you get when calling getSourceCountries      |
| Destination currency | Text    | Same code as you get when calling getDestinationCountries |

If source and destination currencies are not entered, then the default source and destination currencies will be used instead.

### Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>338</responseId>
  <status>SUCCESS</status>
  <result>
    <source_currency>GBP</source_currency>
    <source_amount>0.98</source_amount>
    <rate>102.44072914</rate>
    <destination_currency>INR</destination_currency>
    <destination_amount>100.00</destination_amount>
    <commission>0.23</commission>
    <agent_fee>0</agent_fee>
    <hq_fee>0</hq_fee>
    <total_charges>0.23</total_charges>
    <tax>0.00</tax>
  </result>
</response>
```

---

## getDeliveryBanks

Group: deliveryBank

Method: getDeliveryBanks

Input fields:

| Name         | Type | Notes                                                                                                                                   |
|--------------|------|-----------------------------------------------------------------------------------------------------------------------------------------|
| dest_country | Text | The name of the Destination Country, as per the output of getDestinationCountries.<br>You can provide destination country name or code. |

|              |      |                                                                                                                                                               |
|--------------|------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| country_code | Text | The code of the Destination Country, as per the output of <b>getDestinationCountries</b> . You can provide destination country name or code.                  |
| bank_code    | Text | The code of the processing bank connected to the delivery bank. If no dest_country, country_code and bank_code is given, all the delivery banks are returned. |

### Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>73</responseId>
  <status>SUCCESS</status>
  <result>
    <delivery_banks>
      <delivery_bank>
        <bank_id>4</bank_id>
        <name>Test Proc Bank India</name>
        <country_id>999</country_id>
        <bank_code>TestProcBank</bank_code>
        <swift_code></swift_code>
        <address>78 Dalston Street</address>
        <city>Dhaka</city>
        <state>N/A</state>
        <telephone></telephone>
        <account_number_mask></account_number_mask>
        <enabled>t</enabled>
        <third_party_id></third_party_id>
        <third_party_name></third_party_name>
        <third_party_code></third_party_code>
      </delivery_bank>
    </delivery_banks>
  </result>
</response>
```

## getDeliveryBankBranches

Group: deliveryBankBranch

Method: getDeliveryBankBranches

Input fields:

| Name                     | Type | Notes                                                                                                                                 |
|--------------------------|------|---------------------------------------------------------------------------------------------------------------------------------------|
| delivery_bank            | Text | The name of the delivery bank, as per the output of getDeliveryBanks.                                                                 |
| destination_country      | Text | Name of country retrieved from calling getDestinationCountries. This will be used if the destination_country_code is not provided.    |
| destination_country_code | Text | Iso code of country retrieved from calling getDestinationCountries. This will be used in priority over the destination_country value. |

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>75</responseId>
  <status>SUCCESS</status>
  <result>
    <delivery_bank_branches>
      <delivery_bank_branch>
        <id>2</id>
        <name>Test Delivery Branch</name>
        <branch_code>1234</branch_code>
        <enabled>t</enabled>
        <delivery_bank>4</delivery_bank>
        <city>Akola</city>
        <state>N/A</state>
        <telephone></telephone>
        <manager></manager>
        <ifsc_code></ifsc_code>
        <third_party_id></third_party_id>
        <third_party_name></third_party_name>
        <third_party_code></third_party_code>
      </delivery_bank_branch>
    </delivery_bank_branches>
  </result>
</response>
```

## getCollectionPoints

Group: collectionPoint

Method: getCollectionPoints

Input fields:

| Name                     | Type | Notes                                                                                                                                 |
|--------------------------|------|---------------------------------------------------------------------------------------------------------------------------------------|
| delivery_bank            | Text | The name of the delivery bank, as per the output of getDeliveryBanks.                                                                 |
| destination_country      | Text | Name of country retrieved from calling getDestinationCountries. This will be used if the destination_country_code is not provided.    |
| destination_country_code | Text | Iso code of country retrieved from calling getDestinationCountries. This will be used in priority over the destination_country value. |

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>95</responseId>
  <status>SUCCESS</status>
  <result>
    <collection_points>
      <collection_point>
        <collection_id>3</collection_id>
        <name>Test Collection Point India</name>
        <bank>Test Proc Bank India</bank>
        <delivery_bank>4</delivery_bank>
        <address>23 Collection Road</address>
        <city>City123</city>
        <state>State123</state>
        <country_id>999</country_id>
        <code>1234</code>
        <telephone>+919798798798</telephone>
        <fax></fax>
        <email>test@collectionpoint.com</email>
        <working_hours>6</working_hours>
        <contact_person>John Doe</contact_person>
        <default_in_country>f</default_in_country>
        <enabled>t</enabled>
        <collection_pin_prefix></collection_pin_prefix>
        <rate_markup></rate_markup>
        <third_party_id>01</third_party_id>
        <third_party_name>ThirdPartyName</third_party_name>
        <third_party_code>9876</third_party_code>
      </collection_point>
    </collection_points>
  </result>
</response>
```

## getMobileNetworkOperators

Group : mobileNetworkOperator

Method : getMobileNetworkOperators

Input fields :

| Name         | Type    | Notes                                                                            |
|--------------|---------|----------------------------------------------------------------------------------|
| country_id   | Integer | The id of the Destination Country, as per the output of getDestinationCountries. |
| country_code | Text    | The ISO code of the Destination Country.                                         |

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>42</responseId>
  <status>SUCCESS</status>
  <result>
    <count>1</count>
    <mnos>
      <mno>
        <mobile_network_id>1</mobile_network_id>
        <name>AT&T</name>
        <code>ATT</code>
        <country_id>999</country_id>
        <number_pattern></number_pattern>
        <regex_pattern></regex_pattern>
        <enabled>t</enabled>
      </mno>
    </mnos>
  </result>
</response>
```

## getMobileNetworkCreditTypes

Group : mobileNetworkCreditType

Method : getMobileNetworkCreditTypes

Input fields :

| Name                         | Type   | Notes                                                                                                                                                                                                                                                                              |
|------------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| username                     | Text   | The username given to authenticate                                                                                                                                                                                                                                                 |
| password                     | Text   | The password given for the user                                                                                                                                                                                                                                                    |
| PIN                          | Number | The 5-digits number given to authenticate along with username and password                                                                                                                                                                                                         |
| country_id                   | Number | Optional. The ID of the country where to find credit types in. If it is empty and the destination country is empty, it will search for all the credit types. If the user has type WS_Bank, the country_id will be extracted from the user information, so this field can be empty. |
| dest_country                 | Text   | Optional. The name of the country where to find credit types in. If it is empty and the country_id is empty, it will search for all the credit types. If the user has type WS_Bank, the country_id will be extracted from the user information, so this field can be empty.        |
| country_code                 | Text   | Option. The ISO code of the Destination Country.                                                                                                                                                                                                                                   |
| mobile_network_operator_name | Text   | Optional. The mobile network operator name.                                                                                                                                                                                                                                        |
| enabled                      | Text   | Optional. The enabled field. Supported values are true or false. If you send it empty it will return both the enabled and disabled mobile network credit types.                                                                                                                    |

### Example Output XML :

```

<?xml version="1.0" encoding="utf-8"?>
<response>
  <responseId>121</responseId>
  <status>SUCCESS</status>
  <result>
    <count>1</count>
    <mncts>
      <mnct>
        <credit_type_id>1</credit_type_id>
      </mnct>
    </mncts>
  </result>
</response>

```



```
<mobile_network_id>1</mobile_network_id>
<name>My First MNCT</name>
  <code>MNCTO</code>
  <country_id>999</country_id>
  <type>Open</type>
  <currency>EUR</currency>
  <minimum>12000.00</minimum>
  <maximum>85000.00</maximum>
  <amount>90000.00</amount>
  <enabled>t</enabled>
</mnct>
</mncts>
</result>
</response>
```

---

## Appendix A : Destination Country ISO Codes

| Name                           | ISO code | Currency |
|--------------------------------|----------|----------|
| Afghanistan                    | AF       | AFG      |
| Albania                        | AL       | ALL      |
| Algeria                        | DZ       | DZD      |
| American Samoa                 | AS       |          |
| Andorra                        | AD       | ADP      |
| Angola                         | AO       | AON      |
| Anguilla                       | AI       |          |
| Antarctica                     | AQ       |          |
| Antigua and Barbuda            | AG       |          |
| Argentina                      | AR       | ARS      |
| Armenia                        | AM       | AMD      |
| Aruba                          | AW       | AWG      |
| Australia                      | AU       | AUD      |
| Austria                        | AT       | EUR      |
| Azerbaijan                     | AZ       | AZN      |
| Bahamas                        | BS       | BSD      |
| Bahrain                        | BH       | BHD      |
| Bangladesh                     | BD       | BDT      |
| Barbados                       | BB       | BBD      |
| Belarus                        | BY       | BYR      |
| Belgium                        | BE       | EUR      |
| Belize                         | BZ       | BZD      |
| Benin                          | BJ       |          |
| Bermuda                        | BM       | BMD      |
| Bhutan                         | BT       | BTN      |
| Bolivia                        | BO       | BOB      |
| Bosnia and Herzegovina         | BA       | BAM      |
| Botswana                       | BW       | BWP      |
| Bouvet Island                  | BV       |          |
| Brazil                         | BR       | BRE      |
| British Indian Ocean Territory | IO       |          |
| Brunei Darussalam              | BN       | BND      |
| Bulgaria                       | BG       | BGL      |

|                                       |    |     |
|---------------------------------------|----|-----|
| Burkina Faso                          | BF |     |
| Burundi                               | BI | BIF |
| Cambodia                              | KH | KHR |
| Cameroon                              | CM | XAF |
| Canada                                | CA | CAD |
| Cape Verde                            | CV | CVE |
| Cayman Islands                        | KY | KYD |
| Central African Republic              | CF | XAF |
| Chad                                  | TD | XAF |
| Chile                                 | CL | CLF |
| China                                 | CN | CNY |
| Christmas Island                      | CX |     |
| Cocos (Keeling) Islands               | CC |     |
| Colombia                              | CO | COP |
| Comoros                               | KM |     |
| Congo                                 | CG |     |
| Congo, the Democratic Republic of the | CD |     |
| Cook Islands                          | CK |     |
| Costa Rica                            | CR | CRC |
| Cote D'Ivoire                         | CI |     |
| Croatia                               | HR | HRK |
| Cuba                                  | CU | CUP |
| Cyprus                                | CY | CYP |
| Czech Republic                        | CZ | CZK |
| Denmark                               | DK | DKK |
| Djibouti                              | DJ | DJF |
| Dominica                              | DM |     |
| Dominican Republic                    | DO | DOP |
| Ecuador                               | EC | ECS |
| Egypt                                 | EG | EGP |
| El Salvador                           | SV | SVC |
| Equatorial Guinea                     | GQ |     |
| Eritrea                               | ER |     |
| Estonia                               | EE | EEK |
| Ethiopia                              | ET | ETB |
| Falkland Islands (Malvinas)           | FK |     |
| Faroe Islands                         | FO |     |

|                                   |    |     |
|-----------------------------------|----|-----|
| Fiji                              | FJ | FJD |
| Finland                           | FI | EUR |
| France                            | FR | EUR |
| French Guiana                     | GF |     |
| French Polynesia                  | PF |     |
| French Southern Territories       | TF |     |
| Gabon                             | GA |     |
| Gambia                            | GM | GMD |
| Georgia                           | GE |     |
| Germany                           | DE | EUR |
| Ghana                             | GH | GHC |
| Gibraltar                         | GI | GIP |
| Greece                            | GR | GRD |
| Greenland                         | GL |     |
| Grenada                           | GD |     |
| Guadeloupe                        | GP |     |
| Guam                              | GU |     |
| Guatemala                         | GT | GTQ |
| Guinea                            | GN | GNF |
| Guinea-Bissau                     | GW | GWP |
| Guyana                            | GY | GYD |
| Haiti                             | HT | HTG |
| Heard Island and McDonald Islands | HM |     |
| Holy See (Vatican City State)     | VA |     |
| Honduras                          | HN | HNL |
| Hong Kong                         | HK | HKD |
| Hungary                           | HU | HUF |
| Iceland                           | IS | ISK |
| India                             | IN | INR |
| Indonesia                         | ID | IDR |
| Iran, Islamic Republic of         | IR |     |
| Iraq                              | IQ | IQD |
| Ireland                           | IE | EUR |
| Israel                            | IL | ILS |
| Italy                             | IT | EUR |
| Jamaica                           | JM | JMD |
| Japan                             | JP | JPY |
| Jordan                            | JO | JOD |

|                                            |    |     |
|--------------------------------------------|----|-----|
| Kazakhstan                                 | KZ |     |
| Kenya                                      | KE | KES |
| Kiribati                                   | KI |     |
| Korea, Democratic People's Republic of     | KP |     |
| Korea, Republic of                         | KR |     |
| Kuwait                                     | KW | KWD |
| Kyrgyzstan                                 | KG |     |
| Lao People's Democratic Republic           | LA |     |
| Latvia                                     | LV |     |
| Lebanon                                    | LB | LBP |
| Lesotho                                    | LS | LSL |
| Liberia                                    | LR | LRD |
| Libyan Arab Jamahiriya                     | LY | LYD |
| Liechtenstein                              | LI |     |
| Lithuania                                  | LT |     |
| Luxembourg                                 | LU | EUR |
| Macao                                      | MO |     |
| Macedonia, the Former Yugoslav Republic of | MK |     |
| Madagascar                                 | MG | MGF |
| Malawi                                     | MW | MWK |
| Malaysia                                   | MY | MYR |
| Maldives                                   | MV |     |
| Mali                                       | ML |     |
| Malta                                      | MT | MTL |
| Marshall Islands                           | MH |     |
| Martinique                                 | MQ |     |
| Mauritania                                 | MR | MRO |
| Mauritius                                  | MU | MUR |
| Mayotte                                    | YT |     |
| Mexico                                     | MX | MXP |
| Micronesia, Federated States of            | FM |     |
| Moldova, Republic of                       | MD |     |
| Monaco                                     | MC |     |
| Mongolia                                   | MN | MNT |
| Montserrat                                 | MS |     |
| Morocco                                    | MA | MAD |
| Mozambique                                 | MZ | MZN |

|                                  |    |     |
|----------------------------------|----|-----|
| Myanmar                          | MM |     |
| Namibia                          | NA |     |
| Nauru                            | NR |     |
| Nepal                            | NP | NPR |
| Netherlands                      | NL | EUR |
| Netherlands Antilles             | AN | ANG |
| New Caledonia                    | NC |     |
| New Zealand                      | NZ | NZD |
| Nicaragua                        | NI | NIO |
| Niger                            | NE |     |
| Nigeria                          | NG | NGN |
| Niue                             | NU |     |
| Norfolk Island                   | NF |     |
| Northern Mariana Islands         | MP |     |
| Norway                           | NO | NOK |
| Oman                             | OM | OMR |
| Pakistan                         | PK | PKR |
| Palau                            | PW |     |
| Palestinian Territory, Occupied  | PS |     |
| Panama                           | PA | PAB |
| Papua New Guinea                 | PG | PGK |
| Paraguay                         | PY | PYG |
| Peru                             | PE | PEN |
| Philippines                      | PH | PHP |
| Pitcairn                         | PN |     |
| Poland                           | PL | PLZ |
| Portugal                         | PT | EUR |
| Puerto Rico                      | PR |     |
| Qatar                            | QA | QAR |
| Reunion                          | RE |     |
| Romania                          | RO | ROL |
| Russian Federation               | RU |     |
| Rwanda                           | RW | RWF |
| Saint Helena                     | SH |     |
| Saint Kitts and Nevis            | KN |     |
| Saint Lucia                      | LC |     |
| Saint Pierre and Miquelon        | PM |     |
| Saint Vincent and the Grenadines | VC |     |

|                                              |    |     |
|----------------------------------------------|----|-----|
| Samoa                                        | WS | WST |
| San Marino                                   | SM |     |
| Sao Tome and Principe                        | ST |     |
| Saudi Arabia                                 | SA | SAR |
| Senegal                                      | SN |     |
| Serbia and Montenegro                        | CS |     |
| Seychelles                                   | SC | SCR |
| Sierra Leone                                 | SL | SLL |
| Singapore                                    | SG | SGD |
| Slovakia                                     | SK |     |
| Slovenia                                     | SI |     |
| Solomon Islands                              | SB | SBD |
| Somalia                                      | SO | SOS |
| South Africa                                 | ZA | ZAR |
| South Georgia and the South Sandwich Islands | GS |     |
| Spain                                        | ES | EUR |
| Sri Lanka                                    | LK | LKR |
| Sudan                                        | SD | SDP |
| Suriname                                     | SR |     |
| Svalbard and Jan Mayen                       | SJ |     |
| Swaziland                                    | SZ | SZL |
| Sweden                                       | SE | SEK |
| Switzerland                                  | CH | CHF |
| Syrian Arab Republic                         | SY |     |
| Taiwan, Province of China                    | TW |     |
| Tajikistan                                   | TJ |     |
| Tanzania, United Republic of                 | TZ |     |
| Thailand                                     | TH | THB |
| Timor-Leste                                  | TL |     |
| Togo                                         | TG |     |
| Tokelau                                      | TK |     |
| Tonga                                        | TO | TOP |
| Trinidad and Tobago                          | TT | TTD |
| Tunisia                                      | TN | TND |
| Turkey                                       | TR | TRL |
| Turkmenistan                                 | TM |     |
| Turks and Caicos Islands                     | TC |     |

|                                      |    |     |
|--------------------------------------|----|-----|
| Tuvalu                               | TV |     |
| Uganda                               | UG | UGX |
| Ukraine                              | UA |     |
| United Arab Emirates                 | AE | AED |
| United Kingdom                       | GB | GBP |
| United States                        | US | USD |
| United States Minor Outlying Islands | UM |     |
| Uruguay                              | UY | UYP |
| Uzbekistan                           | UZ |     |
| Vanuatu                              | VU | VUV |
| Venezuela                            | VE | VEB |
| Vietnam                              | VN |     |
| Virgin Islands, British              | VG |     |
| Virgin Islands, U.S.                 | VI |     |
| Wallis and Futuna                    | WF |     |
| Western Sahara                       | EH |     |
| Yemen                                | YE | YER |
| Zambia                               | ZM | ZMK |
| Zimbabwe                             | ZW | ZWD |



## Appendix B : Remitter ID Type Codes

| Code               | Description            |
|--------------------|------------------------|
| Passport           | Passport               |
| Driving_License    | Driving License        |
| National_Insurance | National Insurance No. |
| National_ID        | National ID            |
| Utility_Bill       | Utility Bill           |
| Other              | Other                  |

## Appendix C : Beneficiary ID Type Codes

| Code           | Description      |
|----------------|------------------|
| PASSPORT       | Passport         |
| CHEQUEBOOK     | Cheque Book      |
| DRIVINGLICENSE | Driving License  |
| NATIONALID     | National ID      |
| VOTINGCARD     | Voting Card      |
| OTHER          | Other form of ID |

## Appendix D : Payment Method Codes

| Code | Description |
|------|-------------|
| 1    | Cash        |
| 2    | Cheque      |

|   |               |
|---|---------------|
| 3 | Bank Transfer |
|---|---------------|

Note: These codes may vary - please confirm with your Administrator

## **Appendix E : Service Level (Delivery Speed) Codes**

| Code | Description |
|------|-------------|
| 1    | 5 Days      |
| 2    | Next Day    |
| 3    | Immediate   |

Note: These codes may vary - please confirm with your Administrator

## **Appendix F : Source of Income Codes**

| Code | Description          |
|------|----------------------|
| 1    | Salary               |
| 2    | Business             |
| 3    | Return on Investment |
| 4    | Gift                 |
| 5    | Pension              |

Note: These codes may vary - please confirm with your Administrator

## **Appendix G : Remittance Purpose Codes**

| Code | Description     |
|------|-----------------|
| 1    | Family Support  |
| 2    | Medical Support |

|   |                   |
|---|-------------------|
| 3 | Education Support |
| 4 | Investment        |
| 5 | Charity           |

## Appendix H : Transaction Statuses

| Status            | Description                                                                                                                                                                                                 |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PENDING_CLEARANCE | Transaction has been created in the system but the remitter has not paid for transaction. Awaiting payment before transaction will be ready for processing.                                                 |
| ENTERED           | Transaction awaiting approval by sending agent before processing.                                                                                                                                           |
| AGENT_OK          | Transaction awaiting HQ approval or routing before processing.                                                                                                                                              |
| HQ_READY          | Transaction has been approved by HQ and will be sent to processing bank/agent in the next batch. This only applies if you are using batch processing.                                                       |
| HQ_OK             | Transaction awaiting processing bank/agent approval before ready for processing.                                                                                                                            |
| HQ_OK_PAID        | Transaction awaiting processing bank/agent approval before ready for processing but transaction has been credited to processing bank/agent already. This status only applies in error correction scenarios. |
| SENT_FOR_PAY      | Transaction ready to be paid out by processing bank/agent.                                                                                                                                                  |
| SENT_FOR_DELIVERY | Transaction ready to be paid out by processing bank/agent branch.                                                                                                                                           |
| PROCESSED         | Transaction has been processed.                                                                                                                                                                             |
| ABORTED           | Transaction has been accepted by processing bank/agent but now it has been requested to be cancelled. Awaiting processing bank/agent approval for cancellation or rejection of cancellation request.        |
| ERROR             | Transaction has some problem with it and is going through error correction cycle.                                                                                                                           |
| DELETED           | Transaction has been cancelled.                                                                                                                                                                             |