

CS561: Artificial Intelligence

Neural Networks: Perceptron and Backpropagation


Pushpak Bhattacharyya

CSE Dept.,

IIT Patna

From 02/09/19

AI Perspective (post-web)



Symbolic AI

Connectionist AI is contrasted with Symbolic AI

Symbolic AI - Physical Symbol System Hypothesis

Every intelligent system can be constructed by storing and processing symbols and nothing more is necessary.


Symbolic AI has a bearing on models of computation such as

Turing Machine


Von Neumann Machine

Lambda calculus

Turing Machine & Von Neumann Machine



Turing machine



VonNeumann Machine

Challenges to Symbolic AI

Motivation for challenging Symbolic AI

A large number of computations and information process tasks that living beings are comfortable with, are not performed well by computers!

The Differences

Brain computation in living beings computers

Pattern Recognition

Learning oriented

**Distributed & parallel processing
processing**

Content addressable

TM computation in

Numerical Processing

Programming oriented

Centralized & serial

Location addressable


The human brain




Seat of consciousness and cognition

Perhaps the most complex information processing machine in nature

Higher brain (responsible for higher needs)




Maslow Hierarchy



Neuron - “classical”

- Dendrites
 - Receiving stations of neurons
 - Don't generate action potentials
- Cell body
 - Site at which information received is integrated
- Axon
 - Generate and relay action potential
 - Terminal
 - Relays information to next neuron in the pathway





<http://www.educarer.com/images/brain-nerve-axon.jpg>

Perceptron

The Perceptron Model

A perceptron is a computing element with input lines having associated weights and the cell having a threshold value. The perceptron model is motivated by the biological neuron.





Step function / Threshold function

**y $= 1$ for $\sum w_i x_i \geq \theta$
 $= 0$ otherwise**

Features of Perceptron


- Input output behavior is discontinuous and the derivative does not exist at $\sum w_i x_i = \theta$
- $\sum w_i x_i - \theta$ is the net input denoted as net
- Referred to as a linear threshold element - linearity because of \mathbf{x} appearing with power **1**
- $\mathbf{y} = \mathbf{f}(\mathbf{net})$: Relation between y and net is non-linear

Computation of Boolean functions

AND of 2 inputs

X1	x2	y
0	0	0
0	1	0
1	0	0
1	1	1

The parameter values (weights & thresholds) need to be found.



Computing parameter values

$$w_1 * 0 + w_2 * 0 \leq \theta \rightarrow \theta \geq 0; \text{ since } y=0$$

$$w_1 * 0 + w_2 * 1 \leq \theta \rightarrow w_2 \leq \theta; \text{ since } y=0$$

$$w_1 * 1 + w_2 * 0 \leq \theta \rightarrow w_1 \leq \theta; \text{ since } y=0$$

$$w_1 * 1 + w_2 * 1 > \theta \rightarrow w_1 + w_2 > \theta; \text{ since } y=1$$
$$w_1 = w_2 = 0.5$$

satisfy these inequalities and find parameters to be used for computing AND function.

Other Boolean functions

- **OR can be computed using values of $w1 = w2 = 1$ and $\theta = 0.5$**

- **XOR function gives rise to the following inequalities:**

$$w1 * 0 + w2 * 0 \leq \theta \rightarrow \theta \geq 0$$

$$w1 * 0 + w2 * 1 > \theta \rightarrow w2 > \theta$$

$$w1 * 1 + w2 * 0 > \theta \rightarrow w1 > \theta$$

$$w1 * 1 + w2 * 1 \leq \theta \rightarrow w1 + w2 \leq \theta$$

No set of parameter values satisfy these inequalities.

Threshold functions


n	# Boolean functions (2^{2^n})	#Threshold Functions (2^{n^2})
1	4	4
2	16	14
3	256	128
4	64K	1008

- **Functions computable by perceptrons - threshold functions**
- **#TF becomes negligibly small for larger values of #BF.**
- **For $n=2$, all functions except XOR and XNOR are computable.**

AND of 2 inputs

X1	x2	y
0	0	0
0	1	0
1	0	0
1	1	1

The parameter values (weights & thresholds) need to be found.



Constraints on w1, w2 and θ

$$w1 * 0 + w2 * 0 \leq \theta \rightarrow \theta \geq 0; \text{ since } y=0$$

$$w1 * 0 + w2 * 1 \leq \theta \rightarrow w2 \leq \theta; \text{ since } y=0$$

$$w1 * 1 + w2 * 0 \leq \theta \rightarrow w1 \leq \theta; \text{ since } y=0$$

$$w1 * 1 + w2 * 1 > \theta \rightarrow w1 + w2 > \theta; \text{ since } y=1$$
$$w1 = w2 = 0.5$$

These inequalities are satisfied by ONE particular region

Perceptron training



Perceptron Training Algorithm (PTA)

Preprocessing:

1. The computation law is modified to


$$y = 1 \text{ if } \sum w_i x_i > \theta$$

$$y = 0 \text{ if } \sum w_i x_i < \theta$$



PTA – preprocessing cont...

2. Absorb θ as a weight



3. Negate all the zero-class examples

Example to demonstrate preprocessing

■ **OR perceptron**

1-class $\langle 1, 1 \rangle$, $\langle 1, 0 \rangle$, $\langle 0, 1 \rangle$

0-class $\langle 0, 0 \rangle$

Augmented x vectors:-

1-class $\langle -1, 1, 1 \rangle$, $\langle -1, 1, 0 \rangle$, $\langle -1, 0, 1 \rangle$

0-class $\langle -1, 0, 0 \rangle$

Negate 0-class:- $\langle 1, 0, 0 \rangle$

Example to demonstrate preprocessing cont..

Now the vectors are

	x_0	x_1	x_2
x_1	-1	0	1
x_2	-1	1	0
x_3	-1	1	1
x_4	1	0	0


Perceptron Training Algorithm

1. Start with a random value of w
ex: $\langle 0, 0, 0 \dots \rangle$
2. Test for $w x_i > 0$
If the test succeeds for $i=1, 2, \dots, n$
then return w
3. Modify w , $w_{\text{next}} = w_{\text{prev}} + x_{\text{fail}}$


PTA on NAND

NAND:

X_2	X_1	Y
0	0	1
0	1	1
1	0	1
1	1	0



Converted To



Preprocessing

NAND Augmented:

X_2	X_1	X_0	Y
0	0	-1	1
0	1	-1	1
1	0	-1	1
1	1	-1	0

NAND-0 class Negated

	X_2	X_1	X_0
$V_0:$	0	0	-1
$V_1:$	0	1	-1
$V_2:$	1	0	-1
$V_3:$	-1	-1	1

Vectors for which
 $W = \langle W_2 \ W_1 \ W_0 \rangle$ has to
be found such that
 $W \cdot V_i > 0$

PTA Algo steps

Algorithm:

1. Initialize and Keep adding the failed vectors until $W \cdot V_i > 0$ is true.

$$\text{Step 0: } W = \langle 0, 0, 0 \rangle$$

$$\begin{aligned} W_1 &= \langle 0, 0, 0 \rangle + \langle 0, 0, -1 \rangle \quad \{V_0 \text{ Fails}\} \\ &= \langle 0, 0, -1 \rangle \end{aligned}$$

$$\begin{aligned} W_2 &= \langle 0, 0, -1 \rangle + \langle -1, -1, 1 \rangle \quad \{V_3 \text{ Fails}\} \\ &= \langle -1, -1, 0 \rangle \end{aligned}$$

$$\begin{aligned} W_3 &= \langle -1, -1, 0 \rangle + \langle 0, 0, -1 \rangle \quad \{V_0 \text{ Fails}\} \\ &= \langle -1, -1, -1 \rangle \end{aligned}$$

$$\begin{aligned} W_4 &= \langle -1, -1, -1 \rangle + \langle 0, 1, -1 \rangle \quad \{V_1 \text{ Fails}\} \\ &= \langle -1, 0, -2 \rangle \end{aligned}$$

Trying convergence

$$\begin{aligned} W_5 &= \langle -1, 0, -2 \rangle + \langle -1, -1, 1 \rangle && \{V_3 \text{ Fails}\} \\ &= \langle -2, -1, -1 \rangle \end{aligned}$$

$$\begin{aligned} W_6 &= \langle -2, -1, -1 \rangle + \langle 0, 1, -1 \rangle && \{V_1 \text{ Fails}\} \\ &= \langle -2, 0, -2 \rangle \end{aligned}$$

$$\begin{aligned} W_7 &= \langle -2, 0, -2 \rangle + \langle 1, 0, -1 \rangle && \{V_0 \text{ Fails}\} \\ &= \langle -1, 0, -3 \rangle \end{aligned}$$

$$\begin{aligned} W_8 &= \langle -1, 0, -3 \rangle + \langle -1, -1, 1 \rangle && \{V_3 \text{ Fails}\} \\ &= \langle -2, -1, -2 \rangle \end{aligned}$$

$$\begin{aligned} W_9 &= \langle -2, -1, -2 \rangle + \langle 1, 0, -1 \rangle && \{V_2 \text{ Fails}\} \\ &= \langle -1, -1, -3 \rangle \end{aligned}$$

Trying convergence

$$\begin{aligned} W_{10} &= \langle -1, -1, -3 \rangle + \langle -1, -1, 1 \rangle && \{V_3 \text{ Fails}\} \\ &= \langle -2, -2, -2 \rangle \end{aligned}$$

$$\begin{aligned} W_{11} &= \langle -2, -2, -2 \rangle + \langle 0, 1, -1 \rangle && \{V_1 \text{ Fails}\} \\ &= \langle -2, -1, -3 \rangle \end{aligned}$$

$$\begin{aligned} W_{12} &= \langle -2, -1, -3 \rangle + \langle -1, -1, 1 \rangle && \{V_3 \text{ Fails}\} \\ &= \langle -3, -2, -2 \rangle \end{aligned}$$

$$\begin{aligned} W_{13} &= \langle -3, -2, -2 \rangle + \langle 0, 1, -1 \rangle && \{V_1 \text{ Fails}\} \\ &= \langle -3, -1, -3 \rangle \end{aligned}$$

$$\begin{aligned} W_{14} &= \langle -3, -1, -3 \rangle + \langle 0, 1, -1 \rangle && \{V_2 \text{ Fails}\} \\ &= \langle -2, -1, -4 \rangle \end{aligned}$$

$$\begin{aligned} W15 &= \langle -2, -1, -4 \rangle + \langle -1, -1, 1 \rangle \quad \{\text{V3 Fails}\} \\ &= \langle -3, -2, -3 \rangle \end{aligned}$$

$$\begin{aligned} W16 &= \langle -3, -2, -3 \rangle + \langle 1, 0, -1 \rangle \quad \{\text{V2 Fails}\} \\ &= \langle -2, -2, -4 \rangle \end{aligned}$$

$$\begin{aligned} W17 &= \langle -2, -2, -4 \rangle + \langle -1, -1, 1 \rangle \quad \{\text{V3 Fails}\} \\ &= \langle -3, -3, -3 \rangle \end{aligned}$$

$$\begin{aligned} W18 &= \langle -3, -3, -3 \rangle + \langle 0, 1, -1 \rangle \quad \{\text{V1 Fails}\} \\ &= \langle -3, -2, -4 \rangle \end{aligned}$$

$$W2 = -3, \quad W1 = -2, \quad W0 = \Theta = -4$$

Succeeds for all vectors



PTA convergence

Statement of Convergence of PTA

- Statement:

Whatever be the initial choice of weights and whatever be the vector chosen for testing, PTA converges if the vectors are from a linearly separable function.

Proof of Convergence of PTA

- Suppose w_n is the weight vector at the n^{th} step of the algorithm.
- At the beginning, the weight vector is w_0
- Go from w_i to w_{i+1} when a vector X_j fails the test $w_i X_j > 0$ and update w_i as

$$w_{i+1} = w_i + X_j$$

- Since X_j s form a linearly separable function,

$$\exists w^* \text{ s.t. } w^* X_j > 0 \quad \forall j$$

Proof of Convergence of PTA

(cntd.)

- Consider the expression

$$G(w_n) = \frac{w_n \cdot w^*}{|w_n|}$$

where w_n = weight at nth iteration

- $$G(w_n) = \frac{|w_n| \cdot |w^*| \cdot \cos \theta}{|w_n|}$$

where θ = angle between w_n and w^*

- $$G(w_n) = |w^*| \cdot \cos \theta$$

- $$G(w_n) \leq |w^*| \quad (\text{as } -1 \leq \cos \theta \leq 1)$$

Behavior of Numerator of G

$$\begin{aligned}w_n \cdot w^* &= (w_{n-1} + X_{\text{fail}}^{n-1}) \cdot w^* \\&= w_{n-1} \cdot w^* + X_{\text{fail}}^{n-1} \cdot w^* \\&= (w_{n-2} + X_{\text{fail}}^{n-2}) \cdot w^* + X_{\text{fail}}^{n-1} \cdot w^* \dots \\&= w_0 \cdot w^* + (X_{\text{fail}}^0 + X_{\text{fail}}^1 + \dots + X_{\text{fail}}^{n-1}) \cdot w^*\end{aligned}$$

$w^* \cdot X_{\text{fail}}^i$ is always positive: note carefully

- Suppose $|X_j| \geq \delta$, where δ is the minimum magnitude.
- Num of G $\geq |w_0 \cdot w^*| + n \delta \cdot |w^*|$
- So, numerator of G grows with n.

Behavior of Denominator of G

- $|w_n| = \sqrt{w_n \cdot w_n}$
 $= \sqrt{(w_{n-1} + X_{fail}^{n-1})^2}$
 $= \sqrt{(w_{n-1})^2 + 2 \cdot w_{n-1} \cdot X_{fail}^{n-1} + (X_{fail}^{n-1})^2}$
 $\leq \sqrt{(w_{n-1})^2 + (X_{fail}^{n-1})^2} \quad (\text{as } w_{n-1} \cdot X_{fail}^{n-1} \leq 0)$
 $\leq \sqrt{(w_0)^2 + (X_{fail}^0)^2 + (X_{fail}^1)^2 + \dots + (X_{fail}^{n-1})^2}$
- $|X_j| \leq \rho$ (max magnitude)
- So, Denom $\leq \sqrt{(w_0)^2 + n\rho^2}$

Some Observations


- Numerator of G grows as n
- Denominator of G grows as \sqrt{n}
=> Numerator grows faster than denominator
- If PTA does not terminate, $G(w_n)$ values will become unbounded.

Some Observations contd.

- But, as $|G(w_n)| \leq |w^*|$ which is finite, this is impossible!
- Hence, PTA has to converge.
- Proof is due to Marvin Minsky.

Feedforward Network and Backpropagation

Example - XOR



Gradient Descent Technique


- Let E be the error at the output layer

$$E = \frac{1}{2} \sum_{j=1}^p \sum_{i=1}^n (t_i - o_i)_j^2$$

- t_i = target output; o_i = observed output
- i is the index going over n neurons in the outermost layer
- j is the index going over the p patterns (1 to p)
- Ex: XOR:— $p=4$ and $n=1$


Weights in a FF NN

- w_{mn} is the weight of the connection from the n^{th} neuron to the m^{th} neuron
- E vs \overline{W} surface is a complex surface in the space defined by the weights w_{ij}
- $-\frac{\delta E}{\delta w_{mn}}$ gives the direction in which a movement of the operating point in the w_{mn} co-ordinate space will result in maximum decrease in error



$$\Delta w_{mn} \propto -\frac{\delta E}{\delta w_{mn}}$$

Backpropagation algorithm



- Fully connected feed forward network
- Pure FF network (no jumping of connections over layers)

Gradient Descent Equations

$$\Delta w_{ji} = -\eta \frac{\delta E}{\delta w_{ji}} \quad (\eta = \text{learning rate}, 0 \leq \eta \leq 1)$$

$$\frac{\delta E}{\delta w_{ji}} = \frac{\delta E}{\delta net_j} \times \frac{\delta net_j}{\delta w_{ji}} \quad (net_j = \text{input at the } j^{th} \text{ layer})$$

$$\frac{\delta E}{\delta net_j} = -\delta_j$$

$$\Delta w_{ji} = \eta \delta_j \frac{\delta net_j}{\delta w_{ji}} = \eta \delta_j o_i$$

Backpropagation – for outermost layer


$$\delta j = -\frac{\delta E}{\delta net_j} = -\frac{\delta E}{\delta o_j} \times \frac{\delta o_j}{\delta net_j} \text{ (} net_j = \text{input at the } j^{th} \text{ layer)}$$

$$E = \frac{1}{2} \sum_{p=1}^m (t_p - o_p)^2$$

$$\text{Hence, } \delta j = -(-(t_j - o_j)o_j(1 - o_j))$$

$$\Delta w_{ji} = \eta(t_j - o_j)o_j(1 - o_j)o_i$$

Backpropagation for hidden layers



δ_k is propagated backwards to find value of δ_j

Backpropagation – for hidden layers

$$\Delta w_{ji} = \eta \delta_j o_i$$

$$\delta_j = -\frac{\delta E}{\delta net_j} = -\frac{\delta E}{\delta o_j} \times \frac{\delta o_j}{\delta net_j}$$

$$= -\frac{\delta E}{\delta o_j} \times o_j (1 - o_j)$$

$$= -\sum_{k \in \text{next layer}} \left(\frac{\delta E}{\delta net_k} \times \frac{\delta net_k}{\delta o_j} \right) \times o_j (1 - o_j)$$

$$\text{Hence, } \delta_j = -\sum_{k \in \text{next layer}} (-\delta_k \times w_{kj}) \times o_j (1 - o_j)$$

$$= \sum_{k \in \text{next layer}} (w_{kj} \delta_k) o_j (1 - o_j)$$

General Backpropagation Rule

- General weight updating rule:

$$\Delta w_{ji} = \eta \delta_j o_i$$


- Where

$$\delta_j = (t_j - o_j) o_j (1 - o_j) \quad \text{for outermost layer}$$


$$= \sum_{k \in \text{next layer}} (w_{kj} \delta_k) o_j (1 - o_j) o_i \quad \text{for hidden layers}$$

How does it work?

- Input propagation forward and error propagation backward (e.g. XOR)



Can Linear Neurons Work?



$$h_1 = m_1(w_1x_1 + w_2x_2) + c_1$$

$$h_1 = m_1(w_1x_1 + w_2x_2) + c_1$$

$$\begin{aligned} Out &= (w_5h_1 + w_6h_2) + c_3 \\ &= k_1x_1 + k_2x_2 + k_3 \end{aligned}$$

Note: The whole structure shown in earlier slide is reducible to a single neuron with given behavior

$$Out = k_1x_1 + k_2x_2 + k_3$$

Claim: A neuron with linear I-O behavior can't compute X-OR.

Proof: Considering all possible cases:

[assuming 0.1 and 0.9 as the lower and upper thresholds]

For (0,0), Zero class:

$$m(w_1.0 + w_2.0 - \theta) + c < 0.1$$
$$\Rightarrow c - m.\theta < 0.1$$

For (0,1), One class:

$$m(w_2.1 + w_1.0 - \theta) + c > 0.9$$
$$\Rightarrow m.w_1 - m.\theta + c > 0.9$$

For (1,0), One class: $m.w_1 - m.\theta + c > 0.9$

For (1,1), Zero class: $m.w_1 - m.\theta + c > 0.9$

These equations are inconsistent. Hence X-OR can't be computed.

Observations:

1. A linear neuron can't compute X-OR.
2. A multilayer FFN with linear neurons is collapsible to a single linear neuron, hence **no a additional power due to hidden layer.**
3. Non-linearity is essential for power.