Inter-Process-Communication

Interprocess Communication

- Processes within a system may be ***independent*** or ***cooperating***
- Cooperating process can affect or be affected by other processes, including sharing data
- Reasons for cooperating processes:
  - Information sharing
  - Computation speedup
  - Modularity
  - Convenience
- Cooperating processes need **inter-process communication** (**IPC**)
- Two models of IPC
  - **Shared memory**
  - **Message passing**

Communications Models

(a) Message passing. (b) shared memory.



Shared Memory

- One process will create an area in RAM which the other process can access
- Both processes can access shared memory like a regular working memory
  - Reading/writing is like regular reading/writing
  - Fast
- Limitation : Error prone. Needs synchronization between processes



Producer-Consumer Problem

- Paradigm for cooperating processes, *producer* process produces information that is consumed by a *consumer* process
  - **unbounded-buffer** places no practical limit on the size of the buffer
  - **bounded-buffer** assumes that there is a fixed buffer size

Bounded-Buffer – Shared-Memory Solution

- Shared data

```
#define BUFFER_SIZE 10
typedef struct {
  . . .
} item;

item buffer[BUFFER_SIZE];
int in = 0;
int out = 0;
```

Bounded-Buffer – Producer

```
item next_produced;
while (true) {
        /* produce an item in next produced */
        while (((in + 1) % BUFFER_SIZE) == out)
                ; /* do nothing */
        buffer[in] = next_produced;
        in = (in + 1) % BUFFER_SIZE;
}
```

Bounded Buffer – Consumer

```
item next_consumed;
while (true) {
     while (in == out)
          ; /* do nothing */
     next_consumed = buffer[out];
     out = (out + 1) % BUFFER_SIZE;

     /* consume the item in next
consumed */
}
```

Shared Memory in Linux

int shmget (key, size, flags)

- Create a shared memory segment;
- Returns ID of segment : shmid
- key : unique identifier of the shared memory segment
- size : size of the shared memory (rounded up to the PAGE_SIZE)

int shmat(shmid, addr, flags)

- Attach shmid shared memory to address space of the calling process
- addr : pointer to the shared memory address space

int shmdt(shmid)

- Detach shared memory

server.c

```c
#include <sys/types.h>
#include <sys/ipc.h>
#include <sys/shm.h>
#include <stdio.h>
#include <stdlib.h>

#define SHMSIZE     27 /* Size of shared memory */

main()
{
    char c;
    int shmid;
    key_t key;
    char *shm, *s;

    key = 5678; /* some key to uniquely identifies the shared memory */

    /* Create the segment. */
    if ((shmid = shmget(key, SHMSIZE, IPC_CREAT | 0666)) < 0) {
        perror("shmget");
        exit(1);
    }

    /* Attach the segment to our data space. */
    if ((shm = shmat(shmid, NULL, 0)) == (char *) -1) {
        perror("shmat");
        exit(1);
    }

    /* Now put some things into the shared memory */
    s = shm;
    for (c = 'a'; c <= 'z'; c++)
        *s++ = c;
    *s = 0; /* end with a NULL termination */

    /* Wait until the other process changes the first character
     * to '*' the shared memory */
    while (*shm != '*')
        sleep(1);
    exit(0);
}
```

client.c

```c
#include <sys/types.h>
#include <sys/ipc.h>
#include <sys/shm.h>
#include <stdio.h>
#include <stdlib.h>

#define SHMSIZE     27

main()
{
    int shmid;
    key_t key;
    char *shm, *s;

     /* We need to get the segment named "5678", created by the server
    key = 5678;

    /* Locate the segment. */
    if ((shmid = shmget(key, SHMSIZE, 0666)) < 0) {
        perror("shmget");
        exit(1);
    }

    /* Attach the segment to our data space. */
    if ((shm = shmat(shmid, NULL, 0)) == (char *) -1) {
        perror("shmat");
        exit(1);
    }

    /* read what the server put in the memory. */
    for (s = shm; *s != 0; s++)
        putchar(*s);
    putchar('\n');

    /*
     * Finally, change the first character of the
     * segment to '*', indicating we have read
     * the segment.
     */
    *shm = '*';

    exit(0);
```

Message Passing

Shared memory created in the kernel

System calls such as send and receive used for communication

– Cooperating : each send must have a receive

Advantage : Explicit sharing, less error prone



Message Passing (Cont.)

- Implementation of communication link
  - Physical:
    - Shared memory
    - Hardware bus
    - Network
  - Logical:
    - Direct or indirect
    - Synchronous or asynchronous
    - Automatic or explicit buffering

Direct Communication

- Processes must name each other explicitly:
  - **`send`** (*P, message*) – send a message to process P
  - **`receive`**(*Q, message*) – receive a message from process Q
- Properties of communication link
  - Links are established automatically
  - A link is associated with exactly one pair of communicating processes
  - A pair of processes can have at most one link
  - The link may be unidirectional, but is usually bi-directional

Indirect Communication

- Messages are directed and received from mailboxes (also referred to as ports)
  - Send (A, message) – Send message to mailbox A
  - receive (A, message) – receive message from mailbox A
  - Each mailbox has a unique id

- Properties of communication link
  - Link established only if processes share a common mailbox
  - A link may be associated with many processes
  - Each pair of processes may share several communication links
  - Link may be unidirectional or bi-directional

Indirect Communication

- Mailbox sharing
  - P_1, P_2, and P_3 share mailbox A
  - P_1, sends; P_2 and P_3 receive
  - Who gets the message?
- Solutions
  - Allow a link to be associated with at most two processes
  - Allow only one process at a time to execute a receive operation
  - Allow the system to select arbitrarily the receiver. Sender is notified who the receiver was.

Indirect Communication

- Mailbox may be owned either by process or OS.
- If a mailbox is owned by a process then only that process can receive message through that mailbox and it can allow a set of processes to send message via this mailbox.
- With termination of process such mailbox destroyed
- Mailbox owned by OS remains forever.

Synchronization

- Message passing may be either blocking or non-blocking
- **Blocking** is considered **synchronous**
  - **Blocking send** -- the sender is blocked until the message is received
  - **Blocking receive** -- the receiver is blocked until a message is available
- **Non-blocking** is considered **asynchronous**
  - **Non-blocking send** -- the sender sends the message and continue
  - **Non-blocking receive** -- the receiver does not do busy waiting, it receives
    - A valid message, or
    - Null message
- Different combinations possible

Buffering

- Queue of messages attached to the link.
- implemented in one of three ways
    1. Zero capacity – no messages are queued on a link. Sender must wait for receiver
    2. Bounded capacity – finite length of *n* messages. Sender must wait if link full
    3. Unbounded capacity – infinite length Sender never waits

Pipe

Always between parent and child

Always unidirectional

Accessed by two associated file descriptors:

- fd[0] for reading from pipe
- fd[1] for writing to the pipe



- Ordinary Pipes allow communication in standard producer-consumer style
- Producer writes to one end (the **write-end** of the pipe)
- Consumer reads from the other end (the **read-end** of the pipe)

Created using *pipe()*:

```
int filedes[1];
pipe(filedes);

...

write(filedes[1], buf, count);
read(filedes[0], buf, count);
```



```c
int filedes[2];

pipe(filedes);

child_pid = fork();
if (child_pid == 0) {
    close(filedes[1]);
    /* Child now reads */
} else {
    close(filedes[0]);
    /* Parent now writes */
}
```



Named Pipes

- Named Pipes are more powerful than ordinary pipes
- Communication is bidirectional
- No parent-child relationship is necessary between the communicating processes
- Several processes can use the named pipe for communication
- Provided on both UNIX and Windows systems