

AMPACITY	MVA RATING	COND TEMP	SHEATH TEMP	TOTAL LOSS	STATUS
806 A	46.12 MVA	90.0 degC	70.7 degC	61.009 W/m	Converged

1. Design Data & Input Parameters

Parameter	Formula / Symbol	Value	Unit
Conductor material		Cu	
Conductor size		300	mm²
Conductor type		stranded	
Conductor diameter Dc		20.3	mm
Conductor screen OD Dc_sc		22.0	mm
Max conductor temp theta_max		90	degC
Insulation material		XLPE	
Insulation screen OD Di		40.0	mm
Ins outer screen OD Di_sc		41.7	mm
Insulation thickness t_ins		9.00	mm
Relative permittivity er		2.5000	
Loss tangent tan(delta)		0.001000	
Screen type		Cu_tape	
Screen mean diameter ds		42.5	mm
Screen area As		35.0	mm²
Armour type		none	
Oversheath material		PE	
Cable outer diameter De		49.5	mm
Rated voltage U		33.0	kV
U0 line-to-earth		19.053	kV
Frequency		50	Hz
Bonding		solid	
Formation		trefoil_spaced	
Depth to cable centre L		800	mm
Axial spacing s		100.0	mm
Ambient ground temp theta_a		25	degC
Soil thermal resistivity rho_soil		1.00	K.m/W

2. DC Resistance [IEC 60287-1-1 Cl.2.1.1]

Parameter	Formula / Symbol	Value	Unit
IEC 60228 R0 at 20 degC		6.0100e-05	ohm/m
Temperature coefficient a20		3.9300e-03	1/K
R0 at theta_amb = 25 degC		6.1281e-05	ohm/m
R0 at theta_max = 90 degC		7.6634e-05	ohm/m

3. AC Resistance at theta_max [IEC 60287-1-1 Cl.2.1.2, 2.1.4]

Parameter	Formula / Symbol	Value	Unit
ks strand constant		1.0000	
kp proximity constant		0.8000	
$xs4 = [ks(8\pi i f / R0) \times 10^{-7}]^2$		2.688947	
ys skin effect factor		0.013850	
$xp4 = [kp(8\pi i f / R0) \times 10^{-7}]^2$		1.720926	
yp" intermediate proximity		0.008899	
yp proximity factor		0.001556	
R at theta_max AC = $R0(1+ys+yp)$		7.7814e-05	ohm/m

4. Dielectric Losses [IEC 60287-1-1 Cl.2.2]

Parameter	Formula / Symbol	Value	Unit
Relative permittivity er		2.5000	
Loss tangent tan(delta)		0.001000	
U0 line-to-earth		19.0530	kV
Capacitance C = $er / (18 \ln(Di_sc / Dc_sc)) \times 10^{-9}$		0.217198	nF/m
$\omega = 2 \pi f$		314.1593	rad/s
$Wd = \omega C U0^2 \tan(\delta)$		2.4770e-02	W/m
TB880 GP7		Applied	

5. Screen / Sheath Setup [IEC 60287-1-1 Cl.2.3]

Parameter	Formula / Symbol	Value	Unit
Screen material		Cu	
Screen resistivity rho_s		1.7241e-08	ohm.m
Screen area As		35.00	mm2
Lay factor LFs		1.000000	
Screen Rs0 at 20 degC (with LFs)		4.9260e-04	ohm/m

6. Armour Losses [IEC 60287-1-1 Cl.2.4]

Parameter	Formula / Symbol	Value	Unit
Armour type		None	
lam2		0.000000	

7. Thermal Resistances [IEC 60287-2-1]

Parameter	Formula / Symbol	Value	Unit
rho_ins		3.50	K.m/W
rho_sc semiconducting screen		2.50	K.m/W
rho_tape bedding tape		6.00	K.m/W
T1_cs conductor screen		0.031999	K.m/W
T1_i insulation		0.333020	K.m/W
T1_si insulation screen		0.016561	K.m/W
T1_uwbt bedding tape under wire screen		0.000000	K.m/W
T1_raw = sum of layers		0.381580	K.m/W
T1 correction factor x1.00 (wire coverage check)		0.381580	K.m/W
T2 filler/bedding single-core = 0		0.000000	K.m/W
T3_raw oversheath		0.084931	K.m/W
T3 x1.0 touching trefoil factor		0.084931	K.m/W
u = 2L/De		32.3232	
T4 soil		0.663468	K.m/W
Sum T = T1+T2+T3+T4		1.129980	K.m/W

8. Sheath Losses at Convergence [IEC 60287-1-1 Cl.2.3]

Parameter	Formula / Symbol	Value	Unit
theta_s at convergence		70.6594	degC
Rs at theta_s		5.9067e-04	ohm/m
X sheath reactance		9.7315e-05	ohm/m
lam1' circulating current		0.200596	
lam1" eddy current		0.002891	
lam1 = lam1' + lam1"		0.203486	
lam2 armour		0.000000	

9. Ampacity Calculation [IEC 60287-1-1 Cl.1.4]

Parameter	Formula / Symbol	Value	Unit
Delta_theta = theta_max - theta_amb		65.00	K
Etop numerator		64.976736	
Ebot denominator		9.9779e-05	
I = sqrt(Etop/Ebot) exact		806.9752	A
I rounded TB880 GP2		806	A
MVA = sqrt(3) x U x I		46.125	MVA
Iterations		5	
Convergence		YES	

10. Temperature Profile Through Cable

Parameter	Formula / Symbol	Value	Unit
theta_c conductor target		90.0	degC
theta_c back-calculated		90.0000	degC
theta_s sheath surface		70.6594	degC
theta_j cable outer surface		65.4778	degC
theta_a ambient ground		25.0	degC

11. Loss Budget

Parameter	Formula / Symbol	Value	Unit
Conductor Wc = I ² x R		50.673256	W/m
Sheath Ws = lam1 x Wc		10.311316	W/m
Armour Wa = lam2 x Wc		0.000000	W/m
Dielectric Wd		2.4770e-02	W/m
Total		61.009343	W/m

12. Electrical Parameters

Parameter	Formula / Symbol	Value	Unit
Inductance L		0.309763	uH/m
Reactance X = omega L		97.3148	uOhm/m
Pos-seq resistance R1		93.6482	uOhm/m
Pos-seq impedance Z1		135.0562	uOhm/m
Capacitance C		0.217198	nF/m
Charging current Ic		1.3001	mA/m

Standards: IEC 60287-1-1:2023 | IEC 60287-2-1:2015 | CIGRE TB 880 guidance applied.
GP2: ampacity rounded down. GP6: eddy losses always calculated. GP7: dielectric losses always calculated. GP8: exact T4 formula. T3: 1.6x factor for touching trefoil.
Report generated: 2026-04-29 20:44:24