

# Unit Testing Lab

Our environment could be considered complete. But many people would say that you can't call it complete until unit testing is incorporated.

In this lab, we're going to set up unit tests using jasmine and then we'll allow them to run in Karma.

## Setting up Jasmine

The first step would normally be to create an npm script entry called "test" that runs jasmine. But we already did that when we initialized npm. Let's verify.

1. Edit your package.json file. Look for the "test" entry. If it isn't there, go ahead and add it.

2. Next, install Jasmine with npm

```
npm install --save-dev jasmine
```

3. Open a bash shell and run it to initialize the jasmine environment

```
npm run test init
```

4. Notice that this has created a folder called spec and a config file called jasmine.json. Take a look at this file. See that line where it mentions spec\_files? That means that any file that ends in "spec.js" will be considered a test file and will be run by jasmine. Let's create one!

5. Create a test file in the spec folder called romanNumeralConverter.spec.js. Make it say this:

```
describe('Roman numeral converter', () => {  
  });
```

*describe* is a grouping of tests. You'll put all tests that are related to one another in a describe group.

6. Rerun Jasmine:

```
npm run test
```

7. Look in the bash window. You should see that it saw the group of roman numeral tests but there were no tests/specs to run.

Let's create one!

## Writing a simple test

8. Inside the *describe* grouping, create a test:

```
it('will return 1 given i', () => {  
  let actual = convert('i');  
  expect(actual).toEqual(1);  
});
```

9. One more time, run Jasmine. This time it will fail because the convert() function doesn't exist. But, hey, you have Jasmine running and you have a test! Now let's automate it.

## Making tests part of the build process

It might make sense for us to re-run all unit tests as part of every build and before deploying our site. This will ensure that we have regression testing to protect us from new code breaking existing working code.

10. Open package.json and add find your "build" script entry. Add "npm test" to the end of it.

```
"build": "eslint src --ext .js && webpack && npm run test",
```

11. Run this script and notice that after the compile your tests are also run. Since your tests are currently failing, the build throws. Nice.

## Testing with Karma

We have Jasmine running our tests that do not require a UI. But sometimes problems can crop up when a browser or UI is involved. So let's run our Jasmine tests in every browser we can get our hands on and make sure they're good.

12. Install Karma and any launchers you may need:

```
npm install --save-dev karma karma-chrome-launcher karma-firefox-launcher  
karma-edge-launcher karma-safari-launcher karma-opera-launcher karma-ie-  
launcher karma-phantomjs-launcher
```

Note: You don't have to install all of those launchers, just the ones for the browsers you have and for PhantomJS.

13. Initialize karma's config file by running this:

```
./node_modules/karma/bin/karma init
```

It asks you a series of questions. Read the instructions and questions and answer them. As before, this is merely creating a config file. Here are some suggestions, though:

- Testing framework: jasmine
- RequireJS: no
- Browsers: Choose all you have installed including phantomJS
- Location of test files: "spec/\*[sS]pec.js"
- Watch files? no

14. Take a look at your new karma.conf.js file.

15. Now Karma is ready to run tests but let's make it easy on ourselves before we do. Edit

package.json and add a new script:

```
"ui-test": "karma --singleRun"
```

16. Save and run that script. Once it is finished, look in the console for the error messages. They'll probably be the same error messages you'd have gotten from running through Jasmine, but now we have more options.