ASSIGNMENT 7

Sample Data Insertion

Online Shopping Management System

1. Aim

To insert realistic sample data into all tables while respecting primary-key and foreign-key relationships.

2. Sample data summary

Table	Records	Sample content
Customers	5	Names, unique emails, phones and addresses
Products	5	Electronics, accessories and furniture
Orders	6	Orders linked to existing customers
OrderDetails	8	Products and quantities linked to orders
Payments	6	Payment methods, amounts and statuses

3. SQL INSERT statements

This script matches the sample records already inserted in MySQL Workbench. Execute it only once on an empty database; running it again will cause duplicate email values and duplicate sample rows.

```
USE OnlineShoppingDB;

INSERT INTO Customers (CustomerName, Email, Phone, Address) VALUES
('Arun Prabu', 'arun@example.com', '9876543210', 'Bangalore'),
('Rahul Kumar', 'rahul@example.com', '9876543211', 'Chennai'),
('Priya Sharma', 'priya@example.com', '9876543212', 'Mumbai'),
('Sneha Reddy', 'sneha@example.com', '9876543213', 'Hyderabad'),
('Karthik Raj', 'karthik@example.com', '9876543214', 'Coimbatore');

INSERT INTO Products (ProductName, Category, Price, Stock) VALUES
('Laptop', 'Electronics', 55000.00, 10),
('Smartphone', 'Electronics', 25000.00, 20),
('Headphones', 'Accessories', 1500.00, 30),
('Keyboard', 'Accessories', 800.00, 25),
('Office Chair', 'Furniture', 4500.00, 8);

INSERT INTO Orders (CustomerID, OrderDate, Status) VALUES
(1, '2026-10-01', 'Delivered'),
(2, '2026-10-03', 'Shipped'),
(3, '2026-10-05', 'Pending'),
(1, '2026-10-07', 'Delivered'),
(4, '2026-10-10', 'Cancelled'),
(5, '2026-10-12', 'Delivered');

INSERT INTO OrderDetails (OrderID, ProductID, Quantity, UnitPrice) VALUES
(1, 1, 1, 55000.00),
(1, 3, 2, 1500.00),
(2, 2, 1, 25000.00),
(2, 4, 2, 800.00),
(3, 3, 1, 1500.00),
(4, 5, 1, 4500.00),
(5, 2, 1, 25000.00),
(6, 4, 1, 800.00);
```

```
INSERT INTO Payments (OrderID, PaymentMethod, Amount, PaymentStatus) VALUES
(1, 'UPI', 58000.00, 'Completed'),
(2, 'Credit Card', 26600.00, 'Completed'),
(3, 'UPI', 1500.00, 'Pending'),
(4, 'Debit Card', 4500.00, 'Completed'),
(5, 'UPI', 25000.00, 'Refunded'),
(6, 'Cash on Delivery', 800.00, 'Completed');
```

4. Output

Customers Table

CustomerID	CustomerName	Email	Phone	Address
1	Arun Prabu	arun@example.com	9876543210	Bangalore
2	Rahul Kumar	rahul@example.com	9876543211	Chennai
3	Priya Sharma	priya@example.com	9876543212	Mumbai
4	Sneha Reddy	sneha@example.com	9876543213	Hyderabad
5	Karthik Raj	karthik@example.com	9876543214	Coimbatore
NULL	NULL	NULL	NULL	NULL

Products Table

CustomerID	CustomerName	Email	Phone	Address
1	Arun Prabu	arun@example.com	9876543210	Bangalore
2	Rahul Kumar	rahul@example.com	9876543211	Chennai
3	Priya Sharma	priya@example.com	9876543212	Mumbai
4	Sneha Reddy	sneha@example.com	9876543213	Hyderabad
5	Karthik Raj	karthik@example.com	9876543214	Coimbatore
NULL	NULL	NULL	NULL	NULL

Orders Table

OrderID	CustomerID	OrderDate	Status
1	1	2026-10-01	Delivered
2	2	2026-10-03	Shipped
3	3	2026-10-05	Pending
4	1	2026-10-07	Delive
5	4	2026-10-10	Cancelled
6	5	2026-10-12	Delivered
NULL	NULL	NULL	NULL

Delivered

OrderDetails Table

OrderDetailID	OrderID	ProductID	Quantity	UnitPrice
1	1	1	1	55000.00
2	1	3	2	1500.00
3	2	2	1	25000.00
4	2	4	2	800.00
5	3	3	1	1500.00
6	4	5	1	4500.00
7	5	2	1	25000.00

Payments Table

PaymentID	OrderID	PaymentMethod	Amount	PaymentStatus
1	1	UPI	58000.00	Completed
2	2	Credit Card	26600.00	Completed
3	3	UPI	1500.00	Pending
4	4	Debit Card	4500.00	Completed
5	5	UPI	25000.00	Refunded
6	6	Cash on Delivery	800.00	Completed
NULL	NULL	NULL	NULL	NULL

5. Data integrity notes

Customer emails are unique. Every order refers to an existing customer. Every order-detail row refers to an existing order and product. Every payment refers to an existing order. OrderDetails.UnitPrice records the price at purchase time; Products.Price represents the current catalog price.

6. Evidence for submission

Capture screenshots from MySQL Workbench showing successful INSERT messages, each table's result grid, and the combined row-count query. Add the screenshots if your instructor requires actual execution evidence. The row counts above are expected outputs based on the sample script.

7. Conclusion

The sample data supports the filtering, grouping, aggregate, join, and subquery examples in Assignments 8 and 9.