REC-CIS

GE23131-Programming Using C-2024

Quiz navigation

| 1 | 2 | 3 |

Show one page at a time

Finish review

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Tuesday, 5 November 2024, 10:35 PM
Duration	47 days 18 hours

Question **1**

Correct

Marked out of 3.00

⚑ Flag question

Some data sets specify dates using the year and day of year rather than the year, month, and
sequential day number starting with day 1 on January 1st.

There are two calendars - one for normal years with 365 days, and one for leap years with 366
like 1900, are not leap years unless they are divisible by 400. So, 2000 was a leap year.

To find the day of year number for a standard date, scan down the Jan column to find the day
month column and read the day of year number. Reverse the process to find the standard da

Write a program to print the Day of Year of a given date, month and year.

Sample Input 1

18
6
2020

Sample Output 1

170

Answer: (penalty regime: 0 %)

```c
1  #include<stdio.h>
2  int main()
3  {
4      int day,month,year;
5      scanf("%d %d %d" , &day,&month,&year);
6      int a[12] = {31,59,90 ,120 ,151 , 181 ,212 ,243 ,273 ,304 ,334,365};
7      int ans = a[month-2]+day;
8      if(year%4==0)
9      ans+=1;
10     printf("%d",ans);
11 }
```

	18 6 2020	170	170	

Passed all tests!

Question **2**

Correct

Marked out of 5.00

⚑ Flag question

Suppandi is trying to take part in the local village math quiz. In the first round, he is asked ab
was never any good at math. And also, he is bad at remembering the names of shapes. Instea
shapes.

·   When he says rectangle he is actually referring to a square.

·   When he says square, he is actually referring to a triangle.

·   When he says triangle he is referring to a rectangle.

·   And when he is confused, he just says something random. At this point, all you can do

Help Suppandi by printing the correct answer in an integer.

Input Format

·   Name of shape (always in upper case R à Rectangle, S à Square, T à Triangle)
·   Length of 1 side
·   Length of other side

Note: In case of triangle, you can consider the sides as height and length of base

Output Format

·   Print the area of the shape.

Sample Input 1

T
10
20

Sample Output 1

200

Sample Input 2

S
30
40

Sample Output 2

600

Sample Input 3

10

10

Sample Output 3

100

Sample Input 4

G
8
8

Sample Output 4

0

Sample Input

C
9
10

Sample Output 4

0

Explanation:

· 	First is output of area of rectangle
· 	Then, output of area of triangle
· 	Then output of area square
· 	Finally, something random, so we print 0

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
int main()
{
    int rect,square, triangle;
    char ch;
    int a,b;
    scanf("%c %d %d",&ch, &a, &b);
    rect = a*b;
    square = 0.5*a*b;
    triangle = a*b;
    if(ch == 'T')
    printf("%d",triangle);
    else if(ch == 'S')
    printf("%d",square);
    else if (ch == 'R')
    printf("%d",rect);
    else
    printf("0");

}
```

REC-CIS

T 10 20	200	200	
S 30 40	600	600	
B 2 11	0	0	
R 10 30	300	300	
S 40 50	1000	1000	

Passed all tests!

Question **3**

Correct

Marked out of 7.00

⚑ Flag question

Superman is planning a journey to his home planet. It is very important for him to know whic day week like us. Instead, they follow a 10-day week with the following days: Day Number Na Wednesday 5 Thursday 6 Friday 7 Saturday 8 Kryptonday 9 Coluday 10 Daxamday Here are th with Sunday always. • It has only 296 days. After the 296th day, it goes back to Sunday. You b after n. You have to tell on which day you will arrive when you reach there.

Input format: •

 Contain a number n (0 < n)

Output format: Print the name of the day you are arriving on

Example Input

7

Example Output

 Kryptonday

Example Input

1

Example Output Monday

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
int main()
{
    int day;
    scanf("%d",&day);
    day = day % 296;
    if(day % 10 == 0)
    printf("Sunday");
    else if(day % 10 == 1)
    printf("Monday");
    else if(day % 10 == 2)
    printf("Tuesday");
    else if(day % 10 == 3)
    printf("Wednesday");
    else if(day % 10 == 4)
    printf("Thursday");
    else if (day % 10 == 5)
    printf("Friday");
    else if (day % 10 == 6)
    printf("Sunday");
    else if (day % 10 == 7)
    printf("Kryptonday");
    else if (day % 10 == 8)
    printf("Clouday");
    else if (day % 10 == 9)
    printf("Daxamday");
    else if (day % 10 == 10)
    return 0;
}
```

REC-CIS

| | 7 | Kryptonday | Kryptonday | |
| | 1 | Monday | Monday | |

Passed all tests!