



# Python Guide: Closures

---



## What is a Closure?

A **closure** is a function that **remembers** the variables from its **enclosing scope** — even after the outer function has finished executing.

In simple words:

The **inner function** "remembers" the values passed to the **outer function**.

---



## Closure Example:

```
def outer(msg):
    def inner():
        return f"Message is: {msg}"
    return inner

say_hi = outer("Vanakkam da mapla")
print(say_hi()) # Output: Message is: Vanakkam da mapla
```

---

## What's Happening Here?

Line	Meaning
outer("Vanakkam da mapla")	msg = "Vanakkam da mapla" is set
inner()	Uses msg from outer()
return inner	Returns the inner() function itself (not the result)

`say_hi()`

Executes the returned function, which still "remembers"  
`msg`

⌚ Even though `outer()` has finished, the `inner()` function **still has access** to `msg`.

✓ That's a **Closure**.

---

## ⌚ Real-Life Analogy:

Imagine a **custom voice recorder** app where:

```
recorder = create_recorder("Gowtham says:")
recorder("I am here") # Output: Gowtham says: I am here
recorder("Let's go") # Output: Gowtham says: Let's go
```

That "**Gowtham says:**" is remembered forever — just like how `msg` is remembered in a closure.

---

## ✓ Why Use Closures?

Benefit	Explanation
<b>Remembers outer variables</b>	Even when outer function is gone
<b>Used in HOF Type 2</b>	Return function with context saved
<b>Build reusable logic</b>	Like dynamic SQL builders, custom filters, etc.
<b>Foundation for decorators</b>	All Python decorators rely on closures

---

## ❖ Closure Use Cases:

1. **SQL Query Builders**
  2. **Custom Greeting Generators**
  3. **Event Handlers**
  4. **Decorators (@login\_required)**
  5. **Validation/Plugin Systems**
- 



## Debug Tip: See Closure with `.__closure__`

```
say_hi = outer("Vanakkam da mapa")
print(say_hi.__closure__[0].cell_contents) # Output: Vanakkam da mapa
```

It shows what the closure **remembers**.

---



## Closure Pattern Template

```
def outer(value):
    def inner():
        # uses `value` here
        return ...
    return inner
```

---



## TL;DR:

A **closure** is when a function **returns another function**, and that inner function **remembers the outer function's variables**, even after the outer is done.

Gowtham SB

[www.linkedin.com/in/sbgowtham/](https://www.linkedin.com/in/sbgowtham/)

Instagram - @dataengineeringtamil

## **About the Author**

**Gowtham SB** is a **Data Engineering expert, educator, and content creator** with a passion for **big data technologies, as well as cloud and Gen AI**. With years of experience in the field, he has worked extensively with **cloud platforms, distributed systems, and data pipelines**, helping professionals and aspiring engineers master the art of data engineering.

Beyond his technical expertise, Gowtham is a **renowned mentor and speaker**, sharing his insights through engaging content on **YouTube and LinkedIn**. He has built one of the **largest Tamil Data Engineering communities**, guiding thousands of learners to excel in their careers.

Through his deep industry knowledge and hands-on approach, Gowtham continues to **bridge the gap between learning and real-world implementation**, empowering individuals to build **scalable, high-performance data solutions**.

## **Socials**

 **YouTube** - <https://www.youtube.com/@dataengineeringvideos>

 **Instagram** - <https://instagram.com/dataengineeringtamil>

 **Instagram** - <https://instagram.com/thedatatech.in>

 **Connect for 1:1** - <https://topmate.io/dataengineering/>

 **LinkedIn** - <https://www.linkedin.com/in/sbgowtham/>

 **Website** - <https://codewithgowtham.blogspot.com>

 **GitHub** - <http://github.com/Gowthamdataengineer>

 **WhatsApp** - <https://lnkd.in/g5JrHw8q>

Gowtham SB

[www.linkedin.com/in/sbgowtham/](https://www.linkedin.com/in/sbgowtham/)

Instagram - @dataengineeringtamil

✉ Email - [atozknowledge.com@gmail.com](mailto:atozknowledge.com@gmail.com)

🌐 All My Socials - <https://lnkd.in/gf8k3aCH>