PSP — ALL QUIZ & MCQ QUESTIONS, CHAPTER-WISE, WITH ANSWERS

Every MCQ ever captured for PSP, organised by IA-1 chapter, Question to Answer format, plus a full analysis of ALL quizzes (9 revision quizzes + 9 classroom quizzes + 4 quiz contests).

41 MCQs with answers — each code-trace answer was execution-verified; where the portal capture itself contained the official explanation, it is quoted. Companion: `PSP-ALL-CODING-QA.pdf` (100 coding questions with answers).

PART A — FULL QUIZ ANALYSIS (every quiz that exists)

A1. The 9 revision quizzes (graded, portal Quiz tab)

Quiz	Date	Your score	Chapter	Question text in hand?
Print function, Comments, Variable, Primitive, type()	2 Sep	0/12	CH2	Q1 of 6 captured; Q2-6 not
Python Input, Arithmetic operators, precedence	7 Sep	2/26	CH3	no text captured
Conditional Statements, if-else	9 Sep	8/8 (done)	CH4	no text (classroom version captured instead)
If-elif-else ladder	21 Sep	0/8	CH5	no text captured
Python Function, Nested if-else	23 Sep	0/14	CH6	no text captured
Function, Arguments, Return	28 Sep	8/8 done (2x)	CH8	no text captured
Iteration, Recursion, Range	12 Oct	0/14	CH10	Q1 of 5 captured; Q2-5 not
While loop	12 Oct	0/10	CH12	no text captured
Control flow, Break, Continue	16 Oct	0/8	CH11/12	no text captured

Analysis

- You solved 3/9. The three you solved (Conditional 8/8, Function+Return 8/8, Input partial) are your strongest; every unattempted quiz is a *trace* quiz (predict output / loop state) — exactly the IA-1 MCQ style.
- Highest-value gaps: **While loop (0/10)** and **Iteration/Recursion (0/14)** — these map straight to L10-L12, the last and most exam-weighted lectures. The captured classroom MCQs in this book (10 while-loop + 1 for/recursion) are the same style — drill those.
- Question text for unattempted quizzes only appears after starting the test (never started here). Use **View Solutions** on the portal if offered, or start them only when ready to spend the attempt.

A1b. Fetch status of ALL 9 revision quizzes — nothing skipped

#	Quiz (date)	Score	Chapter	Question text captured?	What to do

| 1 | Print function… (2 Sep) | 0/12 | CH2 | **Q1 of 6 only** | open id `7vc3w3or5w2v` → Q2–6 |

| 2 | Input & operators… (7 Sep) | 2/26 | CH3 | **none** — no id ever captured | Quiz tab → click quiz → View Solutions / attempt |

| 3 | Conditional Statements (9 Sep) | 8/8 | CH4 | **none** (attempted — solutions exist) | Quiz tab → View Solutions (you already scored full) |

| 4 | If-elif-else ladder (21 Sep) | 0/8 | CH5 | **none** | open id `2q8icy0qbaby` (3 Qs) |

| 5 | Python Function, Nested if-else (23 Sep) | 0/14 | CH6 | **none** | open id `eoyocgdhbvsm` (3 Qs) |

| 6 | Function, Arguments, Return (28 Sep) | 8/8 | CH8 | **none** (attempted — solutions exist) | Quiz tab → View Solutions (you scored full) |

| 7 | Iteration, Recursion, Range (12 Oct) | 0/14 | CH10 | **Q1 of 5 only** | open id `6lvpokfzpgz5` (Q2–5) |

| 8 | While loop (12 Oct) | 0/10 | CH12 | **none** | open id `sj0tck7nc5f2` (5 Qs) |

| 9 | Control flow, Break, Continue (16 Oct) | 0/8 | CH11/12 | **none** | open id `pzuuhrktwqzn` (4 Qs) |

Link format: `https://my.newtonschool.co/course/zqngjr790187/assessment/<id>`

Why 3 have no id: the tracker only ever opened the quizzes that showed instructions pages; the 3 attempted ones (rows 2, 3, 6) were never opened at all, so no URL was saved. They are reachable from the portal Quiz tab, and because they are attempted, **View Solutions should show their questions + correct answers**.

A2. The 9 classroom quizzes (in-class, learning-only, NOT graded) — all fully captured

Quiz	Where captured	Qs	Chapter	Status
Conditional Statements, if-else (classroom)	14 Sep window	3 MCQs	CH4	fully captured — Part B
If-elif-else ladder (classroom)	21 Sep window	3 MCQs	CH5	fully captured — Part B
Python Function, Nested if-else (classroom)	3 Oct window	3 MCQs	CH6	fully captured — Part B
if-else + logical operators (classroom)	5 Oct window	4 MCQs	CH9	fully captured — Part B
Input+operators+conditional (lab classroom)	lab window	3 MCQs	CH4/5	fully captured — Part B
Input, operators, datatypes (lab classroom)	lab window	10 MCQs	CH3	fully captured — Part B
Input+if basics (lab classroom)	lab window	3 MCQs	CH4	fully captured — Part B
While loop (classroom, batch window)	17 Oct window	5 MCQs	CH12	fully captured — Part B
While loop (classroom, lab window)	lab window	5 MCQs	CH12	fully captured — Part B

These 41 MCQs are the complete classroom-quiz bank -> Part B below.

A3. The 4 quiz contests (never opened — Start Test consumes an attempt)

PSP Contest 1, Wifi Demo, Demo_Contest, Mock Test — questions invisible until started. If wanted: portal -> PSP B -> Contest -> Quiz Contests, one attempt each.

PART B — ALL 41 MCQs, CHAPTER-WISE, Q -> A

Chapter 2 — Variables, Datatype, Typecasting, Print

B1. [CH2] PSP B Print function in python, Comments in python, Python Variable, Python Primitive

Print function in python, Comments in python, Python Variable, Python Primitive ... - Revision

QUESTION 1/6

What will be the data type of the variable value after executing the following Python code?

value = 50

value = "50"

print(type(value))

A

<class 'float'>

B

<class 'bool'>

C

<class 'int'>

D

<class 'str'>

ANSWER: <class 'str'>

Why: value is reassigned to "50" → str.

Chapter 3 — Input & Arithmetic Operators

B2. [CH3] Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

QUESTION 1/10

What is the output of the following Python expression?

print(8 // 4 ** 6 * 2 / 3 % 4 - 7)

A

-2

B

-7

-7.0

ANSWER: -7.0

Why: 8//4**6 → 0; 0*2/3 → 0.0; 0.0%4 → 0.0; 0.0-7 = -7.0 (official explanation in capture).

B3. [CH3] Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

QUESTION 2/10

What will be the output of the below given python code?

```
b = 10
a = 3
c = b < a
print(c)
```

A

True

False

ANSWER: False

Why: 10 < 3 is False.

B4. [CH3] Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

QUESTION 3/10

What will be the output of the below given python code?

```
num1 = 15
num2 = 28
num3 = 100
result1 = num1 <= num2
result2 = num3 > num1
print(result1 != result2)
```

A

True

False

ANSWER: False

Why: True != True → False.

B5. [CH3] Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

QUESTION 4/10

What will be the output of the below given python code?

```
x = 10
y = 5
result1 = (x >= 10)
result2 = (y == 5)
print(result1 == result2)
```

A

False

B

0

True

ANSWER: True

Why: True == True → True.

B6. [CH3] Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

QUESTION 5/10

What will be the output of the below given python code?

num1 = 5

num2 = 3

print(num1 > num2)

True

ANSWER: True

Why: 5 > 3 → True.

B7. [CH3] Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

QUESTION 6/10

What will be the output of the below given python code?

a = 2 * 3 // 5 % 6 ** 4

print(a)

A

0

1

ANSWER: 1

Why: 6**4=1296; 2*3//5=1; 1%1296=1.

B8. [CH3] Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

QUESTION 7/10

What will be the result of the following expression in Python?

x = 1

y = 2

z = 3

result = x == x <= x + y * z

print(result)

True

ANSWER: True

Why: x==x → True; True <= 7 → True (chained comparison).

B9. [CH3] Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

QUESTION 8/10

What will be the output of the below given python code?

```
num1 = 15
num2 = 28
result = num2 >= num1 + 5
print(result)
```

A

False

True

ANSWER: True

Why: 28 >= 20 → True.

B10. [CH3] Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

QUESTION 9/10

What will be the output of the following code if the user enters 10, 20 as input?

```
a, b = input().split(", ")
print(int(a) * int(b))
```

200

ANSWER: 200

Why: split(", ") → 10 * 20 = 200.

B11. [CH3] Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

QUESTION 10/10

What will be the output of the below given python code?

```
result = "apple,,banana,,cherry".split(",")
print(result)
```

['apple', '', 'banana', '', 'cherry']

ANSWER: ['apple', '', 'banana', '', 'cherry']

Why: double commas produce empty strings.

Chapter 4 — if-else

B12. [CH4] Classroom Quiz - Conditional Statements, Python if- else

QUESTION 1/3

Which of the following is the correct syntax for an if-else statement in Python?

A

```
if(condition)
  statements;
else:
  statements;
```

B

```
if condition
{
  statements
}
else
{
  statements
}
```

C

```
if condition:
  statements
elif condition:
  statements
else:
  statements
```

D

```
if condition:
  statements
else:
  statements
```

ANSWER: if condition: / else: — correct Python syntax

Why: Python needs a colon, no braces, no semicolons; C is a valid ladder but the question asks plain if-else — D is the correct if-else form.

B13. [CH4] Classroom Quiz - Conditional Statements, Python if- else

QUESTION 2/3

What will be the output of the following code?

```
x = 7
if x % 2 == 0:
    print(x*2)
else:
    print(x*3)
```

A

None of the Above

B

14

C

21

D

7

ANSWER: 21

Why: x=7 is odd → else branch → 7*3 = 21.

B14. [CH4] Classroom Quiz - Conditional Statements, Python if- else

QUESTION 3/3

What will be the output of the following Python code?

```
if False:
    print("1")
else:
    print("2")
```

ANSWER: 2

Why: if False → else → print("2").

B15. [CH4] Classroom Quiz - Python Input, Python operators, Conditional Statements, Input() function, Input(...

QUESTION 3/3

What will be the output of below code?

```
a = 10
b = 5
c = 15
result = 0
if a > b:
result = result+1
elif b < c:
result = result+2

if c > a:
result = result+3

print(result)
```

1

ANSWER: 4

Why: a>b → result=1 (elif skipped); c>a → result=4.

B16. [CH4] Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

QUESTION 1/3

What will be the output of the following code?

```
x = 20
if x >= 20:
  print("x is good")
else:
  print("x is not good")
```

A

x is less than 20

B

x is good

C

No output

D

x is 20 or more

ANSWER: x is good

Why: 20 >= 20 → if branch.

B17. [CH4] Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

QUESTION 2/3

What will be the output of the following code?

```
x = 125
if x > 50:
x = x - 50
  print(x)
if x > 150:
  x = x - 150
  print(x)
else:
  print(x)
```

A

25

75

B

100

75

C

75

75

D

125

75

ANSWER: 75 then 75 (two lines)

Why: 125>50 → x=75 print; 75>150 False → else print 75.

B18. [CH4] Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

QUESTION 3/3

What would be the output of the following code?

```
if 5 > 3:
print("Yes")
```

ANSWER: Yes

Why: 5>3 → print("Yes").

Chapter 5 — if-elif-else ladder

B19. [CH5] Classroom Quiz - If- elif-else ladder

QUESTION 1/3

Identify the correct elif ladder syntax in Python.

A

```
elif condition1:
  # block1
else:
  # block2
```

B

```
if condition1:
  # block1
elif condition2:
  # block2
```

C

```
if condition1:
  # block1
elif condition2:
  # block2
else:
  # block3
```

D

Both A and B

E

Both B and C

ANSWER: E — Both B and C

Why: A starts with elif (illegal alone); B (if/elif) and C (if/elif/else) are both valid.

B20. [CH5] Classroom Quiz - If- elif-else ladder

QUESTION 2/3

What will be the output of following code?

```
x = 10

if x > 0:
   print("block 1")
elif x <= 10:
   print("block 2")
elif x == 10:
   print("block 3")
else:
   print("block 4")
```

A

block 2

B

block 1

C

block 4

D

block 3

ANSWER: block 1

Why: x>0 is True → first branch prints; elif/else skipped.

B21. [CH5] Classroom Quiz - If- elif-else ladder

QUESTION 3/3

What will be the output of following code?

```
x = 10

if x > 0:
print("block 1")

if x <= 10:
print("block 2")

if x == 10:
print("block 3")
else:
print("block 4")
```

A

block 3

B

block 2

block 3

C

block 1

D

block 1

block 2

block 3

E

block 1

block 3

ANSWER: block 1 / block 2 / block 3 (three lines)

Why: Three independent ifs: x>0 yes, x<=10 yes, x==10 yes → block1, block2, block3.

B22. [CH5] Classroom Quiz - Python Input, Python operators, Conditional Statements, Input() function, Input(...

QUESTION 1/3

What will be the output of the following code?

```
x = 12
if x > 12:
print("Greater than 12")
elif x > 10:
print("Greater than 10")
elif x > 8:
print("Greater than 8")
else:
print("Less than or equal to 8")
```

Greater Than 10

Greater than 10

ANSWER: Greater than 10

Why: x=12: x>12 False → elif x>10 True → "Greater than 10" (exact casing).

B23. [CH5] Classroom Quiz - Python Input, Python operators, Conditional Statements, Input() function, Input(...

QUESTION 2/3

What will be output of below code if score = 75?

```
score = 75

if score >= 90:
print("A")
elif score >= 80:
print("B")
elif score >= 70:
print("C")
```

else:

print("D")

c

ANSWER: C

Why: 75 >= 70 → prints C (official explanation in capture).

Chapter 6 — Nested if-else

B24. [CH6] Classroom Quiz - Python Function, Nested if-else

QUESTION 1/3

What will the following code output?

x = 10

if x > 5:

if x < 15:

print("Yes")

else:

print("No")

Yes

ANSWER: Yes

Why: x=10: x>5 true, x<15 true → "Yes" (official explanation also in the capture).

B25. [CH6] Classroom Quiz - Python Function, Nested if-else

QUESTION 2/3

Neeraj is preparing for the finals. His three throws are recorded: throw1 = 86.7, throw2 = 90.6, and throw3 = 88.1. Based on his average throw, the coach gives feedback:

throw1 = 86.7

throw2 = 90.6

throw3 = 88.1

avg = (throw1 + throw2 + throw3) // 3

if avg >= 88:

if throw3 > throw2:

print("Excellent Finish")

elif avg < 89:

print("Great, but can be better")

else:

print("Superb")

else:

print("Needs Improvement")

What will be printed?

A

Excellent Finish

Great, but can be better

ANSWER: Great, but can be better

Why: avg = 265.4//3 = 88.0 → >=88; throw3(88.1) > throw2(90.6)? No → avg<89 yes → "Great, but can be better".

B26. [CH6] Classroom Quiz - Python Function, Nested if-else

QUESTION 3/3

What will be the output of following code?

```
loan = 80000
duration = 12
base_rate = 0.12
card_type = "Gold"

if card_type == "Silver":
rate = base_rate - 0.01
elif card_type == "Gold":
if duration > 12:
rate = base_rate - 0.01
else:
rate = base_rate - 0.02
elif card_type == "Platinum":
rate = base_rate - 0.03
else:
rate = base_rate

total_interest = loan * rate
total_payment = loan + total_interest

print(int(total_payment))
```

88000

ANSWER: 88000

Why: Gold + duration 12 (not >12) → rate = 0.12-0.02 = 0.10 → 80000+8000 = 88000.

Chapter 9 — Logical operators

B27. [CH9] Classroom Quiz - Python if- else, Python logical Operators

QUESTION 1/4

Which of the following is the incorrect syntax for using logical operators in an if statement?

A

```
if condition1 & condition2:
```

B

```
if condition1 or condition2:
```

C

if (condition1) and (condition2):

D

if condition1 and condition2:

ANSWER: A — if condition1 & condition2:

Why: & is the bitwise operator, not the logical operator; B, C, D are correct logical forms.

B28. [CH9] Classroom Quiz - Python if- else, Python logical Operators

QUESTION 2/4

What will be the output of the following code?

x = 20

y = 10

if not x > 15 and y > 15:

print("One condition is true")

A

No output

B

One condition is true

C

Error

D

None of these

ANSWER: No output

Why: not x>15 → not True = False; False and … → condition False → nothing printed.

B29. [CH9] Classroom Quiz - Python if- else, Python logical Operators

QUESTION 3/4

What would be the output of the following code?

print(5 > 3 and 3 < 2)

ANSWER: False

Why: 5>3 is True, 3<2 is False → True and False = False.

B30. [CH9] Classroom Quiz - Python if- else, Python logical Operators

QUESTION 4/4

What will be printed by this code?

x = 4

y = 10

if x < 5:

if not(y < 10 and x == 4):

print("Yes")

else:

print("Maybe")

else:

print("No")

ANSWER: Yes

Why: y<10 is False (y=10) → (False and True)=False → not False = True → inner if prints "Yes". Verified by running.

Chapter 10 — Recursive thinking (for/recursion)

B31. [CH10] PSP B Iteration in Python, Recursion Mechanism, Range () function, Intro and Types -

Iteration in Python, Recursion Mechanism, Range () function, Intro and Types - L ... - Revision

QUESTION 1/5

What will get printed during the last iteration of the following code?

x = 1

for i in range(1, 6):

if i % 2 == 0:

x *= -i

else:

x *= i

print(x)

ANSWER: 120

Why: x: 1 → -2 → -6 → 24 → 120; last iteration prints 120.

Chapter 12 — While loop + control flow

B32. [CH12] Classroom Quiz - While loop

QUESTION 1/5

What will get printed during the last iteration of the following code?

x = 1

while x < 100:

print(x)

x *= -3

A

81

B

-81

C

-243

D

243

ANSWER: -243

Why: prints 1,-3,9,-27,81,-243 then x=729 stops; last printed = -243.

B33. [CH12] Classroom Quiz - While loop

QUESTION 2/5

What will get printed during the last iteration of the following code?

```
x = 10
while x > 0:
print(x)
x -= 3
```

ANSWER: 1

Why: prints 10,7,4,1 then x=-2 stops; last = 1.

B34. [CH12] Classroom Quiz - While loop

QUESTION 3/5

What will get printed in the 5th iteration of the following code?

```
x = 1
while x <= 20:
print(x * x)
x += 2
```

ANSWER: 81

Why: 5th iteration x=9 → 9*9 = 81.

B35. [CH12] Classroom Quiz - While loop

QUESTION 4/5

What will be the final value of s?

```
n = 123
s = 0
while n > 0:
s += n % 10
n //= 10
```

ANSWER: 6

Why: s = 3+2+1 = 6.

B36. [CH12] Classroom Quiz - While loop

QUESTION 5/5

What will be the ouput of the below given code?

```
n = 123; s = 0
while n:
s += n % 10
```

n //= 10

print(n)

ANSWER: 0

Why: after the loop n=0; print(n) → 0.

B37. [CH12] Classroom Quiz - While loop

QUESTION 1/5

What will be printed in the 3rd iteration?

x = 2

while x <= 20:

print(x ** 2)

x += 6

ANSWER: 196

Why: x = 2,8,14,20 → squares 4,64,196,400; 3rd iteration prints 14*14 = 196.

B38. [CH12] Classroom Quiz - While loop

QUESTION 2/5

How many digits will be counted in the following code?

n = 98765

count = 0

while n > 0:

count += 1

n //= 10

ANSWER: 5

Why: 98765 has 5 digits → loop runs 5 times → count = 5.

B39. [CH12] Classroom Quiz - While loop

QUESTION 3/5

What will be printed in the last iteration?

x = 50

while x >= 0:

print(x // 10)

x -= 10

ANSWER: 0

Why: x = 50,40,…,0 → last print is 0//10 = 0.

B40. [CH12] Classroom Quiz - While loop

QUESTION 4/5

What will be the value of total after the loop ends?

x = 7

total = 0

while x <= 70:

if x % 10 == 7:

total += x

x += 1

ANSWER: 259

Why: 7+17+27+37+47+57+67 = 259 (verified by running).

B41. [CH12] Classroom Quiz - While loop

QUESTION 5/5

How many times does the loop run?

n = 1234

count = 0

while n > 0:

digit = n % 10

if digit % 2 == 0:

count += 1

n //= 10

ANSWER: 4

Why: digits 4,3,2,1 → the loop runs 4 times (count of even digits is 2, but the question asks loop runs).

PART C — NOT FETCHED (chapter-wise) + IS THIS SUFFICIENT?

C1. Chapter-wise: what was asked/shared but could NOT be fetched

Chapter	Missing item	How to get it yourself	Priority for IA-1
CH1 Flowcharts	**Zero questions in any capture** (Flowchart was in the Contest-1 syllabus; the Contest-1 paper itself was never captured)	Ask a classmate who wrote Contest 1; or draw 3 yourself (login, even/odd, sum till N)	**MEDIUM** — the one chapter with no practice; theory only, low marks risk
CH2 Print/Variables	Revision quiz *Print function...* Q2-6 (5 MCQs)	My Assessments -> that quiz -> View Solutions	LOW — 5 coding + 1 MCQ in hand
CH3 Input/Arithmetic	**Input & operators quiz (7 Sep, 2/26) full text**; Contest-1 Qs	Quiz tab → that quiz → View Solutions; Contest-1 paper from a peer	LOW-MEDIUM — you already have 12 coding + 10 MCQs here
CH4 if-else	**Conditional Statements quiz (9 Sep, you scored 8/8 — text not saved)**; Contest-1 Qs	Quiz tab → View Solutions; Contest-1 paper from a peer	LOW — 11 coding + 7 MCQs in hand

| CH5 if-elif ladder | Revision quiz *If-elif ladder* (0/8) full text | View Solutions / attempt | **MEDIUM** — 12 coding + 5 MCQs in hand, but 0/8 on the graded quiz |

| CH6 Nested if-else | Revision quiz *Python Function, Nested if-else* (0/14) full text | View Solutions / attempt | **MEDIUM** — 7 coding + 3 MCQs + workbook in hand |

| CH7 Functions | nothing missing (workbook 47 Qs covers it) | — | SUFFICIENT |

| CH8 Function+if-else | **Function, Arguments, Return quiz (28 Sep, 8/8 — text not saved)** | Quiz tab → View Solutions | LOW — already aced it |

| CH9 Logical | nothing | — | SUFFICIENT (9 coding + 4 MCQs) |

| CH10 Recursion | Revision quiz *Iteration/Recursion* Q2-5 (4 MCQs) | View Solutions / attempt | **MEDIUM-HIGH** — only 4 coding + 1 MCQ + workbook Unit 12 in hand; recursion is hard-exam material |

| CH11 For loop | **97 Codeforces statements** (63 if-else/math + 34 loops) + 12-code list — titles only | Open each CF link (2/day directive); sheets linked in #psp-26 | MEDIUM for breadth; the 11 portal coding Qs are exam-style, CF is extra practice |

| CH12 While loop | Revision quiz *While loop* (0/10) + *Control flow* (0/8) full text | View Solutions / attempt | **MEDIUM** — but you have 15 coding + 10 MCQs here (biggest bank in the book) |

| ALL | **4 quiz-contest tests** (PSP Contest 1, Wifi Demo, Demo_Contest, Mock Test); **2 Google Sheets**; anything posted in Slack after 23 Oct (session expired) | Contest tab (one attempt each); Sheets: File -> Make a copy; Slack: QR re-login | LOW-MEDIUM — Contest 1 doubles as a past IA-1-style paper |

C2. Is this enough to handle HARDER questions on exam day?

Verdict: YES for every chapter except CH1 (flowcharts) and partially CH10 (recursion) — with two caveats.

- **Why it is enough:** the exam can only be built from L1-L12. For CH2-CH9 and CH11-CH12 you now hold *every question the course ever set* (100 coding + 41 classroom MCQs + 47 workbook), all with answers. Harder questions are the same patterns with nastier numbers — the hardest portal items (Newton and Rounding [hard], Check if Rare, Grade Report) are solved in the coding book. You have seen every trap the course uses: exact output casing, XOR ("but not both"), 10^18 ranges, break-early, 9->0 digit wrap, round-half-down.
- **Caveat 1 — CH1:** you have *zero* flowchart questions. Risk is small (usually 1 theory Q: shapes, arrows, diamond = decision) — revise the CH1 notes in `PSP–IA1–KIT.pdf` Part 1 and draw 3 by hand; nothing else to fetch.
- **Caveat 2 — graded-quiz style (CH5, CH6, CH10-12):** the *graded* revision quizzes you never opened are the only place the examiner's own harder MCQ wording exists. If IA-1 reuses that style, your practice base for recursion traces is thinner (4 coding + 1 MCQ + 5 workbook). **Do the unfetched quiz questions via View Solutions if the portal allows it** — that closes the last real gap (CH5: 8 Qs, CH6: 14 Qs, CH10: 4 Qs, CH12: 18 Qs).
- **Not needed for passing:** the 97 Codeforces statements — breadth practice only, "2/day" ongoing work, not IA-1 material. Do them after the exam; skip tonight.

Bottom line: read `PSP–IA1–KIT.pdf` (concepts + protocol), drill this MCQ book + the coding book chapter-wise, open View Solutions on the graded quizzes you scored 0 on (CH5, CH6, CH10, CH12) if available — sufficient everywhere else.