EVERY PSP question (portal, till now)

Generated: 2026-10-23T12:59:09 by `scrape.py --export PSP`

For the AI tutor: teach these in due-date order. Status and XP are the student's real portal state. Question text is included in a code block wherever the tracker captured it; questions without text are listed at the end.

Print function in python, Comments in python, Python Variable, Python Primitive ... [Post Class] — due 2026-09-08 21:00

Print Mirror Right Angle Triangle — 10/20 XP — SOLVED — deadline 2026-09-08 21:00

Topics: Print function in python

URL: https://my.newtonschool.co/playground/code/sc5dsftdd5ak

Back

Print Mirror Right Angle Triangle

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Print Mirror Right Angle Triangle

Easy

10/20

Time Limit: 2, Memory Limit: 256000

Write a Python program to print the mirror image of a right-angled triangle using asterisks (*). The triangle should have 5 rows. Each row should:

Contain stars in increasing order (1 in the first row, 2 in the second, and so on)

Include spaces on the left side so that the stars are right-aligned.

See the example below for clarity.

Input

You do not need to take any input.

Output

Print the mirror right-angled triangle as shown in the example.

Example

Output

```
    *
    *

   **
   **

  ***
  ***
```

```
 ****
 ****


*****
*****
```

Print Inverted Triangle — 10/20 XP — SOLVED — deadline 2026-09-08 21:00

Topics: Print function in python

URL: https://my.newtonschool.co/playground/code/yby7ujad18f7

Back

Print Inverted Triangle

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Print Inverted Triangle

Easy

10/20

Time Limit: 2, Memory Limit: 256000

Write a Python program to print an inverted right-angled triangle using asterisks (*).

The triangle should have 5 rows.

The first row should contain 5 stars.

Each subsequent row should have one less star than the previous row.

Input

You do not need to take any input.

Output

Print the inverted right-angled triangle as shown in the example.

Example

Output:

*****

*****

****

****

```
***
***


**
**


*
*
```

Print Numbers Right-Angled Triangle — 10/20 XP — SOLVED — deadline 2026-09-08 21:00

Topics: Print function in python

URL: https://my.newtonschool.co/playground/code/ts5h6mew954q

Back

Print Numbers Right-Angled Triangle

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Print Numbers Right-Angled Triangle

Easy

10/20

Time Limit: 2, Memory Limit: 256000

Write a Python program to print a right-angled triangle made of numbers.

The triangle should have 5 rows.

The first row should contain the number 1.

The second row should contain 1 2.

The third row should contain 1 2 3, and so on.

See the example below for clarity.

Note: There should be a space between each number in a row.

Input

You do not need to take any input.

Output

Print the right-angled triangle of numbers as shown in the example.

Example

Output

```
1
```

```
1


1


2
1 2


1


2


3
1 2 3


1


2


3


4
1 2 3 4


1


2


3


4


5
1 2 3 4 5
```

Print Hollow Square — 10/20 XP — SOLVED — deadline 2026-09-08 21:00

Topics: Print function in python

URL: https://my.newtonschool.co/playground/code/0ku6oqeccpe3

Back

Print Hollow Square

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Print Hollow Square

Easy

10/20

Time Limit: 2, Memory Limit: 256000

Write a Python program to print a hollow square pattern using asterisks (*).

The square should have 5 rows and 5 columns.

The stars should form the border of the square.

The inside of the square should be empty (filled with spaces).

See the example below for clarity.

Input

You do not need to take any input.

Output

Print the hollow square pattern as shown in the example.

Example

Output

```
*****
*****


*   *
*   *


*   *
```

```
*   *


*   *

*   *


*****

*****
```

No Time to Newline — 10/20 XP — SOLVED — deadline 2026-09-08 21:00

Topics: Endline and formatting

URL: https://my.newtonschool.co/playground/code/rlpkygvrjcpc

Back

No Time to Newline

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

No Time to Newline

Easy

10/20

Time Limit: 2, Memory Limit: 256000

Write a program to print the below quote in a single line.

Quote

1.Do not watch the clock

2.Do what it does keep going

Your task is to print only the line number 1 of the quote.

Line number 2 of the quote will automatically appear in the output section when you run your code.

Input

You do not need to take any input. You need to print only line number 1 of the Quote.

Output

The output will be the quote in a single line as per below example.

```
Example

Input:



Output:

Do not watch the clock Do what it does keep going
```

Python Input, Input() function, Input() for different datatypes, Python operator ... [In Class] — due 2026-09-12 16:20

Swap Two Variables — 60/60 XP — SOLVED — deadline 2026-09-12 16:20

Topics: Input() function

URL: https://my.newtonschool.co/playground/code/il2gc70cns3y

Back

Swap Two Variables

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Swap Two Variables

Hard

2x

60/60

Time Limit: 2, Memory Limit: 256000

Write a program to swap two integers a and b, using a third variable.

Input

User Task

You need not handle input or output. Your task is to swap the numbers stored in variables a and b.

Custom Input

The first line of input contains an integer a.

The second and final line contains an integer b.

Output

You need not to output anything.

Custom Output

The driver code will print two space-separated numbers representing the swapped values.

Constraints

0

≤

a

≤

1

0

3

0≤a≤10

3

0

≤

b

≤

1

0

3

0≤b≤10

3

Example

Input

10

20

Output

20 10

Explanation

Given the two integer numbers 10 and 20, after the swap the numbers will be 20 and 10.

Hence, the output is 20 10.

Python Input, Python operators, Input() function, Input() for different datatype ... [Post Class] — due 2026-09-12 17:00

Find The Square — 20/20 XP — SOLVED — deadline 2026-09-12 17:00

Topics: Python Arithmetic operators

URL: https://my.newtonschool.co/playground/code/tjil7yari3ay

Back

Find The Square

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Find The Square

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Write a program to take a number X as input and print its square.

Input

The first and only line of input contains a single integer X.

Output

Print an integer, representing the square of X.

Constraints

0

≤

X

≤

5

0≤X≤5

The input number will always be an integer.

Example

Input

4

Output

16

Explanation

```
The given number is 4, and its square will be 4 * 4 = 16.
```

Rectangle Area Calculator — 20/20 XP — SOLVED — deadline 2026-09-12 17:00

Topics: Python Arithmetic operators

URL: https://my.newtonschool.co/playground/code/987hc9looztb

Back

Rectangle Area Calculator

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Rectangle Area Calculator

Easy

2x

20/20

Time Limit: 2, Memory Limit: 128000

Write a program that calculates the area of a rectangle given its length and width.

The program should prompt the user to enter the length and width of the rectangle, and then calculate and print the area.

Input

The first line of input contains a single integer, representing the length of rectangle.

The second line of input contains a single integer, representing the width of rectangle.

Output

Print the answer in following format:

"Area of the rectangle is: [calculated area]"

Constraints

1

≤

L

e

n

g

t

h

,

W

i

d

t

h

≤

100

1≤Length,Width≤100

Length and width will be positive numbers.

Example

Input

5

3

Output

Area of the rectangle is: 15

Calculate and Print Age — 20/20 XP — SOLVED — deadline 2026-09-12 17:00

Topics: Python Arithmetic operators

URL: https://my.newtonschool.co/playground/code/dpqdzb37tiuh

Back

Calculate and Print Age

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Calculate and Print Age

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Write a Python program that takes two integers as input: the birth year and the current year.

Your task is to calculate the age by subtracting the birth year from the current year, and print the result.

Input

The first line of input contains a single integer, the birth year.

The second line also contains a single integer, the current year.

Output

Print an integer, the calculated age.

Constraints

1950 <= Birth Year <= Current Year <= 2025

Example

Input

2000

2024

Output

24

Explanation

Brith Year = 2000

Current Year = 2024

```
Age = 2024 - 2000 = 24


Input

2006

2025

Output

19

Explanation

Brith Year = 2006

Current Year = 2025

Age = 2025 - 2006 = 19
```

Energy Consumption Calculation — 20/20 XP — SOLVED — deadline 2026-09-12 17:00

Topics: Python Arithmetic operators

URL: https://my.newtonschool.co/playground/code/k8718dpafb9h

Back

Energy Consumption Calculation

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Energy Consumption Calculation

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given two integers: units representing the total electricity consumed and cost representing the cost of each unit.

Your task is to write a Python program that calculates the total electricity cost and prints the result.

Input

The first and only line of input contains two space-separated integers, representing units and cost respectively.

Output

Print an integer representing the total electricity cost.

Constraints

0

≤

u

n

i

t

s

≤

1000

0≤units≤1000

1

≤

c

o

s

t

≤

1000

1≤cost≤1000

Example

Input

20 10

Output

200

Explanation

Since 20 units of electricity was consumed and the cost per unit is 10. The total cost would be 200.

Celsius to Fahrenheit Conversion — 20/20 XP — SOLVED — deadline 2026-09-12 17:00

Topics: Precedence and Associativity

URL: https://my.newtonschool.co/playground/code/haikjdpg2f4e

Back

Celsius to Fahrenheit Conversion – 2

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Celsius to Fahrenheit Conversion – 2

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given an integer, representing the temperature in celsius.

Your task is to convert it to Fahrenheit, using the below given formula:

Fahrenheit = (Celsius × 9 / 5) + 32

You must complete the function celsius_to_fahrenheit(celsius) that returns the equivalent temperature in Fahrenheit.

Function Signature:

def celsius_to_fahrenheit(celsius):

It takes a single parameter, celsius, the temperature in Celsius.

Input

User Task

As this is a functional problem, there is no need to handle input from the user. Your task is to complete the function celsius_to_fahrenheit(celsius), which takes single parameter, celsius, the temperature in celsius.

Custom Input

The first and only line of input contains a single integer, celsius, representing the temperature in celsius.

Output

Return the corresponding temperature in Fahrenheit (as a float).

```
Constraints

−100 ≤ celsius ≤ 100

Example

Input

0

Output

32.0

Explanation

Input Celsius = 0

Fahrenheit = (0 × 9/5) + 32 = 0 + 32 = 32.0

So the output is 32.0.


Input

37

Output

98.6

Explanation

Input Celsius = 37

Fahrenheit = (37 × 9/5) + 32 = 98.6

So the output is 98.6.
```

Convert Minute to Hour and Minute Format — 20/20 XP — SOLVED — deadline 2026-09-12 17:00

Topics: Python Arithmetic operators

URL: https://my.newtonschool.co/playground/code/1cgxc2by8uqq

Back

Convert Minute to Hour and Minute Format

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Convert Minute to Hour and Minute Format

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Write a program to convert total minutes into hours and remaining minutes.

Print the hours and minutes in the below given format:

Time: {x} hour(s) and {y} minute(s)

where {x} will be replaced by hours and {y} by minutes.

Input

The first and only line of input contains a single integer, representing the total minutes.

Output

Print the hours and minutes in the below given format:

Time: {x} hour(s) and {y} minute(s)

where {x} will be replaced by hours and {y} by minutes.

Constraints

0 ≤ total minutes ≤ 103

Example

Input

135

Output

Time: 2 hour(s) and 15 minute(s)

```
Input

60

Output

Time: 1 hour(s) and 0 minute(s)
```

PSP LAb [In Class] — due 2026-09-14 10:52

Average of Three — 20/20 XP — SOLVED — deadline 2026-09-14 10:52

Topics: Input() for different datatypes

URL: https://my.newtonschool.co/playground/code/4kb4el5cnb5z

Back

Average of Three

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Average of Three

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Write a program that takes three numbers as input and prints their average.

Note: The result should be rounded to two decimal places.

Input

The first and only line of input contains three space-separated numbers (integer or float).

Output

Print the average of the three numbers rounded to two decimal places.

Constraints

−

100

≤

a

,

b

,

c

≤

100

−100≤a,b,c≤100

```
Each number will be a valid integer or float.

Example

Input

10 20 30

Output

20.0

Explanation

Average = (10 + 20 + 30) / 3 = 60 / 3 = 20.0



Input

3.3 1.2 1

Output

1.83

Explanation

To calculate the average, we add all the values:

3.3 + 1.2 + 1 = 5.5



Now, divide the total by the number of values:

5.5 ÷ 3 = 1.8333333333333333



Since the question requires the answer to be rounded to two decimal places, we round
1.8333333333333333 to 1.83.



Final Answer: 1.83
```

Compound Interest Calculation in Python -1 — 20/20 XP — SOLVED — deadline 2026-09-14 10:52

Topics: Python Arithmetic operators

URL: https://my.newtonschool.co/playground/code/jlzmjfrkte1s

Back

Compound Interest Calculation in Python -1

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Compound Interest Calculation in Python -1

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Write a program that calculates the compound interest.

The program should take principal amount (P), rate of interest (r), and time period (t) as inputs.
Use the formula:

$$
C
$$

$$
I
$$

=

(

$$
P
$$

*

(

1

+

(

$$
r
$$

/

100

)

)

t

)

−

P

CI=(P∗(1+(r/100))

t

)−P

Note: Display the result rounded to one decimal point.

Input

The first and only line of input contains three space-separated numbers, representing the principal amount (P), rate of interest (r), and time period (t) respectively

Note: The principal amount (P) and the time period (t) are provided as integers, while the rate of interest (r) is given as a floating-point number.

Output

The program should print the calculated compound interest.

Note: Display the result rounded to one decimal point.

Constraints

1

≤

P

≤

1

0

3

1≤P≤10

3

1

≤

r

≤

1

0

2

1≤r≤10

2

1

≤

t

≤

10

1≤t≤10

Example

Input:

1000 5.0 3

Output:

157.6

Explanation:

principal amount: 1000

rate of interest (as a percentage): 5

the time period (in years): 3

Compound interest: 157.63, calculated using formula CI = (P * (1 + (r / 100)) ^ t) - P

Conditional Statements, Python if- else [In Class] — due 2026-09-14 16:54

Even or Odd Checker — 20/20 XP — SOLVED — deadline 2026-09-14 16:54

Topics: Python if- else

URL: https://my.newtonschool.co/playground/code/nh90a28g9oyx

Back

Even or Odd Checker

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Even or Odd Checker

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Write a Python program that checks if a given number is even or odd.

Input

The input contains a single integer number

Output

The program should print a single word either – Even or Odd according to number.

Example

Input:

7

Output:

Odd

Input:

6

Output:

```
Even
```

Integer Type — 20/20 XP — SOLVED — deadline 2026-09-14 16:54

Topics: Python if- else

URL: https://my.newtonschool.co/playground/code/5k61xy0qc0u0

Back

Integer Type

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Integer Type

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given a non-zero integer num. Your task is to check whether the number is Positive or Negative.

Input

The first and only line contains an integer num.

Output

Print exactly one word, either Positive or Negative, depending on the value of the input.

Constraints

−

30

≤

n

u

m

≤

30

−30≤num≤30

n

u

m

```
≠

0

num

□

=0

Example

Input:

5

Output:

Positive


Input:

-9

Output:

Negative
```

Who is Greater? — 20/20 XP — SOLVED — deadline 2026-09-14 16:54

Topics: Python if- else

URL: https://my.newtonschool.co/playground/code/606bjkv3zvdm

Back

Who is Greater?

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Who is Greater?

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given two distinct integers a and b. Your task is to compare two numbers a and b, and print the comparison in the following format:

print "a is greater than b", if a is greater than b, or

print "b is greater than a", if b is greater than a

Note: You are guaranteed that a ≠ b.

Input

A single line containing two space-separated integers a and b.

Output

Print exactly one line in one of the following formats:

a is greater than b – if a is greater than b

b is greater than a – if b is greater than a

Note: You must use the actual values of a and b in the output.

```
Constraints

-102 ≤ a, b ≤ 102


a ≠ b

Example


Input:


12 5


Output:


12 is greater than 5









Input:


-3 10


Output:


10 is greater than -3
```

Conditional Statements, Python if- else [Post Class] — due 2026-09-14 21:05

Weather Report — 20/20 XP — SOLVED — deadline 2026-09-14 21:05

Topics: Python if- else, If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/krjnhzw8l2lp

Back

Weather Report

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

Try AI Plan Mode

QUESTION

Weather Report

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Write a program that takes an integer current temperature as input, and determines the type of weather using the below conditions:

Temp < 0 : Freezing Weather

Temp 0–9 : Very Cold

Temp 10–19 : Cold

Temp 20–29 : Normal

Temp 30–39 : Hot

Temp >=40 : Very Hot

Input

A line containing an integer number representing the temperature.

Output

Print the weather according to the temperature as The weather today is classified as: answer

Example

Input

29

Output

```
The weather today is classified as: Normal

Explanation

According to the given question the temperature 20–29 are considered Normal



Input

9

Output

The weather today is classified as: Very Cold

Explanation

According to the given question the temperature 0–9 are considered Very Cold
```

AM_PM — 20/20 XP — SOLVED — deadline 2026-09-14 21:05

Topics: Python if- else

URL: https://my.newtonschool.co/playground/code/9fd6gabsf4f0

Back

AM_PM

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

AM_PM

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Write a program that takes the hour (0–23) in 24-hour format as input and prints whether it is AM or PM.

Note:

The time is considered AM if the hour is between 0 and 11 (inclusive).

The time is considered PM if the hour is between 12 and 23 (inclusive).

Input

First line will contain an integer hour (0–23) as input.

Output

The program should print the appropriate answer(AM or PM) based on the hour.

Constraints

0 ≤ hour ≤ 23

Example

Example 1

Input:

10

Output:

```
AM


Example 2

Input:

13


Output:

PM
```

Identify Square or Rectangle — 20/20 XP — SOLVED — deadline 2026-09-14 21:05

Topics: Python if- else

URL: https://my.newtonschool.co/playground/code/5oyx5ukgsyae

Back

Identify Square or Rectangle

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Identify Square or Rectangle

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given two integers representing the length and breadth of a rectangle.

You need to print "Square" if the given rectangle is square as well, otherwise print "Rectangle".

Input

The first and only line of input contains two space-separated integers, representing the length and breadth of the rectangle respectively.

Output

Print "Square" or "Rectangle" based on the dimensions.

Constraints

1

≤

l

e

n

g

t

h

,

b

r

e

a

d

t

h

≤

100

1≤length,breadth≤100

Example

Input

5 5

Output

Square

Input

10 9

Output

Rectangle

Python Input, Python operators, Input() function, Input() for different datatype ... [In Class] — due 2026-09-21 11:10

Absolute Difference of Two Numbers — 20/20 XP — SOLVED — deadline 2026-09-21 11:10

Topics: Python if- else

URL: https://my.newtonschool.co/playground/code/cymrq6g9ua89

Back

Absolute Difference of Two Numbers

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Absolute Difference of Two Numbers

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Rakshit has two numbers, and he wants to find how far apart they are on the number line — that is, their absolute difference.

Your task is to find and print the absolute difference of the two given numbers.

Input

The first line of input contains two space-separated integers a and b.

Output

Print the absolute difference of a and b in the output.

Constraints

1

≤

a

,

b

≤

1000

1≤a,b≤1000

Example

Input

8 19

```
Output

11

Explanation

The absolute difference between 8 and 19 is | 8 - 19 | = 11.
```

Check if Profit or Loss — 20/20 XP — SOLVED — deadline 2026-09-21 11:10

Topics: Python if- else

URL: https://my.newtonschool.co/playground/code/f7muynmik3if

Back

Check if Profit or Loss

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Check if Profit or Loss

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given two integers:

CP — the Cost Price of an item

SP — the Selling Price of the item

Your task is to determine whether the transaction resulted in a Profit or a Loss.

Note: There will be no test case where SP = CP.

Input

The first line contains two space-separated integers CP and SP.

Output

Print:

Profit if the selling price is greater than the cost price.

Loss if the selling price is less than the cost price.

Constraints

```
1 ≤ CP, SP ≤ 109

Example

Input



100 150

Output


Profit

Explanation




Since SP > CP, the transaction resulted in a profit.




Input


200 120

Output


Loss

Explanation




Since SP < CP, the transaction resulted in a loss.
```

Voter Eligibility II — 20/20 XP — SOLVED — deadline 2026-09-21 11:10

Topics: Python if- else

URL: https://my.newtonschool.co/playground/code/rm8oeu6qxg9g

Back

Voter Eligibility II

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Voter Eligibility II

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given an integer input, representing the age of a person.

You task is to check whether the person is eligible to vote or not.

A person is eligible to vote if their age is greater than or equal to 18.

Print Yes if the person can vote, otherwise print No.

Input

The first and only line of input contains a single integer, representing the age.

Output

Print Yes if the person can vote, otherwise print No.

Constraints

0

≤

a

g

e

≤

100

```
0≤age≤100

Example

Input

20

Output

Yes


Input

15

Output

No
```

If- elif-else ladder [In Class] — due 2026-09-21 16:57

Grade Calculator — 10/20 XP — SOLVED — deadline 2026-09-21 16:57

Topics: If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/zdxcy5xxzbt4

Back

Grade Calculator

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Grade Calculator

Easy

10/20

Time Limit: 2, Memory Limit: 256000

Write a Python program that takes a student's score as input and prints their grade based on the following criteria:

Grading Criteria:

If the score is 90 or above, the grade is A.

If the score is 80 or more but less than 90, the grade is B.

If the score is 70 or more but less than 80, the grade is C.

If the score is 60 or more but less than 70, the grade is D.

If the score is less than 60, the grade is F.

Input

The one and only line containing a single integer representing the student's score.

Output

Print in a line containing the grade corresponding to the score.

```
Constraints

1<=score<=100

Example

Sample 1:


Input:

85


Output:

Grade B


Explanation:

The score is 85, which falls in the range of 80 or more but less than 90. So, the grade is B.




Sample 2:


Input:

60


Output:

Grade D


Explanation:

The score is 60, which is 60 or more but less than 70. Therefore, the grade is D.
```

The Number Detective — 10/20 XP — SOLVED — deadline 2026-09-21 16:57

Topics: If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/8n06m3da1116

Back

The Number Detective

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

The Number Detective

Easy

10/20

Time Limit: 2, Memory Limit: 256000

Given a number n, write a Python program to check whether the number n is positive, negative, or zero.

Print Positive if n is greater than 0

Print Negative if n is less than 0

Print Zero if n is equal to 0

Input

The one and only line contains a single integer n.

Output

Print whether the number is Positive, Negative, or Zero.

Constraints

−1000 ≤ number ≤ 1000

Example

Sample Input 1:

```
13

Sample Output 1:

Positive

Explanation:



Since 13 is greater than 0, that's why the output is Positive number.









Sample Input 2:

-13

Sample Output 2:

Negative

Explanation:



Since -13 is less than 0, that's why the output is Negative number.
```

Greater or Equal — 10/20 XP — SOLVED — deadline 2026-09-21 16:57

Topics: If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/ewx4lamuv3as

Back

Greater or Equal

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Greater or Equal

Easy

10/20

Time Limit: 2, Memory Limit: 256000

You are given two integers a and b.

Your task is to compare the two numbers and print:

a is greater than b if the value of a is greater than the value of b

b is greater than a if the value of b is greater than the value of a

a and b are equal if both values are equal

Note: Replace a and b with their actual input values in the output.

Input

The first line contains two space-separated integers a and b.

Output

Print exactly one line in one of the following formats:

a is greater than b – if the value of a is greater than the value of b

b is greater than a – if the value of b is greater than the value of a

a and b are equal – if both values are equal

Note: Replace a and b with their actual input values in the output.

Constraints

1 ≤ a , b ≤ 100

1≤a,b≤100

Example

Example 1

Input

12 5

Output

12 is greater than 5

Explanation

Among the two given numbers, 12 is greater than 5.

Example 2

Input

1 10

Output

10 is greater than 1

Explanation

Among the two given numbers, 10 is greater than 1.

Example 3

```
Input

7 7

Output

7 and 7 are equal

Explanation

Both numbers have the same value.
```

Python Input, Python operators, Input() function, Input() for different datatype ... [In Class] — due 2026-09-26 10:43

FizzBuzz II — 20/20 XP — SOLVED — deadline 2026-09-26 10:43

Topics: If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/c64zs11c5ukr

Back

FizzBuzz II

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

FizzBuzz II

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Arjun has recently started learning about divisibility rules. His friend gave him a simple problem to test his understanding.

Given an integer n, your task is to help Arjun print:

"FizzBuzz" if n is divisible by both 3 and 5.

"Fizz" if n is divisible by 3 only.

"Buzz" if n is divisible by 5 only.

Otherwise, print the number n itself.

Input

A single integer n — the number to be evaluated.

Output

Print:

"FizzBuzz" if divisible by both 3 and 5

"Fizz" if divisible only by 3

```
"Buzz" if divisible only by 5

Else, print the number itself



Constraints

-10^9 <= n <= 10^9

Example

1. Sample Input:

15

Sample Output:

FizzBuzz

Explanation: 15 is divisible by 3 and 5, hence the output as per the condition is "FizzBuzz".


2. Sample Input:

5


Sample Output:

Buzz


Explanation: 5 is divisible by 5, hence the output as per the condition is "Buzz".


3. Sample Input:

3

Sample Output:

Fizz

Explanation: 3 is divisible by 3, hence the output as per the condition is "Fizz".
```

Income Tax Calculator — 40/40 XP — SOLVED — deadline 2026-09-26 10:43

Topics: If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/nr7d9k6xdb5a

Back

Income Tax Calculator

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Income Tax Calculator

Medium

2x

40/40

Time Limit: 2, Memory Limit: 128000

Write a program to calculate the income tax for an individual based on their annual income in Indian Rupees (₹) provided as input. The tax is calculated according to the following slabs:

Income Range (₹)	Tax Calculation
Up to ₹2,50,000	No tax.
₹2,50,001 to ₹5,00,000	5% tax on amount between ₹2,50,001 to ₹5,00,000
₹5,00,001 to ₹10,00,000	₹12,500 plus 10% tax on amount between ₹5,00,001 to ₹10,00,000
Above ₹10,00,000	₹62,500 plus 20% tax on amount above ₹10,00,000.

The program should read the annual income from the user, calculate the tax accordingly, and output the tax amount upto 1 decimal places.

Note: We can round the output to 1 decimal place using print(round(tax,1)).

Input

A single integer representing the annual income in rupees.

Output

Print the tax amount as a float number up to 1 decimal places.

Constraints

1

≤

Income

≤

1

0

9

1≤Income≤10

9

Example

input

200000

output

0.0

Explanation: As income is less than 250000, there will not be any tax that the individual is paying, that's why the output is 0.0.

input

550000

output

17500.0

Explanation:

Total income = 550000

1. No tax upto 250000

2. 5% tax in between 250000 to 500000 = 250000*0.05 = 12500.0

3. 10% tax in between 500000 to 1000000,

there for remaining taxable income = 550000 – 500000 = 50000

10% of 50000 = 50000 * 0.1 = 5000.0

Total Tax to be paid = 0.0 + 12500.0 + 5000.0 = 17500.0

Calculate Electricity Bill — 30/60 XP — SOLVED — deadline 2026-09-26 10:43

Topics: If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/5r6xhlhs40lc

Back

Calculate Electricity Bill – 2

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Calculate Electricity Bill – 2

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

An electricity board calculates monthly power usage bills based on the number of units consumed using a slab-wise tariff system. Each slab charges a different rate per unit as follows:

First 100 units: ₹4 per unit

Next 100 units (i.e., units 101–200): ₹5 per unit

Next 100 units (i.e., units 201–300): ₹6 per unit

Next 100 units (i.e., units 301–400): ₹7 per unit

Units above 400: ₹8 per unit

After calculating the base bill, a 10% surcharge is added to the total bill.

You are required to implement the function calculate_bill(units) that calculates the total electricity bill including the surcharge, and returns a float rounded to 1 decimal place using the built-in round() function.

Function Signature:

def calculate_bill(units): which takes single parameter: units: represents the number of electricity units consumed.

Input

User Task

As this is a functional problem, there is no need to handle input from the user. Your task is to complete the function calculate_bill(units), which takes single parameter: units: represents the number of electricity units consumed.

Custom Input

A Single line containing an integer representing the number of units.

Output

Return a float – the total electricity bill including the 10% surcharge, rounded to 1 decimal place using round().

Example

Input

1

Output

Electricity Bill: Rs. 4.4

Explanation

Units are less than 100 therefore total cost is unit charge + surcharge 4 X 1 + 4 X 0.1 = 4.4

Input

100

Output

Electricity Bill: Rs. 440.0

Explanation

Units are equal to 100 therefore total cost is unit charge + surcharge 4 X 100 + 400 X 0.1 = 440.0

Input

340

Output

Electricity Bill: Rs. 1958.0

```
Explanation

For the first 100 units(i.e from 1 to 100) cost will be: 100*4 = 400

For next 100 units(i.e from 101 to 200) cost will be: 100*5 = 500

For next 100 units(i.e from 201 to 300) cost will be: 100*6 = 600

For remaining 40 units(i.e from 301 to 340) cost will be: 40*7 = 280

Total Cost excluding surcharge = 400 + 500 + 600 + 280 = 1780

Final Bill including 10% surcharge on Total cost = 1780 + (1780*0.1) = 1780 + 178 = 1958
```

If- elif-else ladder [In Class] — due 2026-09-26 15:30

Triangle Type Checker — 20/20 XP — SOLVED — deadline 2026-09-26 15:30

Topics: Nested if-else, If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/qc9ncrcoex1x

Back

Triangle Type Checker

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Triangle Type Checker

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given the lengths of the three sides of a triangle. Your task is to determine and print the type of triangle formed.

Use the following rules:

Equilateral: All three sides are equal

Isosceles: Exactly two sides are equal

Scalene: All sides are different

Input

A single line contains three space-separated integers representing the lengths of the three sides of a triangle.

Output

Print one of the following based on the type of triangle:

Equilateral

Isosceles

Scalene

```
Note: Your output must match the cases exactly as shown above. Outputs are case-sensitive.

Constraints

1 ≤ a, b, c ≤ 100



The input will always represent a valid triangle.

Example

input

3 4 3



output

Isosceles



Explanation:

Two sides of a triangle are equal -> Isosceles
```

Check if All Three Numbers are Equal — 20/20 XP — SOLVED — deadline 2026-09-26 15:30

Topics: Nested if-else

URL: https://my.newtonschool.co/playground/code/m27koht9p2md

Back

Check if All Three Numbers are Equal

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Check if All Three Numbers are Equal

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given three integers a, b, and c.

Your task is to determine whether all three numbers are equal.

Print:

Numbers are equal if all three numbers have the same value.

Numbers are not equal otherwise.

Input

The first line contains three space-separated integers a, b, and c.

Output

Print exactly one line:

Numbers are equal if all three numbers are equal.

Numbers are not equal otherwise.

Constraints

1

≤

a

,

b

,

c

≤

100

1≤a,b,c≤100

Example

Example 1

Input

5 5 5

Output

Numbers are equal

Explanation

All three numbers have the same value.

Example 2

Input

5 5 7

Output

Numbers are not equal

Explanation

The three numbers do not all have the same value.

Find the Biggest ! — 20/20 XP — SOLVED — deadline 2026-09-26 15:30

Topics: Nested if-else, Python if- else, If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/0jmhf4wwbnt8

Back

Find the Biggest !

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Find the Biggest !

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Comparing numbers is a common task in programming. Your goal is to determine the largest of three given numbers.

Your task:

Given three integers A, B, and C, print the largest among them.

Input

The first and only line of input contains three space-separated integers, A, B, and C respectively.

Output

Print an integer, the largest number among the given three numbers.

Constraints

0

≤

A

,

B

,

C

≤

100

0≤A,B,C≤100

```
Example

Input

1 2 3

Output

3


Input

5 3 1

Output

5


Input

10 9 10

Output

10
```

If- elif-else ladder [Post Class] — due 2026-09-26 16:00

Library fine — 10/20 XP — SOLVED — deadline 2026-09-26 16:00

Topics: If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/x8aarbvbrgnw

Back

Library fine

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

Try AI Plan Mode

QUESTION

Library fine

Easy

10/20

Time Limit: 2, Memory Limit: 256000

Calculate the fine for a late return of a library book based on the following details:

For the first 3 days, the fine is Rs. 10.

For the next 4 to 10 days, the fine is Rs. 20.

For any period exceeding 10 days, the fine is Rs.100.

Input

A line containing an integer representing the number of late days.

Output

Print a line containing the total fine amount.

Example

Input

10

Output

20

Explanation

Fine for 10 late days is 20 Rs according to the question.

```
Input

20

Output

100

Explanation

Fine for 10 late days is 100 Rs according to the question.
```

Calculate salary — 10/20 XP — SOLVED — deadline 2026-09-26 16:00

Topics: If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/8u4fn097c5xk

Back

Calculate salary

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Calculate salary

Easy

10/20

Time Limit: 2, Memory Limit: 256000

Calculate the gross salary of an employee based on their basic salary according to the following criteria:

basic salary <= 10,000, HRA = 20% and DA = 80%.

20,000 >= basic salaries > 10,000 , the HRA = 25% and DA = 90%.

basic salary > 20,000, HRA = 30% and DA = 95%.

Hint: Gross Salary = Basic Salary + HRA + DA

Input

A line containing an integer representing the basic salary of the employee.

Output

Print the total gross salary as The gross salary of the employee is: answer

Example

Input

10001

Output

The gross salary of the employee is: 21502.15

```
Explanation

By using the formula answer is 21502.15
```

Check Profit or Loss — 10/20 XP — SOLVED — deadline 2026-09-26 16:00

Topics: Python if- else, If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/gdnv1arw8xa9

Back

Check Profit or Loss

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Check Profit or Loss

Easy

10/20

Time Limit: 2, Memory Limit: 256000

You are given two integers, cost and sell, representing the cost price and the selling price of a product.

Your task is to determine whether the transaction results in a profit, a loss, or no profit and no loss.

Also, you need to calculate the corresponding amount.

Input

The first line of input contains a single integer, representing cost.

The second line also contains a single integer, representing sell.

Output

The program should print two lines.

The first line should contain one of the words Profit, Loss, or No Profit No Loss.

The second line should contain an integer representing the profit or loss amount, and it should be 0 in case of no profit and no loss.

Constraints

1

≤

c

o

s

t

≤

1000

1≤cost≤1000

1

≤

s

e

l

l

≤

1000

1≤sell≤1000

Example

Input

150

100

Output

Loss

50

Input

100

100

Output

No Profit No Loss

0

BMI Calculator-1 — 10/20 XP — SOLVED — deadline 2026-09-26 16:00

Topics: If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/yvepr94fgd09

Back

BMI Calculator-1

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

BMI Calculator-1

Easy

10/20

Time Limit: 2, Memory Limit: 256000

You are asked to determine a person's Body Mass Index (BMI) based on their weight and height.

The BMI is calculated using the following formula:

BMI = weight / (height_in_meters x height_in_meters)

Here,

weight is given in kilograms

height is given in centimeters and must be converted to meters

You must round the BMI value to exactly 1 decimal place using the built-in round() function.

Based on the rounded BMI value, print the corresponding BMI category:

If BMI is less than 18.5, print Underweight

If BMI is between 18.5 and 24.9 (inclusive), print Normal weight

If BMI is between 25 and 29.9 (inclusive), print Overweight

If BMI is 30 or greater, print Obese

Input

The input consists of two lines as follows:

The first line contains an integer weight — the person's weight in kilograms.

The second line contains an integer height — the person's height in centimeters.

Output

Print two lines:

First line: the BMI value rounded to one decimal place using round()

Second line: the corresponding BMI category.

Constraints

1 ≤ weight ≤ 300

50 ≤ height ≤ 250

Example

Input

60

165

Output

22.0

Normal weight

Explanation:

BMI = 60/1.65*1.65 = 22.0

22.0 is in range 18.5 to 24.9

Category = Normal weight

Python Input, Python operators, Conditional Statements, Input() function, Input(... [In Class] — due 2026-09-28 10:38

Can It Be a Triangle ? — 10/20 XP — SOLVED — deadline 2026-09-28 10:38

Topics: Nested if-else

URL: https://my.newtonschool.co/playground/code/zmbd9rh1pinh

Back

Can It Be a Triangle ?

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Can It Be a Triangle ?

Easy

10/20

Time Limit: 2, Memory Limit: 256000

You are given the lengths of three sides. Your task is to check whether these three sides can form a valid triangle.

Input

The first and only line of input contains three space-separated integers, representing the lengths of three sides.

Output

Print Yes if the sides form a valid triangle.

Print No otherwise.

Constraints

1

≤

S

i

d

e

L

e

n

g

t

h

$\leq$

100

$1 \leq SideLength \leq 100$

Example

Input

20 10 13

Output

Yes

Explanation

All combinations of side pairs sum to more than the third side. So, a triangle is possible.

Input

2 5 3

Output

No

Explanation

2 + 3 is not greater than 5, so a triangle cannot be formed.

Leap Year Checker — 40/40 XP — SOLVED — deadline 2026-09-28 10:38

Topics: Nested if-else, If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/lds6jda0joac

Back

Leap Year Checker

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Leap Year Checker

Medium

2x

40/40

Time Limit: 2, Memory Limit: 256000

You are given an integer representing a year. Your task is to determine whether it is a leap year or not.

Input

The input contains a single integer: year — the year to check

Output

Print a single line as follows:

Leap year if the year is a leap year

Not a leap year otherwise

Constraints

1 ≤ year ≤ 10^9

Example

Example 1:

Input:

2000

Output:

Leap year

Explanation:

2000 is divisible by 400 ⇒

2000

mod

400

=

0

2000mod400=0

So, it's a leap year.

Example 2:

Input:

1900

Output:

Not a leap year

Explanation:

1900 is divisible by 100 ⇒

1900

mod

100

=

0

1900mod100=0

```
but not divisible by 400 ⇒

1900


mod


400

≠

0

1900mod400

□

=0


So, it's not a leap year.
```

Roller Coaster Ride — 20/40 XP — SOLVED — deadline 2026-09-28 10:38

Topics: Nested if-else, If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/8a67fz5d44vl

Back

Roller Coaster Ride

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Roller Coaster Ride

Medium

20/40

Time Limit: 2, Memory Limit: 256000

A theme park wants to check if Alice can ride their roller coaster. You are given the height (in cm) and age (in years) of Alice.

Eligibility and ticket rules are as follows:

Height Requirements:

Less than 120 cm → Not Allowed

120 – 140 cm → Must ride with Adult

Above 140 cm → Can ride alone

Age Restrictions:

Less than 5 years → Not Allowed

5 – 12 years → Must ride with Adult

Above 12 → Can ride alone

Ticket Price Calculation:

If Allowed Alone → ₹300

Allowed with Adult → ₹200

Your task is to print whether Alice is allowed to ride or not. If Alice is allowed to ride, print the ticket price of ride in the next line.

Note: Alice's eligibility is determined by both height and age. If either height or age imposes a stricter restriction, that restriction takes precedence.

For example, if her age requires her to ride with an adult, she cannot ride alone even if her

height allows it.

Similarly, if her age or height disqualifies her from riding, she is not allowed to ride regardless of the other factor.

Input

The first line of input contains a single integer, representing height.

The second line also contains a single integer, representing age.

Output

The output should contain one or two lines:

On the first line, print Alice's riding status:

Not Allowed – if Alice is not allowed to ride.

Must ride with Adult – if Alice can ride only with an adult.

Can ride alone – if Alice can ride by herself.

If Alice is allowed to ride (either with an adult or alone), print the ticket price on the second line (without ₹ sign).

Constraints

50

≤

h

e

i

g

h

t

≤

300

50≤height≤300

1

≤

a

g

e

≤

```
100

1≤age≤100

Example

Input

145

14

Output

Can ride alone

300

Explanation

Height of Alice is greater than 140 cm and also the age is above 12.

Therefore, Alice can ride alone and the ticket price will be ₹300.


Input

110

4

Output

Not Allowed
```

Python Function, Nested if-else [Post Class] — due 2026-09-28 20:35

Accommodation Decision — 10/20 XP — SOLVED — deadline 2026-09-28 20:35

Topics: Nested if-else

URL: https://my.newtonschool.co/playground/code/iue8zuqmsvel

Back

Accommodation Decision

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Accommodation Decision

Easy

10/20

Time Limit: 2, Memory Limit: 256000

A student wants to check whether they will stay On-Campus or Off-Campus based on the rules provided in the NST rulebook.

The rules for accommodation are:

If the student is a girl, she will definitely stay On-Campus, irrespective of the year.

If the student is a boy:

In first year → he will stay On-Campus

In second year → he will stay Off-Campus

Given the student's gender and year of study, determine their accommodation type.

Input

The input consists of two lines:

The first line contains a string gender, representing the gender of the student:

G for girl

```
B for boy

The second line contains an integer year, representing the year of study:

1 for first year

2 for second year

Output

Print a single line, either:

On-Campus or Off-Campus, according to the rules.

Constraints

The value of gender will be either "G" or "B".

The value of year will be either 1 or 2.

Example

Input

G

2

Output

On-Campus


Input

B

2

Output

Off-Campus
```

Calculate Tax Based on Age and Income — 10/20 XP — SOLVED — deadline 2026-09-28 20:35

Topics: Nested if-else

URL: https://my.newtonschool.co/playground/code/gggefmp1dam2

Back

Calculate Tax Based on Age and Income

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Calculate Tax Based on Age and Income

Easy

10/20

Time Limit: 2, Memory Limit: 256000

You are given two values:

age – the age of a person

income – the annual income of the person (in rupees)

Your task is to calculate the amount of tax that the person needs to pay.

The tax rate depends on both the person's age and annual income.

Tax Slabs

Income Bracket	Tax Rate (Age < 18)	Tax Rate (Age ≥ 18)
Income ≤ 10,00,000	5%	10%
10,00,000 < Income ≤ 30,00,000	15%	20%
Income > 30,00,000	25%	30%

Print the tax amount that must be paid.

Input

The first line contains two space-separated integers age and income.

Output

Print a single integer representing the tax amount.

Constraints

$1 \leq age \leq 120$

$0 \leq income \leq 109$

Example

Example 1

Input

25 800000

Output

80000

Explanation The person's age is at least 18 and the income falls in the first tax slab. Therefore, the applicable tax rate is 10%. Tax = 10% of 800000 = 80000.

Example 2

Input

15 2000000

Output

300000

Explanation The person's age is less than 18 and the income falls in the second tax slab. Therefore, the applicable tax rate is 15%. Tax = 15% of 2000000 = 300000.

Example 3

Input

40 5000000

Output

1500000

Explanation The person's age is at least 18 and the income falls in the third tax slab. Therefore, the applicable tax rate is 30%. Tax = 30% of 5000000 = 1500000.

Find the Smallest ! — 10/20 XP — SOLVED — deadline 2026-09-28 20:35

Topics: Nested if-else, If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/d0irgxswik71

Back

Find the Smallest !

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Find the Smallest !

Easy

10/20

Time Limit: 2, Memory Limit: 256000

Just like finding the largest value, identifying the smallest number is another common task in programming.

Your task:

Given three integers A, B, and C, print the smallest among them.

Input

The first and only line of input contains three space-separated integers, A, B, and C respectively.

Output

Print an integer, the smallest number among the given three numbers.

Constraints

0

≤

A

,

B

,

C

≤

100

0≤A,B,C≤100

Example

```
Input

1 2 3

Output

1


Input

5 3 1

Output

1


Input

10 9 10

Output

9
```

Nested if-else, Python Function [In Class] — due 2026-10-03 10:59

Calculate Percentage Using Function — 10/20 XP — SOLVED — deadline 2026-10-03 10:59

Topics: Return statement

URL: https://my.newtonschool.co/playground/code/87ji7g9e8qin

Back

Calculate Percentage Using Function

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Calculate Percentage Using Function

Easy

10/20

Time Limit: 2, Memory Limit: 256000

You are required to complete the function calculate_percentage(marks, total), which calculates the percentage score of a student.

The function receives two integer parameters:

marks – the number of marks obtained

total – the total number of marks

It should return the percentage score as an integer.

Note:

This is a functional problem. You do not need to take any input or print anything.

Just complete the function calculate_percentage(marks, total) which returns the percentage score.

Percentage should be returned as an integer.

Input

The function calculate_percentage receives two space-separated integers as parameters:

marks – the marks obtained.

total – the total marks.

You do not need to take input from the user. The values will be passed to the function directly.

Output

Return a single integer – the percentage score. You do not need to print anything. Just return the integer percentage value from the function calculate_percentage().

Constraints

1 ≤ total ≤ 300

1 ≤ marks ≤ total

Example

Input 1

45 50

Output 1

90

Explanation

Marks obtained = 45

Total marks = 50

Percentage = (45 × 100) // 50 = 4500 // 50 = 90

So, the function should return 90.

Input 2

72 80

Output 2

90

```
Explanation

Marks obtained = 72

Total marks = 80

Percentage = (72 × 100) // 80 = 7200 // 80 = 90

So, the function should return 90.
```

Percentage-1 — 10/20 XP — SOLVED — deadline 2026-10-03 10:59

Topics: Arguments and parameter

URL: https://my.newtonschool.co/playground/code/93a2jn9drf3p

Back

Percentage-1

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Percentage-1

Easy

10/20

Time Limit: 2, Memory Limit: 256000

Alice appeared for an exam in one subject. The exam is out of total marks. She wants to know her percentage score.

A predefined function PrintPercentage(total_marks, obtained_marks) is available. It takes two integer arguments:

total_marks – total marks of the exam

obtained_marks – marks obtained by Alice

The function prints the percentage (up to 2 decimal places).

Note: You do not need to define this function, just take the inputs and call this function and it will automatically print the percentage.

Input

A single line contains two space separated integers total marks and marks obtained by Alice.

Output

Use the predefined function PrintPercentage() and just call the function.

Constraints

1<= total_marks <= 100

```
0<= marks<= total_marks

Example

Input:

10 8



Output:

80.00




Explanation:

The input line is split into two integers: total_marks = 10 and obtained_marks = 8.


The predefined function PrintPercentage(10, 8) is called.


It calculates:

(8/10)×100=80.00

The function prints 80.00 as the final percentage.
```

Percentage-2 — 10/20 XP — SOLVED — deadline 2026-10-03 10:59

Topics: Arguments and parameter

URL: https://my.newtonschool.co/playground/code/4vcout7nqz0o

Back

Percentage-2

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Percentage-2

Easy

10/20

Time Limit: 2, Memory Limit: 256000

Alice appeared for an exam in a single subject. The exam has a certain total number of marks, and she wants to know her percentage score.

A predefined function GetPercentage(total_marks, obtained_marks) is available. It takes two integer arguments:

total_marks – the maximum marks of the exam

obtained_marks – the marks obtained by Alice

The function returns the percentage (as a float, rounded to two decimal places).

Note: You do not need to define this function. Just call it and print the returned value.

Input

A single line containing two space-separated integers: total_marks and obtained_marks

Output

Print the percentage returned by GetPercentage() function.

Constraints

1<= total_marks <= 100

```
0<= marks<= total_marks

Example

Input:

10 8



Output:

80.00




Explanation:

The input line is split into two integers: total_marks = 10 and obtained_marks = 8.


The predefined function PrintPercentage(10, 8) is called.


It calculates:

(8/10)×100=80.00

print 80.00 as the final percentage.
```

Python Function, Nested if-else, Arguments and parameter, Return statement [In Class] — due 2026-10-03 15:02

Basic Greater or Smaller — 20/20 XP — SOLVED — deadline 2026-10-03 15:02

Topics: Python Function, Nested if-else, Python if- else

URL: https://my.newtonschool.co/playground/code/poxmks7bvp48

Back

Basic Greater or Smaller

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Basic Greater or Smaller

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given two functions:

greater(a, b) → prints the greater of two integers a and b.

smaller(a, b) → prints the smaller of two integers a and b.

Note: You should call these functions as required

Write a program that takes:

A single character input: "G" for greater or "S" for smaller

Two space-separated integers

Task:

If the character is "G", print the greater of the two numbers .

If the character is "S", print the smaller of the two numbers .

```
Input

The first line contains choice: A single character, either "G" or "S"

The second line contains a, b: Two space-separated integers

a!=b

Output

Print the greater or smaller of the two numbers as per input constraints.




Constraints

a, b are integers between -10⁴ and 10⁴

The first input is guaranteed to be "G" or "S"

Example

Input

G

4 9


Output

9


Explanation

"G" means print the greater number.

Between 4 and 9, the greater is 9, so the output is 9
```

Basic Greater or Smaller-2 — 20/20 XP — SOLVED — deadline 2026-10-03 15:02

Topics: Python Function, Nested if-else, Python if- else

URL: https://my.newtonschool.co/playground/code/xb23mpkn7y8m

Back

Basic Greater or Smaller-2

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Basic Greater or Smaller-2

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Write a program that takes:

A single character input: "G" for greater or "S" for smaller

Two space-separated integers

Task:

If the character is "G", print the greater of the two numbers using the greater() function.

If the character is "S", print the smaller of the two numbers using the smaller() function.

You are supposed to implement two functions:

greater(a, b) → Gives greater of two integers a and b.

smaller(a, b) → Gives smaller of two integers a and b.

Note: You should implement and then call these functions as required.

```
Input

The first line contains choice: A single character, either "G" or "S"

The second line contains a, b: Two space-separated integers

Output

Print the greater or smaller of the two numbers using the given functions.


Constraints

a, b are integers between -10⁴ and 10⁴

The first input is guaranteed to be "G" or "S"

Example

Input

G

4 9


Output

9


Explanation

"G" means print the greater number.

Between 4 and 9, the greater is 9, so the output is 9
```

Greater of Three — 20/20 XP — SOLVED — deadline 2026-10-03 15:02

Topics: Python Function, Nested if-else, Python if- else

URL: https://my.newtonschool.co/playground/code/hyytojgv0yno

Back

Greater of Three

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Greater of Three

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given three integers a, b, and c.

A built-in function greater(x, y) is available to you. It returns the greater of the two values x and y.

Your task is to find the greatest among the three given numbers using the greater() function.

Note: You must use the provided greater() function. Do not compare all three numbers directly.

Input

The first line contains three space-separated integers a, b, and c.

Output

Print a single integer — the greatest among the three numbers.

Constraints

1 ≤ a, b, c ≤ 103

```
Example

Example 1

Input

10 25 15

Output

25


Example 2

Input

5 2 8

Output

8
```

Subject Grades — 20/20 XP — SOLVED — deadline 2026-10-03 15:02

Topics: Python Function, Nested if-else, Python if- else

URL: https://my.newtonschool.co/playground/code/xjpuonh5dgrn

Back

Subject Grades

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Subject Grades

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given the marks obtained in three subjects as integers: A, B, and C.

Your task is to call the predefined function GetGrade(marks) for each subject’s marks. The function returns the grade (a string) corresponding to the given marks.

Print the grade of each subject on a new line, in the order of A, B, and C.

Note: You do not need to define the GetGrade() function. It is already provided.

Input

The first line of input contains a single integer, representing A.

The second line contains an integer B.

The last line of input contains an integer C.

Output

You have to print the grade for each subject on a new line.

Constraints

0

≤

A

≤

100

0≤A≤100

0

≤

B

≤

100

0≤B≤100

0

≤

C

≤

100

0≤C≤100

Example

Input

99

84

45

Output

A

B

E

Explanation

The marks for the three subjects are 99, 84, and 45 respectively.

The grade for marks = 99, is A.

The grade for marks = 84, is B.

```
The grade for marks = 45, is E.
```

Python Function, Nested if-else, Arguments and parameter, Return statement [Post Class] — due 2026-10-03 16:00

Bridge Between Villages -2 — 20/20 XP — SOLVED — deadline 2026-10-03 16:00

Topics: Python Function, Nested if-else, Python logical Operators, Return statement, Arguments and parameter

URL: https://my.newtonschool.co/playground/code/wuioa3508kse

Back

Bridge Between Villages -2

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Bridge Between Villages -2

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

In a rural district, three villages — Raga, Sora, and Tula — are planning to connect to each other with straight bridges. The government has provided the proposed lengths for these bridges as follows:

Raga to Sora: a kilometers

Sora to Tula: b kilometers

Tula to Raga: c kilometers

You are required to implement the function is_triangle(a, b, c) that returns "YES" or "NO" depending on whether the given bridge lengths can form a valid triangle.

Function Signature:

def is_triangle(a, b, c): which takes three parameters: a: represents proposed length from Raga to Sora, b: represents proposed length from Sora to Tula, c: represents proposed length from Tula to Raga

Input

User Task

As this is a functional problem, there is no need to handle input from the user. Your task is to

complete the function is_triangle(a, b, c), which takes three parameters: a: represents proposed length from Raga to Sora, b: represents proposed length from Sora to Tula, c: represents proposed length from Tula to Raga

Custom Input

Input consist of single line that contains three space-separated positive integers:

a b c

Output

Return YES if the construction plan can go ahead, otherwise return NO.

Constraints

1 ≤ a, b, c ≤ 104

Example

Input:

6 7 10

Output:

YES

Explanation

The bridge lengths are (6, 7, 10) which satisfy

6 + 7 > 10 (13 > 10), 7 + 10 > 6 (17 > 6), and 10 + 6 > 7 (16 > 7).

Since all pairs of bridges can connect to enclose a region, the output is "YES".

Input:

3 5 8

Output:

NO

Explanation

The bridge lengths are(3, 5, 8) not follows the below condition

```
3 + 5 > 8 → 8 > 8 (False).

5 + 8 > 3 -> 13 > 3 (True)

3 + 8 > 5 -> 11 > 5 (True)

Since one condition is False, bridges cannot enclose a region; the output is "NO".
```

Calculate Electricity Bill - 2 — 20/20 XP — SOLVED — deadline 2026-10-03 16:00

Topics: Return statement, Arguments and parameter

URL: https://my.newtonschool.co/playground/code/5r6xhlhs40lc

Back

Calculate Electricity Bill – 2

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Calculate Electricity Bill – 2

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

An electricity board calculates monthly power usage bills based on the number of units consumed using a slab-wise tariff system. Each slab charges a different rate per unit as follows:

First 100 units: ₹4 per unit

Next 100 units (i.e., units 101–200): ₹5 per unit

Next 100 units (i.e., units 201–300): ₹6 per unit

Next 100 units (i.e., units 301–400): ₹7 per unit

Units above 400: ₹8 per unit

After calculating the base bill, a 10% surcharge is added to the total bill.

You are required to implement the function calculate_bill(units) that calculates the total electricity bill including the surcharge, and returns a float rounded to 1 decimal place using the built-in round() function.

Function Signature:

def calculate_bill(units): which takes single parameter: units: represents the number of electricity units consumed.

Input

User Task

As this is a functional problem, there is no need to handle input from the user. Your task is to complete the function calculate_bill(units), which takes single parameter: units: represents the number of electricity units consumed.

Custom Input

A Single line containing an integer representing the number of units.

Output

Return a float – the total electricity bill including the 10% surcharge, rounded to 1 decimal place using round().

Example

Input

1

Output

Electricity Bill: Rs. 4.4

Explanation

Units are less than 100 therefore total cost is unit charge + surcharge 4 X 1 + 4 X 0.1 = 4.4

Input

100

Output

Electricity Bill: Rs. 440.0

Explanation

Units are equal to 100 therefore total cost is unit charge + surcharge 4 X 100 + 400 X 0.1 = 440.0

Input

340

Output

Electricity Bill: Rs. 1958.0

```
Explanation

For the first 100 units(i.e from 1 to 100) cost will be: 100*4 = 400

For next 100 units(i.e from 101 to 200) cost will be: 100*5 = 500

For next 100 units(i.e from 201 to 300) cost will be: 100*6 = 600

For remaining 40 units(i.e from 301 to 340) cost will be: 40*7 = 280

Total Cost excluding surcharge = 400 + 500 + 600 + 280 = 1780

Final Bill including 10% surcharge on Total cost = 1780 + (1780*0.1) = 1780 + 178 = 1958
```

Smart Conditional Calculator — 20/20 XP — SOLVED — deadline 2026-10-03 16:00

Topics: Return statement, Arguments and parameter

URL: https://my.newtonschool.co/playground/code/e66cy6dbjxgb

Back

Smart Conditional Calculator

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Smart Conditional Calculator

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given two integers. Your task is to implement a smart calculator that chooses the arithmetic operation based on the parity (even/odd nature) of the two numbers.

Rules:

If both numbers are even, return their sum.

If both numbers are odd, return their product.

If one number is even and the other is odd, return the absolute difference between the two (i.e., subtract the smaller from the larger).

🔧 Task

Write the function definition for smart_calculator(a, b). This means:

✅ You must write the function header (starting with def)

✅ You must also write the function body with correct logic

❌ Do not write any code for input or output (e.g., no input() or print() statements)

Input

User Task

As this is a functional problem, there is no need to handle input from the user. Your task is to complete the function definition smart_calculator(a, b), which takes two parameters:

a: an integer

b: an integer

Custom Input

A Single line containing two space-separated integers:

a and b, representing the two numbers to process.

Output

Return single integer representing the result of the operation.

Constraints

$-10^4 \leq a, b \leq 10^4$

Example

Input

4 8

Output

12

Explanation

Both numbers are even → 4 + 8 = 12

Celsius to Fahrenheit Conversion - 2 — 20/20 XP — SOLVED — deadline 2026-10-03 16:00

Topics: Return statement, Arguments and parameter

URL: https://my.newtonschool.co/playground/code/haikjdpg2f4e

Back

Celsius to Fahrenheit Conversion – 2

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Celsius to Fahrenheit Conversion – 2

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given an integer, representing the temperature in celsius.

Your task is to convert it to Fahrenheit, using the below given formula:

Fahrenheit = (Celsius × 9 / 5) + 32

You must complete the function celsius_to_fahrenheit(celsius) that returns the equivalent temperature in Fahrenheit.

Function Signature:

def celsius_to_fahrenheit(celsius):

It takes a single parameter, celsius, the temperature in Celsius.

Input

User Task

As this is a functional problem, there is no need to handle input from the user. Your task is to complete the function celsius_to_fahrenheit(celsius), which takes single parameter, celsius, the temperature in celsius.

Custom Input

The first and only line of input contains a single integer, celsius, representing the temperature in celsius.

Output

Return the corresponding temperature in Fahrenheit (as a float).

```
Constraints

−100 ≤ celsius ≤ 100

Example

Input

0

Output

32.0

Explanation

Input Celsius = 0

Fahrenheit = (0 × 9/5) + 32 = 0 + 32 = 32.0

So the output is 32.0.


Input

37

Output

98.6

Explanation

Input Celsius = 37

Fahrenheit = (37 × 9/5) + 32 = 98.6

So the output is 98.6.
```

Python if- else, Python logical Operators [In Class] — due 2026-10-05 10:55

Leap Year or Not ? — 20/40 XP — SOLVED — deadline 2026-10-05 10:55

Topics: Python if- else

URL: https://my.newtonschool.co/playground/code/mpbp2fcg56oh

Back

Leap Year or Not ?

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Leap Year or Not ?

Medium

20/40

Time Limit: 2, Memory Limit: 256000

A leap year occurs every 4 years, with some exceptions. But you don’t need to worry about the logic — we’ve already written the leap year checker function for you.

Your task is to use the pre-defined function and print whether the given year is a leap year or not.

Your task:

Take an integer input year

Call the function is_leap(year)

If it returns True, print Leap Year

If it returns False, print Not a Leap Year

Note: Use only the pre-defined functions provided as comments in the starter code.

Input

The first and only line of input contains a single integer, representing the year.

Output

If the input year is leap year, print "Leap Year", else print "Not a Leap Year".

Constraints

0

≤

y

e

a

r

≤

3

∗

1

0

3

0≤year≤3∗10

3

Example

Input

0

Output

Leap Year

Input

2003

Output

Not a Leap Year

Great Dragon Tournament. — 20/40 XP — SOLVED — deadline 2026-10-05 10:55

Topics: Python if- else

URL: https://my.newtonschool.co/playground/code/eni755r2q5o3

Back

Great Dragon Tournament.

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Great Dragon Tournament.

Medium

20/40

Time Limit: 2, Memory Limit: 256000

In the Great Dragon Tournament, every dragon is judged based on two attributes:

Power (how strong the dragon’s attack is)

Stamina (how long the dragon can endure a fight)

The judges decide each dragon’s category based on these two values.

BALANCED – If power is equal to stamina.

OVERPOWERED – If power is at least twice the stamina.

UNBREAKABLE – If stamina is at least twice the power.

MIGHTY – If power is greater than stamina, but less than double.

ENDURING – If stamina is greater than power, but less than double.

Your task is to complete the function dragon_category(power, stamina) that returns the correct category of the dragon based on the given values of power and stamina.

Note: You don't need to print anything, just return the final output from the function. You don't have to take any input.

Input

The first line contains an integer power.

The second line contains an integer stamina.

Note: The input section shown is only for debugging purposes. You don’t need to explicitly take input in your code. It simply illustrates the format in which inputs should be provided when creating your own test cases.

Output

The correct category of the dragon.

Constraints

1

≤

p

o

w

e

r

≤

1000

1≤power≤1000

1

≤

s

t

a

m

i

n

a

≤

1000

1≤stamina≤1000

Example

Input

500

500

Output

BALANCED

Explanation

Here, the power of dragon is equal to stamina, i.e. 500.

Therefore, the correct category of dragon is BALANCED.

Function Based Calculator. — 20/40 XP — SOLVED — deadline 2026-10-05 10:55

Topics: Python if- else

URL: https://my.newtonschool.co/playground/code/16km8rga31m7

Back

Function Based Calculator.

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

Try AI Plan Mode

QUESTION

Function Based Calculator.

Medium

2x

80/80

Time Limit: 2, Memory Limit: 256000

You are building a calculator — but this time, you're not allowed to use direct arithmetic operators.

All the arithmetic operations have already been defined as functions in the code for you.

Your Task:

Read two integers and one operator symbol from the input

Based on the operator, call the appropriate function

Print the result returned by that function

If the operator is invalid (other than ' + ' , ' - ' , ' * ', , ' // ', ' % ') for this question , print Invalid Operator

Note: Do not use arithmetic operators directly in your code. Use only the pre-defined functions provided as comments in the starter code.

Input

The first line of input contains two space-separated integers, representing A and B.

The second line contains a string op, representing the operation to perform.

Output

A single line — the result of the operation, or Invalid Operator if the symbol is not supported.

Note: Use pre-defined functions.

Constraints

–

1

0

3

≤

A

,

B

≤

1

0

3

−10

3

≤A,B≤10

3

B

≠

0

B

=0, for op = '/' or '%'

Example

Input

20 10

+

Output

30

Input

```
5 3

^

Output

Invalid Operator
```

Python if- else, Python logical Operators [In Class] — due 2026-10-05 17:03

NST Library — 60/60 XP — SOLVED — deadline 2026-10-05 17:03

Topics: Python Function, Nested if-else, Python if- else

URL: https://my.newtonschool.co/playground/code/4jzfl2d9wjpa

Back

NST Library

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

NST Library

Hard

2x

60/60

Time Limit: 2, Memory Limit: 256000

You are tasked with implementing a library rental system that calculates the rental fee for a single book based on specific criteria.

The rental fee is calculated according to the following rules:

Rental Duration:

If the rental duration is between 1 and 3 days, the daily fee is 1 Rupee per day.

If the rental duration is between 4 and 7 days, the daily fee is 0.75 Rupees per day.

If the rental duration is 8 days or more, the daily fee is 0.50 Rupees per day.

If the rental duration is 0 days or negative, output Invalid rental duration.

Book Type:

1 for New Release (add a surcharge of 2 Rs to the total fee).

2 for Classic (apply a discount of 10% on the total fee).

3 for Children’s Book (no additional charge or discount).

Membership Status:

1 for Premium (apply an additional 10% discount on the total fee).

2 for Basic (no changes are applied).

Note: The rental fee should be calculated in the given order only. Also, typecast the final amount to integer before printing.

Input

The first line contains an integer days representing the number of days the book was rented.

The second line contains an integer book representing the type of book.

The third line contains an integer status representing the membership status.

Output

Print a single line containing either the calculated rental amount or the message Invalid rental duration.

Constraints

−

10

≤

d

a

y

s

≤

10

−10≤days≤10

1

≤

b

o

o

k

≤

3

1≤book≤3

1

≤

s

t

a

t

u

s

≤

2

1≤status≤2

Example

Input

4

1

1

Output

4

Explanation:

The daily fee is 0.75 rupees for rentals between 4 and 7 days.

For 4 days, the base fee is calculated as 4 × 0.75 = 3 rupees.

Since the book type is a New Release, a surcharge of 2 rupees is added, bringing the total to 5 rupees.

With a Premium membership, a discount of 10% applies.

The discount on 5 rupees is 0.5, so the adjusted amount becomes 4.5 rupees.

After typecasting the final value to an integer, the result becomes 4.

Input

-1

2

2

Output

```
Invalid rental duration
```

Python if- else, Python logical Operators [Post Class] — due 2026-10-05 20:35

Movie Mania — 20/20 XP — SOLVED — deadline 2026-10-05 20:35

Topics: Python Function, Nested if-else

URL: https://my.newtonschool.co/playground/code/cnbbqdvnjjr6

Back

Movie Mania

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Movie Mania

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Four movies were released: Spiderman, Superman, Batman, and Aquaman in four distinct years given as four space-separated integers: year1, year2, year3, and year4 respectively.

Movie

Release year

Spiderman year1

Superman year2

Batman year3

Aquaman year4

You are required to print the name of the movie that was released earliest of the four.

Note-1: Refer Input section, output section and example test cases.

Note-2: Use of built-in mathematical functions is strictly prohibited in this question.

Input

The first and only line of input contains four distinct space separated integers year1, year2, year3, and year4 representing the years of release of the corresponding movies given in the problem statement.

Output

Print a single line representing the name of the movie which was released earliest.

Constraints

The values

year1

,

year2

,

year3

,

year4

year1,year2,year3,year4 represent four distinct years.

Each year satisfies the condition

1

≤

year

i

≤

4000

1≤year

i

≤4000 for

i

∈

{

1

,

2

,

3

,

```
4

}

i∈{1,2,3,4}.

Example

Input:

2014 2015 2019 1989



Output:

Aquaman



Explanation:

1989, the 4th number, is the minimum and the earliest year among the given years, and hence the
movie corresponding to it, Aquaman, is the answer.
```

Will Ramandeep Sir Fly? - 2 — 20/20 XP — SOLVED — deadline 2026-10-05 20:35

Topics: Python Function, Nested if-else

URL: https://my.newtonschool.co/playground/code/7lor16gzent8

Back

Will Ramandeep Sir Fly? – 2

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Will Ramandeep Sir Fly? – 2

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Ramandeep Sir is known for his highly selective flying decisions after past flight troubles. He follows a strict set of rules before agreeing to board a plane.

Here are his conditions:

If the trip is international, Ramandeep Sir will not fly, regardless of any other conditions.

If the trip is domestic, and the flight duration is less than or equal to 1.5 hours, he will fly.

If the trip is domestic and the duration is more than 1.5 hours, he will not fly if:

His seat is a middle seat, or

The airline is IngidoX

In all other cases, he will fly.

Your task is to determine whether Ramandeep Sir will fly given the flight details.

Input

The input consists of four lines:

The first line contains a floating-point number d — the duration of the flight in hours.

The second line contains a string seat_type — one of "window", "middle", or "aisle".

The third line contains a string airline — the airline name (case-sensitive, no spaces).

The fourth line contains a string trip_type — either "domestic" or "international".

Output

Print a single line as following:

Ramandeep Sir will fly — if he agrees to board the flight.

Ramandeep Sir will not fly — otherwise.

Note: Output must exactly match the above (case-sensitive, no extra spaces).

Constraints

0.5 ≤ d ≤ 10.0

0.5≤d≤10.0

seat_type ∈ {"window", "middle", "aisle"}

airline is a non-empty string with no whitespace

trip_type ∈ {"domestic", "international"}

Example

Example 1:

Input:

```
2.0

middle

IngidoX

international


Ouput:

Ramandeep Sir will not fly


Example 2:

Input:

1.0

middle

IngidoX

domestic


Ouput:

Ramandeep Sir will fly
```

NST Bus Route Optimization — 20/20 XP — SOLVED — deadline 2026-10-05 20:35

Topics: Python Function, Nested if-else

URL: https://my.newtonschool.co/playground/code/2kxfo1p28ay2

Back

NST Bus Route Optimization

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

NST Bus Route Optimization

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

The bus driver at NST Campus is planning his daily pickup route. He needs to pick up students from two hostels: Hostel 1 and Hostel 2, and return to the NST campus afterward. To save fuel, he wants to choose the route that results in the minimum total distance traveled.

There are three roads available:

A road of length d1 connects the NST campus and Hostel 1

A road of length d2 connects the NST campus and Hostel 2

A road of length d3 directly connects Hostel 1 and Hostel 2

The driver can travel on any road any number of times, and in any direction. He must start at NST campus, pick up students from both hostels, and return back to the campus, while minimizing the total distance.

Please refer to the following image for further clarity:

Click to enlarge

Input

A single line contains three integers:

d1 — the distance between NST campus and Hostel 1

d2 — the distance between NST campus and Hostel 2

d3 — the distance between Hostel 1 and Hostel 2

Output

Print a single integer — the minimum total distance the bus must travel.

Constraints

1 ≤ d_1, d_2, d_3 ≤ 10

8

Example

Example 1:

Input

4 6 2

Output

12

```
Explanation:

Try all possible loops:

Campus → Hostel 1 → Hostel 2 → Campus: 4 + 2 + 6 = 12

Campus → Hostel 2 → Hostel 1 → Campus: 6 + 2 + 4 = 12

Campus → Hostel 1 → Campus → Hostel 2 → Campus: 4 + 4 + 6 + 6 = 20, not minimal


So, minimum = 12




Example 2:

Input

2 2 8


Output

8
```

Museum Ticket Booking System — 20/20 XP — SOLVED — deadline 2026-10-05 20:35

Topics: Python Function, Nested if-else, Python if- else

URL: https://my.newtonschool.co/playground/code/ty9vjaz6iw3s

Back

Museum Ticket Booking System

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Museum Ticket Booking System

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are tasked with implementing the function calculateTicketPrice for a Museum Ticket Booking system.

The function should calculate the ticket price based on the following rules:

The base ticket price is $12.

If the visitor is under 12 years old, apply a discount of $5.

If the visit is on a weekend, add a surcharge of $3.

If the visitor has a student card, apply an additional discount of $2.

The function calculateTicketPrice accepts the following parameters:

age (number) – The age of the visitor.

isWeekend (boolean) – true if the visit is on a weekend, otherwise false.

hasStudentCard (boolean) – true if the visitor has a student card, otherwise false.

Your task is to return the final ticket price after applying all applicable discounts and surcharges.

Input

The first line contains an integer age — the age of the visitor.

The second line contains a boolean isWeekend — true if the visit is on a weekend, otherwise false.

The third line contains a boolean hasStudentCard — true if the visitor has a student card, otherwise false.

Output

Return a single integer representing the final ticket price.

Constraints

1

≤

a

g

e

≤

100

1≤age≤100

Example

Example

Input

23

true

false

Output

15

Explanation

Base ticket price = 12.

```
The visitor is 23 years old, so no age discount is applied.

The visit is on a weekend, so 3 is added to the ticket price.

The visitor does not have a student card, so no student discount is applied.



Therefore, the final ticket price is 15.
```

Greater of Four — 20/20 XP — SOLVED — deadline 2026-10-05 20:35

Topics: Python Function, Nested if-else, Python if- else

URL: https://my.newtonschool.co/playground/code/ympu0ctxfxs1

Back

Greater of Four

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Greater of Four

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given four integers a, b, c, and d.

A built-in function greater(x, y) is available to you. It returns the greater of the two values x and y.

Your task is to find the greatest among the four given numbers using the greater() function.

Note: You must use the provided greater() function. Do not compare all four numbers directly.

Input

The first line contains four space-separated integers a, b, c, and d.

Output

Print a single integer — the greatest among the four numbers.

Constraints

1 ≤ a, b, c, d ≤ 103

```
Example

Example 1

Input

10 25 15 24

Output

25


Example 2

Input

5 2 8 7

Output

8
```

PSP Contest 2 [Contest] — due 2026-10-09 11:45

Find the remainder — 40/40 XP — SOLVED — deadline 2026-10-09 11:45

Topics: Python Arithmetic operators

URL: https://my.newtonschool.co/playground/code/wrtaigg345ws

Back

Find the remainder

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Find the remainder

Easy

2x

40/40

Time Limit: 2, Memory Limit: 256000

You are given two numbers a and b. Find the remainder when a is divided by b.

Input

The first line contains integer a.

The second line contains integer b.

Output

Print the remainder when a is divided by b.

Constraints

0

≤

a

≤

200

$0 \le a \le 200$

1

≤

b

≤

200

```
1≤b≤200




Example

Input

9

7

Output

2

Explanation

When we divide 9 by 7, we get 2 as remainder.

Therefore, ans = 2.
```

The Frame — 40/40 XP — SOLVED — deadline 2026-10-09 11:45

Topics: Python if- else

URL: https://my.newtonschool.co/playground/code/bb3jyl2rf4tp

Back

The Frame

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

The Frame

Easy

2x

40/40

Time Limit: 2, Memory Limit: 256000

In the annual design festival of a small town, a young engineer is given four wooden pieces to create the frame of a special display panel.

Each piece is straight and has a fixed length. The engineer is not allowed to cut, break or bend any of the pieces. All four pieces must be used exactly once.

The display panel is supposed to have a perfectly balanced shape. This means that its four sides must have exactly the same length, and the four pieces must be arranged so that they form a proper square.

The engineer has received the lengths of the four available pieces. Determine whether the four pieces can be arranged to form the required shape.

Input

The input contains a single line with four integers a, b, c, and d, representing the lengths of the four wooden pieces.

$1 \le a, b, c, d \le 10$

All four pieces must be used.

No piece can be cut, bent, broken, or modified.

Output

Print YES if the four pieces can be arranged to form a square.

Otherwise, print NO.

Constraints

1 ≤ a , b , c , d ≤ 10

1≤a,b,c,d≤10

All four pieces must be used exactly once.

The pieces cannot be modified in any way.

Example

Example 1

Input:

1 2 3 4

Output:

NO

Explanation:

The four pieces have different lengths, so they cannot form desired shape.

Example 2

Input:

5 5 5 5

```
Output:

YES


Explanation:

All four pieces have the same length. Therefore, they can be arranged as the desired shape.
```

Function Based Calculator. — 80/80 XP — SOLVED — deadline 2026-10-09 11:45

Topics: Python if- else

URL: https://my.newtonschool.co/playground/code/16km8rga31m7

Back

Function Based Calculator.

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

Try AI Plan Mode

QUESTION

Function Based Calculator.

Medium

2x

80/80

Time Limit: 2, Memory Limit: 256000

You are building a calculator — but this time, you're not allowed to use direct arithmetic operators.

All the arithmetic operations have already been defined as functions in the code for you.

Your Task:

Read two integers and one operator symbol from the input

Based on the operator, call the appropriate function

Print the result returned by that function

If the operator is invalid (other than ' + ' , ' - ' , ' * ', , ' // ', ' % ') for this question , print Invalid Operator

Note: Do not use arithmetic operators directly in your code. Use only the pre-defined functions provided as comments in the starter code.

Input

The first line of input contains two space-separated integers, representing A and B.

The second line contains a string op, representing the operation to perform.

Output

A single line — the result of the operation, or Invalid Operator if the symbol is not supported.

Note: Use pre-defined functions.

Constraints

–

1

0

3

≤

A

,

B

≤

1

0

3

−10

3

≤A,B≤10

3

B

≠

0

B

=0, for op = '/' or '%'

Example

Input

20 10

+

Output

30

Input

```
5 3

^

Output

Invalid Operator
```

Calculate Final Price — 40/80 XP — SOLVED — deadline 2026-10-09 11:45

Topics: Datatypes & Variables, Functions (DSA), Python Arithmetic operators

URL: https://my.newtonschool.co/playground/code/8eaek8eib11u

Back

Calculate Final Price

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Calculate Final Price

Medium

40/80

Time Limit: 2, Memory Limit: 256000

Riya is shopping for a new product. The product has an original price, but she receives a discount on it. After applying the discount, a tax is added to the discounted price.

Given the original price, discount percentage, and tax percentage, define and implement the following function to calculate the final price:

```
def final_price(price, discount, tax):
```

The function should calculate the final price and return the result. The returned value must then be stored and printed outside the function.

Steps to be followed:

Use the function signature def final_price(price, discount, tax):.

The function must return the final price.

Do not print the result inside the function.

Take input and call the function outside the function.

Store the returned value in a variable and print it outside the function.

Input

The input consists of three lines:

The first line contains a integer number price, representing the original price.

The second line contains a integer number discount, representing the discount percentage.

The third line contains a integer number tax, representing the tax percentage.

Output

Print a single floating number representing the final price.

Constraints

1 ≤ price ≤ 100000

0 ≤ discount ≤ 100

0 ≤ tax ≤ 100

Example

Input 1:

1000

10

5

Output 1:

945.0

Explanation:

The original price is 1000.

```
After a 10% discount, the price becomes 900.

A 5% tax is then added to this discounted price.

The final price is 945.0.


Input 2:


2000

20

10


Output 2:


1760.0


Explanation:


The original price is 2000.

After a 20% discount, the price becomes 1600.

A 10% tax is then added to this discounted price.

The final price is 1760.0
```

The Gatekeeper — 0/80 XP — NOT SOLVED — deadline 2026-10-09 11:45

Topics: If- elif-else ladder

URL: https://my.newtonschool.co/playground/code/1dja9ovexna6

Back

The Gatekeeper

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

The Gatekeeper

Medium

0/80

Time Limit: 2, Memory Limit: 256000

Write a Python program to simulate a simple login system.

Login Details:

The correct username is admin.

The correct password is password123.

The program should take two inputs from the user:

username

password

Based on the input, the program should print:

Login successful – if both the username and password are correct.

Check username or password – if only one of them is correct.

Invalid credentials – if both are incorrect.

Input

The first line contains a string representing the username.

The second line contains a string representing the password.

Output

Print a single line containing one of the following message based on the entered credentials:

Login successful – if both the username and password are correct.

Check username or password – if only one of them is correct.

Invalid credentials – if both are incorrect.

Example

Sample 1:

Input:

admin

password123

Output:

Login successful

Explanation:

Both the entered username (admin) and password (password123) match the correct credentials.

Hence, the program prints Login successful.

Sample 2:

Input:

admin

wrongpass

Output:

Check username or password

```
Explanation:


The username is correct (admin), but the password (wrongpass) is incorrect.

Since only one of the credentials is correct, the output is Check username or password.
```

Newton and Rounding — 0/120 XP — NOT SOLVED — deadline 2026-10-09 11:45

Topics: Python Arithmetic operators

URL: https://my.newtonschool.co/playground/code/6h902kkag1my

Back

Newton and Rounding

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Newton and Rounding

Hard

0/120

Time Limit: 2, Memory Limit: 256000

Newton has a non-negative integer n. He wants to round it to the nearest multiple of 10.

If n already ends with 0, it is already rounded.

If the last digit is 1–4, move to the lower multiple of 10.

If the last digit is 6–9, move to the higher multiple of 10.

If the last digit is 5, always move to the lower multiple of 10.

Your task is to find and print the number Newton will round to.

Input

A single integer n — the number that Newton has.

Output

Print the result of rounding n.

Constraints

0

≤

n

≤

5000

0≤n≤5000

Example

Input

5

Output

0

Explanation

Normally, 5 could be rounded to 0 or 10, but as per the problem rule, when n = 5, always output 0.

Input

113

Output

110

Explanation

113 is closer to 110 than 120, so the rounded number is 110.

Input

2359

Output

2360

Explanation

2359 is closer to 2360 than 2350, so it rounds up.

Grade Report — 0/80 XP — NOT SOLVED — deadline 2026-10-09 11:45

Topics: Functions (DSA)

URL: https://my.newtonschool.co/playground/code/go5ltf2xj034

Back

Grade Report

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Grade Report

Medium

0/80

Time Limit: 2, Memory Limit: 256000

You are given marks in three subjects. Your task is to determine the student's grade.

Complete the following function:

```
def get_grade(mark1, mark2, mark3):
    # Write your code here
```

Rules

If marks in any subject are below 40, return Fail.

Otherwise, calculate the percentage out of 300.

Grade based on percentage:

90% and above → A+

75% to below 90% → A

60% to below 75% → B

40% to below 60% → C

Note

You only need to complete get_grade().

You do not need to take input or print anything.

The function should return the grade (A+, A, B, C, or Fail).

Input

The first line contains an integer mark1, representing marks obtained in the first subject.

The second line contains an integer mark2, representing marks obtained in the second subject.

The third line contains an integer mark3, representing marks obtained in the third subject.

Output

The output should contain the final grade returned by the get_grade(mark1, mark2, mark3) function.

The grade will be one of A+, A, B, C, or Fail.

Constraints

0 ≤ mark1, mark2, mark3 ≤ 100

Example

Example 1

Input

95

92

88

Output

A+

Explanation

The student scores at least 40 in all subjects. The total is 275 out of 300, giving a percentage of 91.7%. Therefore, the grade is A+.

Example 2

Input

80

90

70

Output

A

Explanation

The student passes all three subjects. The total is 240 out of 300, giving a percentage of 80.0%. Therefore, the grade is A.

Example 3

Input

```
75

35

80


Output


Fail


Explanation



The student scored below 40 in one subject (35), so the final grade is Fail.
```

Nested if-else [In Class] — due 2026-10-10 10:43

Palindrome with Digit Validation — 20/20 XP — SOLVED — deadline 2026-10-10 10:43

Topics: Nested if-else

URL: https://my.newtonschool.co/playground/code/0paxymnbok5k

Back

Palindrome with Digit Validation

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Palindrome with Digit Validation

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Write a program that take an integer number n and an integer digit d, then prints one of these messages based on the conditions below:

1. If n is a palindrome and its last digit is d:

    "Number is palindrome and last digit is d"

2. If n is a palindrome but its last digit is not d:

    "Number is palindrome and last digit is not d"

3. If n is not a palindrome:

    "Number is not a palindrome"

Note:

Use the provided isPalindrome(n) function returns True or False. Do not rewrite it.

A palindrome number is a number that reads the same backward as forward.

Examples: 121, 1331, 44444

Numbers that are not palindrome do not read the same backward.

Examples: 123, 4567, 1201

Input

The Input will be the two space-separated integers n and d.

Output

The output will be the string message as per the problem description.

Constraints

1 <= n <= 1000

1 <= d <= 9

Example

Input 1:

121 1

Output 1:

Number is palindrome and last digit is 1

Explanation:

121 is palindrome and last digit in 121 is d as well

so print "Number is palindrome and last digit is 1"

Input 2:

121 3

Output 2:

Number is palindrome and last digit is not 3

Explanation:

121 is palindrome but last digit in 121 is not d that is 3,

so print "Number is palindrome and last digit is not 3"

Input 3:

123 3

```
Output 3:

Number is not a palindrome


Explanation:

123 is not even palindrome so we don't check for last digit

just print Number is not a palindrome
```

NewForces Ratings Calculator — 60/60 XP — SOLVED — deadline 2026-10-10 10:43

Topics: Nested if-else

URL: https://my.newtonschool.co/playground/code/vm6i10bc0it6

Back

NewForces Ratings Calculator

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

NewForces Ratings Calculator

Hard

2x

60/60

Time Limit: 2, Memory Limit: 256000

In the Newforces contest, participants ratings can increase or decrease based on the contest type they participate in and whether they hack any solutions. The new rating is calculated based on following rules:

Rules based on Rating Criteria:

If the participant's rating is below 1200:

Div. 1 (Type 1): Rating increases by 200 points.

Div. 2 (Type 2): Rating increases by 80 points.

Educational (Type 3): Rating increases by 50 points.

If the participant's rating is between 1200 and 2000 (inclusive):

Div. 1 (Type 1): Rating increases by 100 points.

Div. 2 (Type 2): Rating remains the same.

Educational (Type 3): Rating decreases by 30 points.

If the participant's rating is above 2000:

Div. 1 (Type 1): Rating increases by 50 points.

Div. 2 (Type 2): Rating decreases by 30 points.

Educational (Type 3): Rating decreases by 100 points.

Rules based on whether the user has hacked any solution or not:

If the user has hacked any solution: Applies a further increase of 50 points to the rating.

Did Not Hack: No additional change is applied.

Note: Please check input format for more details

Input

The input consists of three lines:

r — an integer representing the current rating of the participant

t — an integer representing the contest type:

1 → Div. 1

2 → Div. 2

3 → Educational

h — an integer indicating hacking status:

1 → Hacked at least one solution

2 → Did not hack any solution

Output

Print a single integer — the new rating of the participant after considering both contest type and hacking bonus (if any).

Constraints

$1100 \le r \le 2100$

$t \in \{1, 2, 3\}$

$h \in \{1, 2\}$

Example

Example 1

Input:

1100

1

1

Output:

1350

```
Explanation:

Rating < 1200, contest is Div. 1 → +200

Hacked a solution → +50

Final rating = 1100 + 200 + 50 = 1350


------------------------------------------------------------


Example 2

Input:

1500

3

2


Output:

1470


Explanation:

Rating is between 1200 and 2000, contest is Educational → −30

Did not hack → no bonus

Final rating = 1500 − 30 = 1470
```

Recursion Mechanism, Iteration in Python, Range () function [In Class] — due 2026-10-12 10:50

Find the Sum of Numbers in Range L to R — 20/20 XP — SOLVED — deadline 2026-10-12 10:50

Topics: Recursion, Range () function

URL: https://my.newtonschool.co/playground/code/l3psf4gfskvg

Back

Find the Sum of Numbers in Range L to R

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Find the Sum of Numbers in Range L to R

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Write a program that takes two integers, L and R, as input and calculates the sum of all numbers from L to R inclusive.

Input

The first line of input contains a single integer L.

The second line of input contains a single integer R.

Output

Print an integer, representing the sum of all numbers from L to R inclusive.

Constraints

1

≤

L

≤

R

≤

100

1≤L≤R≤100

Example

Input

5

10

```
Output

45

Explanation

Numbers in range 5 to 10 are: 5, 6, 7, 8, 9, 10. And their sum is 45.


Input

5

5

Output

5
```

Recursion Mechanism, Iteration in Python, Range () function [In Class] — due 2026-10-17 11:03

Multiplication Table of N — 20/20 XP — SOLVED — deadline 2026-10-17 11:03

Topics: For Loop, Recursion

URL: https://my.newtonschool.co/playground/code/m5pmhpi8obpm

Back

Multiplication Table of N

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Multiplication Table of N

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Given a positive integer N, your task is to print the multiplication table of N from 1 to 10.

Each line should follow the format:

N x i = result

,where i ranges from 1 to 10, and result is the product of N and i.

Input

The first and only line of input contains a single integer N.

Output

Print 10 lines, where each line is in format:

N x i = result

,where i ranges from 1 to 10, and result is the product of N and i.

Constraints

1

≤

N

≤

10

1≤N≤10

Example

```
Input

5

Output

5 x 1 = 5

5 x 2 = 10

5 x 3 = 15

5 x 4 = 20

5 x 5 = 25

5 x 6 = 30

5 x 7 = 35

5 x 8 = 40

5 x 9 = 45

5 x 10 = 50
```

Print all divisors of N — 20/20 XP — SOLVED — deadline 2026-10-17 11:03

Topics: For Loop, Recursion

URL: https://my.newtonschool.co/playground/code/ebgggw9ce1f0

Back

Print all divisors of N

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Print all divisors of N

Easy

2x

20/20

Time Limit: 2, Memory Limit: 128000

You are given a positive integer N. Your task is to find and print all the positive divisors of N in increasing order.

Note: A divisor of N is a number d such that d divides N completely.

Input

The first and only line of input contains a single integer N.

Output

Print space-separated integers, representing the positive divisors of N in increasing order.

Constraints

1

≤

N

≤

1

0

5

1≤N≤10

5

```
Example

Input

10

Output

1 2 5 10

Explanation

A divisor of 10 is any number that divides 10 exactly, i.e., with no remainder.

Let’s check which numbers divide 10:

1 → 10 ÷ 1 = 10 → ✅ (no remainder)

2 → 10 ÷ 2 = 5 → ✅

3 → 10 ÷ 3 = 3.33… → ❌

4 → 10 ÷ 4 = 2.5 → ❌

5 → 10 ÷ 5 = 2 → ✅

6 to 9 → None divide 10 evenly

10 → 10 ÷ 10 = 1 → ✅
```

Multiples of 3 and 5 — 20/20 XP — SOLVED — deadline 2026-10-17 11:03

Topics: For Loop, Recursion

URL: https://my.newtonschool.co/playground/code/07vg13m6mszo

Back

Multiples of 3 and 5

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Multiples of 3 and 5

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given a positive integer N. Your task is to print all numbers between 1 and N (inclusive) that are divisible by both 3 and 5.

Input

The first and only line of input contains a single integer N.

Output

Print all numbers from 1 to N that are divisible by both 3 and 5, in increasing order.

The numbers should be printed on a single line, separated by a space.

Note: If there are no such numbers, you need not to print anything.

Constraints

1

≤

N

≤

1

0

6

1≤N≤10

```
6

Example

Input

30

Output

15 30

Explanation

For input 30, the numbers between 1 and 30 that are divisible by both 3 and 5 are: 15 and 30.


Input

5

Output


Explanation

It can be seen that upto 5, there is no number which is a multiple of 5 and 3 both.
```

Iteration in Python, Recursion Mechanism, Range () function, Intro and Types - L ... [Post Class] — due 2026-10-17 15:00

Find The Even Numbers — 20/20 XP — SOLVED — deadline 2026-10-17 15:00

Topics: Recursion, Range () function

URL: https://my.newtonschool.co/playground/code/8tluckwr59xq

Back

Find The Even Numbers

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Find The Even Numbers

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

Write a program that takes a positive integer N as input and prints all even numbers from 1 to N (inclusive), each on a separate line.

Input

The first and only line of input contains a single integer N, the number of bridges.

Output

Print all even numbers from 1 to N (inclusive), each on a separate line.

Constraints

1

≤

N

≤

20

1≤N≤20

Example

Input

3

Output

2

Input

```
6

Output

2

4

6
```

Sum from 1 to N — 20/20 XP — SOLVED — deadline 2026-10-17 15:00

Topics: For Loop, Recursion

URL: https://my.newtonschool.co/playground/code/lvr71f9ssooi

Back

Sum from 1 to N

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Sum from 1 to N

Easy

2x

20/20

Time Limit: 2, Memory Limit: 256000

You are given a positive integer N. Your task is to calculate and print the sum of all integers from 1 to N (inclusive).

Input

The first and only line of input contains a single integer N.

Output

Print an integer, representing the sum of all integers from 1 to N (inclusive).

Constraints

1

≤

N

≤

50

1≤N≤50

Example

Input

10

Output

55

Explanation

The sum of number from 1 to 10 is equal to 55.

```
Input

20

Output

Total Energy: 210

Explanation

The sum of number from 1 to 20 is equal to 210.
```

Count Numbers Divisible by 3 or 5 — 0/20 XP — NOT SOLVED — deadline 2026-10-17 15:00

Topics: For Loop, Recursion

URL: https://my.newtonschool.co/playground/code/wqfz7z0xggkm

Back

Count Numbers Divisible by 3 or 5

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Count Numbers Divisible by 3 or 5

Easy

0/20

Time Limit: 2, Memory Limit: 256000

You are given a positive integer N. Your task is to print all numbers in the range from 1 to N (inclusive) that are divisible by 3 or 5, but not both.

Input

The first and only line of input contains a positive integer N.

Output

Print all numbers in the range from 1 to N (inclusive) that are divisible by 3 or 5, but not both.

Constraints

3

≤

N

≤

100

3≤N≤100

Example

Input

15

Output

3 5 6 9 10 12

Explanation

From 1 to 15, numbers like 3, 5, 6, 9, 10, and 12 are divisible by 3 or 5, but not both.

```
15 is divisible by both, so it's excluded.
```

Squares from 1 to N (Part I) — 0/20 XP — NOT SOLVED — deadline 2026-10-17 15:00

Topics: For Loop

URL: https://my.newtonschool.co/playground/code/to18n5q10fsj

Back

Squares from 1 to N (Part I)

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Squares from 1 to N (Part I)

Easy

0/20

Time Limit: 2, Memory Limit: 256000

You are given a positive integer N. Your task is to print the squares of all integers from 1 to N, one per line.

In other words, print:

1^2, 2^2, 3^2, ..., N^2, each on a separate line.

Input

The first and only line of input contains a single integer N.

Output

Print N lines, where the i-th line contains the square of integer i, where

1

≤

i

≤

N

1≤i≤N

Constraints

1 ≤ N ≤ 20

Example

Input

5

Output

```
1

4

9

16

25


Input

3

Output

1

4

9
```

Squares from 1 to N (Part II) — 0/20 XP — NOT SOLVED — deadline 2026-10-17 15:00

Topics: For Loop

URL: https://my.newtonschool.co/playground/code/qyf5g3girt88

Back

Squares from 1 to N (Part II)

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Squares from 1 to N (Part II)

Easy

0/20

Time Limit: 2, Memory Limit: 256000

You are given a positive integer N. Your task is to print the squares of all integers from 1 to N, on the same line, separated by a space.

Input

The first and only line of input contains a single integer N.

Output

A single line containing N space-separated integers, representing the squares of all integers from 1 to N.

Constraints

$1 \leq N \leq 20$

Example

Input

5

Output

1 4 9 16 25

Recursion Mechanism, Iteration in Python, Range () function [In Class] — due 2026-10-17 15:52

Factorial-Loops — 0/20 XP — NOT SOLVED — deadline 2026-10-17 15:52

Topics: Recursion, While loop

URL: https://my.newtonschool.co/playground/code/ehuog873narx

Back

Factorial-Loops

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Factorial-Loops

Easy

0/20

Time Limit: 2, Memory Limit: 128000

You are given a positive integer N. Your task is to compute and print the factorial of N.

Note: The factorial of a number N, denoted as N!, is the product of all positive integers less than or equal to N.

Input

The first and only line of input contains a positive integer N.

Output

Print an integer, factorial of N

Constraints

0

≤

N

≤

20

0≤N≤20

Example

Input

5

Output

120

Explanation

```
5!= 5 * 4 * 3 * 2 * 1 = 120


Input

10

Output

3628800
```

Check if a Number is a Palindrome — 0/20 XP — NOT SOLVED — deadline 2026-10-17 15:52

Topics: Recursion, While loop

URL: https://my.newtonschool.co/playground/code/g9n232k86ta1

Back

Check if a Number is a Palindrome

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Check if a Number is a Palindrome

Easy

0/20

Time Limit: 2, Memory Limit: 256000

Given a positive integer N, determine whether it is a palindrome.

Note: A number is called a palindrome if it reads same backwards and forwards

Input

The first and only line of input contains a positive integer N.

Output

Print "Yes" if the given number is a palindrome, otherwise "No" (without quotes).

Constraints

1

≤

N

≤

1

0

9

1≤N≤10

9

Example

Input

54145

```
Output

Yes

Explanation

The given number reads same backwards and forwards. Thus it is a palindromic number.


Input

12345

Output

No
```

Digit Sum using Loop — 0/20 XP — NOT SOLVED — deadline 2026-10-17 15:52

Topics: Recursion, While loop

URL: https://my.newtonschool.co/playground/code/w61cb0h3z1fr

Back

Digit Sum using Loop

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Digit Sum using Loop

Easy

0/20

Time Limit: 2, Memory Limit: 128000

You are provided with a function sumOfDigits(n), where the integer n is passed as a parameter.

Input

You don't need to take the input.

Output

You need to return the sum of digits of n.

Constraints

1

≤

N

≤

1

0

9

1≤N≤10

9

Example

Input

28393

```
Output

25

Explanation

The digits of the given number are: 2, 8, 3, 9 and 3. And their sum is 25.
```

While loop [Post Class] — due 2026-10-17 19:35

Count the Digits — 0/20 XP — NOT SOLVED — deadline 2026-10-17 19:35

Topics: Recursion, While loop

URL: https://my.newtonschool.co/playground/code/uxi69ufxz200

Back

Count the Digits

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Count the Digits

Easy

0/20

Time Limit: 2, Memory Limit: 256000

You are given a positive integer N. Your task is to find the count of digits in N. There will be no leading zeroes in the input number N. For example, inputs like 0023 or 0005 will not be given.

Note: The following things are blocked in the backend, so please don’t use them in your code:

String literals, list literals, and conversions using str() or list().

Indexing, iteration, or applying string methods on variables obtained from input().

Input

The first and only line of input contains a positive integer N.

Output

Print an integer, the count of digits in the given number.

Constraints

1

≤

N

≤

1

0

```
9

1≤N≤10

9

There will be no leading zeroes in the input number N. For example, inputs
like 0023 or 0005 will not be given.

Example

Input

28232

Output

5

Explanation

There are total 5 digits in the given number that are: 2, 8, 2, 3 and 2.
```

Reverse a Number — 0/20 XP — NOT SOLVED — deadline 2026-10-17 19:35

Topics: While loop

URL: https://my.newtonschool.co/playground/code/u5nc58u56gp9

Back

Reverse a Number

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Reverse a Number

Easy

0/20

Time Limit: 2, Memory Limit: 128000

You are given a positive integer N. Your task is to reverse the given number.

Input

The first and only line of input contains a positive integer N.

Output

Print an integer, representing the reversed number.

Constraints

1

≤

N

≤

1

0

9

1≤N≤10

9

Example

Input

536446

Output

644635

```
Input

100

Output

1
```

Sum of First and Last Digits of a Number — 0/20 XP — NOT SOLVED — deadline 2026-10-17 19:35

Topics: While loop

URL: https://my.newtonschool.co/playground/code/7qgquvnt2dlx

Back

Sum of First and Last Digits of a Number

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Sum of First and Last Digits of a Number

Easy

0/20

Time Limit: 2, Memory Limit: 128000

You are given a positive integer N. Your task is to calculate the sum of the first and last digits of the number.

Input

The first and only line of input contains a positive integer N.

Output

Print an integer, the sum of the first and last digits of the number.

Constraints

1

≤

N

≤

1

0

9

1≤N≤10

9

Example

Input

14368

Output

9

```
Explanation

1 and 8 are the first and last digits of the given number respectively, and their sum is 9.
```

Find the Count of Even and Odd Digits — 0/20 XP — NOT SOLVED — deadline 2026-10-17 19:35

Topics: While loop

URL: https://my.newtonschool.co/playground/code/itxgoou9wvbd

Back

Find the Count of Even and Odd Digits

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Find the Count of Even and Odd Digits

Easy

0/20

Time Limit: 2, Memory Limit: 256000

You are given a positive integer N. Your task is to separately find the count of its even digits and the count of its odd digits.

Input

The first and only line of input contains a positive integer N.

Output

Print two space-separated integers, representing the count of even and odd digits in the given number N.

Constraints

1

≤

N

≤

1

0

9

1≤N≤10

9

Example

Input

295892

Output

```
3 3

Explanation

The even digits in the given number are: 2, 8, and 2.

And the odd digits in the given number are: 9, 5, and 9.

Thus the count of even and odd digits will be 3 and 3 respectively.
```

Find the Largest Digit in a Number — 0/40 XP — NOT SOLVED — deadline 2026-10-17 19:35

Topics: Recursion, While loop

URL: https://my.newtonschool.co/playground/code/3nhaa69c3fr2

Back

Find the Largest Digit in a Number

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Find the Largest Digit in a Number

Medium

0/40

Time Limit: 2, Memory Limit: 256000

You are given a positive integer N. Your task is to find the largest digit in the given number.

Input

The first and only line of input contains a positive integer N.

Output

Print an integer, the largest digit in the given number.

Constraints

0

≤

N

≤

1

0

9

0≤N≤10

9

Example

Input

2839

Output

9

```
Explanation

The given number 2839 contains digits: 2, 8, 3 and 9, amongst them 9 is the largest digit.
```

While loop [In Class] — due 2026-10-19 10:52

Find the Sum of Even and Odd Digits — 40/40 XP — SOLVED — deadline 2026-10-19 10:52

Topics: While loop

URL: https://my.newtonschool.co/playground/code/8jp917i4ddjs

Back

Find the Sum of Even and Odd Digits

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Find the Sum of Even and Odd Digits

Medium

2x

40/40

Time Limit: 2, Memory Limit: 256000

You are given a positive integer N. Your task is to separately find the sum of its even digits and the sum of its odd digits.

Input

The first and only line of input contains a positive integer N.

Output

Print two space-separated integers, representing the sum of even and odd digits in the given number N.

Constraints

1

≤

N

≤

1

0

9

1≤N≤10

9

Example

Input

295892

```
Output

12 23

Explanation

The even digits in the given number are: 2, 8, and 2.

And the odd digits in the given number are: 9, 5, and 9.

Thus the sum of even and odd digits will be 12 and 23 respectively.
```

Find the Smallest Digit in a Number — 40/40 XP — SOLVED — deadline 2026-10-19 10:52

Topics: Recursion, While loop

URL: https://my.newtonschool.co/playground/code/8alnm0d8n23c

Back

Find the Smallest Digit in a Number

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Find the Smallest Digit in a Number

Medium

2x

40/40

Time Limit: 2, Memory Limit: 256000

You are given a positive integer N. Your task is to find the smallest digit in the given number.

Input

The first and only line of input contains a positive integer N.

Output

Print an integer, the smallest digit in the given number.

Constraints

1

≤

N

≤

1

0

9

1≤N≤10

9

Example

Input

2839

Output

```
2

Explanation

The given number 2839 contains digits: 2, 8, 3 and 9, amongst them 2 is the smallest digit.
```

Armstrong or not II — 40/40 XP — SOLVED — deadline 2026-10-19 10:52

Topics: While loop

URL: https://my.newtonschool.co/playground/code/j7fkycqnxqvx

Back

Armstrong or not II

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Armstrong or not II

Medium

2x

40/40

Time Limit: 2, Memory Limit: 256000

You are given a number. Your task is to check if this number is an Armstrong number.

An Armstrong number is a number that is equal to the sum of its own digits, each raised to the power of the number of digits.

Input

First line will contain an Integer N.

Output

Print True if the number is Armstrong, otherwise print False.

Example

Input:

153

Output:

True

Explanation

The number 153 has 3 digits: 1, 5, and 3.

If we raise each digit to the power of 3 (the total number of digits) and sum them:

13 + 53 + 33 = 153

Since the sum is equal to the original number, 153 is an Armstrong number.

```
Input:

12

Output:

False

Explanation

The number 12 has 2 digits: 1 and 2.

If we raise each digit to the power of 2 (the total number of digits) and sum them:

12 + 22 = 5

Since the sum is not equal to the original number, 12 is not an Armstrong Number.
```

Loops, Control flow statements, Break, Continue, Python Function, Scope, Variabl ... [In Class] — due 2026-10-19 17:02

Is It Prime? — 0/20 XP — NOT SOLVED — deadline 2026-10-19 17:02

Topics: Loops, Recursion

URL: https://my.newtonschool.co/playground/code/6ysp7dm11g43

Back

Is It Prime?

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Is It Prime?

Easy

0/20

Time Limit: 2, Memory Limit: 128000

You are given a positive integer N. Your task is to determine whether N is a prime number. Print "YES" if the number is prime, otherwise print "NO".

Note: A prime number is a number greater than 1 that has no positive divisors other than 1 and itself.

Input

The first and only line of input contains a positive integer N.

Output

Print "YES" if N is a prime number.

Print "NO" otherwise.

Constraints

1

≤

N

≤

1

0

3

```
1≤N≤10

3

Example

Input

7

Output

YES

Explanation

7 is only divisible by 1 and 7 → Prime → Output "YES"


Input

10

Output

NO

Explanation

10 is divisible by 1, 2, 5, 10 → Not prime → Output "NO"
```

Add 1 to Each Digit — 0/20 XP — NOT SOLVED — deadline 2026-10-19 17:02

Topics: Loops

URL: https://my.newtonschool.co/playground/code/9kgf3qfr0tsp

Back

Add 1 to Each Digit

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Add 1 to Each Digit

Easy

0/20

Time Limit: 2, Memory Limit: 256000

Write a program to add 1 to each digit of the given number and print the result.

Note: Consider adding 1 to digit 9 makes it 0.

Input

The first and only line of input contains a positive integer N.

Output

Print an integer, the resultant number formed after adding 1 to each digit.

Constraints

1

≤

N

≤

1

0

9

1≤N≤10

9

Example

```
Input

765392

Output

876403
```

Fibonacci Series of a given input — 0/20 XP — NOT SOLVED — deadline 2026-10-19 17:02

Topics: Loops

URL: https://my.newtonschool.co/playground/code/u04pck04jkzy

Back

Fibonacci Series of a given input

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Fibonacci Series of a given input

Easy

0/20

Time Limit: 2, Memory Limit: 128000

You are given a positive integer N. Your task is to print the first N terms of the Fibonacci series.

Input

The first and only line of input contains a positive integer N.

Output

Print N space-separated integers, representing the first N terms of the Fibonacci series.

Constraints

1

≤

N

≤

20

1≤N≤20

Example

input:

5

output:

0 1 1 2 3

Control flow statements, Loops, Break, Continue [Post Class] — due 2026-10-21 11:00

Find Odd Factors — 0/20 XP — NOT SOLVED — deadline 2026-10-21 11:00

Topics: Loops, For Loop

URL: https://my.newtonschool.co/playground/code/mjgqoptuk9qj

Back

Find Odd Factors

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Find Odd Factors

Easy

0/20

Time Limit: 2, Memory Limit: 256000

You are given a positive integer N. Your task is to print all the odd factors of N in increasing order.

Input

The first and only line of input contains a positive integer N.

Output

Print space-separated integers, the odd factors of the given number.

Constraints

1

≤

N

≤

1

0

5

1≤N≤10

5

Example

Input

21

Output

```
1 3 7 21
```

Check if Even Sum is Divisible by 2 — 0/20 XP — NOT SOLVED — deadline 2026-10-21 11:00

Topics: Loops, While loop

URL: https://my.newtonschool.co/playground/code/1v2ig3ylqca8

Back

Check if Even Sum is Divisible by 2

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Check if Even Sum is Divisible by 2

Easy

0/20

Time Limit: 2, Memory Limit: 256000

You are given two positive integers L and R representing a range. Your task is to calculate the sum of all even numbers in the range [L, R] (inclusive), and check whether this sum is divisible by 2.

Input

The first and only line of input contains two space-separated integers L and R.

Output

Print "Yes" if the sum of all even numbers in the range [L, R] is divisible by 2, else "No" (without quotes).

Constraints

1

≤

L

≤

R

≤

1

0

18

1≤L≤R≤10

18

Example

Input

```
23 29

Output

Yes

Explanation

The even numbers in the given range are: 24, 26 and 28. And the sum of the numbers is 78, which is
divisible by 2.
```

Check for Perfect Number — 0/20 XP — NOT SOLVED — deadline 2026-10-21 11:00

Topics: Loops, While loop

URL: https://my.newtonschool.co/playground/code/ijfi1qbt2wzt

Back

Check for Perfect Number

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Check for Perfect Number

Easy

0/20

Time Limit: 2, Memory Limit: 256000

Given an integer N, your task is to determine if N is a perfect number.

Note: A perfect number is a positive integer that is equal to the sum of its proper divisors (all positive divisors excluding the number itself). For example, 6 is a perfect number because 1 + 2 + 3 = 6.

Input

The first and only line of input contains a positive integer N.

Output

Print "True" if the number is a perfect number, otherwise "False" (without quotes).

Constraints

1

≤

N

≤

1

0

5

1≤N≤10

5

Example

Input

```
6

Output

True

Explanation

Divisors of 6 are 1, 2, 3 and 6. We are not required to include the number itself, thus the
remaining divisors are 1, 2, and 3, that sum up to 6.
```

First Number Divisibly by 7 — 0/20 XP — NOT SOLVED — deadline 2026-10-21 11:00

Topics: Loops, For Loop, Break

URL: https://my.newtonschool.co/playground/code/qi7iukfehbkg

Back

First Number Divisibly by 7

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

First Number Divisibly by 7

Easy

0/20

Time Limit: 2, Memory Limit: 256000

You are given two positive integers L and R representing a range. Your task is to find the smallest number divisible by 7 in the range [L, R] (inclusive). If no such number is found, print "NOT FOUND".

Input

The first and only line of input contains two space-separated integers L and R.

Output

Print the smallest number divisible by 7 in the range [L, R]. If no such number exist, print "NOT FOUND".

Constraints

1

≤

L

≤

R

≤

1

0

18

1≤L≤R≤10

18

Example

Input

```
23 29

Output

28

Explanation

28 is the only number divisible by 7 in the given range [23, 29].


Input

23 27

Output

NOT FOUND

Explanation

There is no number divisible by 7 in the given range [23, 27].
```

Check if All Digits are Same — 0/40 XP — NOT SOLVED — deadline 2026-10-21 11:00

Topics: While loop, Break

URL: https://my.newtonschool.co/playground/code/51trq43f8x5h

Back

Check if All Digits are Same

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Check if All Digits are Same

Medium

0/40

Time Limit: 2, Memory Limit: 256000

You are given a positive integer N. Your task is to check whether all the digits in the number are the same.

Input

The first and only line of input contains a positive integer N.

Output

Print "Yes" if all the digits in the number are the same, else "No" (without quotes).

Constraints

1

≤

N

≤

1

0

9

1≤N≤10

9

Example

Input

77777

Output

Yes

```
Input

22888

Output

No
```

Check if Rare — 0/40 XP — NOT SOLVED — deadline 2026-10-21 11:00

Topics: While loop, Break

URL: https://my.newtonschool.co/playground/code/z86pihq0ztw8

Back

Check if Rare

Total XP

5,795

Leaderboard Unlocked

Rank Increased

Run

Submit

QUESTION

Check if Rare

Medium

0/40

Time Limit: 2, Memory Limit: 256000

A number is called rare if all of its digits are divisible by a given number X.

Given a positive integer N and another positive integer X, write a program to check whether N is a rare number with respect to X.

That is, check if every digit of N is divisible by X. If all digits satisfy this condition, print True; otherwise, print False.

Input

The first and only line of input contains two space-separated integer N and X.

Output

If all digits satisfy the given condition, print "True"; otherwise, print "False" (without quotes).

Constraints

1

≤

N

≤

1

0

9

1≤N≤10

9

```
1

≤

X

≤

9

1≤X≤9

Example

Input

28 2

Output

True

Explanation

The given value 2 divides both the digits of given number (2 and 8). Thus the given number is the
rare number.
```

Quizzes / quiz contests (9) — schedules only

(Portal shows quiz QUESTIONS only after starting a test — starting tests is forbidden, so no question text exists for these.)

- Print function in python, Comments in python, Python Variable, Python Primitive ... - Revision — 2026-09-02 20:00 -> 2026-09-07 20:00 — xp 0/12
- Python Input, Python operators, Input() function, Input() for different datatype ... - Revision — 2026-09-07 17:00 -> 2026-09-12 17:00 — xp 2/26
- Conditional Statements, Python if- else - Revision — 2026-09-09 21:05 -> 2026-09-14 21:05 — xp 8/8
- If- elif-else ladder - Revision — 2026-09-21 16:00 -> 2026-09-26 16:00 — xp 0/8
- Python Function, Nested if-else - Revision — 2026-09-23 20:35 -> 2026-09-28 20:35 — xp 0/14
- Python Function, Nested if-else, Arguments and parameter, Return statement - Revision — 2026-09-28 16:00 -> 2026-10-03 16:00 — xp 8/8
- Iteration in Python, Recursion Mechanism, Range () function, Intro and Types - L ... - Revision — 2026-10-12 15:00 -> 2026-10-17 15:00 — xp 0/14
- While loop - Revision — 2026-10-12 19:35 -> 2026-10-17 19:35 — xp 0/10
- Control flow statements, Loops, Break, Continue - Revision — 2026-10-16 11:00 -> 2026-10-21 11:00 — xp 0/8

Questions below lecture videos (per lecture)

19wxczhsm2y8 [zqngjr790187]

=== Assignments tab (quiz cards + in-class + post-class sections) ===

Assignments1

In-class Quizzes

1

Lecture Notes

QUIZ

Conditional Statements, Python if- else - Revision

Attempt duration - Sep 9th 2026 9:05 pm to Sep 14th 2026 9:05 pm

Attempted on Sep 12th 2026 12:32 am

View Solutions

In class assignments

This section contains the assignments and questions solved in the class

No in-class assignments for this lecture

Post class assignments

This section contains the assignments related to the topics covered in this lecture

Q1. Weather Report

Write a program that takes an integer current temperature as input, and determines the type of weather using the below conditions:

Temp < 0 : Freezing Weather

Temp 0-9 : Very Cold

Temp 10-19 : Cold

Temp 20-29 : Normal

Temp 30-39 : Hot

Temp >=40 : Very Hot

Read More

Your Solution

Q2. AM_PM

Write a program that takes the hour (0-23) in 24-hour format as input and prints whether it is AM or PM.

Note:

The time is considered AM if the hour is between 0 and 11 (inclusive).

The time is considered PM if the hour is between 12 and 23 (inclusive).

Read More

Your Solution

Q3. Identify Square or Rectangle

You are given two integers representing the length and breadth of a rectangle.

You need to print "Square" if the given rectangle is square as well, otherwise print "Rectangle".Read More

Your Solution

=== In-class Quizzes tab ===

In-class Quizzes

1

Lecture Notes

In-class Quizzes

These in-class quizzes are only for learning purposes and are not meant for evaluation.

Classroom Quiz - Conditional Statements, Python if- else

not attempted

Total Questions

3 Questions

Your Score

0/5

Classroom Quiz - Conditional Statements, Python if- else

Submit Quiz

QUESTION 1/3

Mark for review

Clear Selection

Which of the following is the correct syntax for an if-else statement in Python?

A

```
if(condition)
  statements;
else:
  statements;
```

B

```
if condition
{
  statements
}
else
{
  statements
}
```

C

```
if condition:
  statements
elif condition:
  statements
else:
  statements
```

D

```
if condition:
  statements
else:
  statements
```

Previous

Next

Newton SchoolQUESTION 2/3

Mark for review

Clear Selection

What will be the output of the following code?

```
x = 7
if x % 2 == 0:
    print(x*2)
else:
    print(x*3)
```

A

None of the Above

B

14

C

21

D

7

Previous

Next

Newton SchoolQUESTION 3/3

Mark for review

Clear Selection

What will be the output of the following Python code?

```
if False:
    print("1")
else:
    print("2")
```

Previous

Next

Newton School

d4amrhe6jend [zqngjr790187]

=== Assignments tab (quiz cards + in-class + post-class sections) ===

Assignments1

Lecture Notes

QUIZ

Control flow statements, Loops, Break, Continue - Revision

Attempt duration - Oct 16th 2026 11:00 am to Oct 21st 2026 11:00 am

Your submission will be marked as “LATE SUBMISSION” because you have crossed the given submission deadline

Attempt Now

In class assignments

This section contains the assignments and questions solved in the class

No in-class assignments for this lecture

Post class assignments

This section contains the assignments related to the topics covered in this lecture

Q1. Find Odd Factorseasy

You are given a positive integer N. Your task is to print all the odd factors of N in increasing order.Read More

Complete Now

Q2. Check if Even Sum is Divisible by 2easy

You are given two positive integers L and R representing a range. Your task is to calculate the sum of all even numbers in the range [L, R] (inclusive), and check whether this sum is divisible by 2.Read More

Complete Now

Q3. Check for Perfect Numbereasy

Given an integer N, your task is to determine if N is a perfect number.

Note: A perfect number is a positive integer that is equal to the sum of its proper divisors (all positive divisors excluding the number itself). For example, 6 is a perfect number because 1 + 2 + 3 = 6.Read More

Complete Now

Q4. First Number Divisibly by 7easy

You are given two positive integers L and R representing a range. Your task is to find the smallest number divisible by 7 in the range [L, R] (inclusive). If no such number is found, print "NOT FOUND".Read More

Complete Now

Q5. Check if All Digits are Samemedium

You are given a positive integer N. Your task is to check whether all the digits in the number are the same.Read More

Complete Now

Q6. Check if Raremedium

A number is called rare if all of its digits are divisible by a given number X.

Given a positive integer N and another positive integer X, write a program to check whether N is a rare number with respect to X.

That is, check if every digit of N is divisible by X. If all digits satisfy this condition, print True; otherwise, print False.Read More

Complete Now

dflwfh8lf150 [zqngjr790187]

=== Assignments tab (quiz cards + in-class + post-class sections) ===

Assignments1

Lecture Notes

QUIZ

Print function in python, Comments in python, Python Variable, Python Primitive ... - Revision

Attempt duration - Sep 2nd 2026 8:00 pm to Sep 7th 2026 8:00 pm

Your submission will be marked as “LATE SUBMISSION” because you have crossed the given submission deadline

Complete Now

In class assignments

This section contains the assignments and questions solved in the class

No in-class assignments for this lecture

Post class assignments

This section contains the assignments related to the topics covered in this lecture

Q1. Print Mirror Right Angle Triangleeasy

Write a Python program to print the mirror image of a right-angled triangle using asterisks (*). The triangle should have 5 rows. Each row should:

Contain stars in increasing order (1 in the first row, 2 in the second, and so on)

Include spaces on the left side so that the stars are right-aligned.

See the example below for clarity.Read More

Your Solution

Q2. Print Inverted Triangleeasy

Write a Python program to print an inverted right-angled triangle using asterisks (*).

The triangle should have 5 rows.

The first row should contain 5 stars.

Each subsequent row should have one less star than the previous row.

Read More

Your Solution

Q3. Print Numbers Right-Angled Triangleeasy

Write a Python program to print a right-angled triangle made of numbers.

The triangle should have 5 rows.

The first row should contain the number 1.

The second row should contain 1 2.

The third row should contain 1 2 3, and so on.

See the example below for clarity.

Note: There should be a space between each number in a row.

Read More

Your Solution

Q4. Print Hollow Squareeasy

Write a Python program to print a hollow square pattern using asterisks (*).

The square should have 5 rows and 5 columns.

The stars should form the border of the square.

The inside of the square should be empty (filled with spaces).

See the example below for clarity.Read More

Your Solution

Q5. No Time to Newlineeasy

Write a program to print the below quote in a single line.

Quote

1.Do not watch the clock

2.Do what it does keep going

Your task is to print only the line number 1 of the quote.

Line number 2 of the quote will automatically appear in the output section when you run your code.

Read More

Your Solution

dulnk24cx9gi [zqngjr790187]

=== Assignments tab (quiz cards + in-class + post-class sections) ===

Assignments1

Lecture Notes

QUIZ

Python Function, Nested if-else, Arguments and parameter, Return statement - Revision

Attempt duration - Sep 28th 2026 4:00 pm to Oct 3rd 2026 4:00 pm

Attempted on Sep 30th 2026 5:59 pm

View Solutions

In class assignments

This section contains the assignments and questions solved in the class

No in-class assignments for this lecture

Post class assignments

This section contains the assignments related to the topics covered in this lecture

Q1. Bridge Between Villages -2easy

In a rural district, three villages — Raga, Sora, and Tula — are planning to connect to each other with straight bridges. The government has provided the proposed lengths for these bridges as follows:

Raga to Sora: a kilometers

Sora to Tula: b kilometers

Tula to Raga: c kilometers

You are required to implement the function is_triangle(a, b, c) that returns "YES" or "NO" depending on whether the given bridge lengths can form a valid triangle.

Function Signature:

def is_triangle(a, b, c): which takes three parameters: a: represents proposed length from Raga to Sora,
b: represents proposed length from Sora to Tula, c: represents proposed length from Tula to Raga

Read More

Your Solution

Q2. Calculate Electricity Bill - 2easy

An electricity board calculates monthly power usage bills based on the number of units consumed using a slab-wise tariff system. Each slab charges a different rate per unit as follows:

First 100 units: ₹4 per unit

Next 100 units (i.e., units 101–200): ₹5 per unit

Next 100 units (i.e., units 201–300): ₹6 per unit

Next 100 units (i.e., units 301–400): ₹7 per unit

Units above 400: ₹8 per unit

After calculating the base bill, a 10% surcharge is added to the total bill.

You are required to implement the function calculate_bill(units) that calculates the total electricity bill including the surcharge, and returns a float rounded to 1 decimal place using the built-in round() function.

Function Signature:

def calculate_bill(units): which takes single parameter: units: represents the number of electricity units consumed.

Read More

Your Solution

Q3. Smart Conditional Calculatoreasy

You are given two integers. Your task is to implement a smart calculator that chooses the arithmetic operation based on the parity (even/odd nature) of the two numbers.

Rules:

If both numbers are even, return their sum.

If both numbers are odd, return their product.

If one number is even and the other is odd, return the absolute difference between the two (i.e., subtract the smaller from the larger).

🔧 Task

Write the function definition for smart_calculator(a, b). This means:

✅ You must write the function header (starting with def)

✅ You must also write the function body with correct logic

❌ Do not write any code for input or output (e.g., no input() or print() statements)

Read More

Your Solution

Q4. Celsius to Fahrenheit Conversion - 2easy

You are given an integer, representing the temperature in celsius.

Your task is to convert it to Fahrenheit, using the below given formula:

Fahrenheit = (Celsius × 9 / 5) + 32

You must complete the function celsius_to_fahrenheit(celsius) that returns the equivalent temperature in Fahrenheit.

Function Signature:

def celsius_to_fahrenheit(celsius):

It takes a single parameter, celsius, the temperature in Celsius.Read More

Your Solution

idsydvrzm6yp [zqngjr790187]

=== Assignments tab (quiz cards + in-class + post-class sections) ===

Assignments1

In-class Quizzes

1

Lecture Notes

QUIZ

If- elif-else ladder - Revision

Attempt duration - Sep 21st 2026 4:00 pm to Sep 26th 2026 4:00 pm

Your submission will be marked as “LATE SUBMISSION” because you have crossed the given submission deadline

Attempt Now

In class assignments

This section contains the assignments and questions solved in the class

No in-class assignments for this lecture

Post class assignments

This section contains the assignments related to the topics covered in this lecture

Q1. Library fine

Calculate the fine for a late return of a library book based on the following details:

For the first 3 days, the fine is Rs. 10.

For the next 4 to 10 days, the fine is Rs. 20.

For any period exceeding 10 days, the fine is Rs.100.

Read More

Your Solution

Q2. Calculate salary

Calculate the gross salary of an employee based on their basic salary according to the following criteria:

basic salary <= 10,000, HRA = 20% and DA = 80%.

20,000 >= basic salaries > 10,000 , the HRA = 25% and DA = 90%.

basic salary > 20,000, HRA = 30% and DA = 95%.

Hint: Gross Salary = Basic Salary + HRA + DA

Read More

Your Solution

Q3. Check Profit or Loss

You are given two integers, cost and sell, representing the cost price and the selling price of a product.

Your task is to determine whether the transaction results in a profit, a loss, or no profit and no loss.

Also, you need to calculate the corresponding amount.Read More

Your Solution

Q4. BMI Calculator-1easy

You are asked to determine a person's Body Mass Index (BMI) based on their weight and height.

The BMI is calculated using the following formula:

BMI = weight / (height_in_meters x height_in_meters)

Here,

weight is given in kilograms

height is given in centimeters and must be converted to meters

You must round the BMI value to exactly 1 decimal place using the built-in round() function.

Based on the rounded BMI value, print the corresponding BMI category:

If BMI is less than 18.5, print Underweight

If BMI is between 18.5 and 24.9 (inclusive), print Normal weight

If BMI is between 25 and 29.9 (inclusive), print Overweight

If BMI is 30 or greater, print Obese

Read More

Your Solution

=== In-class Quizzes tab ===

In-class Quizzes

1

Lecture Notes

In-class Quizzes

These in-class quizzes are only for learning purposes and are not meant for evaluation.

Classroom Quiz - If- elif-else ladder

not attempted

Total Questions

3 Questions

Your Score

0/6

Classroom Quiz - If- elif-else ladder

Submit Quiz

QUESTION 1/3

Mark for review

Clear Selection

Identify the correct elif ladder syntax in Python.

A

```
elif condition1:
  # block1
else:
  # block2
```

B

```
if condition1:
  # block1
elif condition2:
  # block2
```

C

```
if condition1:
  # block1
elif condition2:
  # block2
else:
  # block3
```

D

Both A and B

E

Both B and C

Previous

Next

Newton SchoolQUESTION 2/3

Mark for review

Clear Selection

What will be the output of following code?

```
x = 10

if x > 0:
   print("block 1")
elif x <= 10:
   print("block 2")
elif x == 10:
   print("block 3")
else:
   print("block 4")
```

A

block 2

B

block 1

C

block 4

D

block 3

Previous

Next

Newton SchoolQUESTION 3/3

Mark for review

Clear Selection

What will be the output of following code?

```
x = 10

if x > 0:
print("block 1")

if x <= 10:
print("block 2")

if x == 10:
print("block 3")
else:
print("block 4")
```

A

block 3

B

block 2

block 3

C

block 1

D

block 1

block 2

block 3

E

block 1

block 3

Previous

Next

Newton School

irtusths65xb [zqngjr790187]

=== Assignments tab (quiz cards + in-class + post-class sections) ===

Assignments1

Lecture Notes

QUIZ

Iteration in Python, Recursion Mechanism, Range () function, Intro and Types - L ... - Revision

Attempt duration - Oct 12th 2026 3:00 pm to Oct 17th 2026 3:00 pm

Your submission will be marked as “LATE SUBMISSION” because you have crossed the given submission deadline

Complete Now

In class assignments

This section contains the assignments and questions solved in the class

No in-class assignments for this lecture

Post class assignments

This section contains the assignments related to the topics covered in this lecture

Q1. Find The Even Numberseasy

Write a program that takes a positive integer N as input and prints all even numbers from 1 to N (inclusive), each on a separate line.Read More

Your Solution

Q2. Sum from 1 to Neasy

You are given a positive integer N. Your task is to calculate and print the sum of all integers from 1 to N (inclusive).Read More

Your Solution

Q3. Count Numbers Divisible by 3 or 5easy

You are given a positive integer N. Your task is to print all numbers in the range from 1 to N (inclusive) that are divisible by 3 or 5, but not both.Read More

Complete Now

Q4. Squares from 1 to N (Part I)easy

You are given a positive integer N. Your task is to print the squares of all integers from 1 to N, one per line.

In other words, print:

1^2, 2^2, 3^2, ..., N^2, each on a separate line.Read More

Complete Now

Q5. Squares from 1 to N (Part II)easy

You are given a positive integer N. Your task is to print the squares of all integers from 1 to N, on the same line, separated by a space.Read More

Complete Now

lxbwc1pqpdt7 [zqngjr790187]

=== Assignments tab (quiz cards + in-class + post-class sections) ===

Assignments1

Lecture Notes

QUIZ

Python Input, Python operators, Input() function, Input() for different datatype ... - Revision

Attempt duration - Sep 7th 2026 5:00 pm to Sep 12th 2026 5:00 pm

Attempted on Sep 10th 2026 9:53 am

View Solutions

In class assignments

This section contains the assignments and questions solved in the class

No in-class assignments for this lecture

Post class assignments

This section contains the assignments related to the topics covered in this lecture

Q1. Find The Squareeasy

Write a program to take a number X as input and print its square.Read More

Your Solution

Q2. Rectangle Area Calculatoreasy

Write a program that calculates the area of a rectangle given its length and width.

The program should prompt the user to enter the length and width of the rectangle, and then calculate and print the area.Read More

Your Solution

Q3. Calculate and Print Ageeasy

Write a Python program that takes two integers as input: the birth year and the current year.

Your task is to calculate the age by subtracting the birth year from the current year, and print the result.Read More

Your Solution

Q4. Energy Consumption Calculationeasy

You are given two integers: units representing the total electricity consumed and cost representing the cost of each unit.

Your task is to write a Python program that calculates the total electricity cost and prints the result.Read More

Your Solution

Q5. Celsius to Fahrenheit Conversioneasy

Write a program to convert a temperature value from Celsius to Fahrenheit using the formula:

F

a

h

r

e

n

h

e

i

t

$=$

$($

C

e

l

s

i

u

s

$*$

9

/

5

)

+

32

Fahrenheit=(Celsius∗9/5)+32.

Note: Use the round() function to round numbers to 1 decimal place.Read More

Your Solution

Q6. Convert Minute to Hour and Minute Formateasy

Write a program to convert total minutes into hours and remaining minutes.

Print the hours and minutes in the below given format:

Time: {x} hour(s) and {y} minute(s)

where {x} will be replaced by hours and {y} by minutes.Read More

Your Solution

rvt849y0o66i [zqngjr790187]

=== Assignments tab (quiz cards + in-class + post-class sections) ===

Assignments1

In-class Quizzes

1

Lecture Notes

QUIZ

While loop - Revision

Attempt duration - Oct 12th 2026 7:35 pm to Oct 17th 2026 7:35 pm

Your submission will be marked as “LATE SUBMISSION” because you have crossed the given submission deadline

Attempt Now

In class assignments

This section contains the assignments and questions solved in the class

No in-class assignments for this lecture

Post class assignments

This section contains the assignments related to the topics covered in this lecture

Q1. Count the Digitseasy

You are given a positive integer N. Your task is to find the count of digits in N. There will be no leading zeroes in the input number N. For example, inputs like 0023 or 0005 will not be given.

Note: The following things are blocked in the backend, so please don't use them in your code:

String literals, list literals, and conversions using str() or list().

Indexing, iteration, or applying string methods on variables obtained from input().

Read More

Complete Now

Q2. Reverse a Numbereasy

You are given a positive integer N. Your task is to reverse the given number.Read More

Complete Now

Q3. Sum of First and Last Digits of a Numbereasy

You are given a positive integer N. Your task is to calculate the sum of the first and last digits of the number.Read More

Complete Now

Q4. Find the Count of Even and Odd Digitseasy

You are given a positive integer N. Your task is to separately find the count of its even digits and the count of its odd digits.Read More

Complete Now

Q5. Find the Largest Digit in a Numbermedium

You are given a positive integer N. Your task is to find the largest digit in the given number.Read More

Complete Now

=== In-class Quizzes tab ===

In-class Quizzes

1

Lecture Notes

In-class Quizzes

These in-class quizzes are only for learning purposes and are not meant for evaluation.

Classroom Quiz - While loop

not attempted

Total Questions

5 Questions

Your Score

0/10

Classroom Quiz - While loop

Submit Quiz

QUESTION 1/5

Mark for review

Clear Selection

What will get printed during the last iteration of the following code?

x = 1

```
while x < 100:
print(x)
x *= -3
```

A

81

B

-81

C

-243

D

243

Previous

Next

Newton SchoolQUESTION 2/5

Mark for review

Clear Selection

What will get printed during the last iteration of the following code?

```
x = 10
while x > 0:
print(x)
x -= 3
```

Previous

Next

Newton SchoolQUESTION 3/5

Mark for review

Clear Selection

What will get printed in the 5th iteration of the following code?

```
x = 1
while x <= 20:
print(x * x)
x += 2
```

Previous

Next

Newton SchoolQUESTION 4/5

Mark for review

Clear Selection

What will be the final value of s?

```
n = 123
s = 0
while n > 0:
s += n % 10
n //= 10
```

Previous

Next

Newton SchoolQUESTION 5/5

Mark for review

Clear Selection

What will be the ouput of the below given code?

n = 123; s = 0

while n:

s += n % 10

n //= 10

print(n)

Previous

Next

Newton School

xcqr11359sem [zqngjr790187]

=== Assignments tab (quiz cards + in-class + post-class sections) ===

Assignments1

In-class Quizzes

1

Lecture Notes

QUIZ

Python Function, Nested if-else - Revision

Attempt duration - Sep 23rd 2026 8:35 pm to Sep 28th 2026 8:35 pm

Your submission will be marked as “LATE SUBMISSION” because you have crossed the given submission deadline

Attempt Now

In class assignments

This section contains the assignments and questions solved in the class

No in-class assignments for this lecture

Post class assignments

This section contains the assignments related to the topics covered in this lecture

Q1. Accommodation Decisioneasy

A student wants to check whether they will stay On-Campus or Off-Campus based on the rules provided in the NST rulebook.

The rules for accommodation are:

If the student is a girl, she will definitely stay On-Campus, irrespective of the year.

If the student is a boy:

In first year → he will stay On-Campus

In second year → he will stay Off-Campus

Given the student's gender and year of study, determine their accommodation type.

Read More

Your Solution

Q2. Calculate Tax Based on Age and Income

You are given two values:

age — the age of a person

income — the annual income of the person (in rupees)

Your task is to calculate the amount of tax that the person needs to pay.

The tax rate depends on both the person's age and annual income.

Tax Slabs

Income Bracket Tax Rate (Age < 18) Tax Rate (Age ≥ 18)

Income ≤ 10,00,000 5% 10%

10,00,000 < Income ≤ 30,00,000 15% 20%

Income > 30,00,000 25% 30%

Print the tax amount that must be paid.

Read More

Your Solution

Q3. Find the Smallest !

Just like finding the largest value, identifying the smallest number is another common task in programming.

Your task:

Given three integers A, B, and C, print the smallest among them.Read More

Your Solution

=== In-class Quizzes tab ===

In-class Quizzes

1

Lecture Notes

In-class Quizzes

These in-class quizzes are only for learning purposes and are not meant for evaluation.

Classroom Quiz - Python Function, Nested if-else

attempted

Total Questions

3 Questions

Your Score

2/6

Classroom Quiz - Python Function, Nested if-else

Revise

QUESTION 1/3

What will the following code output?

```
x = 10
if x > 5:
if x < 15:
print("Yes")
```

else:

print("No")

Yes

Explanation:x = 10 x > 5 → True, so the inner if is checked. x < 15 → True, so "Yes" is printed.

B

No

Error

D

Nothing

INCORRECT ANSWER

QUESTION 2/3

Neeraj is preparing for the finals. His three throws are recorded: throw1 = 86.7, throw2 = 90.6, and throw3 = 88.1. Based on his average throw, the coach gives feedback:

throw1 = 86.7

throw2 = 90.6

throw3 = 88.1

avg = (throw1 + throw2 + throw3) // 3

if avg >= 88:

if throw3 > throw2:

print("Excellent Finish")

elif avg < 89:

print("Great, but can be better")

else:

print("Superb")

else:

print("Needs Improvement")

What will be printed?

A

Excellent Finish

Great, but can be better

Explanation:✓ Step 1: Average = (86.7 + 90.6 + 88.1) / 3 = 88

✓ Step 2: avg >= 88 → True → Enters nested if

✓ throw3 > throw2? 88> 90 → False

✓ avg < 89? Yes → So prints "Great, but can be better"

✗ A) Incorrect — throw3 is not greater than throw2

✗ C) Incorrect — only executes if avg ≥ 89 and other conditions fail

✗ D) Incorrect — avg ≥ 88, so else is skipped

C

Superb

Needs Improvement

INCORRECT ANSWER

QUESTION 3/3

Mark for review

Clear Selection

What will be the output of following code?

loan = 80000

duration = 12

base_rate = 0.12

card_type = "Gold"

Apply card-based discount

if card_type == "Silver":

rate = base_rate - 0.01

elif card_type == "Gold":

if duration > 12:

rate = base_rate - 0.01

else:

rate = base_rate - 0.02

elif card_type == "Platinum":

rate = base_rate - 0.03

else:

rate = base_rate

total_interest = loan * rate

total_payment = loan + total_interest

print(int(total_payment))

88000

Explanation:

The initial loan amount is 80000.

The duration of the loan is 12 months.

The base_rate of interest is 12% or 0.12.

The card_type is Gold.

Since the card type is "Gold" and the duration is not more than 12 months, the applicable interest rate becomes base_rate - 0.02 = 0.10.

Then the total interest is calculated as loan × rate = 80000 × 0.10 = 8000.

So, the total_payment is loan + interest = 80000 + 8000 = 88000.

Output: 88000

Correct answer: 88000

Newton School

ztz8mhzw2sws [zqngjr790187]

=== Assignments tab (quiz cards + in-class + post-class sections) ===

Assignments1

In-class Quizzes

1

Lecture Notes

In class assignments

This section contains the assignments and questions solved in the class

No in-class assignments for this lecture

Post class assignments

This section contains the assignments related to the topics covered in this lecture

Q1. Movie Maniaeasy

Four movies were released: Spiderman, Superman, Batman, and Aquaman in four distinct years given as four space-separated integers: year1, year2, year3, and year4 respectively.

Movie

Release year

Spiderman year1

Superman year2

Batman year3

Aquaman year4

You are required to print the name of the movie that was released earliest of the four.

Note-1: Refer Input section, output section and example test cases.

Note-2: Use of built-in mathematical functions is strictly prohibited in this question.Read More

Your Solution

Q2. Will Ramandeep Sir Fly? - 2easy

Ramandeep Sir is known for his highly selective flying decisions after past flight troubles. He follows a strict set of rules before agreeing to board a plane.

Here are his conditions:

If the trip is international, Ramandeep Sir will not fly, regardless of any other conditions.

If the trip is domestic, and the flight duration is less than or equal to 1.5 hours, he will fly.

If the trip is domestic and the duration is more than 1.5 hours, he will not fly if:

His seat is a middle seat, or

The airline is IngidoX

In all other cases, he will fly.

Your task is to determine whether Ramandeep Sir will fly given the flight details.

Read More

Your Solution

Q3. NST Bus Route Optimizationeasy

The bus driver at NST Campus is planning his daily pickup route. He needs to pick up students from two hostels: Hostel 1 and Hostel 2, and return to the NST campus afterward. To save fuel, he wants to choose the route that results in the minimum total distance traveled.

There are three roads available:

A road of length d1 connects the NST campus and Hostel 1

A road of length d2 connects the NST campus and Hostel 2

A road of length d3 directly connects Hostel 1 and Hostel 2

The driver can travel on any road any number of times, and in any direction. He must start at NST campus, pick up students from both hostels, and return back to the campus, while minimizing the total distance.

Please refer to the following image for further clarity:

Click to enlarge

Read More

Your Solution

Q4. Museum Ticket Booking System

You are tasked with implementing the function calculateTicketPrice for a Museum Ticket Booking system.

The function should calculate the ticket price based on the following rules:

The base ticket price is $12.

If the visitor is under 12 years old, apply a discount of $5.

If the visit is on a weekend, add a surcharge of $3.

If the visitor has a student card, apply an additional discount of $2.

The function calculateTicketPrice accepts the following parameters:

age (number) — The age of the visitor.

isWeekend (boolean) — true if the visit is on a weekend, otherwise false.

hasStudentCard (boolean) — true if the visitor has a student card, otherwise false.

Your task is to return the final ticket price after applying all applicable discounts and surcharges.

Read More

Your Solution

Q5. Greater of Four

You are given four integers a, b, c, and d.

A built-in function greater(x, y) is available to you. It returns the greater of the two values x and y.

Your task is to find the greatest among the four given numbers using the greater() function.

Note: You must use the provided greater() function. Do not compare all four numbers directly.

Read More

Your Solution

=== In-class Quizzes tab ===

In-class Quizzes

1

Lecture Notes

In-class Quizzes

These in-class quizzes are only for learning purposes and are not meant for evaluation.

Classroom Quiz - Python if- else, Python logical Operators

not attempted

Total Questions

4 Questions

Your Score

0/8

Classroom Quiz - Python if- else, Python logical Operators

Submit Quiz

QUESTION 1/4

Mark for review

Clear Selection

Which of the following is the incorrect syntax for using logical operators in an if statement?

A

if condition1 & condition2:

B

if condition1 or condition2:

C

if (condition1) and (condition2):

D

if condition1 and condition2:

Previous

Next

Newton SchoolQUESTION 2/4

Mark for review

Clear Selection

What will be the output of the following code?

x = 20

y = 10

if not x > 15 and y > 15:

print("One condition is true")

A

No output

B

One condition is true

C

Error

D

None of these

Previous

Next

Newton SchoolQUESTION 3/4

Mark for review

Clear Selection

What would be the output of the following code?

print(5 > 3 and 3 < 2)

Previous

Next

Newton SchoolQUESTION 4/4

Mark for review

Clear Selection

What will be printed by this code?

x = 4

y = 10

if x < 5:

if not(y < 10 and x == 4):

print("Yes")

else:

print("Maybe")

else:

print("No")

Previous

Next

Newton School

cf7dcfu88onf [kehysh1tot83]

=== Assignments tab (quiz cards + in-class + post-class sections) ===

Assignments0

In-class Quizzes

1

Lecture Notes

In class assignments

This section contains the assignments and questions solved in the class

No in-class assignments for this lecture

Post class assignments

This section contains the assignments related to the topics covered in this lecture

No post-class assignments for this lecture

=== In-class Quizzes tab ===

In-class Quizzes

1

Lecture Notes

In-class Quizzes

These in-class quizzes are only for learning purposes and are not meant for evaluation.

Classroom Quiz - Python Input, Python operators, Conditional Statements, Input() function, Input(...

attempted

Total Questions

3 Questions

Your Score

0/6

Classroom Quiz - Python Input, Python operators, Conditional Statements, Input() function, Input(...

Revise

QUESTION 1/3

What will be the output of the following code?

```
x = 12
if x > 12:
print("Greater than 12")
elif x > 10:
print("Greater than 10")
elif x > 8:
print("Greater than 8")
else:
print("Less than or equal to 8")
```

Greater Than 10

Greater than 10

Explanation:

x = 12

1️⃣ if x > 12 → False

2️⃣ elif x > 10 → 12 > 10 → ✅ True → prints: Greater than 10

⛔ Remaining elif and else are skipped once a condition is true.

C

Greater than 8

D

Less than or equal to 8

INCORRECT ANSWER

QUESTION 2/3

Mark for review

Clear Selection

What will be output of below code if score = 75?

```
score = 75
if score >= 90:
print("A")
elif score >= 80:
print("B")
elif score >= 70:
print("C")
else:
print("D")
```

c

Explanation:

Explanation:

score = 75

Condition 1: score >= 90 → False

Condition 2: score >= 80 → False

Condition 3: score >= 70 → True, so it prints C.

Remaining conditions are skipped after the first True.

Final Output: C

Correct answer: C

QUESTION 3/3

Mark for review

Clear Selection

What will be the output of below code?

a = 10

b = 5

c = 15

result = 0

if a > b:

result = result+1

elif b < c:

result = result+2

if c > a:

result = result+3

print(result)

1

Explanation:Given: a = 10, b = 5, c = 15 Step 1: if a > b → 10 > 5 → True → result += 1 Since the if was true, elif is skipped. Step 2: if c > a → 15 > 10 → True → result += 3 Final result: result = 4 print(result) prints: 4

Correct answer: 4

Newton School

qu5kfoi6edsr [kehysh1tot83]

=== Assignments tab (quiz cards + in-class + post-class sections) ===

Assignments0

In-class Quizzes

1

Lecture Notes

In class assignments

This section contains the assignments and questions solved in the class

No in-class assignments for this lecture

Post class assignments

This section contains the assignments related to the topics covered in this lecture

No post-class assignments for this lecture

=== In-class Quizzes tab ===

In-class Quizzes

1

Lecture Notes

In-class Quizzes

These in-class quizzes are only for learning purposes and are not meant for evaluation.

Classroom Quiz - While loop

not attempted

Total Questions

5 Questions

Your Score

0/11

Classroom Quiz - While loop

Submit Quiz

QUESTION 1/5

Mark for review

Clear Selection

What will be printed in the 3rd iteration?

```
x = 2
while x <= 20:
print(x ** 2)
x += 6
```

Previous

Next

Newton SchoolQUESTION 2/5

Mark for review

Clear Selection

How many digits will be counted in the following code?

```
n = 98765
count = 0
while n > 0:
count += 1
n //= 10
```

Previous

Next

Newton SchoolQUESTION 3/5

Mark for review

Clear Selection

What will be printed in the last iteration?

```
x = 50
while x >= 0:
print(x // 10)
x -= 10
```

Previous

Next

Newton SchoolQUESTION 4/5

Mark for review

Clear Selection

What will be the value of total after the loop ends?

x = 7

total = 0

while x <= 70:

if x % 10 == 7:

total += x

x += 1

Previous

Next

Newton SchoolQUESTION 5/5

Mark for review

Clear Selection

How many times does the loop run?

n = 1234

count = 0

while n > 0:

digit = n % 10

if digit % 2 == 0:

count += 1

n //= 10

Previous

Next

Newton School

sa4adqeyfoaz [kehysh1tot83]

=== Assignments tab (quiz cards + in-class + post-class sections) ===

Assignments0

In-class Quizzes

1

Lecture Notes

In class assignments

This section contains the assignments and questions solved in the class

No in-class assignments for this lecture

Post class assignments

This section contains the assignments related to the topics covered in this lecture

No post-class assignments for this lecture

=== In-class Quizzes tab ===

In-class Quizzes

1

Lecture Notes

In-class Quizzes

These in-class quizzes are only for learning purposes and are not meant for evaluation.

Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

attempted

Total Questions

10 Questions

Your Score

19/19

Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

Revise

QUESTION 1/10

What is the output of the following Python expression?

print(8 // 4 ** 6 * 2 / 3 % 4 - 7)

A

-2

B

-7

-7.0

Explanation:

The expression follows Python's operator precedence rules:

Exponentiation (4 ** 6) is performed first, resulting in 4096.

Floor division (8 // 4096) is next, resulting in 0 because 8 is smaller than 4096.

Multiplication (0 * 2) gives 0.

Division (0 / 3) also results in 0.0.

Modulus (0.0 % 4) results in 0.0.

Subtraction (0.0 - 7) finally gives -7.0.

Therefore, the output of the expression is -7.0.

D

-5.0

CORRECT ANSWER

QUESTION 2/10

What will be the output of the below given python code?

b = 10

a = 3

c = b < a

print(c)

A

True

False

Explanation:

Let’s understand what the code is doing step by step:

b = 10 and a = 3: Two integer variables are initialized.

c = b < a: This compares if b is less than a. Here, 10 < 3 is False.

print(c): This prints the value of c, which is False.

🔍 The comparison operator < checks the relational condition and returns a Boolean value: either True or False.

✅ Final Output: False

C

0

D

1

CORRECT ANSWER

QUESTION 3/10

What will be the output of the below given python code?

num1 = 15

num2 = 28

num3 = 100

result1 = num1 <= num2

result2 = num3 > num1

print(result1 != result2)

A

True

False

Explanation:

Let’s understand the logic step-by-step:

num1 = 15, num2 = 28, num3 = 100: Three integer values are initialized.

result1 = num1 <= num2: This checks if 15 ≤ 28, which is True.

result2 = num3 > num1: This checks if 100 > 15, which is also True.

print(result1 != result2): Now it compares whether True != True. Since both are True, the result is False.

🔍 The != operator checks for inequality — and in this case, both sides are equal.

✅ Final Output: False

C

1

D

0

CORRECT ANSWER

QUESTION 4/10

What will be the output of the below given python code?

x = 10

y = 5

result1 = (x >= 10)

result2 = (y == 5)

print(result1 == result2)

A

False

B

0

True

Explanation:

Let’s go step by step and decode what’s happening:

x = 10 and y = 5: Two variables are assigned integer values.

result1 = (x >= 10): This checks whether x is greater than or equal to 10. Since x is 10, this condition is True.

result2 = (y == 5): This checks whether y is equal to 5. Since it is, this is also True.

print(result1 == result2): Here, we are comparing True == True, which evaluates to True.

✅ Both result1 and result2 are True, so the final comparison also returns True.

🔚 Final Output: True

D

1

CORRECT ANSWER

QUESTION 5/10

What will be the output of the below given python code?

num1 = 5

num2 = 3

print(num1 > num2)

True

Explanation:

Let’s break down what this code is doing:

num1 = 5 and num2 = 3: Two integer variables are assigned values.

num1 > num2 evaluates whether num1 is greater than num2. Here, 5 > 3 is True.

print(num1 > num2) displays the result of the comparison, which is True.

🔍 The > operator is a comparison operator that returns a Boolean value — either True or False — based on whether the left operand is greater than the right one.

✅ Final Output: True

B

False

C

1

D

0

CORRECT ANSWER

QUESTION 6/10

What will be the output of the below given python code?

a = 2 * 3 // 5 % 6 ** 4

print(a)

A

0

1

Explanation:

Let’s evaluate the expression by following Python’s operator precedence rules:

Exponentiation (**) comes first:

→ 6 ** 4 = 1296

Multiplication and Floor Division are left to right:

→ 2 * 3 = 6

→ 6 // 5 = 1

Modulus (%) comes next:

→ 1 % 1296 = 1

So the final value of a is 1.

✅ Final Output: 1

C

6

D

1296

CORRECT ANSWER

QUESTION 7/10

What will be the result of the following expression in Python?

x = 1

y = 2

z = 3

result = x == x <= x + y * z

print(result)

True

Explanation:

The expression x == x <= x + y * z is evaluated as follows:

First, perform the arithmetic operations: y * z results in 6, and x + 6 results in 7.

Next, evaluate the relational comparisons from left to right: x == x evaluates to True, and then True <= 7 evaluates to True.

Finally, combine these results: x == x <= 7 is interpreted as True and True, which evaluates to True.

Therefore, the value of result is True.

B

False

C

0

D

1

CORRECT ANSWER

QUESTION 8/10

What will be the output of the below given python code?

```
num1 = 15
num2 = 28
result = num2 >= num1 + 5
print(result)
```

A

False

True

Explanation:

Let’s evaluate this step-by-step:

num1 = 15 and num2 = 28: Two integer variables are assigned values.

num1 + 5 is evaluated first (due to operator precedence):

→ 15 + 5 = 20

num2 >= 20 → 28 >= 20 is True.

The result is stored in the variable result and then printed.

✅ Final Output: True

C

5

D

6

CORRECT ANSWER

QUESTION 9/10

What will be the output of the following code if the user enters 10, 20 as input?

```
a, b = input().split(", ")
print(int(a) * int(b))
```

200

Explanation:

The input string is "10, 20", which includes a comma followed by a space.

The split(", ") function splits the string into two parts:

a = "10"

b = "20"

Both are then converted to integers and multiplied:

int(a) * int(b) = 10 * 20 = 200

Hence, the output is 200.

B

1020

C

30

D

Error

CORRECT ANSWER

QUESTION 10/10

What will be the output of the below given python code?

result = "apple,,banana,,cherry".split(",")

print(result)

['apple', '', 'banana', '', 'cherry']

Explanation:The split(",") function splits the string at every comma. Here's how it works step-by-step:

The original string is: "apple,,banana,,cherry"

There are double commas (,,) between apple and banana, and again between banana and cherry.

Each , is a splitting point. So, a double comma means an empty string ('') is added in between.

Final List: ['apple', '', 'banana', '', 'cherry']

So, the empty strings appear wherever there were consecutive commas in the original string.

B

['apple', 'banana', 'cherry']

C

['apple', ' ', 'banana', ' ', 'cherry']

D

['apple', 'banana', '', 'cherry']

CORRECT ANSWER

Newton School

vkdt3hwua9yy [kehysh1tot83]

=== Assignments tab (quiz cards + in-class + post-class sections) ===

Assignments0

In-class Quizzes

1

Lecture Notes

In class assignments

This section contains the assignments and questions solved in the class

No in-class assignments for this lecture

Post class assignments

This section contains the assignments related to the topics covered in this lecture

No post-class assignments for this lecture

=== In-class Quizzes tab ===

In-class Quizzes

1

Lecture Notes

In-class Quizzes

These in-class quizzes are only for learning purposes and are not meant for evaluation.

Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

not attempted

Total Questions

3 Questions

Your Score

0/6

Classroom Quiz - Python Input, Python operators, Input() function, Input() for different datatype ...

Submit Quiz

QUESTION 1/3

Mark for review

Clear Selection

What will be the output of the following code?

```
x = 20
if x >= 20:
  print("x is good")
else:
  print("x is not good")
```

A

x is less than 20

B

x is good

C

No output

D

x is 20 or more

Previous

Next

Newton SchoolQUESTION 2/3

Mark for review

Clear Selection

What will be the output of the following code?

```
x = 125
if x > 50:
x = x - 50
  print(x)
if x > 150:
  x = x - 150
  print(x)
else:
  print(x)
```

A

25

75

B

100

75

C

75

75

D

125

75

Previous

Next

Newton SchoolQUESTION 3/3

Mark for review

Clear Selection

What would be the output of the following code?

if 5 > 3:

print("Yes")

Previous

Next

Newton School

WHERE THESE QUESTIONS CAME FROM (sources)

- **Subject assignment pages / My Assignments + Assignment Contests API** — 29 assignments, 100 questions; full statement captured from each question's playground page (read-only visit) — 100/100 texts present.
- **Lecture pages** (Course Content sidebar list) — 14 of 32 lecture windows carry content: post-class question text below the video (`Read More` expanded) and in-class quiz questions via read-only views only (Revise / View Solutions / Next-Previous walk — never Attempt/Start/Submit).
- **Assessments API** — 9 quiz schedules (title, window, XP earned). No question text in the API (hidden until test start).

NOT FETCHED — open these yourself

(These sit behind `Attempt Now` / `Start Test` buttons. I never click those — they consume quiz attempts. Everything else above is complete.)

Revision quizzes whose questions never became visible (4)

(quiz window closed while unattempted — try `Attempt Now` on that lecture's Assignments tab yourself, or check My Assessments)

- Control flow statements, Loops, Break, Continue - Revision
- Iteration in Python, Recursion Mechanism, Range () function, Intro and Types - L ... - Revision
- Python Function, Nested if-else, Arguments and parameter, Return statement - Revision
- Print function in python, Comments in python, Python Variable, Python Primitive ... - Revision

Quiz Contests tab (separate MCQ tests)

- Quiz contest questions only appear after `Start Test` (graded, consumes an attempt): open the Quiz Contests tab manually if you want these: PSP Contest 1, Wifi Demo, Demo_Contest, Mock Test
- What IS captured: all assignment questions (100), all in-class quiz questions shown above, all contest ASSIGNMENT texts (e.g. PSP Contest 2)

TOTALS: 100 assignment questions (77 solved), 9 quizzes, 0 questions without captured text, 14 lecture windows with content.