Q arvaidora@legion: ~ To run a command as administrator (user "root"), use "sudo <command>". See "man sudo root" for details. arvaidora@legion:~\$ ps aux PID %CPU %MEM VSZ RSS TTY STAT START TIME COMMAND USER 1 1.3 0.1 166040 11472 ? 0:01 /sbin/init spla root Ss 19:30 0 ? root 2 0.0 0.0 0 19:30 0:00 [kthreadd] S 0 0 ? root 3 0.0 0.0 19:30 0:00 [rcu_gp] I< I< 19:30 0:00 [rcu_par_gp] root 4 0.0 0.0 0 0 ? 5 0.0 0.0 0 0 ? 19:30 0:00 [kworker/0:0-ev root Ι 6 0.0 0.0 0 0 ? I< 19:30 root 0:00 [kworker/0:0H-k 7 0.0 0 0 ? 19:30 0:00 [kworker/u24:0root 0.0 1 8 0.0 0.0 0 0 ? I< 19:30 0:00 [mm_percpu_wq] root 9 0.0 0.0 0 0 ? S 19:30 0:00 [ksoftirqd/0] root root 10 0.1 0.0 0 0 ? 1 19:30 0:00 [rcu_sched] root 11 0.0 0.0 0 0 ? S 19:30 0:00 [migration/0] 19:30 root 12 0.0 0.0 0 0 ? S 0:00 [idle_inject/0] 0:00 [kworker/0:1-ev root 13 0.0 0.0 0 0 ? 1 19:30 root 14 0.0 0.0 0 0 ? S 19:30 0:00 [cpuhp/0] 0:00 [cpuhp/1] root 15 0.0 0.0 0 0 ? S 19:30 root 16 0.0 0.0 0 0 ? S 19:30 0:00 [idle_inject/1] root 17 0.0 0.0 0 0 ? S 19:30 0:00 [migration/1] root 18 0.0 0.0 0 0 ? S 19:30 0:00 [ksoftirqd/1]

0

root

19

0.0

0.0

0:00 [kworker/1:0-ev

19:30