

DB0201EN-Week6-6-1-Analyzing-1-py-v2

October 11, 2018

Lab: Analyzing a real world data-set SQL and Python

1 Introduction

This notebook shows how to store a dataset into a database using and analyze data using SQL and Python. In this lab you will: 1. Understand a dataset of selected socioeconomic indicators in Chicago 1. Learn how to store data in an Db2 database on IBM Cloud instance 1. Solve example problems to practice your SQL skills

1.1 Selected Socioeconomic Indicators in Chicago

The city of Chicago released a dataset of socioeconomic data to the Chicago City Portal. This dataset contains a selection of six socioeconomic indicators of public health significance and a “hardship index,” for each Chicago community area, for the years 2008 – 2012.

Scores on the hardship index can range from 1 to 100, with a higher index number representing a greater level of hardship.

A detailed description of the dataset can be found on [the city of Chicago’s website](#), but to summarize, the dataset has the following variables:

- **Community Area Number (ca):** Used to uniquely identify each row of the dataset
- **Community Area Name (community_area_name):** The name of the region in the city of Chicago
- **Percent of Housing Crowded (percent_of_housing_crowded):** Percent of occupied housing units with more than one person per room
- **Percent Households Below Poverty (percent_households_below_poverty):** Percent of households living below the federal poverty line
- **Percent Aged 16+ Unemployed (percent_aged_16_unemployed):** Percent of persons over the age of 16 years that are unemployed
- **Percent Aged 25+ without High School Diploma (percent_aged_25_without_high_school_diploma):** Percent of persons over the age of 25 years without a high school education
- **Percent Aged Under 18 or Over 64:** Percent of population under 18 or over 64 years of age (percent_aged_under_18_or_over_64): (ie. dependents)

- **Per Capita Income** (per_capita_income_): Community Area per capita income is estimated as the sum of tract-level aggregate incomes divided by the total population
- **Hardship Index** (hardship_index): Score that incorporates each of the six selected socioeconomic indicators

In this Lab, we'll take a look at the variables in the socioeconomic indicators dataset and do some basic analysis with Python.

1.1.1 Connect to the database

Let us first load the SQL extension and establish a connection with the database

```
In [1]: %load_ext sql
```

```
In [7]: # Remember the connection string is of the format:
# %sql ibm_db_sa://my-username:my-password@my-hostname:my-port/my-db-name
# Enter the connection string for your Db2 on Cloud database instance below
%sql ibm_db_sa://dash6345:_0c3Qpk8ZhJ_@dashdb-entry-yp-dal10-01.services.dal.ibmcloud.com
%sql PERSIST chicago_socioeconomic_data
```

```
Out[7]: 'Connected: dash6345@BLUDB'
```

1.1.2 Store the dataset in a Table

In many cases the dataset to be analyzed is available as a .CSV (comma separated values) file, perhaps on the internet. To analyze the data using SQL, it first needs to be stored in the database.

We will first read the dataset source .CSV from the internet into pandas dataframe

Then we need to create a table in our Db2 database to store the dataset. The PERSIST command in SQL "magic" simplifies the process of table creation and writing the data from a pandas dataframe into the table

```
In [20]: import pandas
chicago_socioeconomic_data = pandas.read_csv('https://data.cityofchicago.org/resource/j
chicago_socioeconomic_data.head()
#chicago_socioeconomic_data.info()
```

```
Out[20]:
```

| | ca | community_area_name | hardship_index | per_capita_income_ | \ |
|---|-----|---------------------|----------------|--------------------|---|
| 0 | 1.0 | Rogers Park | 39.0 | 23939 | |
| 1 | 2.0 | West Ridge | 46.0 | 23040 | |
| 2 | 3.0 | Uptown | 20.0 | 35787 | |
| 3 | 4.0 | Lincoln Square | 17.0 | 37524 | |
| 4 | 5.0 | North Center | 6.0 | 57123 | |

| | percent_aged_16_unemployed | percent_aged_25_without_high_school_diploma | \ |
|---|----------------------------|---|---|
| 0 | 8.7 | 18.2 | |

| | | |
|---|-----|------|
| 1 | 8.8 | 20.8 |
| 2 | 8.9 | 11.8 |
| 3 | 8.2 | 13.4 |
| 4 | 5.2 | 4.5 |

| | percent_aged_under_18_or_over_64 | percent_households_below_poverty \ |
|---|----------------------------------|------------------------------------|
| 0 | 27.5 | 23.6 |
| 1 | 38.5 | 17.2 |
| 2 | 22.2 | 24.0 |
| 3 | 25.5 | 10.9 |
| 4 | 26.2 | 7.5 |

| | percent_of_housing_crowded |
|---|----------------------------|
| 0 | 7.7 |
| 1 | 7.8 |
| 2 | 3.8 |
| 3 | 3.4 |
| 4 | 0.3 |

You can verify that the table creation was successful by making a basic query like:

```
In [9]: %sql SELECT * FROM chicago_socioeconomic_data LIMIT 10;
```

```
db2://dash6345:***@dashdb-entry-yp-dal10-01.services.dal.ibmcloud.com:50000/BLUDB
* ibm_db_sa://dash6345:***@dashdb-entry-yp-dal10-01.services.dal.ibmcloud.com:50000/BLUDB
(ibm_db_dbi.ProgrammingError) ibm_db_dbi::ProgrammingError: SQLNumResultCols failed: [IBM] [CLI D
```

1.2 Problems

1.2.1 Problem 1

How many rows are in the dataset?

```
In [14]: 78
```

```
Out[14]: 78
```

Double-click [here](#) for the solution.

1.2.2 Problem 2

How many community areas in Chicago have a hardship index greater than 50.0?

```
In [48]: hardship = chicago_socioeconomic_data["hardship_index"] > 50
count = 0
i=77
while i>0:
    if hardship[i] == True:
        count +=1
    i -= 1
count
```

Out[48]: 38

Double-click [here](#) for the solution.

1.2.3 Problem 3

What is the maximum value of hardship index in this dataset?

```
In [61]: max(chicago_socioeconomic_data["hardship_index"])
hard = chicago_socioeconomic_data["hardship_index"]
hard = hard == 98.0
i=77
while i>0:
    if hard[i] == True:
        index = i
        break;
    i -= 1
index
```

Out[61]: 53

Double-click [here](#) for the solution.

1.2.4 Problem 4

Which community area which has the highest hardship index?

```
In [62]: import matplotlib.pyplot as plt
#plt.plot(chicago_socioeconomic_data["hardship_index"])
chicago_socioeconomic_data["community_area_name"][53]
```

Out[62]: 'Riverdale'

Double-click [here](#) for the solution.

1.2.5 Problem 5

Which Chicago community areas have per-capita incomes greater than \$60,000?

```
In [65]: hard = chicago_socioeconomic_data["per_capita_income_"]
comm = chicago_socioeconomic_data["community_area_name"]
hard = hard > 60000
i=77
while i>0:
    if hard[i] == True:
        print(comm[i])
    i -= 1
```

Loop
Near North Side
Lincoln Park
Lake View


Double-click [here](#) for the solution.

1.2.6 Problem 6

Create a scatter plot using the variables `per_capita_income_` and `hardship_index`. Explain the correlation between the two variables.

```
In [68]: import matplotlib.pyplot as plt
import seaborn as sns
sns.jointplot(x = "per_capita_income_", y = "hardship_index", data = chicago_socioecon
plt.show()
```

```
/home/jupyterlab/conda/lib/python3.6/site-packages/matplotlib/axes/_axes.py:6462: UserWarning: T
warnings.warn("The 'normed' kwarg is deprecated, and has been "
```



Double-click [here](#) for the solution.

1.2.7 Conclusion

Now that you know how to do basic exploratory data analysis using SQL and python visualization tools, you can further explore this dataset to see how the variable `per_capita_income_` is related to `percent_households_below_poverty` and `percent_aged_16_unemployed`. Try to create interesting visualizations!

1.3 Summary

In this lab you learned how to store a real world data set from the internet in a database (Db2 on IBM Cloud), gain insights into data using SQL queries. You also visualized a portion of the data in the database to see what story it tells. Copyright © 2018 [cognitiveclass.ai](#). This notebook and its source code are released under the terms of the [MIT License](#).