

DB0201EN-Week3-1-1-Connecting-2-py

September 29, 2018

Lab: Connect to Db2 database on Cloud using Python

1 Introduction

This notebook illustrates how to access DB2 Warehouse on Cloud using Python by following the steps below: 1. Import the `ibm_db` Python library 1. Enter the database connection credentials 1. Create the database connection 1. Close the database connection

Notice: Please follow the instructions given in the first Lab of this course to Create a database service instance of Db2 on Cloud and retrieve your database credentials.

1.1 Import the `ibm_db` Python library

The `ibm_db` [API](#) provides a variety of useful Python functions for accessing and manipulating data in an IBM® data server database, including functions for connecting to a database, preparing and issuing SQL statements, fetching rows from result sets, calling stored procedures, committing and rolling back transactions, handling errors, and retrieving metadata.

We first import the `ibm_db` library into our Python Application

Execute the following cell by clicking within it and then press shift and enter keys simultaneously

```
In [1]: import ibm_db
```

When the command above completes, the `ibm_db` library is loaded in your notebook.

1.2 Identify the database connection credentials

Connecting to dashDB or DB2 database requires the following information: * Driver Name * Database name * Host DNS name or IP address * Host port * Connection protocol * User ID (or username) * User Password

Notice: To obtain credentials please refer to the instructions given in the first Lab of this course

Now enter your database credentials below

Replace the placeholder values in angular brackets <> below with your actual database credentials

e.g. replace "< database >" with "BLUDB"

```
In [6]: dsn_driver = "{IBM DB2 ODBC DRIVER}"  
        dsn_database = "BLUDB"           # e.g. "BLUDB"
```

```

dsn_hostname = "dashdb-entry-yp-dal10-01.services.dal.bluemix.net" # e.g.: "awh-yp-small
dsn_port = "50000" # e.g. "50000"
dsn_protocol = "TCPIP" # i.e. "TCPIP"
dsn_uid = "dash6345" # e.g. "dash104434"
dsn_pwd = "_0c3Qpk8ZhJ_" # e.g. "7dBZ3wWt9XN6$o0JiX!m"

```

1.3 Create the DB2 database connection

Ibm_db API uses the IBM Data Server Driver for ODBC and CLI APIs to connect to IBM DB2 and Informix.

Lets build the dsn connection string using the credentials you entered above

```

In [7]: #Create the dsn connection string
dsn = (
    "DRIVER={0};"
    "DATABASE={1};"
    "HOSTNAME={2};"
    "PORT={3};"
    "PROTOCOL={4};"
    "UID={5};"
    "PWD={6};").format(dsn_driver, dsn_database, dsn_hostname, dsn_port, dsn_protocol, d

    #print the connection string to check correct values are specified
    print(dsn)

```

```
DRIVER={IBM DB2 ODBC DRIVER};DATABASE=BLUDB;HOSTNAME=dashdb-entry-yp-dal10-01.services.dal.bluem
```

Now establish the connection to the database

```

In [8]: #Create database connection

try:
    conn = ibm_db.connect(dsn, "", "")
    print ("Connected!")

except:
    print ("Unable to connect to database")

```

Connected!

1.4 Close the Connection

We free all resources by closing the connection. Remember that it is always important to close connections so that we can avoid unused connections taking up resources.

```
In [9]: ibm_db.close(conn)
```

```
Out[9]: True
```

1.5 Summary

In this tutorial you established a connection to a DB2 Warehouse on Cloud database from a Python notebook using `ibm_db` API.

Copyright © 2017 cognitiveclass.ai. This notebook and its source code are released under the terms of the [MIT License](https://creativecommons.org/licenses/by/4.0/).