



| Comment | Description | Designator | Footprint | LibRef | Quantity |
|---------------|--|--|----------------------------|----------------------|----------|
| 470uF | Polarized Capacitor (Radial) | C1, C20, C21, C22, C23, C27, C28, C29 | CAP10x12 | Cap Pol DIP | 8 |
| 470UF | Capacitor | C27, C28, C29 | CAPIUXIZ | Cap Pol DIP | 8 |
| | (Semiconductor SIM | 63.65 | 662246 4206 | | |
| 10uF | Model) Capacitor | C2, C5 C3, C7, C10, C11, C12, | CC3216-1206 | Cap Semi | 2 |
| | (Semiconductor SIM | C14, C15, C16, C17, | | | |
| 100nF | Model) Polarized Capacitor | C18, C19 | CC2012-0805 | Cap Semi | 11 |
| 2200uF | (Axial) | C4 | SV-G | Cap Pol SMD | 1 |
| | Capacitor | | | | |
| 39pF | (Semiconductor SIM Model) | C6, C13 | CC2012-0805 | Cap Semi | 2 |
| P | Capacitor | | | | |
| 20pF | (Semiconductor SIM Model) | C8, C9 | CC2012-0805 | Cap Semi | 2 |
| 20рі | Capacitor | C0, C3 | CC2012 0003 | сар эспіі | - |
| 10 | (Semiconductor SIM Model) | C24 C25 | CC2012 090E | Cap Semi | 2 |
| 10uF | Capacitor | C24, C25 | CC2012-0805 | Сар Зепії | 2 |
| | (Semiconductor SIM | | | | |
| 2.2uF | Model) | C26 | CC2012-0805 | Cap Semi | 1 |
| SS54 | Schottky Diode | D1, D2 | SMA | D Schottky | 2 |
| 24V 3.3V | Typical RED GaAs LED | D3 D4 | D0805 | LED LED | 1 |
| | Typical RED GaAs LED | | D0805 | | |
| BOOT A | Typical RED GaAs LED Typical RED GaAs LED | D5 D6 | D0805 D0805 | LED LED | 1 |
| B B | Typical RED GaAs LED | D7 | D0805 | LED | 1 |
| PWM | Typical RED GaAs LED | D8 | D0805 | LED | 1 |
| DIR | Typical RED GaAs LED | D9 | D0805 | LED | 1 |
| 5V | Typical RED GaAs LED | D10 | D0805 | LED | 1 |
| 20A Fuse | Fuse | F1 | FUSE SOCKET | Fuse | 1 |
| 22uH | Inductor | L1 | CDRH74 | Inductor | 1 |
| FB | Inductor | L2 | CL3225-1210 | Inductor | 1 |
| | HIP4081 Motor Driver | | | | |
| MDRIVE | Module | M1 | HIP4081_Driver | HIP4081 Motor Driver | 1 |
| MOTOR | Header, 2-Pin | P1 | T-CONNECTOR(F) | Header 2 | 1 |
| MDRIVE | Header, 4-Pin | P2 | LOCKEDHDR-4W | Header 4 | 1 |
| CAN | Header, 4-Pin | P3, P4 | LOCKEDHDR-4 | Header 4 | 1 |
| UART SWD | Header, 4-Pin Header, 4-Pin | P5 P6 | LOCKEDHDR-4 LOCKEDHDR-4 | Header 4 Header 4 | 1 |
| POWER | Header, 2-Pin | P7 | T-CONNECTOR(F) | Header 2 | 1 |
| ENC | Header, 5-Pin | P8 | lockedHDR-5 | Header 5 | 1 |
| SWL | Header, 3-Pin | P9 | LOCKEDHDR-3 | Header 3 | 1 |
| SWH | Header, 3-Pin | P10 | LOCKEDHDR-3 | Header 3 | 1 |
| AUX | Header, 3-Pin | P11 | LOCKEDHDR-3 | Header 3 | 1 |
| | | | | | |
| 162k | Semiconductor Resistor | R1, R2 | CR2012-0805 | Res Semi | 2 |
| 53.6k | Semiconductor Resistor | R3 | CR2012-0805 | Res Semi | 1 |
| 10.31 | | | CD 204 2 0005 | | |
| 10.2k | Semiconductor Resistor | R4 R5, R6, R7, R9, R12, | CR2012-0805 | Res Semi | 1 |
| 2200 | | R14, R16, R18, R19, | CD 204 2 | | |
| 330R | Semiconductor Resistor | K20, R21, R26 | CR2012-0805 | Res Semi | 12 |
| 60R | Semiconductor Resistor | R8, R10 | CR2012-0805 | Res Semi | 2 |
| 100k | Semiconductor Resistor | R11, R13, R24 | CR2012-0805 | Res Semi | 3 |
| 200k | Semiconductor Resistor | | CR2012-0805 | Res Semi | 3 |
| 1k | Semiconductor Resistor | | CR2012-0805 | Res Semi | 2 |
| | Single-Pole, Single- | | | | |
| RST | Throw Switch Header, 3-Pin, Dual | SW1 | PUSH SWITCH | SW-SPST | 1 |
| PWR | row | SW2 | POWER SWITCH | Header 3X2 | 1 |
| | STM32 ARM-based 32- bit MCU with 128 | | | | |
| | Kbytes Flash, 48-pin | | | | |
| STM32F103CBT6 | LQFP, Industrial Temperature | U1 | LQFP48_N | STM32F103CBT6 | , |
| STM32F103CBT6 | remperature | 01 | LQCF40_IN | 2 HAID TETROCR ID | 1 |
| | 60 V, 3.5 A , Step Down | | | | |
| TPS54360 | DC-DC Converter with Eco-Mode | U2 | PDSO-8 | TPS54360 | 1 |
| 6N137 | Optocoupler | U3, U5 | DS1302 | 6N137 | 2 |
| | | | | | |
| TJA1050 | 5V to 12V Charge Pump 800mA Low-Dropout | U4 | SOP-8 | TJA1050 | 1 |
| LM1117MP-3.3 | Linear Regulator | U6 | MP04A_N | LM1117MP-3.3 | 1 |
| 8MHz | Crystal Oscillator | X1 | BCY-W2/E4.7 | XTAL | 1 |
| | | | | | |