

```
1 package com.accnture.lkm.business.bean;
2
3 public class PizzaBean {
4
5     private Integer pizzaId;
6     private String pizzaName;
7     private double price;
8
9     public PizzaBean() {
10         super();
11         // TODO Auto-generated constructor stub
12     }
13
14     public Integer getPizzaId() {
15         return pizzaId;
16     }
17
18     public void setPizzaId(Integer pizzaId) {
19         this.pizzaId = pizzaId;
20     }
21
22     public String getPizzaName() {
23         return pizzaName;
24     }
25
26     public void setPizzaName(String pizzaName) {
27         this.pizzaName = pizzaName;
28     }
29
30     public double getPrice() {
31         return price;
32     }
33
34     public void setPrice(double price) {
35         this.price = price;
36     }
37
38 }
39
40
```

Writable

Smart Insert

1 : 1 : 0





PizzaBean.java PizzaOrderBean.java ×

```
1 package com.accenture.ikm.business.bean;
2
3 public class PizzaOrderBean {
4
5     private Integer orderId;
6     private Integer pizzaId;
7     private String customerName;
8     private String contactNumber;
9     private double bill;
10    private Integer numberOfPiecesOrdered;
11
12    public PizzaOrderBean() {
13        super();
14        // TODO Auto-generated constructor stub
15    }
16
17    public Integer getOrderId() {
18        return orderId;
19    }
20
21    public void setOrderId(Integer orderId) {
22        this.orderId = orderId;
23    }
24
25    public Integer getPizzaId() {
26        return pizzaId;
27    }
28
29    public void setPizzaId(Integer pizzaId) {
30        this.pizzaId = pizzaId;
31    }
32
33    public String getCustomerName() {
34        return customerName;
35    }
36
37    public void setCustomerName(String customerName) {
38        this.customerName = customerName;
39    }
40
41    public String getContactNumber() {
42        return contactNumber;
43    }
```

Writable

Smart Insert

1 : 1 : 0

ENG
IN19:28
09-04-2022

```
1 package com.accenture.lkm.business.bean;
2
3 public class BillRangeBean {
4
5     private double fromPrice;
6     private double toPrice;
7
8     public BillRangeBean() {
9         super();
10        // TODO Auto-generated constructor stub
11    }
12
13    public double getFromPrice() {
14        return fromPrice;
15    }
16
17    public void setFromPrice(double fromPrice) {
18        this.fromPrice = fromPrice;
19    }
20
21    public double getToPrice() {
22        return toPrice;
23    }
24
25    public void setToPrice(double toPrice) {
26        this.toPrice = toPrice;
27    }
28
29
30
31
32 }
33
```

Writable

Smart Insert

7 : 5 : 132



```
1 package com.accnture.lkm.dao;
2
3 import java.util.List;
4
10
11 @RepositoryDefinition(idClass = Integer.class, domainClass = PizzaEntity.class)
12 @Transactional("txManager")
13 public interface PizzaDAO {
14     @Query(name = "PIZZA.findAllPizzaDetails")
15     public List<PizzaEntity> findAllPizzaDetails() throws Exception;
16
17 }
18
```

Writable

Smart Insert

1 : 1 : 0



09-04-2022

```
PizzaOrderDAO.java ×
1 package com.accnture.lkm.dao;
2
3 import org.springframework.data.repository.RepositoryDefinition;
4
5 @RepositoryDefinition(domainClass = PizzaOrderEntity.class, idClass = Integer.class)
6 @Transactional("txManager")
7 public interface PizzaOrderDAO {
8     public PizzaOrderEntity save(PizzaOrderEntity pizzaOrderEntity) throws Exception;
9 }
10
11
12
13
```

Writable

Smart Insert

1 : 1 : 0



```
PizzaDAOWrapper.java x
1 package com.accenture.lkm.dao;
2
3 import java.util.ArrayList;
4
5 @Repository
6 @Transactional("txManager")
7 public class PizzaDAOWrapper {
8
9     @Autowired
10     private PizzaDAO pizzaDAO;
11
12     @Autowired
13     private PizzaOrderDAO pizzaOrderDAO;
14
15     @PersistenceContext
16     private EntityManager entityManager;
17
18     public List<PizzaBean> findAllPizzaDetails() throws Exception{
19         List<PizzaEntity> pizzaEntity = pizzaDAO.findAllPizzaDetails();
20         List<PizzaBean> pizzaBean = new ArrayList<PizzaBean>();
21         if(pizzaEntity != null)
22         {
23             for(PizzaEntity each:pizzaEntity) {
24                 pizzaBean.add(convertPizzaEntityToPizzaBean(each));
25             }
26         }
27         else
28             System.out.println("Find All Pizza Detail method did not found anything");
29         return pizzaBean;
30     }
31
32     //::::::::::::::::::Add pizza Order Details()::::::::::::::::::
33     public PizzaOrderBean addPizzaOrderDetails(PizzaOrderBean pizzaOrderBean) throws Exception{
34         PizzaOrderEntity pizzaOrderEntity = new PizzaOrderEntity();
35         pizzaOrderEntity = convertPizzaOrderBeanToPizzaOrderEntity(pizzaOrderBean);
36         PizzaOrderBean pizzaOrderbean = new PizzaOrderBean();
37         pizzaOrderEntity = pizzaOrderDAO.save(pizzaOrderEntity);
38         pizzaOrderbean = convertPizzaOrderEntityToPizzaOrderBean(pizzaOrderEntity);
39         return pizzaOrderbean;
40     }
41
42     //::::::::::::::::::Get Pizza Price::::::::::::::::::
43     public double getPizzaPrice(Integer pizzaId) throws Exception{
44         PizzaEntity pizzaEntity = entityManager.find(PizzaEntity.class, pizzaId);
45         return pizzaEntity.getPrice();
46     }
47 }
```

Writable

Smart Insert

1 : 1 : 0

ENG
IN19:30
09-04-2022


```
PizzaDAOWrapper.java x
54 //::::::::::::::::::::::::::::::::::Get Pizza Price::::::::::::::::::::::::::::::::::
55 public double getPizzaPrice(Integer pizzaId) throws Exception{
56     PizzaEntity pizzaEntity = entityManager.find(PizzaEntity.class, pizzaId);
57     return pizzaEntity.getPrice();
58 }
59 //::::::::::::::::::::::::::::::::::::::::::getOrderDetails::::::::::::::::::::::::::::::::::::::::::
60 public List<PizzaOrderBean> getOrderDetails(double fromPrice, double toPrice) throws Exception{
61     Query query = entityManager.createQuery("select k from PizzaOrderEntity k where k.bill between '"+fromPrice+"' and '"+toPrice+"'");
62     List<PizzaOrderEntity> pizzaOrderEntity = new ArrayList<PizzaOrderEntity>();
63     pizzaOrderEntity = query.getResultList();
64     List<PizzaOrderBean> pizzaOrderBean = new ArrayList<PizzaOrderBean>();
65     if(pizzaOrderEntity != null) {
66         for(PizzaOrderEntity each:pizzaOrderEntity) {
67             pizzaOrderBean.add(convertPizzaOrderEntityToPizzaOrderBean(each));
68         }
69     }
70     else
71         System.out.println("Function did not find any data");
72     return pizzaOrderBean;
73 }
74 //::::::::::::::::::::::::::::::::::::::::::Converter::::::::::::::::::::::::::::::::::::::::::
75 public PizzaBean convertPizzaEntityToPizzaBean(PizzaEntity pizzaEntity) throws Exception{
76     PizzaBean pizzaBean = new PizzaBean();
77     BeanUtils.copyProperties(pizzaEntity, pizzaBean);
78     return pizzaBean;
79 }
80 public PizzaEntity convertPizzaBeanToPizzaEntity(PizzaBean pizzaBean) throws Exception{
81     PizzaEntity pizzaEntity = new PizzaEntity();
82     BeanUtils.copyProperties(pizzaBean, pizzaEntity);
83     return pizzaEntity;
84 }
85 public PizzaOrderBean convertPizzaOrderEntityToPizzaOrderBean(PizzaOrderEntity pizzaOrderEntity) throws Exception{
86     PizzaOrderBean pizzaOrderBean = new PizzaOrderBean();
87     BeanUtils.copyProperties(pizzaOrderEntity, pizzaOrderBean);
88     return pizzaOrderBean;
89 }
90 public PizzaOrderEntity convertPizzaOrderBeanToPizzaOrderEntity(PizzaOrderBean pizzaOrderBean) throws Exception{
91     PizzaOrderEntity pizzaOrderEntity = new PizzaOrderEntity();
92     BeanUtils.copyProperties(pizzaOrderBean, pizzaOrderEntity);
93     return pizzaOrderEntity;
94 }
95
96 }
```

Writable

Smart Insert

1 : 1 : 0

ENG
IN19:30
09-04-2022

PizzaEntity.java ×

```
1 package com.accnture.lkm.entity;
2
3 import javax.persistence.Entity;
4
5 @Entity
6 @Table(name = "Pizza")
7 public class PizzaEntity {
8
9     @Id
10     @GeneratedValue(strategy = GenerationType.AUTO)
11     private Integer pizzaId;
12     private String pizzaName;
13     private double price;
14
15     public PizzaEntity() {
16         super();
17         // TODO Auto-generated constructor stub
18     }
19
20     public Integer getPizzaId() {
21         return pizzaId;
22     }
23
24     public void setPizzaId(Integer pizzaId) {
25         this.pizzaId = pizzaId;
26     }
27
28     public String getPizzaName() {
29         return pizzaName;
30     }
31
32     public void setPizzaName(String pizzaName) {
33         this.pizzaName = pizzaName;
34     }
35
36     public double getPrice() {
37         return price;
38     }
39
40     public void setPrice(double price) {
41         this.price = price;
42     }
43
44 }
```

Writable

Smart Insert

1 : 1 : 0

ENG
IN19:31
09-04-2022


```
PizzaOrderEntity.java x
1 package com.accnture.lkm.entity;
2
3 import javax.persistence.Column;
4
5
6
7
8
9
10 @Entity
11 @Table(name = "Pizza_Order")
12 public class PizzaOrderEntity {
13
14     @Id
15     @GeneratedValue(strategy = GenerationType.AUTO)
16     private Integer orderId;
17     private Integer pizzaId;
18     private String customerName;
19     private String contactNumber;
20     private double bill;
21     private Integer numberOfPiecesOrdered;
22
23     public PizzaOrderEntity() {
24         super();
25         // TODO Auto-generated constructor stub
26     }
27
28     public Integer getOrderId() {
29         return orderId;
30     }
31
32     public void setOrderId(Integer orderId) {
33         this.orderId = orderId;
34     }
35
36     public Integer getPizzaId() {
37         return pizzaId;
38     }
39
40     public void setPizzaId(Integer pizzaId) {
41         this.pizzaId = pizzaId;
42     }
43
44     public String getCustomerName() {
45         return customerName;
46     }
47
48     public void setCustomerName(String customerName) {
```

Writable

Smart Insert

1 : 1 : 0

ENG
IN19:31
09-04-2022

```
PizzaService.java x
1 package com.accenture.lkm.service;
2
3 import java.util.List;
4
5
6
7
8
9
10
11 public interface PizzaService {
12     public List<PizzaOrderBean> getOrderDetails(double fromBill, double toBill) throws Exception;
13     public PizzaOrderBean addPizzaOrderDetails(PizzaOrderBean pizzaOrderBean) throws Exception;
14     public Map<Integer, String> findAllPizzaDetails() throws Exception;
15 }
16
17
```

Writable

Smart Insert

1 : 1 : 0

19:32
09-04-2022

```
1 package com.accenture.lkm.service;
2
3 import java.util.ArrayList;
4
5
6
7
8
9
10
11
12
13
14
15
16 @Service
17 public class PizzaServiceImpl implements PizzaService {
18
19     @Autowired
20     private PizzaDAOWrapper pizzaDAOWrapper;
21
22     @Override
23     public List<PizzaOrderBean> getOrderDetails(double fromBill, double toBill) throws Exception {
24
25         return pizzaDAOWrapper.getOrderDetails(fromBill, toBill);
26     }
27
28     @Override
29     public PizzaOrderBean addPizzaOrderDetails(PizzaOrderBean pizzaOrderBean) throws Exception {
30         double price = pizzaDAOWrapper.getPizzaPrice(pizzaOrderBean.getPizzaId());
31         pizzaOrderBean.setBill(price * pizzaOrderBean.getNumberOfPiecesOrdered());
32         return pizzaDAOWrapper.addPizzaOrderDetails(pizzaOrderBean);
33     }
34
35     @Override
36     public Map<Integer, String> findAllPizzaDetails() throws Exception {
37         Map<Integer, String> map = new HashMap<Integer, String>();
38         List<PizzaBean> pizzaBean = new ArrayList<PizzaBean>();
39         pizzaBean = pizzaDAOWrapper.findAllPizzaDetails();
40         if(pizzaBean != null) {
41             for(PizzaBean each:pizzaBean) {
42                 map.put(each.getPizzaId(), each.getPizzaName());
43             }
44         }
45         return map;
46     }
47
48
49
50 }
51
```

Writable

Smart Insert

1 : 1 : 0

19:32
09-04-2022

```
ReportController.java X
1 package com.accenture.lkm.web.controller;
2
3 import java.util.ArrayList;
4
18
19 @Controller
20 public class ReportController {
21
22     @Autowired
23     private PizzaService pizzaService;
24
25     @RequestMapping(value = "/loadPizzaOrderWithPizzaOrderBean.html",method = RequestMethod.GET)
26     public ModelAndView loadSavePizza() throws Exception{
27         ModelAndView mv = new ModelAndView();
28         mv.setViewName("PizzaOrder");
29         mv.addObject("pizzaOrderBean", new PizzaOrderBean());
30         return mv;
31     }
32
33     @RequestMapping(value = "/OrderReport.html",method = RequestMethod.GET)
34     public ModelAndView loadDateRangeReportPage() throws Exception{
35         ModelAndView mv = new ModelAndView();
36         mv.setViewName("OrderReport");
37         mv.addObject("billRangeBean", new BillRangeBean());
38         return mv;
39     }
40
41     @RequestMapping(value = "/fetch.html",method = RequestMethod.POST)
42     public ModelAndView getOrderDetails(@ModelAttribute("billRangeBean")BillRangeBean billRangeBean) throws Exception{
43         List<PizzaOrderBean> pizzaOrderBean = new ArrayList<PizzaOrderBean>();
44         pizzaOrderBean = pizzaService.getOrderDetails(billRangeBean.getFromPrice(), billRangeBean.getToPrice());
45         ModelAndView mv = new ModelAndView();
46         mv.setViewName("OrderReport");
47         mv.addObject("Orderdetails",pizzaOrderBean);
48         return mv;
49     }
50
51     @RequestMapping(value = "/OrderCompletion.html",method = RequestMethod.POST)
52     public ModelAndView saveCustomer(@ModelAttribute("pizzaOrderBean")PizzaOrderBean pizzaOrderBean) throws Exception{
53         ModelAndView mv = new ModelAndView();
54         if(pizzaOrderBean != null) {
55             PizzaOrderBean pizzaOrderBean = pizzaService.addPizzaOrderDetails(pizzaOrderBean);
56             mv.setViewName("PizzaOrderSuccess");
57             mv.addObject("message","Hi: "+pizzaOrderBean.getCustomerName()+"', your order is placed with orderId:'"+pizzaOrderBean.getOrderid()+"',Bill to be Paid is:'"+pizzaOrderBean.getBillToBePaid()+"'");
58         }
59     }
60 }
```

Writable

Smart Insert

1:1:0

19:32
09-04-2022


```
ReportController.java x
26 public ModelAndView loadSavePizza() throws Exception{
27     ModelAndView mv = new ModelAndView();
28     mv.setViewName("PizzaOrder");
29     mv.addObject("pizzaOrderBean", new PizzaOrderBean());
30     return mv;
31 }
32
33 @RequestMapping(value = "/OrderReport.html",method = RequestMethod.GET)
34 public ModelAndView loadDateRangeReportPage() throws Exception{
35     ModelAndView mv = new ModelAndView();
36     mv.setViewName("OrderReport");
37     mv.addObject("billRangeBean", new BillRangeBean());
38     return mv;
39 }
40 @RequestMapping(value = "/fetch.html",method = RequestMethod.POST)
41 public ModelAndView getOrderDetails(@ModelAttribute("billRangeBean")BillRangeBean billRangeBean) throws Exception{
42     List<PizzaOrderBean> pizzaOrderBean = new ArrayList<PizzaOrderBean>();
43     pizzaOrderBean = pizzaService.getOrderDetails(billRangeBean.getFromPrice(), billRangeBean.getToPrice());
44     ModelAndView mv = new ModelAndView();
45     mv.setViewName("OrderReport");
46     mv.addObject("Orderdetails",pizzaOrderBean);
47     return mv;
48 }
49
50 @RequestMapping(value = "/OrderCompletion.html",method = RequestMethod.POST)
51 public ModelAndView saveCustomer(@ModelAttribute("pizzaOrderBean")PizzaOrderBean pizzaOrderBean) throws Exception{
52     ModelAndView mv = new ModelAndView();
53     if(pizzaOrderBean != null) {
54         PizzaOrderBean pizzaOrderbean = pizzaService.addPizzaOrderDetails(pizzaOrderBean);
55         mv.setViewName("PizzaOrderSuccess");
56         mv.addObject("message","Hi:" +pizzaOrderbean.getCustomerName()+"', your order is placed with orderId:'"+pizzaOrderbean.getOrderId()+"',Bill to be Paid is:'"+pizzaOrderb
57     }
58
59     return mv;
60 }
61 @ModelAttribute("mapOfPizzaName")
62 public Map<Integer,String> populatePizzaNames() throws Exception{
63     Map<Integer, String> map = new HashMap<Integer,String>();
64     return map = pizzaService.findAllPizzaDetails();
65 }
66
67 }
68
```

Writable

Smart Insert

1 : 1 : 0

ENG
IN19:32
09-04-2022


```
1 <?xml version="1.0" encoding="UTF-8"?>
2 <entity-mappings version="1.0" xmlns="http://java.sun.com/xml/ns/persistence/orm"
3   xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
4   xsi:schemaLocation="http://java.sun.com/xml/ns/persistence/orm http://java.sun.com/xml/ns/persistence/orm_1_0.xsd">
5
6   <named-query name="PIZZA.findAllPizzaDetails">
7     <query>Select k from PizzaEntity k</query>
8   </named-query>
9
10 </entity-mappings>
```

Package Explorer

- com.accenture.lkm.dao
 - PizzaDAO.java
 - PizzaDAO
 - findAllPizzaDetails(): List<PizzaEntity>
 - PizzaDAOWrapper.java
 - PizzaOrderDAO.java
- com.accenture.lkm.entity
 - PizzaEntity.java
 - PizzaOrderEntity.java
- com.accenture.lkm.exceptions
- com.accenture.lkm.resources
- com.accenture.lkm.service
 - PizzaService.java
 - PizzaServiceImpl.java
- com.accenture.lkm.web.controller
 - ReportController.java
- META-INF
 - orm.xml
- Web App Libraries
- JRE System Library [jdk-17.0.2]
- build
- WebContent
 - META-INF
 - WEB-INF
 - jspViews
 - GeneralizedExceptionHandlerPage.jsp
 - OrderReport.jsp
 - PizzaOrder.jsp
 - PizzaOrderSuccess.jsp
 - lib
 - cst_jpa_spring_config.xml
 - cst-root-ctx.xml
 - cstspconf-web-servlet.xml
 - web.xml
 - index.jsp
- HandsonProjectStructure
- PizzaHandson

GeneralizedExceptionHandlerPage.jsp

```
1 <%@ page language="java" contentType="text/html; charset=ISO-8859-1"
2   pageEncoding="ISO-8859-1"%>
3 <%@ taglib uri="http://www.springframework.org/tags/form" prefix="form"%>
4 <!DOCTYPE html PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd"
5 <html>
6 <head>
7 <meta http-equiv="Content-Type" content="text/html; charset=ISO-8859-1">
8 <title>Insert title here</title>
9 </head>
10 <body>
11 <center>
12   <h2 style="color:red">Genralized Exception Handler Page</h2>
13   <hr>
14   Exception Occured is: ${message}
15   <hr>
16   Details of Exception
17   <hr>
18   ${exception}
19   <a href="${pageContext.request.contextPath}/">Home</a>
20 </center>
21 </body>
22 </html>
```

Outline

- jsp:directive.page language=java
- jsp:directive.taglib prefix=form
- DOCTYPE:html
- html

Problems

97 errors, 26 warnings, 71 others

Description	Resource	Path	Location	Type
> Errors (97 items)				
> Warnings (26 items)				
> Infos (71 items)				

Writable Smart Insert 1 : 1 : 0

19:33 09-04-2022

```
GeneralizedExceptionHandlerPage.jsp OrderReport.jsp X
1 <%@ page language="java" contentType="text/html; charset=ISO-8859-1"
2   pageEncoding="ISO-8859-1"%>
3 <%@ taglib prefix="form" uri="http://www.springframework.org/tags/form" %>
4 <%@ taglib uri="http://www.springframework.org/tags/form" prefix="form" %>
5 <%@taglib prefix="c" uri="http://java.sun.com/jsp/jstl/core"%>
6 <!DOCTYPE html>
7 <html>
8 <head>
9   <meta charset="ISO-8859-1">
10  <title>Insert title here</title>
11 </head>
12 <body>
13   <center>
14     <h1>Order with in Price Range Report</h1>
15     <form:form modelAttribute="billRangeBean" action="${pageContext.request.contextPath}/fetch.html" method="POST">
16       <table border="2">
17         <tr>
18           <td>From Price:</td>
19           <td><form:input path="fromPrice"/></td>
20           <td>To Price:</td>
21           <td><form:input path="toPrice"/></td>
22         </tr>
23       </table>
24       <br>
25       <br>
26       <button type="submit">Fetch Details</button>
27     </form:form>
28     <br>
29     <br>
30     <br>
31     <br>
32     <form:form>
33       <c:if test="${not empty Orderdetails}">
34         <table border="2">
35           <tr>
36             <th>Order ID</th><th>Customer Name</th><th>Pizza Id</th><th>Bill</th><th>Quality</th>
37           </tr>
38           <c:forEach var="var" items="${Orderdetails}">
39             <tr>
40               <td>${var.orderId}</td><td>${var.customerName}</td><td>${var.pizzaId}</td><td>${var.bill}</td><td>${var.numberofPiecesOrdered}</td>
41             </tr>
42           </c:forEach>
43         </table>
```

<> jsp:directive.page

Writable

Smart Insert

1:1:0

19:34
09-04-2022

```
11 </head>
12 <body>
13   <Center>
14     <h1>Order with in Price Range Report</h1>
15     <form:form modelAttribute="billRangeBean" action="${pageContext.request.contextPath}/fetch.html" method="POST">
16       <table border="2">
17         <tr>
18           <td>From Price:</td>
19           <td><form:input path="fromPrice"/></td>
20           <td>To Price:</td>
21           <td><form:input path="toPrice"/></td>
22         </tr>
23       </table>
24       <br>
25       <br>
26       <button type="submit">Fetch Details</button>
27     </form:form>
28     <br>
29     <br>
30     <br>
31     <br>
32     <form:form>
33       <c:if test="${not empty Orderdetails}">
34         <table border="2">
35           <tr>
36             <th>Order ID</th><th>Customer Name</th><th>Pizza Id</th><th>Bill</th><th>Quality</th>
37           </tr>
38           <c:forEach var="var" items="${Orderdetails}">
39             <tr>
40               <td>${var.orderId}</td><td>${var.customerName}</td><td>${var.pizzaId}</td><td>${var.bill}</td><td>${var.numberofPiecesOrdered}</td>
41             </tr>
42           </c:forEach>
43         </table>
44       </c:if>
45     </form:form>
46     <br>
47     <br>
48     <a href="${pageContext.request.contextPath}/index.jsp">Home</a>
49   </Center>
50
51
52 </body>
53 </html>
```




```
PizzaOrder.jsp x
1 <%@ page language="java" contentType="text/html; charset=ISO-8859-1" pageEncoding="ISO-8859-1"%>
2 <%@ taglib prefix="form" uri="http://www.springframework.org/tags/form" %>
3 <%@ taglib uri="http://www.springframework.org/tags/form" prefix="form"%>
4 <%@taglib prefix="c" uri="http://java.sun.com/jsp/jstl/core"%>
5 <!DOCTYPE html>
6 <html>
7 <head>
8 <meta charset="ISO-8859-1">
9 <title></title>
10 </head>
11 <body>
12 <Center>
13 <h1>Add Pizza Details</h1>
14 <form:form modelAttribute="pizzaOrderBean" action="${pageContext.request.contextPath}/OrderCompletion.html" method="POST">
15 <table border="2">
16 <tr>
17 <td>Customer Name</td>
18 <td><form:input path="customerName"/></td>
19 </tr>
20 <tr>
21 <td>Customer Contact</td>
22 <td><form:input path="contactNumber"/></td>
23 </tr>
24 <tr>
25 <td>Pizza Name</td>
26 <td><form:select path="pizzaId">
27 <form:option value="" label="--Select--"/>
28 <form:options items="${mapOfPizzaName}"/>
29 </form:select>
30 </td>
31 </tr>
32 <tr>
33 <td>Quantity</td>
34 <td><form:input path="numberOfPiecesOrdered"/></td>
35 </tr>
36 </table>
37 <button type="submit">Order</button><br>
38 <a href="${pageContext.request.contextPath}/index.jsp">Home</a>
39 </form:form>
40 </Center>
41
42 </body>
43 </html>
```

Writable

Smart Insert

1 : 1 : 0

ENG
IN19:35
09-04-2022


```
PizzaOrderSuccess.jsp ×
1 <%@ page language="java" contentType="text/html; charset=ISO-8859-1"
2   pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>Insert title here</title>
8 </head>
9 <body>
10 <center>
11 <h1>Add Pizza Order Details Success</h1>
12 <br>
13 <br>
14 <h2>${message}</h2>
15 <br>
16 <br>
17 <a href="${pageContext.request.contextPath}/index.jsp">Home</a>
18 </center>
19
20 </body>
21 </html>
```

Writable

Smart Insert

1 : 1 : 0

ENG
IN19:35
09-04-2022

```
<?xml version="1.0" encoding="UTF-8" ?>
<beans xmlns="http://www.springframework.org/schema/beans"
       xmlns:context="http://www.springframework.org/schema/context"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
       xmlns:aop="http://www.springframework.org/schema/aop"
       xmlns:tx="http://www.springframework.org/schema/tx"
       xmlns:jpa="http://www.springframework.org/schema/data/jpa"
       xsi:schemaLocation="
           http://www.springframework.org/schema/beans
           http://www.springframework.org/schema/beans/spring-beans.xsd
           http://www.springframework.org/schema/context
           http://www.springframework.org/schema/context/spring-context.xsd
           http://www.springframework.org/schema/aop http://www.springframework.org/schema/aop/spring-aop.xsd
           http://www.springframework.org/schema/tx
           http://www.springframework.org/schema/tx/spring-tx.xsd
           http://www.springframework.org/schema/data/jpa
           http://www.springframework.org/schema/data/jpa/spring-jpa.xsd">

    <bean
        class="org.springframework.beans.factory.config.PropertyPlaceholderConfigurer">
        <property name="location">
            <value>classpath:com/accnture/lkm/resources/cst_conn.properties</value> <!-- class path is requiered when runing from web app -->
        </property>
    </bean>

    <tx:annotation-driven transaction-manager="txManager"/>
    <!-- To Enable JPA Repository and to refer to the custom transaction Manager name-->
    <jpa:repositories base-package="com.accnture.lkm.dao" transaction-manager-ref="txManager"> </jpa:repositories>

    <bean id="dataSource" class="org.springframework.jdbc.datasource.DriverManagerDataSource" >
        <property name="driverClassName" value="${cst_db_driver}" />
        <property name="url" value="${cst_db_url}" />
        <property name="username" value="${cst_user}" />
        <property name="password" value="${cst_password}" />
    </bean>

    <!-- Name of the bean should be entityManagerFactory only in Spring JPADat-->
    <bean id="entitvManagerFactory" class="org.springframework.orm.jpa.LocalContainerEntitvManagerFactoryBean">
```

Design Source

beans/#text

Writable

Smart Insert

20:5:1033



```
cst_jpa_spring_config.xml x
http://www.springframework.org/schema/data/jpa/spring-jpa.xsd">
17
18
19
20
21<bean
22    class="org.springframework.beans.factory.config.PropertyPlaceholderConfigurer">
23
24    <property name="location">
25        <value>classpath:com/accnture/lkm/resources/cst_conn.properties</value> <!-- class path is requiried when runing from web app -->
26    </property>
27</bean>
28
29<tx:annotation-driven transaction-manager="txManager"/>
30<!-- To Enable JPA Repository and to refer to the custom transaction Manager name-->
31<jpa:repositories base-package="com.accnture.lkm.dao" transaction-manager-ref="txManager"> </jpa:repositories>
32
33<bean id="dataSource" class="org.springframework.jdbc.datasource.DriverManagerDataSource" >
34    <property name="driverClassName" value="${cst_db_driver}" />
35    <property name="url" value="${cst_db_url}" />
36    <property name="username" value="${cst_user}" />
37    <property name="password" value="${cst_password}" />
38</bean>
39
40
41<!-- Name of the bean should be entityManagerFactory only in Spring JPADat-->
42<bean id="entityManagerFactory" class="org.springframework.orm.jpa.LocalContainerEntityManagerFactoryBean">
43    <property name="dataSource" ref="dataSource" />
44    <property name="jpaVendorAdapter">
45        <bean class="org.springframework.orm.jpa.vendor.HibernateJpaVendorAdapter">
46            <property name="showSql" value="true" />
47            <property name="generateDdl" value="true" />
48            <property name="databasePlatform" value="org.hibernate.dialect.MySQLDialect" />
49        </bean>
50    </property>
51    <property name="packagesToScan" value="com.accnture.lkm.entity"></property>
52</bean>
53
54<bean id="txManager" class="org.springframework.orm.jpa.JpaTransactionManager"> <!-- custom transaction Manager -->
55    <property name="entityManagerFactory" ref="entityManagerFactory" />
56</bean>
57
58</beans>
```

Design Source

beans/#text

Writable

Smart Insert

20:5:1033



```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
       xmlns:context="http://www.springframework.org/schema/context"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
       xmlns:mvc="http://www.springframework.org/schema/mvc"
       xsi:schemaLocation="
           http://www.springframework.org/schema/beans
           http://www.springframework.org/schema/beans/spring-beans.xsd
           http://www.springframework.org/schema/context
           http://www.springframework.org/schema/context/spring-context.xsd
           http://www.springframework.org/schema/mvc
           http://www.springframework.org/schema/mvc/spring-mvc.xsd">

    <!-- scanning service and DAO -->
    <context:component-scan base-package="com.accenture.lkm.service, com.accenture.lkm.dao" />
    <import resource="cst_jpa_spring_config.xml"/>
</beans>
```




```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
       xmlns:context="http://www.springframework.org/schema/context"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
       xmlns:mvc="http://www.springframework.org/schema/mvc"
       xsi:schemaLocation="
           http://www.springframework.org/schema/beans
           http://www.springframework.org/schema/beans/spring-beans.xsd
           http://www.springframework.org/schema/context
           http://www.springframework.org/schema/context/spring-context.xsd
           http://www.springframework.org/schema/mvc
           http://www.springframework.org/schema/mvc/spring-mvc.xsd">

    <!-- scanning just web related dependencies -->
    <context:component-scan base-package="com.accenture.lkm.web" />

    <!--adds support for MVC annotations:
    1. @Valid annotation for validation
    2. @RequestMapping
    3. http message convertors or message body marshalling with @RequestBody/ResponseBody -->
    <mvc:annotation-driven />

    <!-- View Resolver to resolve the views from a custom location -->
    <bean class="org.springframework.web.servlet.view.InternalResourceViewResolver">
        <property name="prefix">
            <value>/WEB-INF/jspViews/</value>
        </property>
        <property name="suffix">
            <value>.jsp</value>
        </property>
    </bean>
</beans>
```

Design Source

Writable

Smart Insert

1 : 1 : 0

loading http://www.spr...pring-context.xsd



```
<?xml version="1.0" encoding="UTF-8"?>
<web-app xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://java.sun.com/xml/ns/javaee" xsi:schemaLocation="http://java.sun.com/xml/ns/javaee http://java.sun.com/
<welcome-file-list>
  <welcome-file>index.jsp</welcome-file>
</welcome-file-list>
<listener>
  <listener-class>
    org.springframework.web.context.ContextLoaderListener
  </listener-class>
</listener>
<context-param>
  <param-name>contextConfigLocation</param-name>
  <param-value>
    /WEB-INF/cst-root-ctx.xml
  </param-value>
</context-param>
<servlet>
  <servlet-name>cstspconf-web</servlet-name>
  <servlet-class>org.springframework.web.servlet.DispatcherServlet</servlet-class>
  <load-on-startup>1</load-on-startup>
</servlet>
<servlet-mapping>
  <servlet-name>cstspconf-web</servlet-name>
  <url-pattern>*.html</url-pattern>
</servlet-mapping>
</web-app>
```



```
1 <%@ page language="java" contentType="text/html; charset=ISO-8859-1"
2   pageEncoding="ISO-8859-1"%>
3 <%@ taglib prefix="form" uri="http://www.springframework.org/tags/form" %>
4 <%@ taglib uri="http://www.springframework.org/tags/form" prefix="form"%>
5 <%@taglib prefix="c" uri="http://java.sun.com/jsp/jstl/core"%>
6 <!DOCTYPE html>
7 <html>
8 <head>
9   <meta charset="ISO-8859-1">
10  <title>Insert title here</title>
11 </head>
12 <body>
13   <center>
14     <h1>Dan Pizza's Stall</h1>
15     <br>
16     <table border="2">
17       <tr>
18         <td><a href="{pageContext.request.contextPath}/loadPizzaOrderWithPizzaOrderBean.html">Save Order</a></td>
19         <td><a href="{pageContext.request.contextPath}/OrderReport.html">Order Report</a></td>
20       </tr>
21     </table>
22   </center>
23 </body>
24 </html>
```

