


Lecture 5: Shannon's Coding theorem

In this lecture, we shall take a look at an important result in error-control coding / information theory that pins down the tradeoff between the rate of a code and its error-correcting capability, in the setting of **stochastic / random noise**.

We work in the setting of transmission of binary codewords over a $BSC(p)$.



WLOG, we assume that $0 < p < \frac{1}{2}$. The case where $p = 0$ is trivial and we note that if $p > \frac{1}{2}$, we can convert the channel to $BSC(p')$, where $p' = 1 - p < \frac{1}{2}$, by simply flipping all bits in y .

Let the message set be M , with $|M| = 2^{nR}$, where R is the code rate.

The task at hand is to design (E, D) so as to guarantee "reliable reconstruction/recovery" of the message, i.e.,

$$P_h[\hat{m} \neq m] \xrightarrow{n \rightarrow \infty} 0.$$

↳ over randomness in encoding, channel noise, & decoding.

Theorem (Shannon's noisy channel coding theorem). Fix $p \in (0, \frac{1}{2})$.

There exists a real number $C = C(p)$ such that

(i) For any rate $R < C(p)$, **there exist** (sequences of) encoding/decoding functions $\{(E_n, D_n)\}_{n \geq 1}$ s.t. $P_h[\hat{m} \neq m] \xrightarrow{n \rightarrow \infty} 0$.

["Achievability"]

(ii) For any rate $R > C(p)$, **for any** (sequences of) encoding/decoding functions $\{(E_n, D_n)\}_{n \geq 1}$, we have that \exists message m s.t.

$$P_h[\hat{m} = m] \xrightarrow{n \rightarrow \infty} 0.$$

["Converse"]

Remark: (i) Shannon's theorem above applies to the broader class of discrete memoryless channels (DMCs) of which the BSC is a part.

(ii) The quantity $C(p)$ is called the "capacity" of the BSC, since

it represents a threshold, at rates below which reliable communication is possible, and at rates above which reliable communication is impossible.


For the BSC, the capacity is

$$C(p) = 1 - h_b(p) \equiv 1 - h(p),$$

where $h(\cdot)$ is the binary entropy function:

$$h(p) = -p \log_2 p - (1-p) \log_2 (1-p),$$

$$\text{with } h(0) = h(1) \triangleq 0.$$



First, a lemma. Let $B(\underline{x}, n)$ be the Hamming ball of radius n around $\underline{x} \in \{0,1\}^n$.

Lemma: We have that for any $\underline{x} \in \{0,1\}^n$,

$$2^{n(h(p) - o(1))} \leq \text{Vol}(B(\underline{x}, np)) = \sum_{j=0}^{np} \binom{n}{j} \leq 2^{nh(p)}.$$

Proof: Note that

$$\begin{aligned} \frac{\text{Vol}(B(\underline{x}, np))}{2^{nh(p)}} &= \frac{\text{Vol}(B(\underline{0}, np))}{2^{nh(p)}} \\ &= \sum_{j=0}^{np} \binom{n}{j} \cdot p^{np} (1-p)^{n(1-p)} \\ &\leq \sum_{j=0}^{np} \binom{n}{j} p^j (1-p)^{n-j} \end{aligned}$$

$$= (1-p)^n \cdot \sum_{j=0}^n \binom{n}{j} \left(\frac{p}{1-p}\right)^j$$

$$\leq (1-p)^n \cdot \sum_{j=0}^n \binom{n}{j} \left(\frac{p}{1-p}\right)^j = (1-p)^n \cdot \left(1 + \frac{p}{1-p}\right)^n = 1.$$


The proof of the lower bound follows via Stirling's inequality. \square

Proof of achievability in Shannon's theorem: Fix $R = 1 - h(p+\epsilon)$, for $\epsilon \in (0, \frac{1}{2}-p)$.

We induce a distribution over (E, D) and show that reliable reconstⁿ holds "with high probability". Hence, there must exist a deterministic (E, D) such that this property holds.

E : Pick $E(m) \sim \text{Unif}(\{0,1\}^n)$.

D : Given $y \in \{0,1\}^n$,



$$D(y) = \begin{cases} \bar{m}, & \text{if } \bar{m} \text{ is the unique } m \in \mathcal{M} \text{ s.t. } d(E(m), y) < (p+\frac{\epsilon}{2})^n \\ \perp, & \text{o.w.} \end{cases}$$

Note that $y = E(m) + \underline{e}$, where $\underline{e} \sim (\text{Ber}(p))^{\otimes n}$.

We define the following "bad events":

$$\mathcal{E}_1: \sum_{i=1}^n e_i > (p+\frac{\epsilon}{2})^n$$

$$\mathcal{E}_2: \exists m' \neq m \text{ s.t. } d(E(m'), y) < (p+\frac{\epsilon}{2})^n.$$

We wish to bound $P[\mathcal{E}_1 \cup \mathcal{E}_2] \leq P[\mathcal{E}_1] + P[\mathcal{E}_2]$. Note that

$$P[\mathcal{E}_1] \leq \begin{cases} e^{-c\epsilon^2 n} & \text{(Chernoff bound)} \\ \frac{c'}{n} & \text{(Chebyshev inequality)} \end{cases}$$

In any case, $P[\mathcal{E}_1] \xrightarrow{n \rightarrow \infty} 0$.

Further,

$$P[\mathcal{E}_2] = \mathbb{E}[P[\mathcal{E}_2 \mid m, E(m), \underline{e}]]$$

$$\leq \mathbb{E}\left[\sum_{m' \neq m} P\left[\underbrace{d(E(m'), y) < (p + \frac{\epsilon}{2})n}_{\text{random length-}n \text{ string lies in a ball of radius } (p + \frac{\epsilon}{2})n} \mid m, E(m), \underline{e}\right]\right]$$

$$= \mathbb{E}\left[\sum_{m' \neq m} P\left[\text{random length-}n \text{ string lies in a ball of radius } (p + \frac{\epsilon}{2})n\right]\right]$$

$$= \sum_{m' \neq m} \frac{\text{Vol}(B(\underline{e}, (p + \frac{\epsilon}{2})n))}{2^n}$$

$$\leq |\mathcal{M}| \cdot 2^{-n(1 - h(p + \frac{\epsilon}{2}))} = 2^{n \cdot (h(p + \frac{\epsilon}{2}) - h(p + \epsilon))}$$

$$\xrightarrow{n \rightarrow \infty} 0$$



Take-away: There exist "good" codes that guarantee reliable recovery in the setting of stochastic noise. But which codes are good?